Great Bear Resources Ltd. Drills 18.57 g/t Gold Over 13.00 m, Within 2.67 g/t Gold Over 104.15 m at LP Fault

04.05.2020 | CNW

VANCOUVER, May 4, 2020 - <u>Great Bear Resources Ltd.</u> (the "Company" or "Great Bear", TSX-V: GBR; OTCQX: GTBDF) today reported results from its ongoing fully funded \$21 million exploration program at its 100% owned flagship Dixie Project in the Red Lake district of Ontario.

Chris Taylor, President and CEO of Great Bear said, "As we approach the one-year anniversary of the discovery of the LP Fault and our 100th drill hole into this target, our sense of enthusiasm continues to build as the LP Fault continues to deliver robust gold results with more detailed drilling. New drill hole BR-118 returned one of the longest high-grade gold intervals to-date, and was completed in the middle of a 150 metre gap in drilling. Mineralization begins immediately at the bedrock surface, with consistent geology and mineralization styles observed in both neighbouring drill sections. Importantly, all other drill holes reported in this release also continue to successfully intersect gold mineralization at all points tested along the LP Fault to-date."

The Company has completed 99 of approximately 300 planned drill holes into the LP Fault target, as part of its 5 kilometre long by 500 metre deep grid drill program. Current drill hole locations and results are provided in Figure 1, and in Table 1, respectively. An updated long section of the LP Fault drilling is provided in Figure 2.

Drill Results Highlights:

- Drill hole BR-118 on drill section 20650 was completed in the middle of a 150 metre gap in drilling. The drill hole contained two significant mineralized intervals:
- 10.17 g/t gold over 6.80 metres, within a broader interval of 3.18 g/t gold over 56.95 metres, beginning at the bedrock surface at 30.20 metres, and
 - 18.57 g/t gold over 13.00 metres, including 132.00 g/t gold over 0.50 metres, within a broader interval of 2.67 g/t over 104.15 metres beginning at 127.15 metres. Figure 3. An image of gold mineralization from this highlight interval is also provided in Figure 6.
- Continuity of gold mineralization is suggested by similar results on both adjacent drill sections:
- Drill section 20750, located 75 100 metres to the northwest of BR-118, includes previously reported drill hole BR-068 which returned 10.58 g/t gold over 21.10 metres (February 13, 2020). Figure 4.
 - Drill section 20600, located 50 75 metres to the southeast of BR-118, includes previously reported drill hole BR-037 which returned 16.60 g/t gold over 6.0 metres, and 5.60 g/t gold over 25.25 metres (October 30, 2019). Figure 5.
- Other new drill highlights include drill hole BR-089 on section 21100, located 450 metres northwest of BR-118. Assays include 18.06 g/t gold over 4.75 metres, which includes 156.00 g/t gold over 0.50 metres, and 11.03 g/t gold over 6.95 metres, which includes 112.00 g/t gold over 0.5 metres. This occurs within a broader interval of 1.93 g/t gold over 52.15 metres.
- Drill hole BR-088 on section 22000, located 900 metres to the northwest of BR-089 and 1.35 kilometres
 to the northwest of BR-118, intersected 0.71 g/t gold over 100.95 metres.

22.05.2025 Seite 1/8

• The Company also relogged and assayed historical drill hole DC-13-07, which was completed in 2007 in the immediate footwall south of the LP Fault by a previous explorer. New assays include 7.87 g/t gold over 2.00 metres, collected from un-sampled, mineralized historic drill core.

Table 1: Current drill results. Drill sections are arranged from southeast (top of Table) to northwest (bottom of Table), corresponding to the map provided in Figure 1.

ir-	s					т.
Drill Hole		From (m)	To (m)	Width* (m)	Gold (g/t)	Section
BR-105		175.00	179.50	4.50	1.35	19900
	and	341.65	344.90	3.25	1.05	
BR-106		318.00	321.00	3.00	0.83	19900
	and	427.15	429.50	2.35	0.61	
BR-104		65.00	69.00	4.00	1.15	19900
	and	77.85	83.00	5.15	1.30	
	and	228.00	240.10	12.10	0.67	
DC-13-07		24.95	26.00	1.05	1.10	19950
	and	105.00	107.00	2.00	7.87	
	including	106.00	107.00	1.00	12.60	
DC-14-07		92.00	93.00	1.00	0.17	19950
BR-103		392.25	396.25	4.00	0.20	19950
	and	417.50	442.00	24.50	0.23	
	and	463.50	464.50	1.00	1.77	
	and	517.75	536.25	18.50	0.87	
	including	523.50	527.00	3.50	2.93	
	and including	526.50	527.00	0.50	16.90	
	and	612.00	624.50	12.50	0.37	

22.05.2025 Seite 2/8

BR-118		30.20	87.15	56.95	3.18	20650
	including	40.00	80.20	40.20	4.42	
	and including	55.10	79.20	24.10	6.00	
	and including	61.70	63.30	1.60	14.91	
	and including	68.40	75.20	6.80	10.17	
	and	127.15	231.30	104.15	2.67	
	including	156.00	184.90	28.90	8.75	
	and including	156.00	169.00	13.00	18.57	
	and including	159.70	169.00	9.30	24.65	
	and including	159.70	162.90	3.20	53.62	
	and including	159.70	160.70	1.00	94.90	
	and including	159.70	160.20	0.50	132.00	
BR-122		446.00	488.00	42.00	0.34	20950
BR-130		165.00	167.50	2.50	2.09	21000
	and	190.25	219.00	28.75	0.33	
BR-131		167.00	169.70	2.70	5.29	21000
	including	168.00	169.20	1.20	11.70	
	and	183.00	187.85	4.85	5.09	
	including	186.50	187.85	1.35	18.02	
	and including	186.50	187.00	0.50	47.70	
	and	324.00	366.30	42.30	0.51	

22.05.2025 Seite 3/8

	ı				1	
BR-089		172.55	182.00	9.45	8.15	21100
	including	172.55	179.50	6.95	11.03	
	including	172.55	175.05	2.50	7.81	
	and including	177.50	178.00	0.50	112.00	
	and	190.50	191.50	1.00	2.86	
	including	191.00	191.50	0.50	5.59	
	and	225.25	228.00	2.75	1.51	
		242.00	293.25	51.25	1.93	
	including	279.00	293.25	14.25	6.18	
	and including	282.50	287.25	4.75	18.06	
	And including	282.50	285.65	3.15	26.89	
	and including	283.65	284.15	0.50	156.00	
BR-099		118.20	138.50	20.30	0.34	21300
	and	291.00	292.00	1.00	4.68	
	and	301.50	322.50	21.00	0.42	
	including	315.00	315.50	0.50	5.46	
	and	446.80	456.00	9.20	2.40	
	including	454.50	456.00	1.50	12.10	
BR-116		288.25	294.25	6.00	0.50	21400
	and	466.60	496.00	29.40	0.39	
	including	492.35	494.15	1.80	3.36	
	and	509.00	513.70	4.70	1.38	
	and	523.35	532.70	9.35	1.10	
	including	527.60	528.70	1.10	7.77	
BR-097		40.60	45.00	4.40	0.15	21400
	and	255.00	259.00	4.00	1.39	
	and	391.70	393.50	1.80	3.49	

22.05.2025 Seite 4/8

BR-098		148.50	153.50	5.00	0.69	21400
	and	310.15	311.65	1.50	1.05	
	and	376.85	396.50	19.65	0.28	
	and	419.70	448.50	28.80	0.65	
	including	431.25	438.00	6.75	2.24	
	and including	431.25	432.65	1.40	8.93	
	and	493.25	495.05	1.80	9.90	
BR-115		428.55	431.00	2.45	0.53	21525
	and	481.80	502.40	20.60	0.43	
	and	527.80	562.65	34.85	0.20	
BR-088		172.50	174.00	1.50	0.70	22000
	and	357.00	366.00	9.00	0.97	
	and	375.35	383.50	8.15	0.74	
	and	449.30	450.45	1.15	3.38	
	and	515.55	616.50	100.95	0.71	
	including	515.55	527.00	11.45	1.38	
	and including	549.95	557.45	7.50	1.12	
	and including	606.30	616.50	10.20	1.80	

*Widths are drill indicated core length, as insufficient drilling has been undertaken to determine true widths at this time. Average grades are calculated with un-capped gold assays, as insufficient drilling has been completed to determine capping levels for higher grade gold intercepts. Average widths are calculated using a 0.10 g/t gold cut-off grade with up to 3 m of internal dilution of zero grade. Drill holes DC-13-07 and DC-14-07 were originally drilled by a past explorer but were assayed by Great Bear, and are located in the immediate footwall south of the LP Fault zone.

Complete assays for the highlighted reported intervals in hole BR-118 are also included graphically within section 20650 in Figure 3 below.

Approximately 200 drill holes remain to be completed as part of the Company's ongoing 2020 LP Fault drill program. Additional drill holes are also planned into the Dixie Limb and Hinge zones, in additional to other regional targets. The Company remains fully funded for this work and does not anticipate requiring further financing in 2020.

22.05.2025 Seite 5/8

Updated drill collar locations, azimuths and dips, together with an updated complete assay table for the LP Fault drilling to-date will be posted to the Company's web site at www.greatbearresources.ca. Drill collar locations, azimuths and dips for the drill holes included in this release are provided in the table below:

Hole ID	Easting Northing Elevation	n Depth	n Dip Azimuth
BR-088	455986 5635191 374	762	-63 225
BR-089	456591 5634475 358	717	-68 214
BR-097	456314 5634687 362	537	-60 220
BR-098	456371 5634762 364	681	-60 220
BR-099	456482 5634659 363	642	-55 220
BR-103	457736 5634241 364	810	-60 210
BR-104	457647 5633886 318	366	-53 206
BR-105	457691 5633975 357	500	-55 207
BR-106	457738 5634071 356	624	-57 207
BR-115	456325 5634908 371	741	-59 220
BR-116	456436 5634848 367	792	-60 220
BR-117	4565545634762364	798	-55 220
BR-118	4569235634183356	771	-68 222
BR-122	456815 5634528 357	777	-54 215
BR-130	4565935634373358	481	-55 215
BR-131	456648 5634454 357	648	-60 218
DC-13-07	457456 5633794 361	200	-50 210
DC-14-07	457489 5633740 360	116	-60 210

Completion of Plan of Arrangement

The Company is pleased to announce that it has received Final TSX Venture Exchange ("TSX-V") approval of the previously announced plan of arrangement ("Arrangement") to reorganize its business, including the spin-off of its wholly-owned subsidiary, Great Bear Royalties Corp. The Arrangement is expected to close as of 12:01 a.m. on May 5, 2020. Existing common shares of Great Bear are expected to be delisted on the TSX-V effective on the close of business on May 4, 2020. New common shares of Great Bear are expected to commence trading on the TSX-V at the market opening on May 5, 2020.

About the Dixie Project

The Dixie Project is 100% owned, comprised of 9,140 hectares of contiguous claims that extend over 22 kilometres, and is located approximately 25 kilometres southeast of the town of Red Lake, Ontario. The project is accessible year-round via a 15 minute drive on a paved highway which runs the length of the northern claim boundary and a network of well-maintained logging roads.

The Dixie Project hosts two principle styles of gold mineralization:

22.05.2025 Seite 6/8

- High-grade gold in quartz veins and silica-sulphide replacement zones (Dixie Limb and Hinge). Hosted by mafic volcanic rocks, and localized near regional-scale D2 fold axes. These mineralization styles are also typical of the significant mined deposits of the Red Lake district.
- High-grade disseminated gold with broad moderate to lower grade envelopes (LP Fault). The LP Fault is a significant gold-hosting structure which has been seismically imaged to extend to 14 kilometres depth (Zeng and Calvert, 2006), and has been interpreted by Great Bear to have up to 18 kilometres of strike length on the Dixie property. High-grade gold mineralization is controlled by structural and geological contacts, and moderate to lower-grade disseminated gold surrounds and flanks the high-grade intervals. The dominant gold-hosting stratigraphy consists of felsic sediments and volcanic units.

About Great Bear

Great Bear Resources Ltd. is a well-financed gold exploration company managed by a team with a track record of success in mineral exploration. Great Bear is focused in the prolific Red Lake gold district in northwest Ontario, where the company controls over 300 km² of highly prospective tenure across 4 projects: the flagship Dixie Project (100% owned), the Pakwash Property (earning a 100% interest), the Dedee Property (earning a 100% interest), and the Sobel Property (earning a 100% interest), all of which are accessible year-round through existing roads.

QA/QC and Core Sampling Protocols

Drill core is logged and sampled in a secure core storage facility located in Red Lake Ontario. Core samples from the program are cut in half, using a diamond cutting saw, and are sent to Activation Laboratories in Ontario, an accredited mineral analysis laboratory, for analysis. All samples are analysed for gold using standard Fire Assay-AA techniques. Samples returning over 10.0 g/t gold are analysed utilizing standard Fire Assay-Gravimetric methods. Pulps from approximately 5% of the gold mineralized samples are submitted for check analysis to a second lab. Selected samples are also chosen for duplicate assay from the coarse reject of the original sample. Selected samples with visible gold are also analyzed with a standard 1 kg metallic screen fire assay. Certified gold reference standards, blanks and field duplicates are routinely inserted into the sample stream, as part of Great Bear's quality control/quality assurance program (QAQC). No QAQC issues were noted with the results reported herein.

Qualified Person and NI 43-101 Disclosure

Mr. R. Bob Singh, P.Geo, Director and VP Exploration, and Ms. Andrea Diakow P.Geo, Exploration Manager for Great Bear are the Qualified Persons as defined by National Instrument 43-101 responsible for the accuracy of technical information contained in this news release.

ON BEHALF OF THE BOARD

"Chris Taylor"

Chris Taylor, President and CEO

Cautionary note regarding forward-looking statements

This release contains certain "forward looking statements" and certain "forward-looking information" as defined under applicable Canadian and U.S. securities laws. Forward-looking statements and information can generally be identified by the use of forward-looking terminology such as "may", "will", "should", "expect", "intend", "estimate", "anticipate", "believe", "continue", "plans" or similar terminology. The forward-looking information contained herein is provided for the purpose of assisting readers in understanding management's current expectations and plans relating to the future. Readers are cautioned that such information may not be appropriate for other purposes.

Forward-looking information are based on management of the parties' reasonable assumptions, estimates,

22.05.2025 Seite 7/8

expectations, analyses and opinions, which are based on such management's experience and perception of trends, current conditions and expected developments, and other factors that management believes are relevant and reasonable in the circumstances, but which may prove to be incorrect.

Great Bear undertakes no obligation to update forward-looking information except as required by applicable law. Such forward-looking information represents management's best judgment based on information currently available. No forward-looking statement can be guaranteed and actual future results may vary materially. Accordingly, readers are advised not to place gundue reliance on forward-looking statements or information.

SOURCE Great Bear Resources Ltd.

Contact

Investor Inquiries: Mr. Knox Henderson, Office: 604-646-8354, Direct: 604-551-2360, info@greatbearresources.ca, www.greatbearresources.ca

Dieser Artikel stammt von Rohstoff-Welt.de Die URL für diesen Artikel lautet:

https://www.rohstoff-welt.de/news/350284--Great-Bear-Resources-Ltd.-Drills-18.57-g~t-Gold-Over-13.00-m-Within-2.67-g~t-Gold-Over-104.15-m-at-LP-Fault.html

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere AGB/Disclaimer!

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt! Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2025. Es gelten unsere <u>AGB</u> und <u>Datenschutzrichtlinen</u>.

22.05.2025 Seite 8/8