

Lara Exploration Ltd: Diamond Drilling Identifies More Extensive Vanadium Mineralization at the Itaituba Project in Brazil

12.04.2021 | [Newsfile](#)

Vancouver, April 12, 2021 - [Lara Exploration Ltd.](#) (TSXV: LRA) ("Lara" or "the Company"), is pleased to report that it has completed a reappraisal of the diamond drilling and ground magnetometer survey results for its Itaituba vanadium project, in the Tapajós region of northern Brazil. Project work initially focused on vanadium-bearing magnetite bodies, but the recent work has shown that the host gabbros also contain disseminated vanadium-bearing magnetite that can be concentrated to enrich the vanadium grade. Surface mapping and the magnetic survey show these gabbros to be extensive within the Lara property and the Company plans to undertake further geophysical surveys and follow-up drilling later in the year.

Half core samples from four scout holes were subjected to Davis Tube Recovery ("DTR") testing and the resulting magnetic concentrates then assayed for vanadium pentoxide ("V2O5"). In the fresh rock sections of three of the holes (holes SR-02, SR-03 and SR-04), significant intervals were identified, where the magnetite concentrate recovery values are in the order of 10 to 20% of the original core sample mass. In two of these holes (SR-03 and SR-04) the V2O5 grades for these concentrates are in the order of 0.8% to 1.1% (see table below). The hole SR-04 has the thickest interval of 47.65m and is still open to depth. The down hole intervals are assumed to be approximately true width, based on the surface mapping information and the drill core logging.

DRILL HOLE	E-UTM	N-UTM	From (m)	To (m)	Width (m)	DTR (%)	V2O5 in concentrate (%)
SR-01	624356	9500481	No significant results				
SR-02	624569	9500559	70.90	75.35	4.45	20.75	0.64
SR-03	624463	9500378	24.03	41.80	17.77	17.34	0.83
SR-04	624362	9500104	25.70	73.35	47.65	11.02	0.91
incl			51.40	55.75	4.35	15.56	1.08
and			66.35	71.85	5.50	14.49	1.15

No significant vanadium enrichment was detected in the magnetic concentrates in the weathered saprolite upper parts of any of the four drill holes. The core logging indicates that the vanadium enriched zones are associated with intercalated units of magnetite-olivine-gabbro and ferro-gabbro. Contacts observed in the cores indicate a sub-horizontal or gently west-dipping attitude for these units consistent with the dips of the overlying massive magnetite bodies.

Review of ground magnetic data indicates that drill hole SR-04 is located central to a large anomaly in the order of 700m (E-W) by 300m to 400m (N-S), at the southern end of the complex, indicating the possibility that the vanadium-bearing disseminated magnetite units could have a large horizontal extent in this southern part of the complex (see Figure 1. below). Holes SR-02 and SR-03, which reported narrower and lower grade vanadium pentoxide intersections, are both located in a similar-sized magnetic anomaly immediately to the north of the SR-04 zone and other strong magnetic anomaly zones are present along the northward extension for a further 2,000m along the main ridge. Surface geological mapping suggests that the entire ridge is underlain by the gabbro complex.

Figure 1

To view an enhanced version of this graphic, please visit:
https://orders.newsfilecorp.com/files/2373/79965_picture1.jpg

Further work is planned, including extensions to the original ground magnetics survey, geological mapping with the objective to identify the more magnetite-rich ferro-gabbro phases within the complex, and drill testing of the priority target unit already identified at the southern end of the complex, as well as scout drilling at

other priority magnetic zones in the central and northern parts of the complex.

Background

Work at the Itaítuba project initially focused on outcropping massive vanadium and titanium bearing magnetite bodies, hosted in a gabbro complex, as a possible direct shipping ore. The surface rock chip sampling indicated that the magnetites contained between 21% and 24% titanium dioxide ("TiO₂") and from 0.35 to 0.5% V₂O₅ (see Lara news release of April 17th, 2012).

Surface geological mapping and the scout drilling of four shallow holes, from 35m to 75m in depth, located in the southern end of the host gabbro complex, show that these magnetite bodies are flat sheet-like bodies from 2m to 8m thick with a shallow westerly dip. The early Quemscan and Davis Tube Recovery testing on selected surface samples suggested that it would not be possible to obtain a concentrate of any better vanadium grade because the titanium and vanadium are both contained within the magnetite crystal structure (see Lara news release of February 11th, 2014).

Logging of the drill core indicated that the massive magnetites are hosted by a multi-phase system of different gabbro intrusives, some of which are extremely enriched in disseminated magnetite (ferro-gabbros). Initial sampling of a few short intervals of these magnetite-rich gabbro phases indicated that it was possible to obtain a magnetite concentrate from some of the samples of between 6.6% and 42.6% of the original sample weight and that these concentrates analyzed V₂O₅ grades from 0.32 % up to 1.03% V₂O₅ with enrichment factors up to 10.8 times the vanadium pentoxide values in the core samples (see Lara news release of February 26th, 2019).

Sampling methodology, Chain of Custody, Quality Assurance and Quality Control

All the rock channel and drill core sampling were carried out by or under the supervision of the Company's Vice-President Exploration and the chain of custody of the samples and drill core from the project area to the Company's sample preparation facilities in Itaítuba and Canãa dos Carajás was continuously monitored.

Sample intervals for the drill core samples varied between 0.2m and 3.0m. The core samples were delivered to the sample preparation laboratories of SGS-Geosol in Parauapebas and to ALS in Goiânia where the samples were crushed and pulverized. SGS-Geosol dispatched sample pulps to their own analytical laboratory at Vespasiano, near Belo Horizonte, Minas Gerais State, Brazil, whereas ALS dispatched the pulps to their dedicated facility in Loughrea, Ireland.

Davis Tube Recovery magnetic concentrates were obtained for each sample, using a magnetic field force of 3000 Gauss and the concentrates, after drying and weighing to determine the percentage of magnetic iron concentrate recovery, were analyzed by XRF for V₂O₅, TiO₂, Fe₂O₃ and seven other oxides after fusion with lithium tetraborate and for Loss on Ignition, which was determined by heating the sample in a furnace at 405 degrees centigrade.

Both SGS-Geosol and ALS inserted blank, certified standard and duplicate samples into each sample batch. Both laboratories are independent from Lara.

Michael Bennell, Lara's Vice President Exploration and a Fellow of the Australasian Institute of Mining and Metallurgy (AusIMM), is a Qualified Person as defined by National Instrument 43-101 Standards of Disclosure for Mineral Projects and has approved the technical disclosure and verified the technical information in this news release.

About Lara Exploration

Lara is an exploration company following the Prospect and Royalty Generator business model, which aims to minimize shareholder dilution and financial risk by generating prospects and exploring them in joint ventures funded by partners, retaining a minority interest and or a royalty. The Company currently holds a diverse portfolio of prospects, deposits and royalties in Brazil, Peru and Chile. Lara's common shares trade on the

TSX Venture Exchange under the symbol "LRA".

For further information on [Lara Exploration Ltd.](http://www.laraexploration.com), please consult our website www.laraexploration.com, or contact Chris MacIntyre, VP Corporate Development, at +1 416 703 0010.

Neither the TSX Venture Exchange nor the Investment Industry Regulatory Organization of Canada accepts responsibility for the adequacy or accuracy of this release.

-30-

To view the source version of this press release, please visit <https://www.newsfilecorp.com/release/79965>

Dieser Artikel stammt von Rohstoff-Welt.de

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/380175--Lara-Exploration-Ltd--Diamond-Drilling-Identifies-More-Extensive-Vanadium-Mineralization-at-the-Itaituba-Project->

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2025. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).