## Founders Metals Expands Upper Antino; Hits 33.0 m of 3.50 g/t Gold

21.05.2025 | Newsfile

Vancouver, May 21, 2025 - Founders Metals Inc. (TSXV: FDR) (OTCQX: FDMIF) (FSE: 9DL0) ("Founders" or the "Company") announces drill core assay results from the Antino Gold Project ("Antino" or "Project") in southeastern Suriname (Figure 1). The Company reports high-grade gold mineralization at Upper Antino including 33.0 metres (m) of 3.50 grams per tonne (g/t) gold (Au) in drilling east of the Main Froyo Shear ("Froyo"). Additional drilling results extend gold mineralization north 125 m, increasing total strike length of Froyo to ~1.7 kilometres (Figure 2).

## **Drilling Highlights**

- Growth-focused drilling expands high-grade gold mineralization in parallel structures (Figures 2 & 3):
  - 33.0 m of 3.50 g/t Au and 19.0 m of 0.84 g/t Au (FR114)
  - 13.0 m of 2.00 g/t Au (FR082)
  - 4.0 m of 5.92 g/t Au (FR105)
- Broad gold zones and 125 m northward extension:
  - 41.9 m of 1.06 g/t Au (FR099)
  - 12.0 m of 1.51 g/t Au and 22.5 m of 0.50 g/t Au (FR101), extending gold mineralization north in two parallel mineralized zones

Colin Padget, President & CEO, commented, "These results clearly demonstrate Upper Antino's growth potential in multiple directions. Gold mineralization continues eastward over substantial intervals while our step-out drilling has successfully expanded the northern boundary by 125 metres. The two broad intervals in hole FR114 align well with our mineralization and structural models and suggest there is potential to 'connect-the-dots' between Froyo and Donut. Additionally, while we have seen some increases in assay turnaround times and have been focusing on certain corporate items, we anticipate releasing additional results from our earlier-stage exploration targets along-side a comprehensive overview in the coming weeks."

Drilling continues to expand Upper Antino gold mineralization and Figure 4 provides a 12-month snapshot showing the growth of the mineralized footprint over that time. In this release, drill hole FR114 intersecting 33.0 m of 3.50 g/t Au, is one of several holes planned to target further eastward growth of Froyo gold mineralization and determine if additional parallel zones link Froyo with the Donut target. Drillhole FR101 intercepted two distinct zones of mineralization with the shallower 22.50 m interval of 0.5 g/t Au beginning at 27.60 m and potentially a new shear as the deeper 12 m of 1.51 g/t Au aligns well with the previously reported 8.0 m of 2.08 g/t Au in hole FR095. These are encouraging intercepts indicating additional northward potential and drill holes are planned further north to continue testing these structures.

About Founders Metals Inc.

Founders Metals is a Canadian-based exploration company focused on advancing the Antino Gold Project located in Suriname, South America, in the heart of the Guiana Shield. Antino is 20,000 hectares and has produced over 500,000 ounces of gold from surface and alluvial mining to date<sup>1</sup>. The Company is fully financed for up to 60,000 metres of drilling in 2025.

<sup>1</sup> 2022 Technical Report - Antino Project; Suriname, South America. K. Raffle, BSc, P. Geo & Rock Lefrançois, BSc, P.Geo.

Table 1: Drill Hole Assay Results

Hole ID From (m) To (m) Interval\* (m) Au (g/t) FR114 201.00 206.005.00 0.47

23.05.2025 Seite 1/4

| Hole ID | From (m) | To (m) | Interval* (m) | Au (g/t) |
|---------|----------|--------|---------------|----------|
| and     | , ,      | 253.00 | , ,           | 3.50     |
| and     | 361.00   | 380.00 | 19.00         | 0.84     |
| FR109   |          |        | NSA           |          |
| FR108   | 24.00    | 30.00  | 6.00          | 0.22     |
| FR106   |          |        | NSA           |          |
| FR105   | 372.00   | 376.00 | 4.00          | 5.92     |
| and     | 439.00   | 451.00 |               | 0.28     |
| FR101   |          | 50.10  |               | 0.50     |
| and     | 306.00   | 318.00 |               | 1.51     |
| FR100   | 0.00     | 8.10   | 8.10          | 0.31     |
| and     | 110.00   | 112.00 | 2.00          | 2.41     |
| FR099   | 29.10    | 71.00  | 41.90         | 1.06     |
| and     | 212.00   | 224.00 |               | 0.38     |
| FR098   | 67.00    | 78.00  | 11.00         | 0.32     |
| FR097   | 84.00    | 95.00  | 11.00         | 0.86     |
| and     | 133.00   | 155.00 | 22.00         | 0.26     |
| FR096   | 0.00     | 14.10  | 14.10         | 0.35     |
| and     | 206.00   | 212.00 | 6.00          | 1.09     |
| FR094   | 99.00    | 111.00 | 12.00         | 0.79     |
| and     | 217.00   | 223.00 | 6.00          | 0.61     |
| FR085   | 340.00   | 356.00 | 16.00         | 0.46     |
| and     | 287.00   | 288.00 | 1.00          | 13.70    |
| FR084   | 92.10    | 96.60  | 4.50          | 0.72     |
| and     | 152.00   | 157.00 | 5.00          | 2.22     |
| FR083   |          |        | NSA           |          |
| FR082   | 14.10    | 20.10  | 6.00          | 0.47     |
| and     | 297.00   | 314.00 | 17.00         | 0.50     |
| and     | 396.00   | 409.00 | 13.00         | 2.00     |
| EV003   | 142.00   | 146.00 | 4.00          | 3.23     |
| EV002   | 166.00   | 171.00 | 5.00          | 1.69     |
| EV001   |          |        | NSA           |          |
|         |          |        |               |          |

<sup>\*</sup>Intervals are down-hole depths. True widths of mineralization are estimated to be approximately 85% of the down-hole interval based on preliminary results and observations. All are diamond drill holes.

Table 2: Drill Hole Location

| Hole ID | Easting (m) | Northing (m) | Elevation ( | m) Azimuth ( | °) Dip (°) Depth (m) |
|---------|-------------|--------------|-------------|--------------|----------------------|
| FR114   | 817305.40   | 401269.27    | 150.73      | 250.20       | -55.10578.03         |
| FR109   | 816949.97   | 401985.23    | 174.91      | 260.00       | -50.40 305.00        |
| FR108   | 817340.15   | 402062.76    | 240.08      | 260.00       | -49.60 171.60        |
| FR106   | 817242.90   | 402026.11    | 243.03      | 259.80       | -50.00 285.40        |
| FR105   | 817348.54   | 401449.94    | 205.99      | 250.40       | -50.00 551.00        |
| FR101   | 817140.66   | 402020.24    | 222.27      | 259.80       | -50.00 332.00        |
| FR100   | 817181.50   | 401652.99    | 152.07      | 259.90       | -60.00 302.10        |
| FR099   | 817020.28   | 401616.99    | 159.05      | 260.40       | -69.80 317.06        |
| FR098   | 816803.12   | 401776.65    | 161.39      | 259.70       | -50.10259.98         |
| FR097   | 816854.85   | 401713.07    | 160.50      | 259.80       | -50.50 293.14        |
| FR096   | 816927.39   | 401661.02    | 161.00      | 260.00       | -50.00 314.04        |
| FR094   | 817042.86   | 401766.69    | 160.99      | 260.00       | -45.00 317.00        |
| FR085   | 817235.12   | 401493.15    | 209.93      | 250.20       | -49.80 472.96        |
| FR084   | 817339.38   | 400826.82    | 208.16      | 240.00       | -55.00 362.00        |
| FR083   | 817163.75   | 401453.62    | 214.58      | 249.60       | -49.80 371.01        |
| FR082   | 817249.02   | 401415.71    | 206.01      | 250.10       | -50.00 439.80        |
| EV003   | 817458.20   | 401129.11    | 162.83      | 235.63       | -56.10 259.66        |
| EV002   | 817475.32   | 400916.25    | 199.46      | 229.91       | -50.84 275.04        |
|         |             |              |             |              |                      |

23.05.2025 Seite 2/4

EV001 817397.23 401073.51 176.66 233.97 -52.20278.12

The coordinate reference system is WGS 84, UTM zone 21N (EPSG 32621)

Figure 1: Antino Property Map

To view an enhanced version of this graphic, please visit: https://images.newsfilecorp.com/files/7574/252894\_dfc006ac9459eaf6\_001full.jpg

Figure 2: Plan Map

To view an enhanced version of this graphic, please visit: https://images.newsfilecorp.com/files/7574/252894\_dfc006ac9459eaf6\_002full.jpg

Figure 3: Cross-Section

To view an enhanced version of this graphic, please visit: https://images.newsfilecorp.com/files/7574/252894\_dfc006ac9459eaf6\_003full.jpg

Figure 4: Upper Antino Gold Footprint - 12-month Snapshot

To view an enhanced version of this graphic, please visit: https://images.newsfilecorp.com/files/7574/252894\_dfc006ac9459eaf6\_004full.jpg

**Quality Assurance and Control** 

Samples were analyzed at FILAB Suriname, a Bureau Veritas Certified Laboratory in Paramaribo, Suriname (a commercial certified laboratory under ISO 9001:2015). Samples are crushed to 75% passing 2.35 mm screen, riffle split (700 g) and pulverized to 85% passing 88 µm. Samples were analyzed using a 50 g fire assay (50 g aliquot) with an Atomic Absorption (AA) finish. For samples that return assay values over 5.0 grams per tonne (g/t), another cut was taken from the original pulp and fire assayed with a gravimetric finish. Founders Metals inserts blanks and certified reference standards in the sample sequence for quality control. External QA-QC checks are performed at ALS Global Laboratories (Geochemistry Division) in Lima, Peru (an ISO/IEC 17025:2017 accredited facility). A secure chain of custody is maintained in transporting and storing of all samples. Drill intervals with visible gold are assayed using metallic screening. Rock chip samples from outcrop/bedrock are selective by nature and may not be representative of the mineralization hosted on the project.

**Qualified Persons** 

The technical content of this news release has been reviewed and approved by Michael Dufresne, M.Sc., P.Geol., P.Geo., an independent qualified person as defined by National Instrument 43-101.

23.05.2025 Seite 3/4

## ON BEHALF OF THE BOARD OF DIRECTORS,

Per: "Colin Padget"

Colin Padget President, Chief Executive Officer, and Director

**Contact Information** 

Katie MacKenzie, Vice President, Corporate Development Tel: 306 537 8903 | katiem@fdrmetals.com

Cautionary Statement Regarding Forward-Looking Information

This press release contains "forward-looking information" within the meaning of applicable Canadian securities legislation. Forward-looking information includes, without limitation, statements regarding the use of proceeds from the Company's recently completed financings and the future or prospects of the Company. Generally, forward-looking information can be identified by the use of forward-looking terminology such as "plans", "expects" or "does not expect ", "is expected ", "budget", "scheduled", "estimates", "forecasts", "intends", "anticipates" or "does not anticipate", or "believes", or variations of such words and phrases or state that certain actions, events or results "may", "could", "would", "might" or "will be taken", "occur" or "be achieved". Forward-looking statements are necessarily based upon a number of assumptions that, while considered reasonable by management, are inherently subject to business, market, and economic risks, uncertainties, and contingencies that may cause actual results, performance, or achievements to be materially different from those expressed or implied by forward-looking statements. Although the Company has attempted to identify important factors that could cause actual results to differ materially from those contained in forward-looking information, other factors may cause results not to be as anticipated, estimated, or intended. There can be no assurance that such information will prove to be accurate, as actual results and future events could differ materially from those anticipated in such statements. Accordingly, readers should not place undue reliance on forward-looking information. Other factors which could materially affect such forward-looking information are described in the risk factors in the Company's most recent annual management discussion and analysis. The Company does not undertake to update any forward-looking information except in accordance with applicable securities laws.

All material information on Founders Metals can be found at www.sedarplus.ca.

To view the source version of this press release, please visit https://www.newsfilecorp.com/release/252894

Dieser Artikel stammt von Rohstoff-Welt.de
Die URL für diesen Artikel lautet:
https://www.rohstoff-welt.de/news/692821--Founders-Metals-Expands-Upper-Antino-Hits-33.0-m-of-3.50-g~t-Gold.html

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere AGB/Disclaimer!

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt! Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2025. Es gelten unsere AGB und Datenschutzrichtlinen.

23.05.2025 Seite 4/4