

Orocobre Completes Grid Auger Drilling at Salinas Grandes Lithium-Potash Project

21.11.2011 | [Marketwired](#)

Highlights

- Follow up auger drilling program completed at the Salinas Grandes Lithium-Potash Project, with an average hole spacing of 1.7 km.
- Auger drilling has defined the shallow stratigraphy and areas of higher permeability (sand).
- Auger drilling results average 9,950 mg/l K, 825 mg/l Li and 2,226 mg/l Mg, with a Mg/Li ratio of 2.7 over an average hole depth of 9.6 m.
- Results confirm the lithium grades and distribution in previous Orocobre pit sampling and in the upper zone intersected with the recent diamond drilling.
- Brine chemistry is attractive, with a low Mg/Li ratio, high K/Li ratio and low sulphate and calcium levels. High recoveries of both potassium and lithium could be expected using a simple, low operating cost, process route.
- Porosity results received from the British Geological Survey show similar values to the Olaroz project for the same sediment types. Pump testing is underway on auger holes and two, 8 inch diameter test wells.
- Resource modeling has commenced. Guidance on brine extractability will be provided with the resource estimate.

BRISBANE, AUSTRALIA -- ([Marketwire](#) - Nov. 20, 2011) - [Orocobre Limited](#) - Orocobre Limited (TSX:ORL) (ASX:ORE) (the Company or Orocobre) is pleased to announce the completion of a grid auger drilling program on the Salinas Grandes Lithium-Potash project ("Salinas Grandes") in Salta Province, North West Argentina as shown Figure 1 and is available on http://www.orocobre.com/Maps/Salinas_Olaroz_Fig1_16Nov11.jpg

Orocobre Managing Director, Richard Seville, stated, "We are pleased to have the additional level of information from the auger drilling program at Salinas Grandes. This complements the previous diamond drilling, increases the density of sample points and provides a solid information base for resource modeling."

"We have received the results of specific yield porosity determinations made at the British Geological Survey Laboratories. These results are very similar to those at our Olaroz project for the same sediment types and will be used in the resource estimate."

"Pump testing of the auger drill holes is underway to provide information on variations in permeability and flow rates across the salar. Two pumping test installations with 8 inch bore holes have been drilled to allow the undertaking of longer term constant flow rate tests. This information will be used to assess the extractability of the brine, with guidance on this aspect of the project to be provided at the same time as the resource estimate."

Auger Drilling Results

A total of 47 solid stem auger holes were drilled on a north-south oriented grid, with an average spacing of 1.7 km between drill holes. Holes were drilled vertically to depths of 2m to 20 m, depending on access conditions within the salar. Geological samples were logged and results compiled on geological sections, which show a significant increase in sand on the northern margins of the salar, where sand has been sourced from the northern alluvial fan. Locations of the auger holes are shown in Figure 2 below and is available on http://www.orocobre.com/Maps/Salinas_Fig2_16Nov11.jpg.

Samples were collected during the drilling by bailing brine from the hole every 4 metres (and at 2 m in 4 m deep holes). The upper 4 m sample is representative of the interval 0-4 m, the deeper samples (4-8 m, 8-12

m, 12-16 m, 16-20 m) are composites from the hole to the depth at the point of sampling. Average results for each auger hole are presented in Table 1.

It should be noted the composite values are influenced by the lithium concentrations in each lithological unit and the permeability of individual lithological units, with higher permeability units influencing brine sample compositions more than lower permeability units. The shallow brine body occurs over an area of approximately 170 square kilometres, of which approximately 110 square kilometres are located within Orocobre's properties.

Samples in the shallow brine body exhibit attractively low Mg/Li ratios, averaging 2.7 for all samples, with lithium values from 0-4 m samples shown in Figure 3. Sulphate levels are low, ranging from 947 mg/l on the margins of the salar to an isolated maximum of 11,978 mg/l within the salar, with an average of 3,628 mg/l. Within the zone of >1,000 mg/l Li in the 0-4 m samples sulphate averages 3,572 mg/l.

The shallow brine body is hosted in a sequence of sand, silt and clay units, with an increase in sand content in the north of the salar. Halite is limited to a maximum thickness of 0.5 m from surface in the center-south of the salar. The elevated lithium brine concentrations encountered during auger sampling correlate well with the distribution of elevated lithium values from previous pit sampling as shown in Figure 3 below and is available at http://www.orocobre.com/Maps/Salinas_Fig3_16Nov11.jpg.

Resource estimation and porosity/permeability measurements

Specific yield porosity determinations have been received for cores samples analysed by the British Geological Survey. The results are similar to those obtained at the company's Olaroz project for the same types of sediments.

The specific yield porosity data, auger drilling and previous diamond drilling results will be used to undertake a resource estimate on the shallow brine body. Guidance on the potential for extraction of the brine will be released with the resource estimate.

Quality Assurance/Quality Control

Auger drilling was conducted with 110 mm diameter solid stem augers, without use of drilling fluids. Sediment samples were collected from the augers and geologically logged, with samples preserved in chip boxes. Single valve steel bailers were used to obtain brine samples once drill holes were purged of water.

Brine samples were submitted to Alex Stuart Assayers (ASA) in Mendoza, Argentina. This ASA laboratory has extensive experience analyzing lithium bearing brines. They are ISO 9001 accredited, and operate according to Alex Stewart Group standards consistent with ISO 17025 methods at other laboratories.

Laboratory prepared standards were submitted in all sample batches sent to ASA, with a minimum of one standard every 5 primary samples. Three standards with different ranges were used to evaluate laboratory performance. Duplicate samples were submitted with one duplicate every ten primary samples.

Overall the analyses are considered to be of acceptable quality, based on the results of the QA/QC samples. The results have been verified by Murray Brooker, Geological and Hydrogeological Consultant, who is a Qualified Person as defined in NI 43-101.

About Orocobre Limited

[Orocobre Limited](http://www.orocobre.com) is listed on the Australian Securities Exchange and Toronto Stock Exchange (ASX:ORE) (TSX:ORL) and is the leading lithium-potash developer in the lithium and potassium rich Puna region of Argentina. For further information, please visit www.orocobre.com.

Competent Person's and Qualified Person's Statement

The technical information in this announcement has been prepared by Murray Brooker. Murray Brooker is a geologist and hydrogeologist and is a Member of the Australian Institute of Geoscientists. Murray has sufficient relevant experience to qualify as a competent person as defined in the 2004 edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves. He is also a "Qualified Person" as defined by Canadian Securities Administrators' National Instrument 43-101. Murray Brooker consents to the inclusion in this announcement of this information in the form and context in which it

appears.

Additional information relating to the Company's Salinas Grandes project is available in the existing technical report entitled "Technical Report – Salinas Grandes Project, Argentina" dated April 30, 2010, which was prepared by John Houston, and in the Company's press release.

Caution Regarding Forward-Looking Information

This report contains "forward-looking information" within the meaning of applicable securities legislation. Forward-looking information contained in this report may include, but is not limited to, the estimation and realization of resources at the Salinas Grandes project, the viability, recoverability and processing of such resources, potential operating synergies between the Salinas Grandes project and the Olaroz project, and other matters related to the development of the Salinas Grandes project.

Such forward-looking information is subject to known and unknown risks, uncertainties and other factors that may cause actual results to be materially different from those expressed or implied by such forward-looking information, including but not limited to the risk that further funding may be required, but unavailable, for the ongoing development of the Company's projects; changes in government regulations, policies or legislation; fluctuations or decreases in commodity prices; the possibility that required permits may not be obtained; uncertainty in the estimation or economic viability of mineral resources; general risks associated with the feasibility and development of the Salinas Grandes project; unexpected capital or operating cost increases; the risk that a definitive joint venture agreement with Toyota Tsusho Corporation in respect of the Company's Olaroz project may not be completed; uncertainty of meeting anticipated program milestones; as well as those factors disclosed in the Company's Annual Information Form for the year ended June 30, 2010 filed at www.sedar.com.

The Company believes that the assumptions and expectations reflected in such forward-looking information are reasonable. Assumptions have been made regarding, among other things: the Company's ability to carry on its exploration and development activities, the timely receipt of required approvals, the prices of lithium and potash, the ability of the Company to operate in a safe, efficient and effective manner and the ability of the Company to obtain financing as and when required and on reasonable terms. Readers are cautioned that the foregoing list is not exhaustive of all factors and assumptions which may have been used.

There can be no assurance that forward-looking information will prove to be accurate, as actual results and future events could differ materially from those anticipated in such information. Accordingly, readers should not place undue reliance on forward-looking information. The Company does not undertake to update any forward-looking information, except in accordance with applicable securities laws.

Table 1: Drilling results as averages per hole

Hole ID (m)	From		To		Intersection		Mg/Li		
	K mg/l		Li mg/l		Mg mg/l				
HCJ001HY	0		12	12	6,336		548		1,223
HCJ002HY	0		4	4	10,887		1098		2,698
HCJ003HY	0		12	12	8,958		684		1,700
HCJ004HY	0		4	4	10,284		962		2,319
HCJ005HY	0		4	4	13,872		1107		2,620
HCJ006HY	0		4	4	18,553		1601		4,889
HCJ007HY	0		8	8	4,289		257	494	1.9
HCJ008HY	0		8	8	7,910		558	1,249	2.0
HCJ009HY	0		12	12	12,647		1049	2,632	
HCJ010HY	0		16	16	2,888		181	338	
HCJ011HY	0		12	12	7,894		599	1,648	
HCJ012HY	0		12	12	13,831		1117	3,008	
HCJ013HY	0		16	16	8,342		752	2,103	
HCJ014HY	0		12	12	7,946		733	2,119	
HCJ015HY	0		12	12	9,398		714	1,790	
HCJ016HY	0		20	20	9,251		744	2,104	
HCJ017HY	0		4	4	17,959		1546	4,691	
HCJ018HY	0		4	4	9,378		775	2,042	2.0
HCJ019HY	0		8	8	9,711		747	2,079	2.0
HCJ020HY	0		12	12	9,994		822	2,168	
HCJ021HY	0		13	12.5	10,827		868	2,587	
HCJ022HY	0		12	12	7,187		539	1,498	
HCJ023HY	0		13	12.5	10,072		809	2,409	
HCJ024HY	0		12	12	9,502		784	1,763	
HCJ025HY	0		12	12	14,735		1356	3,714	
HCJ026HY	0		16	16	9,804		816	2,148	
HCJ027HY	0		12	12	8,852		705	1,744	
HCJ028HY	0		12	12	10,434		878	2,396	
HCJ029HY	0		12	12	8,472		702	1,775	
HCJ030HY	0		4	4	18,459		1608	5,034	
HCJ031HY	0		12	12	15,906		1243	3,625	
HCJ032HY	0		12	12	13,049		1136	3,123	
HCJ033HY	0		12	12	10,990		969	2,590	
HCJ034HY	0		8	8	10,133		858	2,292	
HCJ035HY	0		12	12	6,702		343	496	
HCJ036HY	0		12	12	11,638		1043	2,631	
HCJ037HY	0		12	12	9,450		759	1,744	
HCJ038HY	0		12	12	12,846		1089	3,313	
HCJ039HY	0		12	12	13,282		1079	3,259	
HCJ040HY	0		2	2	131		10	38	3.7
HCJ041HY	0		4	4	333		15	80	5.4
HCJ042HY	0		4	4	12,664		1035	2,961	
HCJ043HY	0		13	12.5	11,896		992	3,223	
HCJ044HY	0		4	4	13,070		1267	3,605	
HCJ045HY	0		4	4	6,024		417	806	1.9
HCJ046HY	0		4	4	6,862		467	934	2.0
HCJ047HY	0		2	2	4,103		478	916	1.9
Average shallow body			9.6		9,950		825	2,226	2.7

ABN 31 112 589 910

Contact

Orocobre Limited
 Richard Seville
 Managing Director
 M +61 419 916 338

Orocobre Limited
 Bruce Rose
 VP - Corporate Development

M + 1 (604) 377 1423
brose@orocobre.com
www.orocobre.com

Dieser Artikel stammt von Rohstoff-Welt.de

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/123659--Orocobre-Completes-Grid-Auger-Drilling-at-Salinas-Grandes-Lithium-Potash-Project.html>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).