

Rock Tech Drills 50 metres of 3.08% Graphite at Lochaber

18.03.2013 | [The Newswire](#)

Mar 18th, 2013 Copyright (c) 2013 TheNewswire - All rights reserved.

(via Thenewswire.ca)

Vancouver, British Columbia, Canada, March 18, 2013 - [Rock Tech Lithium Inc.](#) (TSX-V: RCK; Frankfurt: RJIA) (the "Company" or "Rock Tech") announces assay results for two more drill holes from the drill program it announced on December 10, 2012. This planned 4,600 metre drill program included both step-out and in-fill drill holes and focused primarily on electromagnetic conductors 'A' and 'C'. The electromagnetic conductors were identified on the Plumbago area of the property during geophysical surveys in September, 2012 (click here to view a map).

Highlights of these assay results include:

-Drill hole PB-12-22 intersected 84.56 metres of graphitic carbon ("Cg") at various depths with grades ranging from 1.11% Cg to 4.42% Cg, including 50 metres at 3.08% Cg,

-Drill hole PB-12-23 intersected 117.99 metres of graphitic carbon ("Cg") at various depths with grades ranging from 1.30% Cg to 3.63% Cg, including 5.37 metres at 3.63% Cg, 43.08 metres at 2.28% Cg, and 41.02 metres at 2.45% Cg.

Both drill holes were located on electromagnetic conductor 'C'.

"To date we have traced the graphite mineralization of electromagnetic conductor 'C' for 600 metres along strike with widths ranging from 29 metres to 165 metres. While this conductor is constrained to the south by our property boundary, it remains open to the north and at depth. The Company is also expecting preliminary data from metallurgical tests defining the flake size distribution and purity of the mineralized zones delineated on electromagnetics conductors 'A' and 'C'", said Afzaal Pirzada, Rock Tech's Vice President of Exploration and interim CEO.

To date, the Company has received and announced assay results for twenty three drill holes and seven trenches. Assay results for the final twelve drill holes completed during the fourth quarter of 2012 are pending along with resubmitted core samples from the first phase of drilling.

Quality Assurance/Quality Control

All core samples are logged and split by wet diamond saw with half sent to the lab for analysis and half

stored securely on site. The core sample lengths typically average 1 metre but vary depending on geological boundaries. Additional QA/QC procedures include inserting blanks and standards into the core sample stream at industry standard intervals with duplicate core samples taken at intervals of twenty. Core samples are prepped and analyzed by Global Mineral Research Limited in Burnaby, British Columbia. During analysis, the core samples are dried, pulverized, leached and roasted at 450° Celsius and 1200° Celsius with measured weights taken between double ignitions. The laboratories also conduct duplicate and internal standard samples at intervals of ten as part of their QA/QC program.

For additional details, please see the table below:

Drill Hole ID	?	Length From	Length To	Width	Graphite	Geophysical Conductor
	?	Metres	Metres	Metres	%	
PB-12-22	?	57.00	71.36	14.36	1.11	C
	?	106.10	115.70	9.60	4.42	
	?	133.10	137.00	3.90	1.64	
	?	137.00	187.00	50.00	3.08	
	including	140.93	148.00	7.07	6.85	
	including	172.00	175.00	3.00	5.67	
	?	220.30	226.00	5.70	1.26	
PB-12-23	?	2.20	7.00	4.80	1.32	C
	?	26.15	41.00	14.85	1.33	
	?	54.09	62.96	8.87	1.30	
	?	88.49	93.86	5.37	3.63	
	?	98.86	141.94	43.08	2.28	
	?	156.98	198.00	41.02	2.45	
	?					

Note: The true thickness of the drill intersection may be less than the reported intervals

Drill hole PB-12-22 is located at 474760E, 5055328N (NAD 1983, Zone 18N) with azimuth 90° and dip -50°, drill hole PB-12-23 is located at 474750E, 5055249N (NAD 1983, Zone 18N) with azimuth 108.8° and dip -50.2°.

The technical information contained in this news release has been reviewed by Afzaal Pirzada, P.Geol., Vice President of Exploration and interim CEO of the Company and a Qualified Person as defined in NI 43-101.

On behalf of the Board of Directors,

"Afzaal Pirzada"

Afzaal Pirzada, P.Geo.

Director, Vice President of Exploration and interim CEO

For more information, please contact:

Brad Barnett

Vice President of Corporate Finance and Development

[Rock Tech Lithium Inc.](#)

789 West Pender Street, Suite 1205

Vancouver, B.C., V6C 1H2

Telephone: (604) 688-1140

Facsimile: (604) 688-1173

Email: bbarnett@rocktechlithium.com

Disclaimer and Cautionary Statement Regarding Forward-Looking Information

Neither the TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this press release. This news release shall not constitute an offer to sell or the solicitation of an offer to buy securities in any jurisdiction.

All statements, trend analysis and other information contained in this press release relative to markets about anticipated future events or results constitute forward-looking statements. Forward-looking statements are often, but not always, identified by the use of words such as "seek", "anticipate", "believe", "plan", "estimate", "expect" and "intend" and statements that an event or result "may", "will", "should", "could" or "might" occur or be achieved and other similar expressions. Forward-looking statements are subject to business and economic risks and uncertainties and other factors that could cause actual results of operations to differ materially from those contained in the forward-looking statements. Forward-looking statements are based on estimates and opinions of management at the date the statements are made. The Company does not undertake any obligation to update forward-looking statements even if circumstances or management's

estimates or opinions should change. Investors should not place undue reliance on forward-looking statements.

Copyright (c) 2013 TheNewswire - All rights reserved.

Dieser Artikel stammt von Rohstoff-Welt.de

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/145154--Rock-Tech-Drills-50-metres-of-3.08Prozent-Graphite-at-Lochaber.html>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).