

Barkerville Gold Mines Reports Whole Hole Metallic Screen Fire with Minor Lead Collection/Gravimetric Assay Results of Twenty Nine Diamond Drill Holes Conducted on Cow Mountain

24.03.2014 | [The Newswire](#)

Vancouver, BC / TNW-ACCESSWIRE / March 24, 2014 / [Barkerville Gold Mines Ltd.](#) (TSXV: BGM) (the "Company") announced today, results from complete hole metallic screen fire with minor lead collection/gravimetric assay results of twenty nine diamond drill holes conducted on Cow Mountain in 2011.

As recommended in the Company's NI 43-101 report dated December 31, 2012 (the "Technical Report", see News Release dated June 19 2013) and mentioned in the news release dated December 9, 2013, all reject samples from drill core that was originally analyzed in 2011 with standard fire assays and unassayed infill core samples from those same holes collected in 2013 have been sent for 1,000 g metallic screen and 50 g lead collection/gravimetric fire assay. Considering coarse grained gold is common in the area it has been determined that the original 30 g standard fire assay method possibly undervalued gold grade. Once all drill data has been received, the Company will provide a comparative analysis between new and original drill data. The Company will also provide an updated NI 43-101 resource estimate.

Metallic screen fire assay results of twenty nine drill holes have been received and significant intercepts are listed in Table 1. Highlights include:

CM11-32

-2.6 meters (8.6 feet) of 14.28 g/T (0.416 oz/t) gold between 50.0 and 52.6 meters (164.0 and 172.6 feet)

CM11-52

-0.7 meters (2.4 feet) of 67.64 g/T (1.973 oz/t) gold between 288.4 and 289.1 meters (946.2 and 948.6 feet)

-10.1 meters (33.0 feet) of 7.11 g/T (0.207 oz/t) gold between 378.0 and 388.0 meters (1,240.0 and 1,273.0 feet)

o.including 2.9 meters (9.6 feet) of 11.29 g/T (0.329 oz/t) gold between 378.0 and 380.9 meters (1,240.0 and 1,249.6 feet)

-1.6 meters (5.4 feet) of 11.48 g/T (0.335 oz/t) gold between 395.5 and 397.2 meters (1,297.6 and 1,303.0 feet)

CM11-62

-1.7 meters (5.6 feet) of 9.66 g/T (0.282 oz/t) gold between 34.1 and 35.8 meters (112.0 and 117.6 feet)

-1.7 meters (5.6 feet) of 6.90 g/T (0.201 oz/t) gold between 69.0 and 70.7 meters (226.4 and 232.0 feet)

CM11-63

-2.7 meters (9.0 feet) of 6.81 g/T (0.199 oz/t) gold between 111.0 and 113.8 meters (364.2 and 373.2 feet)

-3.2 meters (10.5 feet) of 7.24 g/T (0.211 oz/t) gold between 236.3 and 239.5 meters (775.1 and 785.6 feet)

-5.3 meters (17.4 feet) of 85.48 g/T (2.493 oz/t) gold between 273.7 and 279.0 meters (897.9 and 915.3 feet)

o.including 2.3 meters (7.6 feet) of 194.9 g/T (5.684 oz/t) gold between 273.7 and 276.0 meters (897.9 and 905.5 feet)

CM11-65A

-2.8 meters (9.3 feet) of 7.115 g/T (0.208 oz/t) gold between 80.0 and 82.8 meters (262.5 and 271.8 feet)

CM11-80B

-2.2 meters (7.2 feet) of 8.24 g/T (0.240 oz/t) gold between 127.1 and 129.3 meters (417.0 and 424.2 feet)

CM11-85

-1.8 meters (5.8 feet) of 13.75 g/T (0.401 oz/t) gold between 284.7 and 286.5 meters (934.2 and 940.0 feet)

CM11-86

-10.2 meters (33.6 feet) of 16.22 g/T (0.473 oz/t) gold between 181.8 and 192.0 meters (596.4 and 630.0 feet)

o.including 2.3 meters (7.6 feet) of 61.86 g/T (1.804 oz/t) gold between 188.4 and 190.7 meters (618.1 and 625.7 feet)

CM11-88

-2.4 meters (7.9 feet) of 23.14 g/T (0.675 oz/t) gold between 233.8 and 236.2 meters (767.0 and 774.9 feet)

CM11-91

-2.9 meters (9.6 feet) of 11.28 g/T (0.329 oz/t) gold between 170.9 and 173.8 meters (560.6 and 570.2 feet)

CM11-97

-0.5 meters (1.8 feet) of 63.44 g/T (1.850 oz/t) gold between 78.2 and 78.7 meters (256.5 and 258.3 feet)

-2.0 meters (6.5 feet) of 6.20 g/T (0.181 oz/t) gold between 100.6 and 102.5 meters (329.9 and 336.4 feet)

CM11-99

-4.4 meters (14.5 feet) of 8.00 g/T (0.233 oz/t) gold between 112.6 and 117.0 meters (369.3 and 383.8 feet)

-1.3 meters (4.2 feet) of 9.07 g/T (0.265 oz/t) gold between 190.4 and 191.7 meters (624.7 and 628.9 feet)

CM11-105

-2.5 meters (8.2 feet) of 9.08 g/T (0.265 oz/t) gold between 26.5 and 29.0 meters (87.0 and 95.2 feet)

-2.9 meters (9.6 feet) of 12.20 g/T (0.356 oz/t) gold between 176.0 and 178.9 meters (577.4 and 587.0 feet)

-2.9 meters (9.4 feet) of 17.36 g/T (0.506 oz/t) gold between 223.3 and 226.2 meters (732.6 and 742.0 feet)

o.including 1.9 meters (6.2 feet) of 25.98 g/T (0.758 oz/t) gold between 224.3 and 226.2 meters (735.8 and 742.0 feet)

CM11-106

-2.0 meters (6.7 feet) of 13.00 g/T (0.379 oz/t) gold between 44.8 and 46.8 meters (147.0 and 153.7 feet)

CM11-107

-1.4 meters (4.5 feet) of 8.29 g/T (0.242 oz/t) gold between 226.8 and 228.2 meters (744.2 and 748.7 feet)

CM11-108

-1.3 meters (4.4 feet) of 9.20 g/T (0.268 oz/t) gold between 112.5 and 113.8 meters (369.0 and 373.4 feet)

CM11-109

-1.2 meters (4.0 feet) of 23.38 g/T (0.682 oz/t) gold between 215.5 and 216.7 meters (707.0 and 711.0 feet)

CM11-124

-1.1 meters (3.6 feet) of 7.12 g/T (0.208 oz/t) gold between 153.8 and 254.9 meters (504.7 and 508.3 feet)

Table 1. SIGNIFICANT INTERCEPTS OF THE WHOLE HOLE METALLIC SCREEN FIRE
WITH MINOR LEAD COLLECTION/GRAVIMETRIC ASSAYS OF BOTH REJECT & INFILL CORE
SAMPLES OF DRILL HOLES CONDUCTED ON COW MOUNTIAN IN 2011

HOLE ID	CORE SAMPLING INTERVAL				METALLIC FIRE ASSAY	
	From	To	WIDTH			
	Feet			Meter	Au (g/T)	Au (oz./t)
CM11-32	164.0	172.6	8.6	2.6	14.28	0.416
	176.4	180.9	4.5	1.4	1.03	0.030
	423.2	425.2	2.0	0.6	3.40	0.099
	465.5	467.5	2.0	0.6	17.13	0.500
	552.4	553.5	1.1	0.3	2.45	0.071
CM11-52	299.0	302.6	3.6	1.1	2.05	0.060
	315.4	317.4	2.0	0.6	5.24	0.153
	472.5	473.7	1.2	0.4	6.20	0.181
	570.8	573.3	2.5	0.8	2.38	0.069
	611.0	613.0	2.0	0.6	3.06	0.089
	946.2	948.6	2.4	0.7	67.64	1.973
	1140.6	1142.6	2.0	0.6	1.81	0.053
	1186.2	1187.6	1.4	0.4	1.23	0.036
	1224.3	1228.5	4.2	1.3	2.38	0.069
	1240.0	1273.0	33.0	10.1	7.11*	0.207*
	including					
	1240.0	1249.6	9.6	2.9	11.29*	0.329*
	1297.6	1303.0	5.4	1.6	11.48*	0.335*
CM11-53	98.7	101.2	2.5	0.8	1.86	0.054
	362.0	372.4	10.4	3.2	2.48*	0.072*
	387.4	388.5	1.1	0.3	1.21	0.035
	408.2	409.7	1.5	0.5	4.36	0.127
	421.6	426.5	4.9	1.5	4.69	0.137
	879.0	881.3	2.3	0.7	2.75	0.080
	982.7	987.4	4.7	1.4	1.64	0.048
CM11-60	839.0	843.2	4.2	1.3	3.25	0.095
CM11-62	112.0	117.6	5.6	1.7	9.66	0.282
	226.4	253.6	27.2	8.3	1.67*	0.049*

	including					
	226.4	232.0	5.6	1.7	6.90*	0.201*
	629.9	637.6	7.7	2.3	1.57	0.046
CM11-63	364.2	373.2	9.0	2.7	6.81	0.199
	499.6	510.5	10.9	3.3	2.98	0.087
	545.9	547.5	1.6	0.5	1.18	0.034
	775.1	785.6	10.5	3.2	7.24*	0.211*
	802.2	807.1	4.9	1.5	2.47	0.072
	897.9	915.3	17.4	5.3	85.48*	2.493*
	including					
	897.9	905.5	7.6	2.3	194.9*	5.684*
	991.3	994.1	2.8	0.9	10.67	0.311
	1020.8	1025.2	4.4	1.3	2.26	0.066
	1106.1	1113.1	7.0	2.1	3.39*	0.099*
	1339.3	1344.1	4.8	1.5	3.12	0.091
	1467.8	1472.6	4.8	1.5	1.58	0.046
CM11-65A	147.0	148.3	1.3	0.4	3.94	0.115
	242.8	258.7	15.9	4.8	1.621*	0.047*
	262.5	271.8	9.3	2.8	7.115*	0.208*
	345.2	351.0	5.8	1.8	1.14	0.033
CM11-80A	288.2	317.0	28.8	8.8	1.21*	0.035*
	813.0	830.1	17.1	5.2	1.51*	0.044*
CM11-80B	129.9	137.0	7.1	2.2	4.97	0.145
	277.0	280.9	3.9	1.2	2.64	0.077
	337.0	342.6	5.6	1.7	2.55	0.074
	417.0	424.2	7.2	2.2	8.24	0.240
CM11-85	77.4	86.4	9.0	2.7	2.12	0.062
	394.8	395.8	1.0	0.3	2.53	0.074
	401.9	409.5	7.6	2.3	2.63*	0.077*
	679.2	681.3	2.1	0.6	22.10	0.645
	695.8	703.5	7.7	2.3	1.52	0.044
	735.2	747.0	11.8	3.6	2.19*	0.064*
	934.2	940.0	5.8	1.8	13.75*	0.401*

	1010.4	1013.0	2.6	0.8	1,942	56.64
CM11-86	117.0	127.0	10.0	3.0	2.20	0.064
	177.0	202.4	25.4	7.7	1.14*	0.033*
	252.2	254.2	2.0	0.6	1.08	0.031
	316.0	317.0	1.0	0.3	17.44	0.509
	511.5	514.0	2.5	0.8	1.27	0.037
	532.3	533.4	1.1	0.3	20.61	0.601
	596.4	630.0	33.6	10.2	16.22*	0.473*
	including					
	618.1	625.7	7.6	2.3	61.86*	1.804*
	729.7	732.3	2.6	0.8	1.11	0.032
	890.3	897.0	6.7	2.0	1.01	0.029
CM11-88	30.0	38.2	8.2	2.5	1.35	0.039
	43.9	44.9	1.0	0.3	14.27	0.416
	62.1	71.6	9.5	2.9	6.64*	0.194*
	87.0	95.2	8.2	2.5	1.96	0.057
	110.1	118.3	8.2	2.5	3.14*	0.092*
	131.5	132.6	1.1	0.3	12.57	0.367
	368.6	395.9	27.3	8.3	3.74*	0.109*
	422.9	433.2	10.3	3.1	3.98*	0.116*
	469.0	470.8	1.8	0.5	2.73	0.080
	499.0	500.2	1.2	0.4	68.60	2.001
	550.3	553.9	3.6	1.1	1.83	0.053
	767.0	774.9	7.9	2.4	23.14	0.675
	1027.0	1035.0	8.0	2.4	1.58	0.046
CM11-91	48.7	52.6	3.9	1.2	1.54	0.045
	344.1	349.6	5.5	1.7	1.28	0.037
	424.9	425.8	0.9	0.3	4.75	0.139
	443.1	445.1	2.0	0.6	2.97	0.087
	483.2	488.2	5.0	1.5	3.06	0.089
	525.4	534.7	9.3	2.8	3.75	0.109
	550.2	590.1	39.9	12.2	3.78*	0.110*
	including					
	560.6	570.2	9.6	2.9	11.28*	0.329*

	706.4	707.5	1.1	0.3	1.20	0.035
	1132.5	1136.5	4.0	1.2	1.33	0.039
	1274.8	1276.1	1.3	0.4	1.71	0.050
	1314.8	1316.6	1.8	0.5	4.13	0.120
	1404.3	1405.9	1.6	0.5	2.95	0.086
CM11-95	227.0	235.1	8.1	2.5	2.07*	0.060*
	265.9	274.8	8.9	2.7	1.28*	0.037*
	435.5	438.3	2.8	0.9	2.00	0.058
	563.0	567.0	4.0	1.2	1.70**	0.050**
CM11-96	42.6	47.2	4.6	1.4	1.22*	0.035*
	215.0	216.3	1.3	0.4	5.79	0.169
	480.4	482.2	1.8	0.5	4.03	0.118
	495.4	504.4	9.0	2.7	1.00	0.029
	580.6	589.7	9.1	2.8	1.19*	0.035*
CM11-97	124.7	127.0	2.3	0.7	2.59	0.076
	150.7	151.9	1.2	0.4	10.19	0.297
	184.4	188.7	4.3	1.3	1.66*	0.048*
	202.2	215.4	13.2	4.0	3.76*	0.110*
	256.5	258.3	1.8	0.5	63.44	1.850
	270.7	271.7	1.0	0.3	1.19	0.035
	276.2	281.5	5.3	1.6	1.52*	0.044*
	299.2	301.9	2.7	0.8	1.08	0.031
	308.4	311.4	3.0	0.9	1.24*	0.036*
	316.2	317.6	1.4	0.4	5.40	0.157
	329.9	336.4	6.5	2.0	6.20*	0.181*
	1153.0	1154.3	1.3	0.4	1.02	0.030
CM11-99	22.0	38.7	16.7	5.1	1.29*	0.038*
	47.0	56.6	9.6	2.9	2.69*	0.078*
	187.3	198.4	11.1	3.4	5.68*	0.166*
	269.6	282.3	12.7	3.9	2.03*	0.059*
	369.3	383.8	14.5	4.4	8.00*	0.233*
	577.0	579.4	2.4	0.7	8.02	0.234
	598.9	600.0	1.1	0.3	16.58	0.484

	624.7	628.9	4.2	1.3	9.07	0.265
	648.8	660.0	11.2	3.4	5.14*	0.15*
	888.4	895.5	7.1	2.2	1.32*	0.039*
	969.0	970.4	1.4	0.4	1.15	0.034
	1058.4	1060.8	2.4	0.7	1.82	0.053
CM11-103	145.6	150.4	4.8	1.5	2.65*	0.077*
	168.8	170.1	1.3	0.4	5.13	0.150
	183.0	184.2	1.2	0.4	1.75	0.051
	231.3	232.4	1.1	0.3	7.83	0.228
	302.1	317.0	14.9	4.5	3.49*	0.102*
CM11-104	Abandoned drill hole, no significant ($\geq$ 0.4 g/T) intercept					
CM11-105	87.0	95.2	8.2	2.5	9.08	0.265
	370.3	371.9	1.6	0.5	2.01	0.059
	453.9	455.9	2.0	0.6	4.62	0.135
	481.0	487.6	6.6	2.0	2.77	0.081
	524.4	529.9	5.5	1.7	3.53	0.103
	577.4	596.4	19.0	5.8	6.40*	0.187*
	including					
	577.4	587.0	9.6	2.9	12.20*	0.356*
	624.1	627.0	2.9	0.9	1.83	0.053
	648.0	651.5	3.5	1.1	3.18	0.093
	732.6	742.0	9.4	2.9	17.36*	0.506*
	including					
	735.8	742.0	6.2	1.9	25.98	0.758
	998.0	1006.5	8.5	2.6	1.12	0.033
CM11-106	70.0	86.9	16.9	5.2	1.53*	0.044*
	147.0	153.7	6.7	2.0	13.00	0.379
	243.0	284.2	41.2	12.6	2.31*	0.067*
	311.1	317.0	5.9	1.8	6.00	0.175
	1087.0	1091.1	4.1	1.2	1.60	0.047

		1461.1	1467.4	6.3	1.9	2.43	0.071
CM11-107		375.5	389.0	13.5	4.1	1.91*	0.056*
		455.5	459.5	4.0	1.2	2.41	0.070
		732.5	737.0	4.5	1.4	7.98	0.233
		744.2	748.7	4.5	1.4	8.29	0.242
		963.0	983.7	20.7	6.3	4.10*	0.119*
		1349.0	1352.0	3.0	0.9	1.49	0.043
CM11-108		162.6	167.2	4.6	1.4	1.14	0.033
		172.1	178.3	6.2	1.9	3.82*	0.111*
		185.2	200.5	15.3	4.7	1.69*	0.049*
		369.0	373.4	4.4	1.3	9.20	0.268
		699.0	704.7	5.7	1.7	1.05	0.031
		966.7	973.0	6.3	1.9	3.17	0.092
		977.4	986.1	8.7	2.7	2.22	0.065
		1397.0	1402.4	5.4	1.6	1.08	0.031
CM11-109		200.9	205.1	4.2	1.3	4.77	0.139
		254.0	255.5	1.5	0.5	2.34	0.068
		434.8	436.2	1.4	0.4	4.51	0.132
		707.0	711.0	4.0	1.2	23.38	0.682
		764.1	765.7	1.6	0.5	2.71	0.079
		948.0	949.2	1.2	0.4	5.45	0.159
		1221.7	1224.8	3.1	0.9	1.14	0.033
		1347.0	1348.0	1.0	0.3	10.31	0.301
		1384.0	1391.9	7.9	2.4	2.13*	0.062*
		1446.7	1448.2	1.5	0.5	14.03	0.409
CM11-110		149.1	150.5	1.4	0.4	6.06	0.177
		262.2	270.5	8.3	2.5	3.18	0.093
		301.6	303.7	2.1	0.6	2.02	0.059
		330.3	335.3	5.0	1.5	4.46	0.130
		667.9	670.7	2.8	0.9	1.165**	0.034**
		920.7	922.9	2.2	0.7	2.09	0.061
CM11-111		94.7	97.5	2.8	0.9	1.02	0.030
		185.2	188.7	3.5	1.1	1.09	0.032

CM11-121	1138.8	1140.4	1.6	0.5	1.19	0.035
	1484.2	1493.3	9.1	2.8	2.34*	0.068*
	1504.0	1505.2	1.2	0.4	9.49	0.277
CM11-123	331.5	347.0	15.5	4.7	1.97*	0.057*
	448.7	477.0	28.3	8.6	4.38*	0.128*
	645.1	649.7	4.6	1.4	1.62	0.047
	654.7	658.8	4.1	1.2	4.58	0.134
	837.0	852.7	15.7	4.8	4.42*	0.129*
CM11-124	125.8	127.0	1.2	0.4	2.27	0.066
	185.8	190.3	4.5	1.4	1.84*	0.054*
	286.5	292.5	6.0	1.8	3.14*	0.092*
	504.7	508.3	3.6	1.1	7.12	0.208
	575.5	583.3	7.8	2.4	1.11*	0.032*
	617.0	634.1	17.1	5.2	1.51***	0.044***
	715.2	718.1	2.9	0.9	14.73	0.430
	732.5	733.5	1.0	0.3	3.72	0.108

Note: Uncut and uncapped grade; * weighted grade; ** lead collection/gravimetric assays

*** weighted intercept of both metallic & lead collection/gravimetric assay results

All the significant intercepts in CM11 drill holes described above and in Table 1 may not be the true width. Due to the complexity of analyzing three types of quartz veins; namely, strike, diagonal & orthogonal veins, the true width will be determined after the Company's 3D geological model is updated.

The standard fire assay technique was conducted on a relatively small (30 g) aliquot of sample material that may or may not be truly representative of the gold content of the sample as a whole, particularly if coarse gold or visible gold is present that is notoriously difficult to homogenize within a sample pulp. The Metallic Screen technique utilized in the Company's Double Assay Program effectively evaluates 1,000 grams of pulverized material for each sample and was specifically developed by laboratories to measure coarse or visible gold within pulverized sample materials to provide a more representative estimate of overall gold content.

The collection of reject samples, infill core sampling and core sample cutting of 239 Cow Mt. drill holes conducted in 2007, 2009, 2010 & 2011 has been completed. News on complete holes that include metallic screen fire assay results of reject samples and lead collection fire assay results of previously unassayed infill core samples will be published as they become available. The Company is in the process of utilizing this information to update the drill hole database.

Drill core processing included descriptive logging and sampling for geochemical analyses. The NQ-size drill core was cut/split in two halves using saws at the Company's Lowhee Creek Compound in Wells-Barkerville, central B.C. One-half of the core is put in a sample bag. After all the samples are placed in the rice bags at the mine site, they are transported by BGM's personnel to a shipping company in Quesnel for trans-shipment to ACME Analytical Laboratories Ltd. in Vancouver, which is under the Bureau Veritas Group Company, for analysis. Sample preparation and geochemical assaying is done at ACME, following their own internal standards for quality control and verification. The gold assaying method uses a 1,000 g metallic screen gold assay and 50 g lead collection fire assay. ACME is certified under the Assayers Certification Program of B.C.

The information contained in this news release has been reviewed and approved by the Company's Chief Geologist Jim Yin, Ph.D., a Qualified Person as defined by National Instrument 43-101 Standards of Disclosure for Mineral Projects.

"J. Frank Callaghan"

J. Frank Callaghan

President and CEO

About Barkerville Gold Mines Ltd.

The Company has focused on exploration and development of gold projects in the Cariboo Mining District in central B.C. from the mid-1990s to present. The Company's mineral tenures cover 1,164 km² along a strike length of 60 km and approximate width of 20 km, including the Cariboo Gold Project, the Bonanza Ledge Gold Project, the Barkerville Mountain and Island Mountain exploration targets and seven past producing hard rock mines. The QR Property was acquired in February 2010 and includes a 900 tonne/day gold milling facility and a permitted gold mine located approximately 110 km by highway and all-weather road from the Barkerville Gold Camp. In November 2010, the Company acquired a second permitted mill currently on care and maintenance in Revelstoke, B.C. The Company has completed significant drilling and exploration programs and, together with the historical data, is compiling all information to determine the geologic models and updated technical reports to continue with exploration and development of the Cariboo Gold projects. This news release has been prepared on behalf of the Board of Directors of the Company which takes full responsibility for its contents.

Cautionary Statement on Forward-Looking Information

Certain information in this news release is forward-looking within the meaning of certain securities laws, and is subject to important risks, uncertainties and assumptions. This forward-looking information includes, among other things, information with respect to the Company's beliefs, plans, expectations, anticipations,

estimates and intentions, including the listing and trading of the Company's common shares on the TSXV. The words "may", "could", "should", "would", "suspect", "outlook", "believe", "anticipate", "estimate", "expect", "intend", "plan", "target" and similar words and expressions are used to identify forward-looking information. The forward-looking information in this news release describes the Company's expectations as of the date of this news release.

The results or events anticipated or predicted in such forward-looking information may differ materially from actual results or events. Material factors which could cause actual results or events to differ materially from such forward-looking information include, among others, the Company's ability to engage and retain qualified key personnel, employees and affiliates, to obtain capital and credit and to protect its property rights.

The Company cautions that the foregoing list of material factors is not exhaustive. When relying on the Company's forward-looking information to make decisions, investors and others should carefully consider the foregoing factors and other uncertainties and potential events. The Company has assumed a certain progression, which may not be realized. It has also assumed that the material factors referred to in the previous paragraph will not cause such forward-looking information to differ materially from actual results or events. However, the list of these factors is not exhaustive and is subject to change and there can be no assurance that such assumptions will reflect the actual outcome of such items or factors.

THE FORWARD-LOOKING INFORMATION CONTAINED IN THIS NEWS RELEASE REPRESENTS THE EXPECTATIONS OF THE COMPANY AS OF THE DATE OF THIS NEWS RELEASE AND, ACCORDINGLY, IS SUBJECT TO CHANGE AFTER SUCH DATE. READERS SHOULD NOT PLACE UNDUE IMPORTANCE ON FORWARD-LOOKING INFORMATION AND SHOULD NOT RELY UPON THIS INFORMATION AS OF ANY OTHER DATE. WHILE THE COMPANY MAY ELECT TO, IT DOES NOT UNDERTAKE TO UPDATE THIS INFORMATION AT ANY PARTICULAR TIME.

Neither the TSXV nor its Regulation Services Provider (as that term is defined in the policies of the TSXV) accepts responsibility for the adequacy or accuracy of this news release.

Copyright (c) 2014 TheNewswire - All rights reserved.

Dieser Artikel stammt von [Rohstoff-Welt.de](https://www.rohstoff-welt.de)

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/169258--Barkerville-Gold-Mines-Reports-Whole-Hole-Metallic-Screen-Fire-with-Minor-Lead-Collection-Gravimetric-Assay-R>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).