

VANCOUVER, BC & MONTREAL, QC / ACCESSWIRE / July 27, 2015 / [Lomiko Metals Inc.](#) (TSXV: LMR) (OTC: LMRMF) (FSE: DH8B) (the "Company") and Canada Strategic Metals (TSXV: CJC) are pleased to announce that Forage Val D'Or Inc. has mobilized a drill rig to the La Loutre Property to start a drilling program of up to 10,000 metres at the La Loutre Crystalline Flake Graphite Properties located in Quebec.

Highlighted Drill Results From La Loutre

Hole # (m)	From To (m)	Length* (m)	Gp %	
LL-14-05	6.65	135.00	128.35	4.72
LL-14-15	3.40	56.65	53.25	4.40
LL-14-17	3.70	17.90	14.20	6.52
LL-14-19	3.00	15.40	12.40	5.36
LL-14 -21	15.3	35.6	20.3	8.01
LL-14-24	14.1	32.25	18.15	7.73

Image: https://www.accesswire.com/uploads/16491_lomiko1.jpg

To view an enhanced version of image 1: Lomiko Flake Graphite samples under magnification reveal crystalline structure, please visit:

http://orders.newsfilecorp.com/files/1944/16491_lomiko2.jpg

Image: https://www.accesswire.com/uploads/16491_lomiko3.jpg

To view an enhanced version of image 2: Lomiko Flake Graphite samples under magnification reveal crystalline structure, please visit:

http://orders.newsfilecorp.com/files/1944/16491_lomiko4.jpg

The 2014 drilling program at La Loutre was managed by Consul-Teck Exploration of Val-d'Or, Quebec, who designed the drilling campaign, supervised the program and logged and sampled the core. A full set of drill results are reported in the February 9, 2015 news release.

*Length along the core. The Company estimates the true width of the mineralized zone at 70 to 90% of the width intersected in the drill holes.

Consul-Teck Exploration implemented QA/QC procedures to ensure best practices in sampling and analysis of the core samples. The drill core was logged and then split, with one half sent for assay and the other retained in the core box as a witness sample. Duplicates and blanks were inserted regularly into the sample stream.

The samples in secure tagged bags were delivered directly to the analytical facility for analysis. In this case, the analytical facility was the ALS minerals in Val-d'Or, Quebec. The samples are weighed and identified prior to sample preparation. The samples are crushed to 70% minus 2 mm, then separated and pulverized to 85% passing 75µm. All samples are analyzed for Carbon Graphite using C-IR18.

Jean-Sebastien Lavallée (OGQ #773), geologist, a shareholder, and Qualified Person as defined by National Instrument 43-101, has reviewed and approved the technical content of this release.

For more information, review the website at www.lomiko.com, contact A. Paul Gill at 604-729-5312 or email:info@lomiko.com

On Behalf of the Board

“A. Paul Gill”

Chief Executive Officer

We seek safe harbor. Neither TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release.

SOURCE: [Lomiko Metals Inc.](#)