

Toachi Mining Intersects 5.42 m grading 4.35 g/t Au, 77.34 g/t Ag, 7.48% Cu, 4.24% Zn and 0.22% Pb at the Gold-Rich La Plata VMS Project

12.04.2017 | [The Newswire](#)

Drilling Extending Mineralization in La Mina North Zone

Toronto, April 12, 2017 - [Toachi Mining Inc.](#), ("Toachi" or the "Company") (TSX-V: TIM) is pleased to announce results from on-going drilling at its La Plata gold-rich volcanogenic massive sulphide ("VMS") project in Ecuador.

Program Highlights

-Hole CMLP-17-45 intersected 5.42 metres (m) of massive and disseminated sulphide mineralization grading 4.35 grams per tonne (g/t) gold, 77.34 g/t silver, 7.48% copper, 4.24% zinc and 0.22% lead from 69.26 m in the La Mina North zone of the La Mina deposit.

-Hole CMLP-17-42, drilled on the same section as CMLP-17-45, intersected 18.25 m of massive and disseminated sulphide mineralization grading 1.57 g/t gold, 12.14 g/t silver, 3.44% copper, 1.06% zinc and 0.15% lead from 138 m.

-Hole CMLP-17-42 included a high grade intersection of 6.38 m grading 2.4 g/t gold, 16.33 g/t silver, 4.9% copper, 1.99% zinc and 0.24% lead from 142 m.

-Hole CMLP-17-41 intersected 0.66 m grading 24.26 g/t gold, 200 g/t silver, 1.94% copper, 31.27% zinc and 9.57% lead from 5.44 m in La Mina North.

Drilling Highlights Hole # (36) (37) (40)	To							
	From (m)	m	Au (g/t)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)	
CMLP-17-43	106.2	107.48	1.28	2.27	35	7.71	0.41	2.48
CMLP-17-37	29.66	31	1.34	8.90	71	4.37	0.77	10.84
CMLP-17-40	104.23	105.09	0.86	0.96	26	5.77	0.11	0.99
CMLP-17-41	4.57	6.9	2.33	10.00	92	1.06	4.14	10.75
including	5.44	6.1	0.66	24.26	200	1.94	9.57	31.27
CMLP-17-42	138	156.25	18.25	1.57	12	3.44	0.15	1.06
including	142	148.38	6.38	2.40	16	4.90	0.24	1.99
CMLP-17-45	69.26	74.68	5.42	4.35	77	7.48	0.22	4.24
	78	81.24	3.24	1.11	13	2.49	0.05	0.59
CMLP-17-47	64.17	71.63	7.46	1.68	152	2.98	0.10	0.86

Core widths in CMLP-17-36, CMLP-17-37 and CMLP-17-45 are considered to be true widths. Core widths in

CMLP-17-40, CMLP-17-41 and CMLP-17-47 are considered close to true widths. CMLP-17-42 was drilled obliquely to the zone with a true width of 8.5 m. Gold assay composites were calculated using uncut assays.

A complete list of all intersections is available in Table 1 below along with a plan map and cross section of CMLP-17-40, CMLP-17-42, CMLP-17-45 and CMLP-17-47.

Program Results

The drill program, which began in August 2016, is designed to validate the historic drilling database at the La Plata project. The drilling program is also intended to infill and expand known resources in the main La Mina VMS lenses leading to the completion of a National Instrument 43-101 resource estimate later this year.

Modelling of historic and current drill results by Toachi staff has delineated four discrete mineralized zones which define the La Mina North and La Mina South blocks. For a 3-D graphic of the wireframed zones, please visit our website at www.toachimining.com and see our latest presentation.

Holes CMLP-17-36, CMLP-17-40, CMLP-17-42, CMLP-17-45 and CMLP-17-47 were collared in the southern part of the La Mina North block and were designed to test the southern extension of the VMS mineralization in Zone 1. These holes were successful in identifying high grade VMS mineralization and extended the mineralized envelope down dip, up to near-surface and to the south.

Holes CMLP-17-37, CMLP-17-41 and CMLP-17-44 were collared in the northern part of the La Mina North block around the old open pit area and were designed to test the northern extension of the near-surface VMS mineralization in Zone 1. These holes were successful in identifying high grade VMS mineralization and confirming continuity of the VMS mineralization in this area.

Nick Tintor, President and CEO, stated, "Our drilling continues to generate exceptional gold, copper and zinc values over good widths at the La Plata project. This drill program is being successful in not only verifying the high grade nature of the project but in extending mineralized envelopes as well."

See the longitudinal section below for the location of the pierce points of these holes in relation to historic resource blocks. A list of drill results, cross section and plan map with collar locations is also available at the end of this press release.

Management believes the La Plata project, which is characterized by geology typical of major gold-rich VMS camps around the world, hosts excellent potential for the discovery of additional discrete VMS zones amongst the 14 exploration targets identified to date.

La Plata Deposit Geology

Gold-bearing sulphide mineralization at La Plata occurs as compositional banding composed of chalcopyrite, sphalerite and pyrite laminae with barite occurring as clasts and also as thin layers.

Base and precious metal mineralization at La Plata is interpreted to have formed as part of multiple volcanic episodes that created a stacked volcanic-exhalite hydrothermal sequence which is considered favorable for hosting multiple VMS lenses.

Examples of this exclusive group of gold-rich VMS camps include Noranda, Doyon-Bousquet-LaRonde and the Flin Flon camps in Canada.

Toachi's exploration staff has identified more than 14 discrete exploration targets across the property concessions which extend for more than 9 kilometres, attesting to the potential of this emerging district.

The La Plata Project

Toachi entered into an option agreement with a private Ecuadorean company to earn between a 60% to 75% interest in the La Plata gold-copper-silver-zinc VMS project, located 85 km south of Quito, Ecuador.

For complete terms of the transaction, please see our press release dated February 11, 2016 which is available on our website at www.toachimining.com or on www.sedar.com.

La Plata is a gold-rich volcanogenic massive sulphide deposit which was the subject of small scale mining from both an open pit and underground workings from 1975-1981.

From 1996 to 2000, [Cambior Inc.](#), a Canadian mining company, completed 8,628 metres of drilling and a preliminary resource estimate totaling 840,000 tonnes grading 4.8 grams gold per tonne, 4.1% copper, 54.4 grams silver per tonne and 0.7% lead and 4.2% zinc per tonne in 1999, according to a report completed by AMEC Foster Wheeler, a mining consulting firm, in March 2015.

Following a drill program by Cornerstone Capital Resources Inc., which included 5,933 metres of drilling from 2006-2007, a revised mineral resource estimate totaling 913,977 tonnes grading

8.01 grams gold per tonne, 88.3 grams silver per tonne, 5.01% copper, 6.71% zinc and 0.78% lead per tonne in the inferred category was completed.

The resource estimates described above are historical estimates as defined by National Instrument 43-101 - Standards of Disclosure for Mineral Projects S.2.4 ("NI 43-101").

Toachi has not completed the work required to independently analyze and verify the results of the previous operators nor has a qualified person completed sufficient work to classify the estimates as current mineral resources or mineral reserves. With respect to the Cambior estimate, the Company is also not aware of what categories were used in the estimate. As a result, Toachi is not treating these estimates as current mineral resources or mineral reserves.

The Company believes these historic results provide an indication of the potential of the property and are relevant from an on-going exploration perspective.

QA/QC Sampling and Core Sampling Protocols

Before sampling, a centreline, representing bottom of hole (or a reference line when this is not known) is marked on the drill core. The core is cut and sampled, always sampling the right-hand side of the drill core. Samples are selected based on logged geological features, such as rock type, mineralization, alteration, veining etc. Sample length does not exceed 1.2 m nor is smaller than 20 cm. In areas of similar geological characteristics, sample length is, in general, 1 m.

A total of 10% of the samples submitted are certified blanks and standards and field duplicates with, as a minimum, one blank submitted at the beginning of each sample batch. Certified standards are submitted at an average of 6% of the samples submitted. Field duplicates are taken at a rate of 1 in 20 of the samples taken.

Drill hole analysis was completed by MS Analytical in Canada.

The analysis was completed by MS Analytical in Canada with preparation performed by Ecuadorian partner, LAC y Asociados. Both LAC y Asociados and MSA are ISO 9001:2008 registered companies. MS Analytical also meets the requirements as outlined in ISO/IEC 17025.

Qualified Person

Phil Fox, MAIG, a Qualified Person as defined by NI 43-101, has reviewed and approved the contents of this press release.

About Toachi Mining Inc.

Toachi brings a disciplined and veteran team of project managers together with a high grade gold-copper-silver-zinc project at La Plata in Ecuador. Toachi is focused on and committed to the development of advanced stage mineral projects throughout the Americas using industry best practices combined with a strong social license from local communities. Toachi Mining has 51,653,935 shares issued and outstanding.

Forward Looking Statements

Certain statements contained in this news release may constitute "forward-looking information" as such term is used in applicable Canadian securities laws. Forward-looking information is based on plans, expectations and estimates of management at the date the information is provided and is subject to certain factors and assumptions, including, that the Company's financial condition and development plans do not change as a result of unforeseen events and that the Company obtains regulatory approval. Forward-looking information is subject to a variety of risks and uncertainties and other factors that could cause plans, estimates and actual results to vary materially from those projected in such forward-looking information. Factors that could cause the forward-looking information in this news release to change or to be inaccurate include, but are not limited to, the risk that any of the assumptions referred to prove not to be valid or reliable, that occurrences such as those referred to above are realized and result in delays, or cessation in planned work, that the Company's financial condition and development plans change, and delays in regulatory approval, as well as the other risks and uncertainties applicable to the Company as set forth in the Company's continuous disclosure filings filed under the Company's profile at www.sedar.com. The Company undertakes no obligation to update these forward-looking statements, other than as required by applicable law.

FOR ADDITIONAL INFORMATION PLEASE CONTACT

Nick Tintor, President and CEO
Telephone: 416 987 0855

Mobile: 416 953 4244
Email: ntintor@rgmi.ca

Neither TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release.

Table 1

La Mina Drill Results

Drill Hole	From (m)	To (m)	m	Au (g/t)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)
CMLP-17-36	106.2	107.48	1.28	2.27	35	7.71	0.41	2.48
CMLP-17-37	29.66	31	1.34	8.90	71	4.37	0.77	10.84
CMLP-17-40	104.23	105.09	0.86	0.96	26	5.77	0.11	0.99
CMLP-17-41	4.57	6.9	2.33	10.00	92	1.06	4.14	10.75

including

CMLP-17-42	126	128	2	1.31	58	0.15	0.34	0.67
	138	156.25	18.25	1.57	12	3.44	0.15	1.06
including	142	148.38	6.38	2.40	16	4.90	0.24	1.99
CMLP-17-44	37.25	39.62	2.37	1.17	12	0.36	0.07	1.07
CMLP-17-45	69.26	74.68	5.42	4.35	77	7.48	0.22	4.24
	78	81.24	3.24	1.11	13	2.49	0.05	0.59
CMLP-17-47	64.17	71.63	7.46	1.68	152	2.98	0.10	0.86

Cross Section

La Mina North - Zone 1

Click Image To View Full Size

Plan Map

Click Image To View Full Size

Longitudinal Section

Click Image To View Full Size

The resource estimates in the longitudinal section above are historical estimates as defined by National Instrument 43-101 - Standards of Disclosure for Mineral Projects S.2.4 ("NI 43-101").

Toachi has not completed the work required to independently analyze and verify the results of the previous operators nor has a qualified person completed sufficient work to classify the estimates as current mineral resources or mineral reserves. As a result, Toachi is not treating these estimates as current mineral resources or mineral reserves.

The Company believes these historic results provide an indication of the potential of the property and are relevant from an on-going exploration perspective.

Copyright (c) 2017 TheNewswire - All rights reserved.

Dieser Artikel stammt von Rohstoff-Welt.de

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/262656--Toachi-Mining-Intersects-5.42-m-grading-4.35-g-t-Au-77.34-g-t-Ag-7.48Prozent-Cu-4.24Prozent-Zn-and-0.22Prozent-Pb>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer](#)!

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinen](#).