

# Toachi Mining Inc. Intersects 6.28 m grading 7.12 g/t Au, 24 g/t Ag, 8.84% Cu, 1.61% Zn and 0.36% Pb at the Gold-Rich La Plata VMS Project

02.05.2017 | [The Newswire](#)

## Mineralization extended 40-m south from CMLP-17-56

Toronto, May 2, 2017 - [Toachi Mining Inc.](#), ("Toachi" or the "Company") (TSX-V: TIM) is pleased to announce results from on-going drilling at its La Plata gold-rich volcanogenic massive sulphide ("VMS") project in Ecuador.

### Program Highlights

-Hole CMLP-17-49 intersected 6.28 metres (m) of massive and disseminated sulphide mineralization grading 7.12 grams per tonne (g/t) gold, 24 g/t silver, 8.84% copper, 1.61% zinc and 0.36% lead from 62.26 m in the La Mina North zone of the La Mina deposit.

-The intersection above is within a wider 12.20-m intercept grading 4.07 g/t gold, 27 g/t silver, 5.79% copper, 1.80% zinc and 0.29% lead from 62.26 m.

-Hole CMLP-17-49 was drilled up dip and on the same section as CMLP-17-45 and 47, and 40 metres south of hole CMLP-17-56. Full results from these holes are available in Toachi press releases dated April 12 and April 25, 2017 and available at [www.toachimining.com](http://www.toachimining.com) or on SEDAR.

### Drilling Highlights

Hole (56)	From (m)	To (m)	m	Au (g/t)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)
CMLP-17-49	62.26		74.46	12.20	4.07	27.00	5.79	0.29
including		62.26	68.54	6.28	7.12	24.00	8.84	0.36

Core widths in CMLP-17-49 are considered close to true width. Gold assay composites were calculated using uncut assays.

### Program Results

The drill program, which began in August 2016, is designed to validate the historic drilling database at the La Plata project. The drilling program is also intended to infill and expand known resources in the main La Mina VMS lenses leading to the completion of a National Instrument 43-101 resource estimate later this year.

Modelling of historic and current drill results by Toachi staff has delineated four discrete mineralized zones which define the La Mina North and La Mina South blocks. For a 3-D graphic of the wireframed zones, please visit our website at [www.toachimining.com](http://www.toachimining.com) and see our latest presentation.

Hole CMLP-17-49 was collared 40-m south of hole CMLP-17-56 which intersected 10.78 m grading 6.35 g/t gold, 54.32 g/t silver, 9.64% copper, 8.70% zinc and 0.43% lead in the southern part of the La Mina North block.

Hole CMLP-17-49 was successful in extending high grade VMS mineralization from CMLP-17-56 towards the south.

Nick Tintor, President and CEO, stated, "Toachi continues to generate exceptional drill results from the La Plata project which underscores the high grade and gold-rich nature of the VMS mineralization in this deposit."

See the longitudinal section below for the location of the pierce point of CMLP-17-49 in relation to historic resource blocks and hole CMLP-17-56. A cross section and plan map with collar locations is also available at the end of this press release.

Management believes the La Plata project, which is characterized by geology typical of major gold-rich VMS camps around the world, hosts excellent potential for the discovery of additional discrete VMS zones amongst the 14 exploration targets identified to date.

#### La Plata Deposit Geology

Gold-bearing sulphide mineralization at La Plata occurs as compositional banding composed of chalcopyrite, sphalerite and pyrite laminae with barite occurring as clasts and also as thin layers.

Base and precious metal mineralization at La Plata is interpreted to have formed as part of multiple volcanic episodes that created a stacked volcanic-exhalite hydrothermal sequence which is considered favorable for hosting multiple VMS lenses.

Examples of this exclusive group of gold-rich VMS camps include Noranda, Doyon-Bousquet-LaRonde and the Flin Flon camps in Canada.

Toachi's exploration staff has identified more than 14 discrete exploration targets across the property concessions which extend for more than 9 kilometres, attesting to the potential of this emerging district.

#### The La Plata Project

Toachi entered into an option agreement with a private Ecuadorean company to earn between a 60% to 75% interest in the La Plata gold-copper-silver-zinc VMS project, located 85 km south of Quito, Ecuador.

For complete terms of the transaction, please see our press release dated February 11, 2016 which is available on our website at [www.toachimining.com](http://www.toachimining.com) or on [www.sedar.com](http://www.sedar.com).

La Plata is a gold-rich volcanogenic massive sulphide deposit which was the subject of small scale mining from both an open pit and underground workings from 1975-1981.

From 1996 to 2000, [Cambior Inc.](#), a Canadian mining company, completed 8,628 metres of drilling and a preliminary resource estimate totaling 840,000 tonnes grading 4.8 grams gold per tonne, 4.1% copper, 54.4 grams silver per tonne and 0.7% lead and 4.2% zinc per tonne in 1999, according to a report completed by AMEC Foster Wheeler, a mining consulting firm, in March 2015.

Following a drill program by Cornerstone Capital Resources Inc., which included 5,933 metres of drilling from 2006-2007, a revised mineral resource estimate totaling 913,977 tonnes grading

8.01 grams gold per tonne, 88.3 grams silver per tonne, 5.01% copper, 6.71% zinc and 0.78% lead per tonne in the inferred category was completed.

The resource estimates described above are historical estimates as defined by National Instrument 43-101 - Standards of Disclosure for Mineral Projects S.2.4 ("NI 43-101").

Toachi has not completed the work required to independently analyze and verify the results of the previous

operators nor has a qualified person completed sufficient work to classify the estimates as current mineral resources or mineral reserves. With respect to the Cambior estimate, the Company is also not aware of what categories were used in the estimate. As a result, Toachi is not treating these estimates as current mineral resources or mineral reserves.

The Company believes these historic results provide an indication of the potential of the property and are relevant from an on-going exploration perspective.

#### QA/QC Sampling and Core Sampling Protocols

Before sampling, a centreline, representing bottom of hole (or a reference line when this is not known) is marked on the drill core. The core is cut and sampled, always sampling the right-hand side of the drill core. Samples are selected based on logged geological features, such as rock type, mineralization, alteration, veining etc. Sample length does not exceed 1.2 m nor is smaller than 20 cm. In areas of similar geological characteristics, sample length is, in general, 1 m.

A total of 10% of the samples submitted are certified blanks and standards and field duplicates with, as a minimum, one blank submitted at the beginning of each sample batch. Certified standards are submitted at an average of 6% of the samples submitted. Field duplicates are taken at a rate of 1 in 20 of the samples taken.

Drill hole analysis was completed by MS Analytical in Canada.

The analysis was completed by MS Analytical in Canada with preparation performed by Ecuadorian partner, LAC y Asociados. Both LAC y Asociados and MSA are ISO 9001:2008 registered companies. MS Analytical also meets the requirements as outlined in ISO/IEC 17025.

#### Qualified Person

Phil Fox, MAIG, a Qualified Person as defined by NI 43-101, has reviewed and approved the contents of this press release.

#### About Toachi Mining Inc.

Toachi brings a disciplined and veteran team of project managers together with a high grade gold-copper-silver-zinc project at La Plata in Ecuador. Toachi is focused on and committed to the development of advanced stage mineral projects throughout the Americas using industry best practices combined with a strong social license from local communities. Toachi Mining has 51,653,935 shares issued and outstanding

#### Forward Looking Statements

Certain statements contained in this news release may constitute "forward-looking information" as such term is used in applicable Canadian securities laws. Forward-looking information is based on plans, expectations and estimates of management at the date the information is provided and is subject to certain factors and assumptions, including, that the Company's financial condition and development plans do not change as a result of unforeseen events and that the Company obtains regulatory approval. Forward-looking information is subject to a variety of risks and uncertainties and other factors that could cause plans, estimates and actual results to vary materially from those projected in such forward-looking information. Factors that could cause the forward-looking information in this news release to change or to be inaccurate include, but are not limited to, the risk that any of the assumptions referred to prove not to be valid or reliable, that occurrences such as those referred to above are realized and result in delays, or cessation in planned work, that the Company's financial condition and development plans change, and delays in regulatory approval, as well as the other risks and uncertainties applicable to the Company as set forth in the Company's continuous disclosure filings filed under the Company's profile at [www.sedar.com](http://www.sedar.com). The Company undertakes no obligation to update these forward-looking statements, other than as required by applicable law.

FOR ADDITIONAL INFORMATION PLEASE CONTACT

Nick Tintor, President and CEO  
Telephone: 416 987 0855

Mobile: 416 953 4244  
Email: ntintor@rgmi.ca

Neither TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release.

Cross Section

La Mina North - Zone 1

[Click Image To View Full Size](#)

Plan Map

[Click Image To View Full Size](#)

Longitudinal Section

[Click Image To View Full Size](#)

The resource estimates in the longitudinal section above are historical estimates as defined by National Instrument 43-101 - Standards of Disclosure for Mineral Projects S.2.4 ("NI 43-101").

Toachi has not completed the work required to independently analyze and verify the results of the previous operators nor has a qualified person completed sufficient work to classify the estimates as current mineral resources or mineral reserves. As a result, Toachi is not treating these estimates as current mineral resources or mineral reserves.

The Company believes these historic results provide an indication of the potential of the property and are relevant from an on-going exploration perspective.

Copyright (c) 2017 TheNewswire - All rights reserved.

---

Dieser Artikel stammt von [Rohstoff-Welt.de](http://Rohstoff-Welt.de)

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/264620--Toachi-Mining-Inc.-Intersects-6.28-m-grading-7.12-g-t-Au-24-g-t-Ag-8.84Prozent-Cu-1.61Prozent-Zn-and-0.36Prozent-Pb>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

---

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!  
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).

---