

Prophecy Technology Partner NWME Produces 98.6% Pure V₂O₅ (Vanadium Pentoxide) from Gibellini Samples, Aims for 99.5% V₂O₅ Next Run

14.08.2018 | [FSCwire](#)

Vancouver, British Columbia (FSCwire) - [Prophecy Development Corp.](#) ("Prophecy" or the "Company") (TSX:PCY, OTCQX:PRPCF, Frankfurt:1P2N) is pleased to announce the results from the metallurgical tests conducted by Northwest Nonferrous Metals Mining Group Co., Ltd. ("NWME") on samples collected from the Company's Gibellini Vanadium Project (the "Project"). Samples were collected by NWME's team during their visit to the Project's site in February 2018, with tests performed at NWME's facility in X

98.6% V2O5 Produced on the 1st Run with Simple Conventional Flowsheet

NWME used solvent extraction ("SX") processing method to recover vanadium from sulfuric acid pregnant leach solution ("PLS") generated by bottle roll and column test acid leaching on Gibellini samples. The solution was then reduced and then precipitated using ammonia to make ammonium metavanadate ("AMV"). The AMV was then filtered, washed and heated then cooled and pulverized. A vanadium pentoxide with 98.56 % purity content was produced. The assay for the product is shown below:

Gibellini vanadium pentoxide assay

V2O5 %	SI %	Fe %	P %	S %	As %	Na2O %	K2O %	Al %	U %
98.56	0.0078	0.88	0.058	0.47	0.0026	0.43	0.052	0.22	0.0001

Uranium content is less than 0.0001% which does not affect the marketability of the product.

The PLS was produced with very low deleterious elements which enabled using an efficient SX process. The PLS V2O5 concentration was 1.15 gram per liter and the Pregnant Strip Solution V2O5 concentration was 39.61 grams per liter.

Overall Vanadium Recovery of Over 60% and Low Acid Consumption

PLS was produced from both bottle roll and column tests. Sulfuric acid was added to the feed material with the bottle roll process. After 24 hours, then the open bottle was allowed to cure for 24 hours and water was added to the bottle to attain the desired density. Initial samples were taken at 6 hours, 12 hours, 24 hours, 36 hours, 48 hours and then once a day until the bottle roll was completed.

In column tests, sulfuric acid was added to the feed material and the material was allowed to cure for 24 hours before leaching. Leaching was conducted by applying 108 grams per liter acid solution over the material. PLS was collected every 24 hours and samples were taken for vanadium analysis. All the tests were performed at room temperature and at atmospheric pressure.

The results of the tests are given below:

Test	Leach Time	Vanadium Recovery
Column Test	21 days	70%
Bottle Roll Test - investigate the effect of the curing method and increase of sulfuric acid addition on the vanadium recovery	50 hours	62%
Bottle Roll Test - investigate addition of NWME prepared leaching agent on the vanadium recovery	144 hours	66%
Bottle Roll Test - investigate the leaching of coarse feed (2mm) on the vanadium recovery	216 hours	63%

The results of the bottle roll and column leach tests performed by NWME largely validate the results of previous tests performed by McClelland Laboratories on Gibellini bulk sample in 2013 (18 tons of material).

The NWME test samples were not agglomerated and were on short leach time of 21 days for column tests and 5 days for bottle roll tests. Prophecy studied both the NWME test and McClelland test in detail and believe the results were consistent, v

70% recovery can be achieved with longer leach cycle (over 100 days McClelland Laboratories vs 21 days NWME) and consumption (50 kg of acid per tonne of material McClelland Laboratories vs 100 kg of acid per tonne of material NWM

A summary of acid heap leach tests of a Gibellini bulk sample, completed at McClelland Laboratories, September 4, 2018, is tabulated below:

Size	Test Type	Time (Days)	Vanadium Recovery %	Head Grade % V2O5	Sulfuric Acid Consumption (kg/tonne)
50 mm (2" diameter)	Column, open circuit	123	76.6	0.53	39.9
12.5 mm (1/2" diameter)	Column, open circuit	123	80.2	0.56	32.7
12.5 mm (1/2" diameter)	Column, closed circuit	230	68.3	0.51	38.1
12.5 mm (1/2" diameter)	Column, closed circuit	198	74.0	0.56	43.5
12.5 mm (1/2" diameter)	Bottle Roll	4	67.1	0.51	33.6
1.7 mm (-10m)	Bottle Roll	4	66.3	0.51	29.9
-75µ	Bottle Roll	4	67.6	0.50	28.1
-75µ	Bottle Roll	30	74.2	0.53	24.5

Representative Feed Grade with Benign Test Conditions that Can be Replicated in Commercial Setting

The leaching bottle roll and column tests were performed at room temperature and at atmospheric pressure based on Gibellini's representative grade from grab sampling method across the width of the mineralization at various locations throughout the Project. These samples are characterized in the following table:

Sample Number	Sample ID	Weight (kg)	Head Grade V2O5 (%)
1	18-L6-28	17.0	0.665
2	18-L6-29	17.0	0.885
3	18-L6-30	12.5	0.370
4	18-L6-31	18.0	0.210
5	18-L6-32	13.5	0.420
6	18-L6-33	22.5	0.280
7	18-L6-34	19.0	0.315
8	18-L6-35	20.0	0.185
9	18-L6-36	18.0	0.165
10	18-L6-37	20.0	0.195
Total		177.5	

For the purpose of metallurgical testing, the samples were mixed to produce a composite material with the average grade of 0.30% V2O5 which is representative of Gibellini resource grade. The composite material was ground to -75 µm feed size. Prophecy believes the test conditions can easily be replicated in a commercial heap leach setting with low technical and implementation risk.

Unique Vanadium Mineralogy in Achieving Remarkable Recovery at Room Temperature and Atmospheric Pressure

NWME performed detailed mineralogical analysis which included microscope identification using Carl Zeiss Axioskop, XRD analysis on Bruker D8-A25 XRD, multi-element analysis, electron probe X-ray microanalysis on JEOL JXA 8230, scanning electron microscopy/energy dispersive X-ray spectroscopy analysis on Mineral Liberation Analyzer 650 and V element phase analysis. This mineralogical analysis confirmed that the Gibellini resource has a high percentage of independent vanadium minerals (“IVM”) such as kazakhstanite, shubnelite, sherwoodite, bokite, which can be leached easily at room temperature and atmospheric pressure within a short time frame.

NWME noted the unique nature of the Gibellini samples with over 45% IVM versus numerous other typical black shale deposits which they have encountered containing less than 10% IVM.

All of the testwork carried out on the material from the Project indicate that there is a two-stage leaching phenomenon in Gibellini ore - about 50% of the vanadium leaches in the first 96 hours (independent vanadium minerals), and the remaining leaching approximately 15 to 20% occurs over a longer time horizon.

Heap leaching is the lowest-cost recovery method compared to roasting, and pressured container VAC leaching, whereby capital costs can compound to multiple times greater for the same throughput. Gibellini’s high IVM content is a key competitive differentiator which places the deposit in the top tier of black shale deposits in terms of pre-production capital cost required based on NWME’s research.

The mineralogical results of the Gibellini ore as characterized by NWME’s testwork is shown in the following table:

Mineral composition		Mineral content	% V content in minerals	% V di
Independent vanadium minerals 45.2% of vanadium content	Kazakhstanite	0.15	40.91	19.7
	Shubnelite	0.13	27.86	11.6
	Sherwoodite	0.08	34.54	8.90
	Bokite	0.03	36.51	3.53
	Melanovanadite	0.01	41.27	1.33
Vanadium-bearing layered aluminosilicate minerals 20.8% of vanadium content	Sericite	8.59	0.57	14.6
	Illite	5.58	0.28	5.03
	Chlorite	0.81	0.44	1.14
	Nacrite-palygorskite	0.70	-	-
Vanadium-bearing layered iron oxide, sulfate 34% of vanadium content	Limonite	1.76	5.48	31.0
	Strengite	0.64	0.49	1.01
	Jarosite	0.48	1.24	1.92

Gangue	Quartz	75.88	-	-
	Apatite	2.83	-	-
	Potassium feldspar	0.73	-	-
	Dolomite	0.66	-	-
	Carbonaceous	0.45	-	-
	Rutile	0.25	-	-
	Barite	0.04	-	-
	Pyrite	0.20	-	-
Total		100.00		100.00

Low Carbon Content Results in Exceptional Low Acid Consumption

NWME detailed mineralogical analysis which included microscope identification using Carl Zeiss Axioskop, XRD analysis on Bruker D8-A25 XRD, multi-element analysis, electron probe X-ray microanalysis on JEOL JXA 8230, scanning electron microscopy/energy dispersive X-ray spectroscopy analysis on Mineral Liberation Analyzer 650 and V element phase analysis, confirmed the extremely low carbonaceous content of Gibellini’s oxide and transition samples. This explains the low acid consumption (less than 50 kg per tonne) compared to other average black shale deposits of 200 kg to 300 kg per tonne based on extensive NWME data compilation. Given acid cost accounts for approximately 50% of the Project’s operating expenses, Gibellini’s low carbon content is a key competitive differentiator which places it in the top tier of black shale deposits in terms of processing cost based on NWME’s findings.

The following table is a generalized comparison of Gibellini’s deposit to a composite of typical black shale vanadium deposits:

Gibellini Vanadium Deposit		
Host Rock	Silica State	
The Mineral Composition	High Silica, Low Aluminium and Low Carbonaceous.	SiO ₂ -78.40%
	4.13%; T(C) - 0.47%	

The next step for NWME will be to investigate the application of NWME’s proprietary technology to Gibellini mineral to produce a high purity vanadium pentoxide product with 99.5% V₂O₅ content. During the Prophecy’s team visit to NWME’s processing facilities in China in June 2018, NWME commented that its own black-shale vanadium mine produces exclusively 99.5% V₂O₅ which commands a 15 to 25% pricing premium (compared to benchmark 98% purity) to supply to the vanadium battery, chemical, and aerospace industries. Prophecy has prepared the representative samples from the Project with a total weight of 1.6 tonnes and is ready to ship the samples to China. Prophecy expects to receive the results from the second phase of metallurgical testing by NWME by the end of 2018.

Management Discussion and Summary

Michael Drozd, V-P, Operations, states: “NWME’s comprehensive Gibellini mineral analysis demonstrates a high concentration of independent vanadium oxide minerals comprising 45% of the contained vanadium with very low carbon content (0.5%). This phenomenon is rare and possibly one-of-a-kind when it comes to black shale vanadium deposits, and enables Gibellini to adopt a heap leach process at ambient temperature and atmospheric pressure with high recovery and low acid consumption. Those important metallurgical attributes are key in establishing a high confidence level in Gibellini’s projected low capital cost, low operating cost, and simple flow sheet with minimal technical and implementation risks.”

With NWME's new findings and confirmation of prior metallurgical tests done by McClelland Laboratories and basic engineering studies carried out by Scotia International, Prophecy has finalized the process flow sheet and is preparing to tender Engineering, Procurement, Construction and Management (EPCM) proposals shortly, in August 2018.

Qualified Person

The technical contents of this news release have been prepared under the supervision of Danniël Oosterman, VP, Exploration. Mr. Oosterman is not independent of the Company in that he is employed as a consultant to the Company and most of his income is derived from the Company. Mr. Oosterman is a Qualified Person as defined in NI 43-101.

About Prophecy

[Prophecy Development Corp.](#) is a Canadian public company listed on the Toronto Stock Exchange. Prophecy's main objective is to develop the Gibellini primary vanadium mining project in the Battle Mountain region in northeastern Nevada to production. Further information on Prophecy can be found at www.prophecydev.com.

[Prophecy Development Corp.](#)

ON BEHALF OF THE BOARD

“JOHN LEE”

Executive Chairman

For more information about Prophecy, please contact Investor Relations:

+1.888.513.6286

ir@prophecydev.com

www.prophecydev.com

Neither the Toronto Stock Exchange nor its Regulation Services Provider (as that term is defined in the policies of the Toronto Stock Exchange) accepts responsibility for the adequacy or accuracy of this release.

Cautionary Note Regarding Forward-Looking Statements

Certain statements contained in this news release, including statements which may contain words such as “expects”, “anticipates”, “intends”, “plans”, “believes”, “estimates”, or similar expressions, and statements related to matters which are not historical facts, are forward-looking information within the meaning of applicable securities laws. Such forward-looking statements, which reflect management's expectations regarding Prophecy's future growth, results of operations, performance, business prospects and opportunities, are based on certain factors and assumptions and involve known and unknown risks and uncertainties which may cause the actual results, performance, or achievements to be materially different from future results, performance, or achievements expressed or implied by such forward-looking statements.

These factors should be considered carefully, and readers should not place undue reliance on the Prophecy's forward-looking statements. Prophecy believes that the expectations reflected in the

forward-looking statements contained in this news release and the documents incorporated by reference herein are reasonable, but no assurance can be given that these expectations will prove to be correct. In addition, although Prophecy has attempted to identify important factors that could cause actual actions, events or results to differ materially from those described in forward looking statements, there may be other factors that cause actions, events or results not to be as anticipated, estimated or intended. Prophecy undertakes no obligation to release publicly any future revisions to forward-looking statements to reflect events or circumstances after the date of this news or to reflect the occurrence of unanticipated events, except as expressly required by law.

To view the original release, please click [here](#)

Source: [Prophecy Development Corp.](#) (TSX:PCY, OTCQX:PRPCF, FWB:1P2N, LSE:0VDT)

To follow [Prophecy Development Corp.](#) on your favorite social media platform or financial websites, please click on the icons below.

Maximum News Dissemination by FSCwire. <https://www.fscwire.com>

Copyright © 2018 FSCwire

Dieser Artikel stammt von [Rohstoff-Welt.de](#)

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/306308--Prophecy-Technology-Partner-NWME-Produces-98.6Prozent-Pure-V2O5-Vanadium-Pentoxide-from-Gibellini-Sam>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).