

# Cantex Mine Development Corp. Intersects 8.95 Metres of Massive Sulphides

01.02.2021 | [CNW](#)

## Including 4.05 Metres of 39.39% Lead-Zinc and 130 g/t Silver at North Rackla, Yukon

KELOWNA, Feb. 1, 2021 - [Cantex Mine Development Corp.](#) (TSXV: CD) (the "Company") has released an update on the work program at its 14,077 hectare North Rackla claim block where drill results continue to define a lead-zinc-silver mineralized system with Broken Hill Type (BHT) affinities.

Dr. Chuck Fipke reports

### HIGHLIGHTS

- Hole YKDD20-174, drilled at the GZ Zone intersects 4.05 metres of 39.39% lead-zinc with 130 g/t silver within an 8.95 metre interval containing 22.77% lead-zinc and 76.4 g/t silver.

### GZ ZONE RESULTS

Assay results have been received for three holes drilled from pad GZ02 at the GZ Zone. As presented in Table 1, a high-grade interval was intersected in hole YKDD20-174, drilled at a -45 degree dip, which contained 32.14% zinc, 7.25% lead and 130 g/t silver. This was contained within an 8.95 metre zone which contained 18.08% zinc, 4.69% lead and 76.4 g/t silver.

The directors are most encouraged by this exceptionally high-grade silver-lead-zinc intersection in a new area covered in glacial till 550 metres southeast of the high-grade extension zone. This exceptionally high grade (which is 1,182 g/ton silver equivalent, calculated using metal prices of \$1.16/lb zinc, \$0.91/lb lead and \$28.60/oz silver) is equivalent to the high-grade intersections into the 2.1 km long Discovery zone which have yielded grades exceeding the average grade of any large silver-lead-zinc mine (see news releases from November 5, 2019; January 30, 2020; and October 28, 2020).

Hole YKDD20-175 also contained a 2.8 metre interval which contained 11.96% zinc, 3.52% lead and 39.5 g/t silver. As limited drilling conducted to date into the GZ Zone covered in overburden has yet to determine the orientation of the mineralization, true widths can not yet be determined. Lengths in this release refer to core lengths.

### MAIN ZONE RESULTS

Results from one hole drilled at the Main Zone have been received. Several small intercepts of mineralization were encountered in hole YKDD20-165 with two intercepts containing over 15% lead-zinc.

Table 1. Drill results

Pad	Dip Hole	From	To	Length	Silver	Lead + Lead	Zinc	Copper	Mn
		(m)	(m)	(m)	(g/t)	(%)	(%)	(%)	(%)
GZ02	-45 YKDD20-174	68.95	69.45	0.50	25.3	10.88	2.06	8.82	0.00
		73.15	82.10	8.95	76.4	22.77	4.69	18.08	0.01
	Including	76.25	80.30	4.05	130.0	39.39	7.25	32.14	0.01
	-55 YKDD20-175	82.10	84.90	2.80	39.5	15.48	3.52	11.96	0.04
	-65	No significant results							
MZ0X	-65 YKDD20-165	421.80	422.30	0.50	9.6	3.81	2.60	1.21	0.01
		465.25	465.90	0.65	75.9	15.43	11.60	3.83	0.03
		484.60	485.10	0.50	11.9	3.39	3.22	0.17	0.01
		587.10	587.60	0.50	25.5	15.78	14.30	1.48	0.04

The Company continues to be impressed with the results from the Massive Sulphide project, where drilling of hidden targets defined by extrapolating geological mapping are being tested. Samples from an additional 13 holes from the 2020 drill program have been submitted for assay and the results will be released as soon as received.

The drill holes reported in this press release were drilled using HQ (63.5mm) diamond drill bits. The core was logged, marked up for sampling and then divided into equal halves using a diamond saw on site. One half of the core was left in the original core box. The other half was sampled and placed into sealed bags which were in turn placed into larger bags closed with security seals prior to being transported to CF Mineral Research Ltd. in Kelowna, BC.

At CF Minerals the drill core was dried prior to crushing to -10 mesh. The samples, which averaged over 3kg, were then mixed prior to splitting off 800g. The 800g splits were pulverized to -200 mesh and a 250g split was sent for assay. Quality control procedures included running a barren sand sample through both the crusher and pulveriser between each sample to ensure no inter-sample contamination occurred. Silica blanks were inserted along with certified reference samples. These quality control samples were each inserted approximately every 20 samples.

ALS Chemex in Vancouver assayed the samples using a four-acid digestion with an ICP-MS finish. The 48 element ME-MS61 technique was used to provide a geochemical signature of the mineralization. Where lead, zinc or copper values exceeded one percent the Pb-OG62, Zn-OG62 or Cu-OG62 techniques were used. These have upper limits of 20% lead, 30% zinc and 50% copper, respectively. Samples with lead and zinc values over these limits were then analyzed by titration methods Pb-VOL70 and Zn-VOL50. Where silver samples exceeded 100 g/t the Ag-OG62 technique was used which has an upper limit of 1,500 g/t. The over limit analyses contributed to delays in receiving final assay results.

The technical information and results reported here have been reviewed by Mr. Chad Ulansky P.Geol., a Qualified Person under National Instrument 43-101, who is responsible for the technical content of this release.

Signed,

Charles Fipke

Charles Fipke  
Chairman

Neither TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release. Information set forth in this news release includes forward-looking statements under applicable securities laws. Forward-looking statements are statements that relate to future, not past, events. In this context, forward-looking statements often address expected future business and financial performance, and often contain words such as "anticipate", "believe", "plan", "estimate", "expect", and "intend", statements that an action or event "may", "might", "could", "should", or "will" be taken or occur, or other similar expressions. All statements, other than statements of historical fact, included herein including, without limitation; statements about the terms and completion of the proposed sale transaction are forward-looking statements. By their nature, forward-looking statements involve known and unknown risks, uncertainties and other factors which may cause the actual results, performance or achievements, or other future events, to be materially different from any future results, performance or achievements expressed or implied by such forward-looking statements. Such factors include, among others, risks identified in the management discussion and analysis section of the Company's interim and most recent annual financial statements or other reports and filings with Canadian securities regulators. Forward looking statements are made based on management's beliefs, estimates and opinions on the date that statements are made and the respective companies undertake no obligation to update forward-looking statements if these beliefs, estimates and opinions or other circumstances should change, except as required by applicable securities laws. Investors are cautioned against attributing undue certainty to forward-looking statements.

SOURCE [Cantex Mine Development Corp.](#)

#### Contact

[Cantex Mine Development Corp.](#), Tel: +1-250-860-8582; Email: [info@cantex.ca](mailto:info@cantex.ca)

---

Dieser Artikel stammt von [Rohstoff-Welt.de](#)

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/373512--Cantex-Mine-Development-Corp.-Intersects-8.95-Metres-of-Massive-Sulphides.html>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

---

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!  
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2025. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).