

Perseus Achieves Near-Mine Exploration Success in Ghana

17.01.2022 | [GlobeNewswire](#)

PERTH, Jan. 18, 2022 - [Perseus Mining Ltd.](#) (ASX/TSX: PRU) is pleased to provide details of exploration success at its Edikan Gold Mine in Ghana during the December 2021 quarter.

HIGHLIGHTS

- Perseus has recorded further impressive drilling results at Nkosuo prospect on the Agyakusu Prospecting Licence, just seven kilometres from its Edikan Gold Mine in Ghana.
- Results continue to demonstrate strong potential for shallow, granite-hosted open-pitiable gold resources, including:
 - NKS0034RC: 37m @ 1.49g/t Au from 3m
 - NKS0050RD: 60m @ 1.28g/t from 6m
 - NKS0037DD: 43m @ 1.79 g/t from 0m
 - NKS0050RD: 24m @ 2.04g/t Au from 6m
 - NKS0059RD: 37m @ 1.74 g/t Au from 8m
 - NKS0060RC: 51m @ 2.09 g/t Au from 20m
 - NKS0081RC: 46m @ 2.31g/t Au from 18m
 - NKS0086RD: 13m @ 4.18g/t Au from 1m & 54m @ 1.63g/t Au from 54m
 - NKS0091RD: 34m @ 1.3g/t Au from surface & 14m @ 2.17 g/t from 58m
 - NKS0092RD: 38m @ 1.83g/t Au from 38m & 24m @ 1.65g/t Au from 90m
 - NKS0102RD: 26m @ 1.55g/t Au from surface
 - NKS0117RC: 22m @ 3.92 g/t from 8m
 - NKS0120RC: 16m @ 4.17 g/t Au from 24m
- Results confirm Nkosuo hosts near-surface, granite-hosted gold mineralisation similar in style to that mined in Edikan's Fobinso and Abnabna ("AG") pits.
- Resource definition drilling is ongoing. Perseus expects to complete a maiden Mineral Resource estimate for Nkosuo early in the June 2022 quarter.
- Nkosuo discovery has the potential to extend Edikan's mine life beyond forecast end in FY2026-2027.

Perseus's Managing Director and CEO Jeff Quartermaine said:

"As Perseus moves closer to achieving our goal of producing 500,000 ounces of gold per year, we have turned our sights to finding ways of sustaining this level of gold production to the end of the decade and beyond.

"Our exploration programme at Nkosuo has returned impressive results that demonstrate this prospect's potential to add to Edikan's mine life, with further successful drilling. We are particularly encouraged by similarities between the Nkosuo deposit and the Fobinso and Abnabna deposits which we've already successfully developed, mined and processed at Edikan.

"While we are working towards completing a maiden Mineral Resource estimate for Nkosuo in the first half of CY2022, we intend to continue exploring on the Agyakusu, Agyakusu-DML and Domenase exploration licence areas, all of which are under option to Perseus and all of which are located within trucking distance of our Edikan mill."

NKOSUO EXPLORATION DRILLING

Results from Perseus's recent exploration activities adjacent to its Edikan Gold Mine (Edikan) in Ghana continue to confirm the outstanding potential to grow its gold inventory at Edikan through further drilling

success.

Perseus secured an option to acquire the 23.85km² Agyakusu prospecting licence (*Appendix 1 - Figure 1.1*), currently held by Ghanaian company Adio-Mabas Ghana Ltd, in November 2019 (see ASX announcement 4 November 2019). Perseus subsequently conducted soil sampling and airborne geophysical surveys whilst negotiating access from farmers to drill the granite-hosted Nkosuo gold prospect. Perseus achieved access in June 2021, with drilling continuing uninterrupted since that date.

Perseus commenced exploration drilling at the Nkosuo prospect on the Agyakusu permit on 1 July 2021, with the first highly encouraging results being reported in our ASX release dated 13 October 2021. Since that date, Perseus had drilled a further 13,008 metres in 36 Reverse Circulation ("RC"), 5 diamond ("DD") holes and 46 RC pre-collared diamond holes ("RD"). Drilling has been conducted on a nominal 80 x 80 metre grid to scope out the extent and overall geometry of the host granite and contained mineralisation, partially infilled to 40 x 40 metres and locally to 40 x 20 metres. Results have continued to provide strong support for the presence of a shallow open-pitiable gold resource within trucking distance of the Edikan mill.

Mineralisation at Nkosuo is hosted by a NNE-trending granitic plug extending at least 1,200 metres in strike, with widths ranging from around 120 metres in the northern part to up to 160 metres in the southern part. The northern part of the intrusive body is dislocated by a roughly NW-SE fault that offsets the northern 400 metres of the body ~160 metres to the northwest (*Appendix 1 - Figure 1.2*).

The strongest mineralisation is focused in the offset northern part of the intrusion and the northern central section of the southern part of the intrusion, gradually waning to the southwest. The granite body dips at around 70° to the west in the northern part of the intrusion, steepening to near vertical towards the south. Mineralisation within the granite consists of variably intense quartz stockwork veining with associated quartz-carbonate-sericite alteration. The veining and alteration are accompanied by 1-2% disseminated and selvage pyrite and arsenopyrite, with better gold grades generally associated with higher concentrations of arsenopyrite. The granite remains open to the south, with indications from surface workings that mineralisation may strengthen within the southern apex of the intrusion, analogous to the situation in the northern apex. Drilling to test this hypothesis is planned for the coming quarter.

Overall, the Nkosuo mineralisation bears strong similarities in style and scale to the western granite-hosted deposits at Edikan such as Fobinso and Abnabna.

Better intercepts from the Nkosuo drilling received between 13 October 2021 and 8 January 2022 are shown below in *Table 1* and on *Appendix 1 - Figure 2*, with a complete summary included in *Appendix 2 - Table 1*. Representative sections are presented in *Appendix 1 - Figures 1.3 to 1.5*.

*Table 1: Intercepts from Agyakusu Prospecting Licence - Nkosuo Prospect
(Based on lower cut-off of 0.5 g/t Au with maximum 2m internal waste <0.5 g/t)*

Hole ID	From (m)	To (m)	Gold Intercept
NKS0024RD 125	125	127	2m @ 7.2 g/t
NKS0024RD 135	135	147	12m @ 0.91 g/t
NKS0024RD 157	157	169	12m @ 1.53 g/t
NKS0024RD 187	187	192	5m @ 1.29 g/t
NKS0024RD 201	201	207	6m @ 1.11 g/t
NKS0025RD 116	116	124	8m @ 1.15 g/t
NKS0025RD 140	140	159.1	19.1m @ 0.72 g/t
NKS0025RD 273	273	281.8	8.8m @ 1.07 g/t
NKS0034RC 3	3	40	37 @ 1.49 g/t
NKS0036RD 162	162	164	2m @ 6.27 g/t
NKS0036RD 284	284	292.65	8.7m @ 1.21 g/t
NKS0037DD 6.9	6.9	44	37.1m @ 2.05 g/t
NKS0037DD 48.6	48.6	60.15	11.6m @ 1.83 g/t
NKS0038DD 0	0	5.59	5.6m @ 1.26 g/t

NKS0040DD 13.3	28.3	15m @ 0.97 g/t
NKS0043RD 234.85	238.13	3.3m @ 3.15 g/t
NKS0044RD 18	24	6m @ 1.95 g/t
NKS0044RD 18	20	2m @ 4.06 g/t
NKS0044RD 28	40	12m @ 0.82 g/t
NKS0044RD 46	64	18m @ 0.65 g/t
NKS0046DD 0	23.9	23.9m @ 0.66 g/t
NKS0046DD 27.3	29.3	2m @ 3.29 g/t
NKS0047RD 12	28	16m @ 1.16 g/t
NKS0047RD 32	64	32m @ 0.89 g/t
NKS0048RD 68	70	2m @ 8.35 g/t
NKS0048RD 102	104	2m @ 3.58 g/t
NKS0048RD 250.5	253	2.5m @ 87.30 g/t
NKS0049RD 28	36	8m @ 1.31 g/t
NKS0049RD 46	50	4m @ 1.35 g/t
NKS0049RD 116	120	4m @ 2.05 g/t
NKS0050RD 6	30	24m @ 2.04 g/t
NKS0050RD 36	42	6m @ 1.51 g/t
NKS0050RD 56	66	10m @ 1.15 g/t
NKS0053RD 104	112	8m @ 1.07 g/t
NKS0059RD 0	4	4m @ 2.47 g/t
NKS0059RD 8	45	37m @ 1.74 g/t
NKS0060RC 20	71	51m @ 2.09 g/t
NKS0061RD 11	50	39m @ 0.98 g/t
NKS0061RD 64	69	5m @ 4.36 g/t
NKS0062RD 74	90	16m @ 1.08 g/t
NKS0063RC 40	52	12m @ 1.74 g/t
NKS0064RD 62	68	6m @ 2.40 g/t
NKS0064RD 82	87	5m @ 2.44 g/t
NKS0065RD 72	78	6m @ 1.62 g/t
NKS0065RD 116	120	4m @ 1.92 g/t
NKS0066RD 62	66	4m @ 2.62 g/t
NKS0066RD 82	92	10m @ 0.81 g/t
NKS0066RD 96	98	2m @ 4.64 g/t
NKS0067RD 46	54	8m @ 3.51 g/t
NKS0067RD 66	78	12m @ 1.31 g/t
NKS0067RD 94	110	16m @ 2.45 g/t
NKS0068RD 36	74	38m @ 0.8 g/t
NKS0068RD 84	106	22m @ 1.76 g/t
NKS0072RD 68	76	8m @ 1.68 g/t
NKS0076RD 2	6	4m @ 1.50 g/t
NKS0079DD 58	95.1	37m @ 0.89 g/t
NKS0079DD 115.3	128.33	13m @ 1.23 g/t
NKS0079DD 142.13	151.5	9.4m @ 2.93 g/t
NKS0081RC 4	8	4m @ 2.01 g/t
NKS0081RC 18	64	46m @ 2.31 g/t
NKS0081RC 86	98	12m @ 0.79 g/t
NKS0082RC 0	4	4m @ 25.8 g/t
NKS0082RC 30	50	20m @ 0.88 g/t
NKS0082RC 70	72	2m @ 3.77 g/t
NKS0083RC 20	66	46m @ 1.2 g/t
NKS0085RD 82	84	2m @ 5.28 g/t

NKS0085RD 96	108	12m @ 2.39 g/t
NKS0085RD 106	108	2m @ 5.4 g/t
NKS0086RD 1	14	13m @ 4.18 g/t
NKS0086RD 54	108	54m @ 1.63 g/t
NKS0087RD 2	16	14m @ 1.15 g/t
NKS0087RD 24	30	6m @ 1.87 g/t
NKS0087RD 46	60	14m @ 1.21 g/t
NKS0087RD 66	86	20m @ 0.63 g/t
NKS0087RD 90	124	34m @ 0.96 g/t
NKS0088RD 10	28	18m @ 0.75 g/t
NKS0088RD 38	60	22m @ 0.89 g/t
NKS0091RD 0	34	34m @ 1.3 g/t
NKS0091RD 58	72	14m @ 2.17 g/t
NKS0091RD 106	128	22m @ 1.01 g/t
NKS0092RD 38	76	38m @ 1.83 g/t
NKS0092RD 80	86	6m @ 1.11 g/t
NKS0092RD 90	114	24m @ 1.65 g/t
NKS0093RC 10	22	12m @ 1.69 g/t
NKS0093RC 36	54	18m @ 1.64 g/t
NKS0093RC 62	72	10m @ 3.78 g/t
NKS0097RC 1	12	11m @ 1.23 g/t
NKS0097RC 20	42	22m @ 1.21 g/t
NKS0102RD 0	26	26m @ 1.55 g/t
NKS0102RD 60	62	2m @ 8.82 g/t
NKS0102RD 120	126	6m @ 2.49 g/t
NKS0103RC 0	28	28m @ 0.95 g/t
NKS0104RD 44	48	4m @ 5.51 g/t
NKS0104RD 52	84	32m @ 1.28 g/t
NKS0104RD 118	124	6m @ 1.69 g/t
NKS0104RD 142	148	6m @ 1.76 g/t
NKS0114RC 42	58	16m @ 0.77 g/t
NKS0114RC 64	76	12m @ 2.22 g/t
NKS0117RC 8	30	22m @ 3.92 g/t
NKS0120RC 24	40	16m @ 4.17 g/t
NKS0121RD 12	14	2m @ 6.99 g/t
NKS0121RD 28	42	14m @ 1.69 g/t
NKS0123RD 9	12	3m @ 6.97 g/t
NKS0123RD 24	42	18m @ 1.96 g/t
NKS0123RD 48	60	12m @ 2.42 g/t
NKS0124RD 18	24	6m @ 2.0 g/t

Results available to date from the Nkosuo drilling confirm the previously declared potential for an Exploration Target of 10 to 15 Mt grading 0.9 to 1.1 g/t gold for 275 to 500koz contained gold (ASX release dated 13 October 2021). Current indications are that the bulk of this resource will be at depths shallower than 150 metres.

The Exploration Target is conceptual in nature and takes no account of geological complexity, possible mining method or metallurgical recovery factors. The Exploration Target was estimated to enable an early assessment of the discovery's potential to add to Edikan's mine life

The potential quantity and grade of the Exploration Target is conceptual in nature and therefore is an approximation. There has been insufficient exploration to estimate a Mineral Resource and it is uncertain if further exploration will result in estimation of a Mineral Resource. The Exploration Target has been prepared

and reported in accordance with the 2012 edition of the JORC Code and NI 43-101.

The Exploration Target is defined by:

- A wireframe of the host granite body used to limit the extent of interpreted mineralisation volume.
- Drill sample intervals composited to uniform 2 metre down-hole lengths with composite gold grades capped at 10g/t.
- Gold grades estimated by inverse distance squared weightings (IDW) into parent blocks with dimensions 20 metres east x 20 metres north x 10 metres elevation using a 50 metres east x 100 metres north x 100 metre elevation search ellipsoid with a minimum of four samples required to make an estimate.
- Estimates informed only by samples within the granite.
- Parent blocks sub-blocked against the granite wireframe and interpreted weathering surfaces using a minimum 5 metres east x 5 metres north x 2.5 metres elevation sub-block to reliably estimate the mineralisation volume.
- Densities for weathered, transition and fresh rock assumed to be 1.8, 2.1 and 2.7 tonnes per cubic metre.
- Sub-blocks grading greater than 0.4g/t gold and to a maximum vertical depth of approximately 170 metres.

NEXT STEPS

- Drilling now underway at Nkosuo will focus on extending 80 x 80 metres coverage to the southern limits of the granite, completing the 40 x 40 metres infill coverage and commencing systematic infill to 40 x 20 metres to support a Mineral Resource estimate to be undertaken in the June 2022 quarter.
- Metallurgical testwork has commenced and Perseus will complete geotechnical drilling to evaluate Ore Reserve potential early in the September Quarter of 2022.
- In anticipation that this work will lead to a positive outcome, the Company is in the process of exercising its option over the Agyakusu permit and has completed some baseline studies to meet the requirements of the ESIA process.
- Exploration more broadly at Edikan will investigate high-order prospects on the adjacent Agyakusu DML and Domenase permits where soil geochemical sampling has identified strong gold-in-soil anomalies associated with mineralised granites.

This announcement has been approved for release by Perseus's Managing Director and Chief Executive Officer, Jeff Quartermaine.

COMPETENT PERSON STATEMENT:

The information in this report and the attachments that relate to exploration drilling results and the Nkosuo Exploration Target on the Agyakusu permit is based on, and fairly represents, information and supporting documentation prepared by Dr Douglas Jones, a Competent Person who is a Chartered Professional Geologist. Dr Jones is the Group General Manager Exploration of the Company. Dr Jones has sufficient experience, which is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken, to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves') and to qualify as a "Qualified Person" under National Instrument 43-101 - Standards of Disclosure for Mineral Projects ("NI 43-101"). Dr Jones consents to the inclusion in this report of the matters based on his information in the form and context in which it appears.

CAUTION REGARDING FORWARD LOOKING INFORMATION:

This report contains forward-looking information which is based on the assumptions, estimates, analysis and opinions of management made in light of its experience and its perception of trends, current conditions and expected developments, as well as other factors that management of the Company believes to be relevant and reasonable in the circumstances at the date that such statements are made, but which may prove to be incorrect. Assumptions have been made by the Company regarding, among other things: the price of gold, continuing commercial production at the Yaour? Gold Mine, Edikan Gold Mine and Sissingu? Gold Mine without any major disruption due to the COVID-19 pandemic or otherwise, the receipt of required governmental approvals, the accuracy of capital and operating cost estimates, the ability of the Company to

operate in a safe, efficient and effective manner and the ability of the Company to obtain financing as and when required and on reasonable terms. Readers are cautioned that the foregoing list is not exhaustive of all factors and assumptions which may have been used by the Company. Although management believes that the assumptions made by the Company and the expectations represented by such information are reasonable, there can be no assurance that the forward-looking information will prove to be accurate. Forward-looking information involves known and unknown risks, uncertainties, and other factors which may cause the actual results, performance or achievements of the Company to be materially different from any anticipated future results, performance or achievements expressed or implied by such forward-looking information. Such factors include, among others, the actual market price of gold, the actual results of current exploration, the actual results of future exploration, changes in project parameters as plans continue to be evaluated, as well as those factors disclosed in the Company's publicly filed documents. The Company believes that the assumptions and expectations reflected in the forward-looking information are reasonable. Assumptions have been made regarding, among other things, the Company's ability to carry on its exploration and development activities, the timely receipt of required approvals, the price of gold, the ability of the Company to operate in a safe, efficient and effective manner and the ability of the Company to obtain financing as and when required and on reasonable terms. Readers should not place undue reliance on forward-looking information. Perseus does not undertake to update any forward-looking information, except in accordance with applicable securities laws.

CONTACTS:

ASX/TSX CODE: PRU

Jeff Quartermaine

REGISTERED OFFICE:

Managing Director & CEO

jeff.quartermaine@perseusmining.com

Level 2

437 Roberts Road
Subiaco WA 6008

Nathan Ryan

Telephone: +61 8 6144 1700

Email: IR@perseusmining.com

Media Relations

+61 4 20 582 887

nathan.ryan@nwrcommunications.com.au

ABN: 27 106 808 986

Claire Hall

www.perseusmining.com

Corporate Communications

claire.hall@perseusmining.com

APPENDIX 1 - FIGURES

Figure 1.1: Edikan Gold Project - Regional Geology, Tenements and Prospects is available at <https://www.globenewswire.com/NewsRoom/AttachmentNg/8b4ae3bf-5b48-4a13-ae43-39047a11f09f>

Figure 1.2: Nkosuo Prospect - Drilling and Selected Results. Locations of Sections 1-3 shown is available at <https://www.globenewswire.com/NewsRoom/AttachmentNg/29afe602-c3e7-4e70-ba66-e246fc22d986>

Figure 1.3: Nkosuo Prospect - Drill Section 1 - 20,160N Local Grid is available at <https://www.globenewswire.com/NewsRoom/AttachmentNg/5fec9b50-112e-45ce-a598-a433aeb30b77>

Figure 1.4: Nkosuo Prospect - Drill Section 2 - 20,080N Local Grid is available at <https://www.globenewswire.com/NewsRoom/AttachmentNg/008f9489-b48b-4684-b2c1-bd9822cae4e2>

Figure 1.5: Nkosuo Prospect - Drill Section 3 - 19,920N Local Grid is available at <https://www.globenewswire.com/NewsRoom/AttachmentNg/f954de10-4e10-4319-9afb-cc04ed4f0463>

APPENDIX 2 - SIGNIFICANT INTERCEPTS

Table 2.1: Nkosuo drill holes and significant assays

Hole ID	East (mE)	North (mN)	Drill Type	Azimuth (?)	Dip (?)	Depth (m)	No of samples	From (m)	To (m)	Width (m)	Grade (g/t)
---------	-----------	------------	------------	-------------	---------	-----------	---------------	----------	--------	-----------	-------------

NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	1	3	4	1	1.57
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	1	19	20	1	1.93
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	2	55	57	2	1.82
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	1	67.2	68	0.8	0.6
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	2	79	81	2	1.13
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	1	85	86	1	0.9
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	3	98.2	100	2.8	0.67
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	1	106	107	1	0.78
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	2	125	127	2	7.2
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	12	135	147	12	0.91
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	1	153.9	155	1.1	0.52
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	12	157	169	12	1.53
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	5	187	192	5	1.29
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	6	201	207	6	1.11
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	2	223	225	2	1.09
NKS0024RD	10878.43	20118.21	RD	119	-55 270.6	1	250.32	251.8	1.48	1.37
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	4	109	113	4	0.72
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	8	116	124	8	1.15
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	6	131	137	6	0.74
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	19	140	159.1	19.1	0.72
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	172	173	1	1.95
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	3	177	180.1	3.1	0.98
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	186	187	1	0.84
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	198	199	1	1.02
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	216	217.1	1.1	0.91
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	9	273	281.8	8.8	1.07
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	4	297.1	301	3.9	1.16
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	300	301	1	3.65
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	320	321	1	0.54
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	326	327	1	1.19
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	331	331.5	0.5	0.93
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	3	335	338	3	0.51
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	346	347	1	0.66
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	366	367	1	0.66
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	374.1	375.2	1.1	0.71
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	1	379	380.1	1.1	0.54
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	5	383.1	387.9	4.8	0.81
NKS0025RD	10921.06	19920.41	RD	119	-55 414.3	2	396	398.1	2.1	0.98
NKS0027RD	11033.98	19677.63	RD	119	-55 210.3	1	96	98	1	0.74
NKS0027RD	11033.98	19677.63	RD	119	-55 210.3	1	103	104	1	0.78
NKS0027RD	11033.98	19677.63	RD	119	-55 210.3	1	117	118	1	0.5
NKS0027RD	11033.98	19677.63	RD	119	-55 210.3	1	165	166.5	1.5	0.74
NKS0028RD	10915.46	19758.01	RD	119	-55 390.3	1	137	138.3	1.3	0.69
NKS0028RD	10915.46	19758.01	RD	119	-55 390.3	1	150	151.5	1.5	0.56
NKS0028RD	10915.46	19758.01	RD	119	-55 390.3	1	169	170.5	1.5	0.54
NKS0028RD	10915.46	19758.01	RD	119	-55 390.3	3	173.5	177.5	4	0.79
NKS0028RD	10915.46	19758.01	RD	119	-55 390.3	1	272	273	1	0.68
NKS0028RD	10915.46	19758.01	RD	119	-55 390.3	3	290	294	4	1.1
NKS0028RD	10915.46	19758.01	RD	119	-55 390.3	1	367	368	1	1.05
NKS0029RD	10999.04	19635.76	RD	119	-55 246.3	1	17	18	1	1.17
NKS0029RD	10999.04	19635.76	RD	119	-55 246.3	1	30	31	1	1.31
NKS0029RD	10999.04	19635.76	RD	119	-55 246.3	1	34	35	1	1.67

NKS0029RD	10999.04	19635.76	RD	119	-55	246.3	1	48	49	1	0.86
NKS0029RD	10999.04	19635.76	RD	119	-55	246.3	1	74	75	1	1.43
NKS0029RD	10999.04	19635.76	RD	119	-55	246.3	1	218.5	220	1.5	0.66
NKS0029RD	10999.04	19635.76	RD	119	-55	246.3	3	224.9	228	3.1	0.8
NKS0029RD	10999.04	19635.76	RD	119	-55	246.3	1	235	236	1	0.79
NKS0030RD	11035.32	19599.79	RD	119	-55	192.2	1	45	46	1	0.61
NKS0030RD	11035.32	19599.79	RD	119	-55	192.2	1	49	50	1	1.33
NKS0030RD	11035.32	19599.79	RD	119	-55	192.2	1	54	55	1	0.52
NKS0030RD	11035.32	19599.79	RD	119	-55	192.2	1	176.7	177.2	0.5	0.59
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	3	1	4	3	1.1
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	6	13	19	6	0.63
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	1	22	23	1	0.52
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	1	27	28	1	0.73
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	1	40	41	1	0.89
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	3	46	49	3	0.55
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	1	51	52	1	1
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	1	59	60	1	0.52
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	1	66	67	1	4.19
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	1	104.5	105.2	0.7	1.14
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	1	108.2	109.5	1.3	0.66
NKS0031RD	10997.39	19761.58	RD	119	-55	252.2	1	122.5	124	1.5	0.63
NKS0032RD	10998.27	19597.35	RC	119	-55	115	1	1	2	1	1.31
NKS0032RD	10998.27	19597.35	RC	119	-55	115	4	7	11	4	0.61
NKS0032RD	10998.27	19597.35	RC	119	-55	115	1	14	15	1	1.82
NKS0032RD	10998.27	19597.35	RC	119	-55	115	1	23	24	1	1.07
NKS0032RD	10998.27	19597.35	RC	119	-55	115	1	42	43	1	0.54
NKS0032RD	10998.27	19597.35	RC	119	-55	115	1	55	56	1	1.37
NKS0032RD	10998.27	19597.35	RC	119	-55	115	1	100	101	1	0.94
NKS0032RD	10998.27	19597.35	RC	119	-55	115	1	114	115	1	0.88
NKS0033RC	11113.34	19838.81	RC	119	-55	70	1	3	4	1	1.07
NKS0033RC	11113.34	19838.81	RC	119	-55	70	4	8	12	4	0.92
NKS0033RC	11113.34	19838.81	RC	119	-55	70	1	17	18	1	0.56
NKS0033RC	11113.34	19838.81	RC	119	-55	70	10	21	31	10	0.5
NKS0034RC	11115.02	19876.78	RC	119	-55	55	37	3	40	37	1.49
NKS0035RD	11075.02	19758.51	RD	119	-55	141.7	1	3	4	1	2.59
NKS0035RD	11075.02	19758.51	RD	119	-55	141.7	1	10	11	1	0.58
NKS0035RD	11075.02	19758.51	RD	119	-55	141.7	1	26	27	1	0.9
NKS0035RD	11075.02	19758.51	RD	119	-55	141.7	1	29	30	1	0.89
NKS0036RD	10842.27	19759.70	RD	119	-55	465	2	162	164	2	6.27
NKS0036RD	10842.27	19759.70	RD	119	-55	465	1	171	172	1	1
NKS0036RD	10842.27	19759.70	RD	119	-55	465	3	175	178	3	1.71
NKS0036RD	10842.27	19759.70	RD	119	-55	465	1	244	245	1	2.45
NKS0036RD	10842.27	19759.70	RD	119	-55	465	1	251	252.3	1.3	3.06
NKS0036RD	10842.27	19759.70	RD	119	-55	465	1	270	270.85	0.85	3.43
NKS0036RD	10842.27	19759.70	RD	119	-55	465	1	273	274	1	0.58
NKS0036RD	10842.27	19759.70	RD	119	-55	465	8	284	292.65	8.65	1.21
NKS0036RD	10842.27	19759.70	RD	119	-55	465	1	302.6	304	1.4	0.76
NKS0036RD	10842.27	19759.70	RD	119	-55	465	1	335.5	336.24	0.74	1.36
NKS0036RD	10842.27	19759.70	RD	119	-55	465	1	350	351	1	0.68
NKS0036RD	10842.27	19759.70	RD	119	-55	465	3	422	425	3	0.56
NKS0037DD	10959.31	20161.06	DD	119	-55	80.9	5	0	6	6	0.74
NKS0037DD	10959.31	20161.06	DD	119	-55	80.9	34	6.9	44	37.1	2.05

NKS0037DD	10959.31	20161.06	DD	119	-55	80.9	13	48.6	60.15	11.55	1.83
NKS0038DD	11012.27	20080.98	DD	119	-55	45.3	7	0	5.59	5.59	1.26
NKS0038DD	11012.27	20080.98	DD	119	-55	45.3	5	9.82	12.3	2.48	1.62
NKS0039DD	11037.19	20040.20	DD	119	-55	12.5	1	2.05	2.8	0.75	0.93
NKS0040DD	11020.69	20002.48	DD	119	-55	45	1	0	1.3	1.3	0.95
NKS0040DD	11020.69	20002.48	DD	119	-55	45	11	13.3	28.3	15	0.97
NKS0040DD	11020.69	20002.48	DD	119	-55	45	1	31.3	32.8	1.5	0.5
NKS0040DD	11020.69	20002.48	DD	119	-55	45	1	38.8	39.64	0.84	0.52
NKS0040DD	11020.69	20002.48	DD	119	-55	45	1	44	45	1	1.21
NKS0041DD	11035.62	19922.24	DD	119	-55	45.1	3	0	3.3	3.3	0.51
NKS0041DD	11035.62	19922.24	DD	119	-55	45.1	2	20.8	22.6	1.8	1.49
NKS0042RD	10835.13	19924.12	RD	119	-55	246.1	1	214.65	215.65	1	4.07
NKS0042RD	10835.13	19924.12	RD	119	-55	246.1	2	225	227	2	0.83
NKS0042RD	10835.13	19924.12	RD	119	-55	246.1	1	244	245	1	0.61
NKS0043RD	10959.8	19674.66	RD	119	-55	330.6	1	2	4	2	0.87
NKS0043RD	10959.88	19674.66	RD	119	-55	330.6	1	34	36	2	0.59
NKS0043RD	10959.88	19674.66	RD	119	-55	330.6	1	46	48	2	0.57
NKS0043RD	10959.88	19674.66	RD	119	-55	330.6	3	70	76	6	0.58
NKS0043RD	10959.88	19674.66	RD	119	-55	330.6	1	135.6	136.3	0.7	0.59
NKS0043RD	10959.88	19674.66	RD	119	-55	330.6	1	141.3	142.3	1	0.59
NKS0043RD	10959.88	19674.66	RD	119	-55	330.6	4	228.2	231.84	3.64	0.61
NKS0043RD	10959.88	19674.66	RD	119	-55	330.6	3	234.85	238.13	3.28	3.15
NKS0043RD	10959.88	19674.66	RD	119	-55	330.6	1	253.1	254.27	1.17	0.57
NKS0043RD	10959.88	19674.66	RD	119	-55	330.6	1	265	266	1	1.27
NKS0043RD	10959.88	19674.66	RD	119	-55	330.6	1	314.77	315.6	0.83	2.09
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	3	18	24	6	1.95
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	1	18	20	2	4.06
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	6	28	40	12	0.82
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	9	46	64	18	0.65
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	2	72	76	4	0.57
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	1	80	82	2	0.72
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	1	92	93	1	0.5
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	1	98.5	99	0.5	0.5
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	1	101	102	1	0.69
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	1	133	134	1	0.77
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	1	136	137	1	1.53
NKS0044RD	11037.62	19756.27	RD	119	-55	198.2	1	191.25	192	0.75	0.62
NKS0045RD	10963.9	19601.62	RD	119	-55	234	1	8	10	2	0.5
NKS0045RD	10963.9	19601.62	RD	119	-55	234	1	30	32	2	0.55
NKS0045RD	10963.9	19601.62	RD	119	-55	234	2	36	40	4	0.62
NKS0045RD	10963.9	19601.62	RD	119	-55	234	1	140.15	141.5	1.35	0.56
NKS0045RD	10963.9	19601.62	RD	119	-55	234	2	144.5	146	1.5	0.51
NKS0045RD	10963.9	19601.62	RD	119	-55	234	1	183.45	184.5	1.05	0.89
NKS0045RD	10963.9	19601.62	RD	119	-55	234	3	203	206	3	0.65
NKS0046DD	11017.85	19840.31	DD	119	-55	45.3	18	0	23.9	23.9	0.66
NKS0046DD	11017.85	19840.31	DD	119	-55	45.3	2	27.3	29.3	2	3.29
NKS0046DD	11017.85	19840.31	DD	119	-55	45.3	1	42	45.3	3.3	0.55
NKS0047RD	11077.35	19798.05	RD	119	-55	125.3	3	2	8	6	0.62
NKS0047RD	11077.35	19798.05	RD	119	-55	125.3	8	12	28	16	1.16
NKS0047RD	11077.35	19798.05	RD	119	-55	125.3	16	32	64	32	0.89
NKS0047RD	11077.35	19798.05	RD	119	-55	125.3	1	68	69	1	0.57
NKS0048RD	10916.56	19679.64	RD	119	-55	378.3	1	68	70	2	8.35

NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	102	104	2	3.58
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	3	114	120	6	0.94
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	131.32	132	0.68	0.59
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	147.1	147.6	0.5	0.66
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	183	184	1	0.72
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	6	209	214.9	5.9	1.01
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	226	227	1	1.46
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	229	229.6	0.6	6.18
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	233.5	234.5	1	1.66
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	236	237	1	0.64
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	244.7	245.2	0.5	0.72
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	3	250.5	253	2.5	87.3
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	257	257.5	0.5	0.56
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	260	260.7	0.7	0.99
NKS0048RD	10916.56	19679.64	RD	119	-55 378.3	1	353.5	355	1.5	1.18
NKS0049RD	10957.08	19838.30	RD	119	-55 323	4	28	36	8	1.31
NKS0049RD	10957.08	19838.30	RD	119	-55 323	2	46	50	4	1.35
NKS0049RD	10957.08	19838.30	RD	119	-55 323	1	60	62	2	0.53
NKS0049RD	10957.08	19838.30	RD	119	-55 323	1	104	106	2	0.98
NKS0049RD	10957.08	19838.30	RD	119	-55 323	2	116	120	4	2.05
NKS0049RD	10957.08	19838.30	RD	119	-55 323	1	126	128	2	0.88
NKS0049RD	10957.08	19838.30	RD	119	-55 323	1	132	134	2	1.21
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	12	6	30	24	2.04
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	3	36	42	6	1.51
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	2	46	50	4	0.75
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	5	56	66	10	1.15
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	5	72	77	5	0.96
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	1	83	84	1	2.4
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	1	90	90.6	0.6	1.6
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	1	102	103	1	1.04
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	2	111	113	2	1.42
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	1	123.6	124.1	0.5	6.1
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	1	132.25	133	0.75	0.54
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	4	158	162	4	0.95
NKS0050RD	11035.07	19836.95	RD	119	-55 180.1	1	166.45	167.4	0.95	0.54
NKS0051RD	10998.13	19677.42	RCDD	119	-55 249.2					NSI
NKS0052RD#	11073.80	19676.61	RCDD	119	-55 159.1	1	100	102	2	0.62
NKS0053RD	11035.07	19836.95	RD	119	-55 312	2	56	60	4	0.88
NKS0053RD	11035.07	19836.95	RD	119	-55 312	1	70	72	2	1.87
NKS0053RD	10959.88	19674.66	RD	119	-55 312	4	104	112	8	1.07
NKS0053RD#	10959.88	19674.66	RD	119	-55 312	1	128	130	2	0.54
NKS0054RD	11036.39	19715.47	RD	119	-55 251.1	4	1	8	7	0.76
NKS0054RD	11036.39	19715.47	RD	119	-55 251.1	1	18	20	2	0.65
NKS0054RD	11036.39	19715.47	RD	119	-55 251.1	1	46	48	2	0.5
NKS0054RD#	11036.39	19715.47	RD	119	-55 251.1	1	66	68	2	0.62
NKS0055RD#	11032.26	19636.53	RD	119	-55 213					NSI
NKS0057RD	10957.68	19635.74	RD	119	-55 273.2	1	20	22	2	1.42
NKS0057RD	10957.68	19635.74	RD	119	-55 273.2	2	30	34	4	0.65
NKS0057RD	10957.68	19635.74	RD	119	-55 273.2	1	42	44	2	0.77
NKS0057RD	10957.68	19635.74	RD	119	-55 273.2	1	48	50	2	0.53
NKS0057RD#	10957.68	19635.74	RD	119	-55 273.2	1	64	66	2	0.72
NKS0058RD	10955.28	19714.11	RD	119	-55 303.2	1	36	38	2	0.78

NKS0058RD	10955.28	19714.11	RD	119	-55	303.2	1	68	70	2	1.31
NKS0058RD#	10955.28	19714.11	RD	119	-55	303.2	1	90	91	1	2.52
NKS0059RD	10957.68	19635.74	RD	119	-55	48	1	0	4	4	2.47
NKS0059RD#	10957.68	19635.74	RD	119	-55	48	18	8	45	37	1.74
NKS0060RC	10936.75	20180.10	RC	119	-55	62	29	20	71	51	2.09
NKS0061RD	10893.36	20157.38	RD	119	-55	171.1	20	11	50	39	0.98
NKS0061RD*	10893.36	20157.38	RD	119	-55	171.1	3	64	69	5	4.36
NKS0062RD	10857.38	20157.94	RD	119	-55	231	1	20	24	4	0.78
NKS0062RD	10857.38	20157.94	RD	119	-55	231	1	30	31	1	0.73
NKS0062RD*	10857.38	20157.94	RD	119	-55	231	8	74	90	16	1.08
NKS0063RC	11112.01	19721.23	RC	119	-55	66	1	18	20	2	0.92
NKS0063RC	11112.01	19721.23	RC	119	-55	66	1	24	26	2	1.09
NKS0063RC	11112.01	19721.23	RC	119	-55	66	1	32	34	2	0.98
NKS0063RC	11112.01	19721.23	RC	119	-55	66	6	40	52	12	1.74
NKS0064RD	10874.77	20137.64	RD	119	-55	225.1	1	4	6	2	1.39
NKS0064RD	10874.77	20137.64	RD	119	-55	225.1	1	10	12	2	2
NKS0064RD	10874.77	20137.64	RD	119	-55	225.1	3	62	68	6	2.4
NKS0064RD*	10874.77	20137.64	RD	119	-55	225.1	3	82	87	5	2.44
NKS0065RD	10957.63	19796.73	RD	119	-55	309	1	0	4	4	0.6
NKS0065RD	10957.63	19796.73	RD	119	-55	309	1	62	64	2	0.68
NKS0065RD	10957.63	19796.73	RD	119	-55	309	3	72	78	6	1.62
NKS0065RD	10957.63	19796.73	RD	119	-55	309	1	84	86	2	1.59
NKS0065RD	10957.63	19796.73	RD	119	-55	309	1	90	92	2	0.94
NKS0065RD#	10957.63	19796.73	RD	119	-55	309	2	116	120	4	1.92
NKS0066RD	10995.92	19796.99	RD	119	-55	237.3	2	32	36	4	0.92
NKS0066RD	10995.92	19796.99	RD	119	-55	237.3	1	50	52	2	0.5
NKS0066RD	10995.92	19796.99	RD	119	-55	237.3	2	62	66	4	2.62
NKS0066RD	10995.92	19796.99	RD	119	-55	237.3	1	76	78	2	0.57
NKS0066RD	10995.92	19796.99	RD	119	-55	237.3	5	82	92	10	0.81
NKS0066RD#	10995.92	19796.99	RD	119	-55	237.3	1	96	98	2	4.64
NKS0067RD	10954.10	19875.91	RD	119	-55	329.9	1	36	38	2	1.9
NKS0067RD	10954.10	19875.91	RD	119	-55	329.9	4	46	54	8	3.51
NKS0067RD	10954.10	19875.91	RD	119	-55	329.9	6	66	78	12	1.31
NKS0067RD	10954.10	19875.91	RD	119	-55	329.9	1	82	84	2	1.64
NKS0067RD	10954.10	19875.91	RD	119	-55	329.9	8	94	110	16	2.45
NKS0067RD*	10954.10	19875.91	RD	119	-55	329.9	1	115	117	2	0.55
NKS0068RD	11037.15	19876.94	RD	119	-55	207.3	1	1	2	1	0.67
NKS0068RD	11037.15	19876.94	RD	119	-55	207.3	5	6	16	10	0.59
NKS0068RD	11037.15	19876.94	RD	119	-55	207.3	19	36	74	38	0.8
NKS0068RD	11037.15	19876.94	RD	119	-55	207.3	1	78	80	2	0.61
NKS0068RD#	11037.15	19876.94	RD	119	-55	207.3	11	84	106	22	1.76
NKS0069RD	10918.09	19713.76	RD	119	-55	393.2	3	86	92	6	0.97
NKS0069RD#	10918.09	19713.76	RD	119	-55	393.2	1	98	100	2	0.57
NKS0070RD#	10916.41	19880.39	RD	119	-55	448					NSI
NKS0071RD#	10916.41	19880.39	RD	119	-55	363.5	1	40	44	4	1.02
NKS0072RD	11035.17	19914.27	RD	119	-55	231	5	42	52	10	0.81
NKS0072RD	11035.17	19914.27	RD	119	-55	231	2	58	62	4	0.76
NKS0072RD	11035.17	19914.27	RD	119	-55	231	4	68	76	8	1.68
NKS0072RD#	11035.17	19914.27	RD	119	-55	231	1	92	94	2	0.85
NKS0073RD	10916.41	19880.39	RD	119	-55	427.2	1	74	76	2	2.8
NKS0073RD#	10916.41	19880.39	RD	119	-55	427.2	1	88	90	2	2.06
NKS0074RD#	10879.52	19797.03	RD	119	-55	285.3					NSI

NKS0075RD#	10837.12	19879.27	RD	119	-55 495.2					NSI
NKS0076RD	10998.52	19714.18	RD	119	-55 273.1	2	6	4		1.5
NKS0076RD	10998.52	19714.18	RD	119	-55 273.1	2	12	16	4	0.69
NKS0076RD	10998.52	19714.18	RD	119	-55 273.1	1	24	26	2	0.76
NKS0076RD#	10998.52	19714.18	RD	119	-55 273.1	1	58	60	2	0.61
NKS0077RD	11030.35	19793.66	RD	119	-55 219.1	2	36	40	4	0.76
NKS0077RD	11030.35	19793.66	RD	119	-55 219.1	1	44	46	2	2.23
NKS0077RD	11030.35	19793.66	RD	119	-55 219.1	1	54	56	2	1.31
NKS0077RD	11030.35	19793.66	RD	119	-55 219.1	1	84	86	2	0.96
NKS0077RD	11030.35	19793.66	RD	119	-55 219.1	1	90	92	2	0.56
NKS0077RD	11030.35	19793.66	RD	119	-55 219.1	1	108	110	2	1.31
NKS0077RD#	11030.35	19793.66	RD	119	-55 219.1	2	114	118	4	0.74
NKS0079DD	11080.76	19911.51	DD	119	-55 168.3	1	0	1.2	1.2	0.57
NKS0079DD	11080.76	19911.51	DD	119	-55 168.3	6	11.3	16.6	5.3	0.88
NKS0079DD	11080.76	19911.51	DD	119	-55 168.3	1	24.1	24.39	0.29	1.97
NKS0079DD	11080.76	19911.51	DD	119	-55 168.3	1	27.1	27.6	0.5	0.62
NKS0079DD	11080.76	19911.51	DD	119	-55 168.3	2	36.6	37.91	1.31	0.96
NKS0079DD	11080.76	19911.51	DD	119	-55 168.3	4	50.28	54.9	4.62	1.3
NKS0079DD	11080.76	19911.51	DD	119	-55 168.3	36	58	95.1	37.1	0.89
NKS0079DD	11080.76	19911.51	DD	119	-55 168.3	13	115.3	128.33	13.03	1.23
NKS0079DD	11080.76	19911.51	DD	119	-55 168.3	3	133.1	137	3.9	0.66
NKS0079DD	11080.76	19911.51	DD	119	-55 168.3	8	142.13	151.5	9.37	2.93
NKS0079DD	11080.76	19911.51	DD	119	-55 168.3	1	154	155	1	0.84
NKS0081RC	11076.31	19874.16	RC	119	-55 114	2	4	8	4	2.01
NKS0081RC	11076.31	19874.16	RC	119	-55 114	1	12	14	2	0.72
NKS0081RC	11076.31	19874.16	RC	119	-55 114	16	18	64	46	2.31
NKS0081RC	11076.31	19874.16	RC	119	-55 114	2	78	82	4	0.87
NKS0081RC	11076.31	19874.16	RC	119	-55 114	6	86	98	12	0.79
NKS0081RC	11076.31	19874.16	RC	119	-55 114	1	102	106	4	0.7
NKS0082RC	11095.58	19855.67	RC	119	-55 78	2	0	4	4	25.8
NKS0082RC	11095.58	19855.67	RC	119	-55 78	2	10	14	4	0.7
NKS0082RC	11095.58	19855.67	RC	119	-55 78	10	30	50	20	0.88
NKS0082RC	11095.58	19855.67	RC	119	-55 78	4	60	68	8	0.83
NKS0082RC	11095.58	19855.67	RC	119	-55 78	1	70	72	2	3.77
NKS0083RC	11075.47	19856.28	RC	119	-55 108	4	3	11	8	0.91
NKS0083RC	11075.47	19856.28	RC	119	-55 108	23	20	66	46	1.2
NKS0083RC	11075.47	19856.28	RC	119	-55 108	1	86	88	2	0.51
NKS0083RC	11075.47	19856.28	RC	119	-55 108	1	94	96	2	0.56
NKS0084RD#	11054.32	19797.45	RD	119	-55 153.4	1	108	110	2	1.33
NKS0085RD	10973.22	19797.97	RD	119	-55 288.2	2	4	8	4	0.67
NKS0085RD	10973.22	19797.97	RD	119	-55 288.2	1	32	34	2	1.34
NKS0085RD	10973.22	19797.97	RD	119	-55 288.2	1	42	44	2	0.84
NKS0085RD	10973.22	19797.97	RD	119	-55 288.2	1	70	72	2	1.4
NKS0085RD	10973.22	19797.97	RD	119	-55 288.2	1	82	84	2	5.28
NKS0085RD	10973.22	19797.97	RD	119	-55 288.2	6	96	108	12	2.39
NKS0085RD#	10973.22	19797.97	RD	119	-55 288.2	1	106	108	2	5.4
NKS0086RD	11078.04	19938.14	RD	119	-55 213.6	7	1	14	13	4.18
NKS0086RD	11078.04	19938.14	RD	119	-55 213.6	4	18	26	8	0.83
NKS0086RD	11078.04	19938.14	RD	119	-55 213.6	27	32	36	4	0.66
NKS0086RD	11078.04	19938.14	RD	119	-55 213.6	2	40	44	4	1.13
NKS0086RD	11078.04	19938.14	RD	119	-55 213.6	2	48	50	2	0.73
NKS0086RD*	11078.04	19938.14	RD	119	-55 213.6	1	54	108	54	1.63

NKS0087RD	11036.71	19894.57	RD	119	-55 216.3	7	2	16	14	1.15
NKS0087RD	11036.71	19894.57	RD	119	-55 216.3	3	24	30	6	1.87
NKS0087RD	11036.71	19894.57	RD	119	-55 216.3	7	46	60	14	1.21
NKS0087RD	11036.71	19894.57	RD	119	-55 216.3	10	66	86	20	0.63
NKS0087RD*	11036.71	19894.57	RD	119	-55 216.3	17	90	124	34	0.96
NKS0088RD	11097.11	20000.10	RD	119	-55 127.1	3	0	6	6	0.93
NKS0088RD	11097.11	20000.10	RD	119	-55 127.1	9	10	28	18	0.75
NKS0088RD	11097.11	20000.10	RD	119	-55 127.1	1	32	34	2	0.95
NKS0088RD	11097.11	20000.10	RD	119	-55 127.1	11	38	60	22	0.89
NKS0090RC	11035.57	20017.78	RC	119	-55 36	1	8	10	2	1.58
NKS0091RD	11013.63	19995.30	RD	119	-55 282.3	17	0	34	34	1.3
NKS0091RD	11013.63	19995.30	RD	119	-55 282.3	1	44	46	2	1.04
NKS0091RD	11013.63	19995.30	RD	119	-55 282.3	1	50	52	2	1.14
NKS0091RD	11013.63	19995.30	RD	119	-55 282.3	7	58	72	14	2.17
NKS0091RD#	11013.63	19995.30	RD	119	-55 282.3	11	106	128	22	1.01
NKS0092RD	10933.02	20077.71	RD	119	-55 131.6	1	0	2	2	1.09
NKS0092RD	10933.02	20077.71	RD	119	-55 131.6	1	6	8	2	0.69
NKS0092RD	10933.02	20077.71	RD	119	-55 131.6	1	30	32	2	0.88
NKS0092RD	10933.02	20077.71	RD	119	-55 131.6	19	38	76	38	1.83
NKS0092RD	10933.02	20077.71	RD	119	-55 131.6	3	80	86	6	1.11
NKS0092RD#	10933.02	20077.71	RD	119	-55 131.6	12	90	114	24	1.65
NKS0093RC	10933.02	20077.71	RC	119	-55 78	6	10	22	12	1.69
NKS0093RC	10933.02	20077.71	RC	119	-55 78	9	36	54	18	1.64
NKS0093RC	10978.41	20099.35	RC	119	-55 78	7	62	72	10	3.78
NKS0095RD	10874.54	20075.53	RD	119	-55 213.1	1	12	14	2	1.01
NKS0095RD	10874.54	20075.53	RD	119	-55 213.1	2	30	34	4	0.63
NKS0095RD	10874.54	20075.53	RD	119	-55 213.1	1	44	46	2	0.72
NKS0095RD#	10874.54	20075.53	RD	119	-55 213.1	1	50	52	2	1.05
NKS0097RC	10995.09	19997.72	RC	299	-50 94	6	1	12	11	1.23
NKS0097RC	10995.09	19997.72	RC	299	-50 94	11	20	42	22	1.21
NKS0097RC	10995.09	19997.72	RC	299	-50 94	1	64	65	1	0.5
NKS0101RC	11074.49	19717.74	RC	119	-55 133	1	20	22	2	2.38
NKS0101RC	11074.49	19717.74	RC	119	-55 133	1	14	16	2	0.52
NKS0102RD	10973.58	19837.31	RD	119	-55 294.2	13	0	26	26	1.55
NKS0102RD	10973.58	19837.31	RD	119	-55 294.2	1	48	50	2	1.28
NKS0102RD	10973.58	19837.31	RD	119	-55 294.2	1	54	56	2	0.88
NKS0102RD	10973.58	19837.31	RD	119	-55 294.2	1	60	62	2	8.82
NKS0102RD	10973.58	19837.31	RD	119	-55 294.2	2	82	86	4	0.89
NKS0102RD	10973.58	19837.31	RD	119	-55 294.2	1	90	92	2	1.4
NKS0102RD#	10973.58	19837.31	RD	119	-55 294.2	1	102	104	2	0.75
NKS0102RD	10973.58	19837.31	RD	119	-55 294.2	3	120	126	6	2.49
NKS0103RC	11112.95	19915.23	RC	119	-55 97	14	0	28	28	0.95
NKS0103RC	11112.95	19915.23	RC	119	-55 97	4	32	40	8	0.71
NKS0104RD	11052.99	19916.20	RD	119	-55 192.2	2	44	48	4	5.51
NKS0104RD	11052.99	19916.20	RD	119	-55 192.2	16	52	84	32	1.28
NKS0104RD	11052.99	19916.20	RD	119	-55 192.2	1	88	90	2	1.03
NKS0104RD	11052.99	19916.20	RD	119	-55 192.2	2	98	102	4	0.67
NKS0104RD	11052.99	19916.20	RD	119	-55 192.2	3	118	124	6	1.69
NKS0104RD*	11052.99	19916.20	RD	119	-55 192.2	3	142	148	6	1.76
NKS0105RD#	11052.07	19755.88	RD	119	-55 183.1					NSI
NKS0106RD	10974.63	19760.15	RD	119	-55 275.8	1	58	60	2	1.07
NKS0106RD	10974.63	19760.15	RD	119	-55 275.8	1	98	100	2	0.56

NKS0106RD	10974.63	19760.15	RD	119	-55	275.8	1	102	104	2	0.78
NKS0113RC	10918.56	20179.69	RC	28.5	-50	80					NSI
NKS0114RC	11157.48	20036.38	RC	208	-50	80	1	36	38	2	0.98
NKS0114RC	11157.48	20036.38	RC	208	-50	80	8	42	58	16	0.77
NKS0114RC	11157.48	20036.38	RC	208	-50	80	6	64	76	12	2.22
NKS0114RC	11157.48	20036.38	RC	208	-50	80	1	78	80	2	0.77
NKS0115RC	11158.99	20078.32	RC	208	-50	75	1	74	75	1	2.64
NKS0117RC	10898.72	20130.51	RC	28.5	-50	100	11	8	30	22	3.92
NKS0117RC	10898.72	20130.51	RC	28.5	-50	100	1	64	65	1	1.33
NKS0118RC	11078.88	20075.19	RC	208	-50	120	4	66	74	8	1.07
NKS0118RC	11078.88	20075.19	RC	208	-50	120	7	78	92	14	1
NKS0118RC	11078.88	20075.19	RC	208	-50	120	2	112	116	4	1.64
NKS0120RC	10918.25	20158.78	RC	28	-50	110	4	24	40	16	4.17
NKS0121RD	10892.72	20076.69	RD	119	-55	174.2	1	6	8	2	0.59
NKS0121RD	10892.72	20076.69	RD	119	-55	174.2	1	12	14	2	6.99
NKS0121RD	10892.72	20076.69	RD	119	-55	174.2	7	28	42	14	1.69
NKS0123RC	10956.18	20156.95	RC	119	-55	78	2	9	12	3	6.97
NKS0123RC	10956.18	20156.95	RC	119	-55	78	9	24	42	18	1.96
NKS0123RC	10956.18	20156.95	RC	119	-55	78	6	48	60	12	2.42
NKS0124RD	10854.04	20074.96	RD	119	-55	242.4	1	4	6	2	0.53
NKS0124RD	10854.04	20074.96	RD	119	-55	242.4	3	18	24	6	2
NKS0124RD	10854.04	20074.96	RD	119	-55	242.4	2	64	68	4	1.65
NKS0085RD	10973.22	19797.97	RD	119	-55	288.2	1	32	34	2	1.34
NKS0085RD	10973.22	19797.97	RD	119	-55	288.2	1	42	44	2	0.84
NKS0085RD	10973.22	19797.97	RD	119	-55	288.2	1	70	72	2	1.4
NKS0085RD	10973.22	19797.97	RD	119	-55	288.2	1	82	84	2	5.28
NKS0085RD	10973.22	19797.97	RD	119	-55	288.2	6	96	108	12	2.39
NKS0085RD#	10973.22	19797.97	RD	119	-55	288.2	1	106	108	2	5.4
NKS0086RD	11078.04	19938.14	RD	119	-55	213.6	7	1	14	13	4.18
NKS0086RD	11078.04	19938.14	RD	119	-55	213.6	4	18	26	8	0.83
NKS0086RD	11078.04	19938.14	RD	119	-55	213.6	27	32	36	4	0.66
NKS0086RD	11078.04	19938.14	RD	119	-55	213.6	2	40	44	4	1.13
NKS0086RD	11078.04	19938.14	RD	119	-55	213.6	2	48	50	2	0.73
NKS0086RD*	11078.04	19938.14	RD	119	-55	213.6	1	54	108	54	1.63
NKS0087RD	11036.71	19894.57	RD	119	-55	216.3	7	2	16	14	1.15
NKS0087RD	11036.71	19894.57	RD	119	-55	216.3	3	24	30	6	1.87
NKS0087RD	11036.71	19894.57	RD	119	-55	216.3	7	46	60	14	1.21
NKS0087RD	11036.71	19894.57	RD	119	-55	216.3	10	66	86	20	0.63
NKS0087RD*	11036.71	19894.57	RD	119	-55	216.3	17	90	124	34	0.96
NKS0088RD	11097.11	20000.10	RD	119	-55	127.1	3	0	6	6	0.93
NKS0088RD	11097.11	20000.10	RD	119	-55	127.1	9	10	28	18	0.75
NKS0088RD	11097.11	20000.10	RD	119	-55	127.1	1	32	34	2	0.95
NKS0088RD	11097.11	20000.10	RD	119	-55	127.1	11	38	60	22	0.89
NKS0090RC	11035.57	20017.78	RC	119	-55	36	1	8	10	2	1.58
NKS0091RD	11013.63	19995.30	RD	119	-55	282.3	17	0	34	34	1.3
NKS0091RD	11013.63	19995.30	RD	119	-55	282.3	1	44	46	2	1.04
NKS0091RD	11013.63	19995.30	RD	119	-55	282.3	1	50	52	2	1.14
NKS0091RD	11013.63	19995.30	RD	119	-55	282.3	7	58	72	14	2.17
NKS0091RD#	11013.63	19995.30	RD	119	-55	282.3	11	106	128	22	1.01
NKS0092RD	10933.02	20077.71	RD	119	-55	131.6	1	0	2	2	1.09
NKS0092RD	10933.02	20077.71	RD	119	-55	131.6	1	6	8	2	0.69
NKS0092RD	10933.02	20077.71	RD	119	-55	131.6	1	30	32	2	0.88

NKS0092RD	10933.02	20077.71	RD	119	-55	131.6	19	38	76	38	1.83
NKS0092RD	10933.02	20077.71	RD	119	-55	131.6	3	80	86	6	1.11
NKS0092RD#	10933.02	20077.71	RD	119	-55	131.6	12	90	114	24	1.65
NKS0093RC	10933.02	20077.71	RC	119	-55	78	6	10	22	12	1.69
NKS0093RC	10933.02	20077.71	RC	119	-55	78	9	36	54	18	1.64
NKS0093RC	10978.41	20099.35	RC	119	-55	78	7	62	72	10	3.78
NKS0095RD	10874.54	20075.53	RD	119	-55	213.1	1	12	14	2	1.01
NKS0095RD	10874.54	20075.53	RD	119	-55	213.1	2	30	34	4	0.63
NKS0095RD	10874.54	20075.53	RD	119	-55	213.1	1	44	46	2	0.72
NKS0095RD#	10874.54	20075.53	RD	119	-55	213.1	1	50	52	2	1.05
NKS0097RC	10995.09	19997.72	RC	299	-50	94	6	1	12	11	1.23
NKS0097RC	10995.09	19997.72	RC	299	-50	94	11	20	42	22	1.21
NKS0097RC	10995.09	19997.72	RC	299	-50	94	1	64	65	1	0.5
NKS0101RC	11074.49	19717.74	RC	119	-55	133	1	20	22	2	2.38
NKS0101RC	11074.49	19717.74	RC	119	-55	133	1	14	16	2	0.52
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	13	0	26	26	1.55
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	1	48	50	2	1.28
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	1	54	56	2	0.88
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	1	60	62	2	8.82
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	2	82	86	4	0.89
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	1	90	92	2	1.4
NKS0102RD#	10973.58	19837.31	RD	119	-55	294.2	1	102	104	2	0.75
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	3	120	126	6	2.49
NKS0103RC	11112.95	19915.23	RC	119	-55	97	14	0	28	28	0.95
NKS0103RC	11112.95	19915.23	RC	119	-55	97	4	32	40	8	0.71
NKS0104RD	11052.99	19916.20	RD	119	-55	192.2	2	44	48	4	5.51
NKS0104RD	11052.99	19916.20	RD	119	-55	192.2	16	52	84	32	1.28
NKS0104RD	11052.99	19916.20	RD	119	-55	192.2	1	88	90	2	1.03
NKS0104RD	11052.99	19916.20	RD	119	-55	192.2	2	98	102	4	0.67
NKS0104RD	11052.99	19916.20	RD	119	-55	192.2	3	118	124	6	1.69
NKS0104RD*	11052.99	19916.20	RD	119	-55	192.2	3	142	148	6	1.76
NKS0105RD#	11052.07	19755.88	RD	119	-55	183.1					NSI
NKS0106RD	10974.63	19760.15	RD	119	-55	275.8	1	58	60	2	1.07
NKS0106RD	10974.63	19760.15	RD	119	-55	275.8	1	98	100	2	0.56
NKS0106RD	10974.63	19760.15	RD	119	-55	275.8	1	102	104	2	0.78
NKS0113RC	10918.56	20179.69	RC	28.5	-50	80					NSI
NKS0114RC	11157.48	20036.38	RC	208	-50	80	1	36	38	2	0.98
NKS0114RC	11157.48	20036.38	RC	208	-50	80	8	42	58	16	0.77
NKS0114RC	11157.48	20036.38	RC	208	-50	80	6	64	76	12	2.22
NKS0114RC	11157.48	20036.38	RC	208	-50	80	1	78	80	2	0.77
NKS0115RC	11158.99	20078.32	RC	208	-50	75	1	74	75	1	2.64
NKS0117RC	10898.72	20130.51	RC	28.5	-50	100	11	8	30	22	3.92
NKS0117RC	10898.72	20130.51	RC	28.5	-50	100	1	64	65	1	1.33
NKS0118RC	11078.88	20075.19	RC	208	-50	120	4	66	74	8	1.07
NKS0118RC	11078.88	20075.19	RC	208	-50	120	7	78	92	14	1
NKS0118RC	11078.88	20075.19	RC	208	-50	120	2	112	116	4	1.64
NKS0120RC	10918.25	20158.78	RC	28	-50	110	4	24	40	16	4.17
NKS0121RD	10892.72	20076.69	RD	119	-55	174.2	1	6	8	2	0.59
NKS0121RD	10892.72	20076.69	RD	119	-55	174.2	1	12	14	2	6.99
NKS0121RD	10892.72	20076.69	RD	119	-55	174.2	7	28	42	14	1.69
NKS0123RC	10956.18	20156.95	RC	119	-55	78	2	9	12	3	6.97
NKS0123RC	10956.18	20156.95	RC	119	-55	78	9	24	42	18	1.96

NKS0123RC	10956.18	20156.95	RC	119	-55	78	6	48	60	12	2.42
NKS0124RD	10854.04	20074.96	RD	119	-55	242.4	1	4	6	2	0.53
NKS0124RD	10854.04	20074.96	RD	119	-55	242.4	3	18	24	6	2
NKS0124RD	10854.04	20074.96	RD	119	-55	242.4	2	64	68	4	1.65
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	1	48	50	2	1.28
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	1	54	56	2	0.88
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	1	60	62	2	8.82
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	2	82	86	4	0.89
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	1	90	92	2	1.4
NKS0102RD#	10973.58	19837.31	RD	119	-55	294.2	1	102	104	2	0.75
NKS0102RD	10973.58	19837.31	RD	119	-55	294.2	3	120	126	6	2.49
NKS0103RC	11112.95	19915.23	RC	119	-55	97	14	0	28	28	0.95
NKS0103RC	11112.95	19915.23	RC	119	-55	97	4	32	40	8	0.71
NKS0104RD	11052.99	19916.20	RD	119	-55	192.2	2	44	48	4	5.51
NKS0104RD	11052.99	19916.20	RD	119	-55	192.2	16	52	84	32	1.28
NKS0104RD	11052.99	19916.20	RD	119	-55	192.2	1	88	90	2	1.03
NKS0104RD	11052.99	19916.20	RD	119	-55	192.2	2	98	102	4	0.67
NKS0104RD	11052.99	19916.20	RD	119	-55	192.2	3	118	124	6	1.69
NKS0104RD*	11052.99	19916.20	RD	119	-55	192.2	3	142	148	6	1.76
NKS0105RD#	11052.07	19755.88	RD	119	-55	183.1					NSI
NKS0106RD	10974.63	19760.15	RD	119	-55	275.8	1	58	60	2	1.07
NKS0106RD	10974.63	19760.15	RD	119	-55	275.8	1	98	100	2	0.56
NKS0106RD#	10974.63	19760.15	RD	119	-55	275.8	1	102	104	2	0.78
NKS0113RC	10918.56	20179.69	RC	28.5	-50	80					NSI
NKS0114RC	11157.48	20036.38	RC	208	-50	80	1	36	38	2	0.98
NKS0114RC	11157.48	20036.38	RC	208	-50	80	8	42	58	16	0.77
NKS0114RC	11157.48	20036.38	RC	208	-50	80	6	64	76	12	2.22
NKS0114RC	11157.48	20036.38	RC	208	-50	80	1	78	80	2	0.77
NKS0115RC	11158.99	20078.32	RC	208	-50	75	1	74	75	1	2.64
NKS0117RC	10898.72	20130.51	RC	28.5	-50	100	11	8	30	22	3.92
NKS0117RC	10898.72	20130.51	RC	28.5	-50	100	1	64	65	1	1.33
NKS0118RC	11078.88	20075.19	RC	208	-50	120	4	66	74	8	1.07
NKS0118RC	11078.88	20075.19	RC	208	-50	120	7	78	92	14	1
NKS0118RC	11078.88	20075.19	RC	208	-50	120	2	112	116	4	1.64
NKS0120RC	10918.25	20158.78	RC	28	-50	110	4	24	40	16	4.17
NKS0121RD	10892.72	20076.69	RD	119	-55	174.2	1	6	8	2	0.59
NKS0121RD	10892.72	20076.69	RD	119	-55	174.2	1	12	14	2	6.99
NKS0121RD#	10892.72	20076.69	RD	119	-55	174.2	7	28	42	14	1.69
NKS0123RC	10956.18	20156.95	RC	119	-55	78	2	9	12	3	6.97
NKS0123RC	10956.18	20156.95	RC	119	-55	78	9	24	42	18	1.96
NKS0123RC	10956.18	20156.95	RC	119	-55	78	6	48	60	12	2.42

Partial assays received RC portion only.

* RC chips ended in mineralisation; partial assays received for RC portion only.

APPENDIX 3: JORC TABLE 1 - NKOSUO PROPERTY

JORC 2012 Table 1 - Section 1 sampling techniques and data

(Criteria in this section apply to all succeeding sections)

Criteria	JORC Code Explanation
	<p><i>Nature and quality of sampling (e.g. cut channels, random chips, or measurement tools appropriate to the minerals under investigation, handheld XRF instruments, etc.). These examples should not be taken as a guide to sampling.</i></p>
<i>Sampling techniques</i>	<p><i>Include reference to measures taken to ensure sample representativeness and measurement tools or systems used.</i></p> <p><i>Aspects of the determination of mineralisation that are Material to standard' work has been done this would be relatively simple (e.g. obtain 1 m samples from which 3 kg was pulverised to produce a more explanation may be required, such as where there is coarse Unusual commodities or mineralisation types (e.g. submarine nodules) information.</i></p>
<i>Drilling techniques</i>	<p><i>Drill type (e.g. core, reverse circulation, open-hole hammer, rotary air leg, etc.) and details (e.g. core diameter, triple or standard tube, depth of diameter, whether core is oriented and if so, by what method, etc.).</i></p> <p><i>Method of recording and assessing core and chip sample recovery and whether core and chip samples are representative of the rock.</i></p>
<i>Drill sample recovery</i>	<p><i>Measures taken to maximise sample recovery and ensure representativeness of the rock.</i></p> <p><i>Whether a relationship exists between sample recovery and grade, and whether this has occurred due to preferential loss/gain of fine/coarse material.</i></p> <p><i>Whether core and chip samples have been geologically and geotechnically support appropriate Mineral Resource estimation, mining studies and mine design.</i></p>
<i>Logging</i>	<p><i>Whether logging is qualitative or quantitative in nature. Core (or cuttings) lithological logs that support Mineral Resource estimation, mining studies and mine design.</i></p> <p><i>The total length and percentage of the relevant intersections logged.</i></p>

If core, whether cut or sawn and whether quarter, half or all core to

If non-core, whether riffled, tube sampled, rotary split, etc. and wh

For all sample types, the nature, quality and appropriateness of th

Sub-sampling techniques and sample preparation

Quality control procedures adopted for all sub-sampling stages to

*Measures taken to ensure that the sampling is representative of th
instance results for field duplicate/second-half sampling.*

Whether sample sizes are appropriate to the grain size of the mat

*The nature, quality and appropriateness of the assaying and labor
technique is considered partial or total.*

Quality of assay data and laboratory tests

*For geophysical tools, spectrometers, handheld XRF instruments,
the analysis including instrument make and model, reading times,
derivation, etc.*

*Nature of quality control procedures adopted (e.g. standards, blan
and whether acceptable levels of accuracy (i.e. lack of bias) and p*

The verification of significant intersections by either independent or

The use of twinned holes.

Documentation of primary data, data entry procedures, data verification (handwritten or electronic) protocols.

Discuss any adjustment to assay data.

Verification of sampling and assaying

Accuracy and quality of surveys used to locate drill holes (collar and down hole), trenches, workings and other locations used in Mineral Resource estimation.

Location of data points

Specification of the grid system used.

Quality and adequacy of topographic control.

Data spacing for reporting of Exploration Results.

Data spacing and distribution

Whether the data spacing and distribution is sufficient to establish continuity appropriate for the Mineral Resource and Ore Reserve category applied.

Whether sample compositing has been applied.

Orientation of data in relation to geological structure

Whether the orientation of sampling achieves unbiased sampling or otherwise, which this is known, considering the deposit type.

If the relationship between the drilling orientation and the orientation of the geological structure is considered to have introduced a sampling bias, this should be assessed and reported.

Sample security

The measures taken to ensure sample security.

Audits or reviews

The results of any audits or reviews of sampling techniques and d

JORC 2012 Table 1 - Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section)

Criteria

JORC Code explanation

Mineral tenement and land tenure status

Type, reference name/number, location and ownership parties such as joint ventures, partnerships, overriding wilderness or national park and environmental setting. The security of the tenure held at the time of reporting licence to operate in the area.

Exploration done by other parties

Acknowledgment and appraisal of exploration by other

Geology

Deposit type, geological setting and style of mineralis

Drill hole Information

A summary of all information material to the understanding of the following information for all Material drill holes:

- *easting and northing of the drill hole collar*
- *elevation or RL (Reduced Level - elevation above sea level)*
- *dip and azimuth of the hole*
- *down hole length and interception depth hole length*

Data aggregation methods

If the exclusion of this information is justified on the basis of the nature of the material, the exclusion does not detract from the understanding of the material. Where necessary, explain why this is the case.

In reporting Exploration Results, weighting averaging calculations, selective truncations (e.g. cutting of high grades) and cut-off grades should be clearly stated. Where aggregate intercepts incorporate short lengths of drilling results, the procedure used for such aggregation should be clearly stated. Aggregations should be shown in detail.

The assumptions used for any reporting of metal equivalent grades should be clearly stated.

These relationships are particularly important in the reporting of Exploration Results.

If the geometry of the mineralisation with respect to the length of the intercept is reported.

Relationship between mineralization widths and intercept lengths

If it is not known and only the down hole lengths are reported (e.g. 'down hole length, true width not known').

Diagrams

Appropriate maps and sections (with scales) and tabular data should be provided for any significant discovery being reported. These should include locations and appropriate sectional views.

Balanced reporting

Where comprehensive reporting of all Exploration Results is not practicable, low and high grades and/or widths should be practically balanced.

Other substantive exploration data

Other exploration data, if meaningful and material, should include: geological observations; geophysical survey results; method of treatment; metallurgical test results; bulk chemical analysis; and other characteristics; potential deleterious or contaminating substances.

Further work

The nature and scale of planned further work (e.g. test drilling, large-scale step-out drilling).

Diagrams clearly highlighting the areas of possible future work and future drilling areas, provided this information is available.

Dieser Artikel stammt von [Rohstoff-Welt.de](https://www.rohstoff-welt.de)

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/404511--Perseus-Achieves-Near-Mine-Exploration-Success-in-Ghana.html>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).