# New Found Discovers Multiple New Gold Zones Extending 1.5km South of Keats, Increases Appleton Fault Zone High-grade Gold Corridor to Over 4km in Strike Length

18.01.2023 | Business Wire

New Found Gold Corp. ("New Found" or the "Company") (TSX-V: NFG, NYSE-A: NFGC) is pleased to announce the results from 51 diamond drill holes that were completed as part of an ongoing systematic and targeted drill program exploring the highly prospective segment of the Appleton Fault Zone ("AFZ") from the south end of the Keats Main Zone to the Knob Zone. New Found's 100% owned Queensway project comprises an approximately 1,650km² area, accessible via the Trans-Canada Highway approximately 15km west of Gander, Newfoundland and Labrador.

This press release features multimedia. View the full release here: https://www.businesswire.com/news/home/20230118005370/en/

Figure 1: Photos of mineralization from: Top L: at ~427.5m in NFGC-22-863, Top R: at ~88.2m in NFGC-22-704, Bottom L: at ~23m in NFGC-22-733, Bottom R: at ~380.25 in NFGC-22-774. ^Note that these photos are not intended to be representative of gold mineralization in holes NFGC-22-704, NFGC-22-733, NFGC-22-774 and NFGC-22-863.

Keats Main South, TCH and Rocket Highlights:

Hole Number From (m) To (m) Interval (m)<sup>1</sup> Au (g/t) Zone

NFGC-22-733	322.30	24.60 2.30	10.45	421
Including	22.80	23.30 0.50	46.80	421
NFGC-22-774	1364.00	366.45 2.45	25.31	
Including	365.00	366.00 1.00	60.50	Keats Main S
And	379.80	382.00 2.20	72.66	Reals Main 3
Including	379.80	380.35 0.55	290.00	
NFGC-22-845	5115.00	129.90 14.90	4.59	Keats Main S/
Including	120.00	121.00 1.00	26.17	
Including	129.00	129.90 0.90	11.50	421
NFGC-22-642	2303.45	305.90 2.45	10.45	
Including	303.80	304.35 0.55	14.46	TCH
Including	305.40	305.90 0.50	32.43	
NFGC-22-703	3 183.00	193.70 10.70	1.02	TCH

19.12.2025 Seite 1/16

Table 1: Keats Main South, TCH and Rocket Drilling Highlights

<sup>1</sup>Note that the host structures are interpreted to be steeply dipping and true widths are generally estimated to be 60% to 90% of the reported interval. Infill veining in secondary structures with multiple orientations crosscutting the primary host structures are commonly observed in drill core which could result in additional uncertainty in true width. Composite intervals reported carry a minimum weighted average of 1 g/t Au diluted over a minimum core length of 2m with a maximum of 2m consecutive dilution. Included high-grade intercepts are reported as any consecutive interval with grades greater than 10 g/t Au. Grades have not been capped in the averaging and intervals are reported as drill thickness.

- Systematic and targeted drilling along the highly prospective AFZ corridor has continued to delineate
  high-grade gold mineralization now extending 1.5km south of Keats, including the discovery of the new
  TCH Zone, and new veins and structures around existing zones. Importantly, the high-grade corridor of
  gold along the AFZ has now been tracked over 4.1km from Lotto North/Zone 36 down to Knob, with
  much of this area remaining underexplored (Figure 1).
- At the southern extension of the Keats Main Zone (Keats Main South) the Company continues to intersect high-grade gold mineralization following up on its October 18, 2022. release. Highlight intercepts include 25.31 g/t Au over 2.45m and 72.7 g/t Au over 2.20m in NFGC-22-774 and 4.59 g/t Au over 14.90m in NFGC-22-845. The high-grade gold associated with the Keats-Baseline Fault Zone, the structure that hosts the Keats Main Zone, has now been traced over a strike length of 1.1km and down to a vertical depth of 400m (Figures 1- 4).
- Systematic reconnaissance grid drilling south of the Trans-Canada highway along the eastern side of the AFZ identified a new gold-bearing zone called "TCH (Trans Canada Highway)" with intercepts of 79.6 g/t Au over 2.00m in NFGC-22-863, 10.5 g/t Au over 2.45m in NFGC-22-642 and 1.02 g/t Au over 10.70m in NFGC-22-703. This structure is located in the footwall to the AFZ and has been intersected over a strike length of 190m and down to a vertical depth of 300m (Figures 1-4).
- At Knob, a new vein called "Rocket" has been discovered 100m to the east, with a highlight interval of 12.63 g/t Au over 4.45m in NFGC-22-704 intersected at a vertical depth of 65m. The Knob zone is a historical discovery with mineralization hosted within an east-west striking structure largely constrained to greywacke which has been traced over a strike length of 160m and has seen minimal modern-day drilling (Figures 1, 2 and 4).
- Additional drilling into the 421 Zone, a moderately southwest-dipping structure that runs at an oblique angle to the Keats Main Zone has intersected the highlight interval of 10.5 g/t Au over 2.30m in NFGC-22-733. This structure likely plays a role in concentrating high-grade gold where it interacts with the Keats-Baseline Fault (Figures 1 and 4).

Melissa Render, VP Exploration for New Found stated: "From the Rocket Vein at Knob to Lotto North measures an impressive 4.1km stretch of the AFZ that continues to produce new discoveries both on the east and west side of this regional-scale fault. It is a lot of ground to cover but from a first pass of drilling, results indicate that the system's strength continues. We will persist with aggressive follow-up drilling which involves tracing the structures that are known to host high-grade gold and determining the controls responsible for producing both high and low-grade gold domains from which we can expand on."

**Drillhole Details** 

Keats Main Zone South:

Hole Number From (m) To (m) Interval (m)<sup>1</sup> Au (g/t) Zone

NFGC-22-71231.10 36.40 5.30 1.13 421

And

19.12.2025 Seite 2/16

332.50

19.12.2025 Seite 3/16

335.50

19.12.2025 Seite 4/16

19.12.2025 Seite 5/16

19.12.2025 Seite 6/16

Keats Main

19.12.2025 Seite 7/16

19.12.2025 Seite 8/16

NFGC-22-733	322.30	24.60 2.30	10.45	404
Including	22.80	23.30 0.50	46.80	421
And	424.40	427.00 2.60	1.76	Keats Main
NFGC-22-756	3431.50	433.55 2.05	9.14	Veeta Main C
And	432.85	433.25 0.40	45.20	Keats Main S
NFGC-22-774	79.40	81.70 2.30	1.05	Keats S
And	364.00	366.45 2.45	25.31	
Including	365.00	366.001.00	60.50	Keats Main S
And	379.80	382.002.20	72.66	Reals Mail S
Including	379.80	380.35 0.55	290.00	)
NFGC-22-778	3439.00	441.55 2.55	2.84	
Including	439.80	440.15 0.35	20.10	
And	488.00	490.802.80	1.40	Keats Main S
And	496.00	498.002.00	1.13	
And	509.00	514.55 5.55	1.45	
NFGC-22-790	453.00	455.00 2.00	1.30	Keats Main S
NFGC-22-804	439.00	441.45 2.45	2.08	Keats Main S
NFGC-22-807	7548.45	551.102.65	2.01	Keats Main S
And	601.00	605.004.00	1.08	Reals Mail S
NFGC-22-821	370.00	372.45 2.45	1.18	Keats Main S
NFGC-22-826	3132.00	137.65 5.65	1.50	Keats Main S
NFGC-22-835	77.85	80.80 2.95	2.18	421
And	162.00	164.85 2.85	3.76	Keats Main S
NFGC-22-837	355.35	357.702.35	1.37	
And	386.00	388.602.60	8.73	Keats Main S
Including	388.10	388.60 0.50	34.88	

19.12.2025 Seite 9/16

NFGC-22-845	552.50	55.00 2.50	1.17	
And	115.00	129.90 14.90	4.59	
Including	120.00	121.00 1.00	26.17	
Including	129.00	129.90 0.90	11.50	Keats Main S/ 421
And	135.00	137.15 2.15	2.89	
And	143.00	145.00 2.00	2.05	
And	188.00	190.002.00	2.42	
NFGC-22-853	3 No Signi	ficant Values		Keats Main S
NFGC-22-87	l No Signi	ficant Values		Keats Main S
TCH Results:				
Hole Number	From (m	)To (m) Interval (m)	¹ Au (g/t	) Zone
NFGC-22-513	3246.60	251.004.40	1.41	TCH
NFGC-22-569	9140.00	142.70 2.70	3.70	TOU
And	147.00	152.00 5.00	1.78	TCH
NFGC-22-604	4 No Signi	ficant Values		TCH
NFGC-22-62	l No Signi	ficant Values		TCH
NFGC-22-632	2 No Signi	ficant Values		TCH
NFGC-22-642	2243.00	245.00 2.00	1.01	
And	290.85	293.00 2.15	2.00	
And	303.45	305.90 2.45	10.45	TCH
Including	303.80	304.35 0.55	14.46	
Including	305.40	305.90 0.50	32.43	
NFGC-22-67	1 223.95	226.45 2.50	1.10	TCH
NFGC-22-679	No Signi	ficant Values		TCH
NFGC-22-694	1165.90	168.702.80	1.16	TCH
And	227.00	231.00 4.00	1.21	1011
NFGC-22-703	3109.30	111.70 2.40	1.63	
And	131.00	133.00 2.00	1.63	TCH
And	183.00	193.70 10.70	1.02	
NFGC-22-715	5 No Signi	ficant Values		TCH

19.12.2025 Seite 10/16

NFGC-22-72	488.00	93.00 5.00	1.29		
And	97.40	101.203.80	1.05	TCH	
And	193.40	196.25 2.85	1.44		
NFGC-22-73	7 No Sign	ificant Values		TCH	
NFGC-22-74	9 No Sign	ificant Values		TCH	
NFGC-22-76	359.00	61.00 2.00	1.09	TCH	
NFGC-22-78	2 No Sign	ificant Values		TCH	
NFGC-22-79	7 No Sign	ificant Values		TCH	
NFGC-22-82	4 No Sign	ificant Values		TCH	
NFGC-22-83	1 No Sign	ificant Values		TCH	
NFGC-22-86	3 307.00	309.402.40	3.38	TCH	
And	427.10	429.102.00	79.62	TCH	
Including	427.10	427.80 0.70	226.46		
NFGC-22-88	5 278.60	280.802.20	7.06	TCH	
Including	279.50	280.200.70	22.01	ТСП	
Rocket Resu	lts:				
Hole Number	From (m	ı) To (m) Interval (ı	m)¹ Au (g/t	) Zone	
NFGC-22-638 No Significant Values Rocket					
NFGC-22-654 No Significant Values Rocket					
NFGC-22-662 No Significant Values Rocket					
NFGC-22-670 No Significant Values Rocket					
NFGC-22-68	7 No Sign	ificant Values		Rocket	
NFGC-22-69	9 No Sign	ificant Values		Rocket	
NFGC-22-70	465.00	67.00 2.00	1.02		
And	86.60	91.05 4.45	12.63	Rocket	
Including	88.00	88.45 0.45	118.50	)	
NFGC-22-71	3 No Sign	ificant Values		Rocket	

94.65 2.40

NFGC-22-731 92.25

NFGC-22-735 No Significant Values

NFGC-22-741 No Significant Values

19.12.2025 Seite 11/16

1.13 Rocket

Rocket

Rocket

NFGC-22-745 No Significant Values	Rocket
NFGC-22-751 No Significant Values	Rocket
NFGC-22-760 No Significant Values	Rocket

Table 2: Summary of composite results reported in this press release for Keats Main South, TCH and Rocket

¹Note that the host structures are interpreted to be steeply dipping and true widths are generally estimated to be 60% to 90% of the reported interval. Infill veining in secondary structures with multiple orientations crosscutting the primary host structures are commonly observed in drill core which could result in additional uncertainty in true width. Composite intervals reported carry a minimum weighted average of 1 g/t Au diluted over a minimum core length of 2m with a maximum of 2m consecutive dilution. Included high-grade intercepts are reported as any consecutive interval with grades greater than 10 g/t Au. Grades have not been capped in the averaging and intervals are reported as drill thickness.

Hole Number Azimuth (°) Dip (°) Length (m) UTM E UTM N Prospect

NFGC-22-513299	-45.5	401	657596 5426437 TCH
NFGC-22-569110	-45	257	657512 5426948 TCH
NFGC-22-604300	-45	343	657589 5426614 TCH
NFGC-22-621 300	-45	200	657619 5426596 TCH
NFGC-22-632300	-45	293	657588 5426557 TCH
NFGC-22-638 300	-45	344	657247 5426118 Rocket
NFGC-22-642300	-45	500	657636 5426511 TCH
NFGC-22-654300	-45	203	657251 5426173 Rocket
NFGC-22-662300	-45	233	657252 5426232 Rocket
NFGC-22-670 300	-45	242	657239 5426008 Rocket
NFGC-22-671 299	-42	302	657637 5426510 TCH
NFGC-22-679300	-45	191	657193 5425976 Rocket
NFGC-22-687 300	-45	338	657186 5425865 Rocket
NFGC-22-694300	-45	284	657539 5426527 TCH
NFGC-22-69970	-50	179	657191 5425870 Rocket
NFGC-22-703300	-45	284	657594 5426495 TCH
NFGC-22-704 100	-50	107	6571925425868 Rocket
NFGC-22-712356	-68	497	657842 5427082 Keats
NFGC-22-713 250	-45	323	657288 5426093 Rocket
NFGC-22-715300	-45	281	657536 5426471 TCH
NFGC-22-724300	-45	233	657494 5426496 TCH
NFGC-22-725110	-45	95	6571925425919 Rocket

19.12.2025 Seite 12/16

NFGC-22-731 120	-70	104	657191 5425919 Rocket
NFGC-22-733354	-66	485	657841 5427082 Keats
NFGC-22-73550	-45	155	657192 5425920 Rocket
NFGC-22-737300	-45	215	657489 5426441 TCH
NFGC-22-7415	-45	89	657193 5425927 Rocket
NFGC-22-74545	-45	143	657148 5425948 Rocket
NFGC-22-749306	-55	557	657596 5426436 TCH
NFGC-22-751 300	-45	293	657192 5425915 Rocket
NFGC-22-756297	-46	538	657813 5426658 Keats
NFGC-22-7605	-45	122	657146 5425949 Rocket
NFGC-22-763300	-45	329	657397 5426378 TCH
NFGC-22-774300	-45	458	657770 5426683 Keats
NFGC-22-778 298	-52	665	657902 5426724 Keats
NFGC-22-782300	-45	290	657350 5426348 TCH
NFGC-22-790300	-45	563	657837 5426702 Keats
NFGC-22-797300	-45	305	657303 5426318 TCH
NFGC-22-804334	-55	575	657599 5426439 TCH
NFGC-22-807 297	-45	701	658003 5426722 Keats
NFGC-22-821 297	-45	416	657794 5426728 Keats
NFGC-22-824300	-45	251	657295 5426205 TCH
NFGC-22-826330	-45.5	240	657799 5427004 Keats
NFGC-22-831 300	-45	572	657426 5426131 TCH
NFGC-22-835300	-45	216	657799 5427004 Keats
NFGC-22-837 297	-46	452	657818 5426771 Keats
NFGC-22-845300	-45	216	657767 5426977 Keats
NFGC-22-853297	-46	452	657783 5426791 Keats
NFGC-22-863300	-45	472	657573 5426335 TCH
NFGC-22-871 297	-46	548	657786 5426497 Keats
NFGC-22-885 120	-70	329	657272 5426509 TCH

Table 3: Details of drill holes reported in this press release

Queensway 500,000m Drill Program Update

The Company is currently undertaking a 500,000m drill program at Queensway. Approximately 51,000m of

19.12.2025 Seite 13/16

core is currently pending assay results.

Sampling, Sub-sampling, and Laboratory

True widths of the intercepts reported in this press release have yet to be determined and further exploration is required. Infill veining in secondary structures with multiple orientations crosscutting the primary host structures are commonly observed in drill core which could result in additional variability in true width. Assays are uncut, and composite intervals are calculated using a minimum weighted average of 1 g/t Au diluted over a minimum core length of 2m with a maximum of 2m consecutive dilution. Included high-grade intercepts are reported as any consecutive interval with grades greater than 10 g/t Au.

All drilling recovers HQ core. Drill core is split in half using a diamond saw or a hydraulic splitter for rare intersections with incompetent core.

A geologist examines the drill core and marks out the intervals to be sampled and the cutting line. Sample lengths are mostly 1.0 meter and adjusted to respect lithological and/or mineralogical contacts and isolate narrow (<1.0m) veins or other structures that may yield higher grades.

Technicians saw the core along the defined cutting line. One-half of the core is kept as a witness sample and the other half is submitted for analysis. Individual sample bags are sealed and placed into totes, sealed and marked with the contents.

NFG submits samples for gold determination by fire assay to ALS Canada Ltd. ("ALS") and by photon assay to MSALABS ("MSA") since June 2022. ALS and MSA operate under a commercial contract with New Found.

Drill core samples are shipped to ALS for sample preparation in Sudbury, Ontario, Thunder Bay, Ontario, or Moncton, New Brunswick. ALS is an ISO-17025 accredited laboratory for the fire assay method.

Drill core samples are also submitted to MSA in Val-d'Or, Quebec. MSA operates numerous laboratories worldwide and maintains ISO-17025 accreditation for many metal determination methods. Accreditation of the photon assay method at the MSA Val D'Or laboratory is in progress.

At ALS, the entire sample is crushed to approximately 70% passing 2mm. A 3,000-g split is pulverized. "Routine" samples do not have visible gold (VG) identified and are not within a mineralized zone. Routine samples are assayed for gold by 30-g fire assay with an inductively-couple plasma spectrometry (ICP) finish. If the initial 30-g fire assay gold result is over 1 g/t, the remainder of the 3,000-g split is screened at 106 microns for screened metallics assay. For the screened metallics assay, the entire coarse fraction (sized greater than 106 microns) is fire assayed and two splits of the fine fraction (sized less than 106 microns) are fire assayed. The three assays are combined on a weight-averaged basis. Samples that have VG identified or fall within a mineralized interval are automatically submitted for screened metallic assay for gold.

At MSA, the entire sample is crushed to approximately 70% passing 2mm. For "routine" samples that do not have VG identified and are not within a mineralized zone, the samples are riffle split to fill two 450g jars for photon assay. The assays reported from both jars are combined on a weight-averaged basis. If one of the jars assays greater than 1 g/t, the remaining crushed material is weighed into multiple jars and are submitted for photon assay.

For samples that have VG identified or are within a mineralized zone, the entire crushed sample is weighed into multiple jars and are submitted for photon assay. The assays from all jars are combined on a weight-averaged basis.

All samples prepared at ALS or MSA are also analyzed for a multi-element ICP package (ALS method code ME-ICP61) at ALS Vancouver.

Drill program design, Quality Assurance/Quality Control and interpretation of results are performed by

19.12.2025 Seite 14/16

qualified persons employing a rigorous Quality Assurance/Quality Control program consistent with industry best practices. Standards and blanks account for a minimum of 10% of the samples in addition to the laboratory's internal quality assurance programs.

Quality Control data are evaluated on receipt from the laboratories for failures. Appropriate action is taken if assay results for standards and blanks fall outside allowed tolerances. All results stated have passed New Found's quality control protocols.

New Found's quality control program also includes submission of the second half of the core for approximately 5% of the drilled intervals. In addition, approximately 1% of sample pulps for mineralized samples are submitted for re-analysis to a second ISO-accredited laboratory for check assays.

The Company does not recognize any factors of drilling, sampling or recovery that could materially affect the accuracy or reliability of the assay data disclosed.

The assay data disclosed in this news release have been verified by the Company's Qualified Person against the original assay certificates.

The Company notes that it has not completed any economic evaluations of its Queensway Project and that the Queensway Project does not have any resources or reserves.

# **Qualified Person**

The scientific and technical information disclosed in this press release was reviewed and approved by Greg Matheson, P. Geo., Chief Operating Officer, and a Qualified Person as defined under National Instrument 43-101. Mr. Matheson consents to the publication of this press release dated January 18, 2023, by New Found. Mr. Matheson certifies that this press release fairly and accurately represents the scientific and technical information that forms the basis for this press release.

About New Found Gold Corp.

New Found holds a 100% interest in the Queensway Project, located 15km west of Gander, Newfoundland and Labrador, and just 18km from Gander International Airport. The project is intersected by the Trans-Canada Highway and has logging roads crosscutting the project, high voltage electric power lines running through the project area, and easy access to a highly skilled workforce. The Company is currently undertaking a 500,000m drill program at Queensway and is well funded for this program with cash and marketable securities of approximately \$90-million as of January 2023.

Please see the Company's website at www.newfoundgold.ca and the Company's SEDAR profile at www.sedar.com.

# Acknowledgements

New Found acknowledges the financial support of the Junior Exploration Assistance Program, Department of Natural Resources, Government of Newfoundland and Labrador.

#### Contact

To contact the Company, please visit the Company's website, www.newfoundgold.ca and make your request through our investor inquiry form. Our management has a pledge to be in touch with any investor inquiries within 24 hours.

Neither the TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the

19.12.2025 Seite 15/16

policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release.

# Forward-Looking Statement Cautions

This press release contains certain "forward-looking statements" within the meaning of Canadian securities legislation, relating to exploration, drilling and mineralization on the Company's Queensway gold project in Newfoundland and Labrador; assay results; the interpretation of drilling and assay results, the results of the drilling program, mineralization and the discovery of zones of high-grade gold mineralization; plans for future exploration and drilling and the timing of same; the merits of the Queensway project;; future press releases by the Company; and funding of the drilling program. Although the Company believes that such statements are reasonable, it can give no assurance that such expectations will prove to be correct. Forward-looking statements are statements that are not historical facts; they are generally, but not always, identified by the words "expects," "plans," "anticipates," "believes," "interpreted," "intends," "estimates," "projects," "suggests," "indicate," "often," "target," "future," "likely," "pending," "potential," "goal," "objective," "prospective," "possibly," "preliminary", and similar expressions, or that events or conditions "will," "would," "may," "can," "could" or "should" occur, or are those statements, which, by their nature, refer to future events. The Company cautions that forward-looking statements are based on the beliefs, estimates and opinions of the Company's management on the date the statements are made, and they involve a number of risks and uncertainties. Consequently, there can be no assurances that such statements will prove to be accurate and actual results and future events could differ materially from those anticipated in such statements. Except to the extent required by applicable securities laws and the policies of the TSX Venture Exchange, the Company undertakes no obligation to update these forward-looking statements if management's beliefs, estimates or opinions, or other factors, should change. Factors that could cause future results to differ materially from those anticipated in these forward-looking statements include risks associated with possible accidents and other risks associated with mineral exploration operations, the risk that the Company will encounter unanticipated geological factors, risks associated with the interpretation of assay results and the drilling program, the possibility that the Company may not be able to secure permitting and other governmental clearances necessary to carry out the Company's exploration plans, the risk that the Company will not be able to raise sufficient funds to carry out its business plans, and the risk of political uncertainties and regulatory or legal changes that might interfere with the Company's business and prospects. The reader is urged to refer to the Company's Annual Information Form and Management's discussion and Analysis, publicly available through the Canadian Securities Administrators' System for Electronic Document Analysis and Retrieval (SEDAR) at www.sedar.com for a more complete discussion of such risk factors and their potential effects.

View source version on businesswire.com: https://www.businesswire.com/news/home/20230118005370/en/

# Contact

New Found Gold Corp.
Per: "Collin Kettell"

Collin Kettell, Chief Executive Officer Email: ckettell@newfoundgold.ca Phone: +1 (845) 535-1486

Dieser Artikel stammt von Rohstoff-Welt.de

Die URL für diesen Artikel lautet:

https://www.rohstoff-welt.de/news/433142--New-Found-Discovers-Multiple-New-Gold-Zones-Extending-1.5km-South-of-Keats-Increases-Appleton-Fault-Zone

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere AGB/Disclaimer!

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt! Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2025. Es gelten unsere <u>AGB</u> und <u>Datenschutzrichtlinen</u>.

19.12.2025 Seite 16/16