Silver Tiger Intersects 3.3 meters of 1,153.6 g/t Silver Equivalent within 10.5 meters of 443.9 g/t Silver Equivalent at the Southern End of the Sulphide Zone

15.08.2023 | ACCESS Newswire

HALIFAX, August 15, 2023 - <u>Silver Tiger Metals Inc.</u> (TSXV:SLV)(OTCQX:SLVTF) ("Silver Tiger" or the "Corporation") has intersected 1,153.6 g/t total silver equivalent over 3.3 meters in the Sulphide Zone in Drill Hole ET-23-462 from 520.5 meters to 523.8 meters, consisting of 378.7 g/t silver, 6.17 g/t gold, 0.31% copper, 3.10% lead and 6.31% zinc within 10.5 meters grading 443.9 g/t total silver equivalent from 513.3 meters to 523.8 meters consisting of 1.51.5 g/t silver, 1.98 g/t gold, 0.14% copper, 1.39% lead and 2.95% zinc in the Sulphide Zone. These high-grade intercepts have tripled the known strike length of the Sulphide Zone, bringing the originally indicated 250 meters of strike extent to more than 750 meters.

Highlights from the drilling program include the following:

Hole ET-23-456: 0.8 meters grading 1,452.0 g/t total silver equivalent from 284.1 meters to 284.9 meters, consisting of 1,135.0 g/t silver, 0.48 g/t gold, 1.57% copper, 2.76% lead and 1.63% zinc within 4.7 meters grading 446.2 g/t total silver equivalent from 280.8 meters to 285.5 meters consisting of 344.3 g/t silver, 0.15 g/t gold, 0.44% copper, 0.65% lead and 0.99% zinc in the Sulphide Zone.

Drill Hole ResultsTable

Hole ID	Comment	From m	To m	Length (1) m	Gold g/t	Silver g/t	Copper %	Lead %	Zinc AgEq Total (2) % g/t
ET-23-454	Sooy Vein	295.0	298.0	3.0	0.02	66.0	80.0	0.41	0.68 107.4
	including	295.0	296.0	1.0	0.01	178.0	0.22	1.00	1.66 278.7
	Sulphide Zone	311.9	322.5	10.7	0.06	73.8	80.0	0.48	0.53 114.6
	including	311.9	314.7	2.8	0.06	174.0	0.20	1.33	1.56 281.0
	including	312.4	314.7	2.3	0.06	190.9	0.22	1.39	1.65 304.3
	including	313.5	314.7	1.2	0.06	157.5	0.19	0.37	0.49 204.9
	including	320.5	322.5	2.0	80.0	128.1	0.12	0.33	0.29 163.0
	including	322.0	322.5	0.6	0.12	344.0	0.31	0.50	0.59 414.3
ET-23-456	S Sulphide Zone	280.8	285.5	4.7	0.15	344.3	0.44	0.65	0.99 446.2
	including	282.5	284.9	2.4	0.24	653.1	0.85	1.26	1.94 847.4
	including	284.1	284.9	8.0	0.48	1,145.0	1.57	2.76	1.63 1,452.0
ET-23-460	El Tigre Vein Zone	403.7	404.2	0.6	0.22	30.4	0.03	1.75	1.68 146.8
	Sulfide Zone	616.7	617.3	0.5	0.26	1,294.0	0.62	3.76	6.30 1,670.4

12.11.2025 Seite 1/10

ET-23-462 Sulphide Zone	385.8 389.2 3.4	1.57 59	92.2	80.0	0.41	0.68 107.4
including	386.5 387.3 0.8	2.94 68	86.0	0.21	0.43	5.91 1,132.8
Sulphide Zone	513.3 523.8 10.5	1.98 1	51.5	0.14	1.39	2.95 443.9
including	513.3 515.1 1.8	0.11 14	42.2	0.13	1.62	4.26 342.6
including	518.5 523.8 5.3	3.87 24	48.7	0.22	2.19	4.37 756.8
including	520.5 523.8 3.3	6.17 3	78.7	0.31	3.10	6.31 1,153.6
including	523.2 523.8 0.5	2.96 7	73.0	0.33	4.94	8.38 1,421.3
including	520.5 521.5 1.0	17.52 58	82.5	0.34	2.64	6.75 2,215.8
including	520.5 521.0 0.5	34.00 72	21.0	0.23	3.10	7.70 3,622.0
ET-23-473 Sooy Vein	323.7 327.7 4.0	0.11 78	85.9	0.68	0.56	1.34 916.7
including	323.7 326.0 2.3	0.15 1,	,298.9	1.12	0.93	2.07 1,508.7
including	323.7 324.3 0.6	0.10 3,	,950.0	3.67	3.23	7.32 4,630.6
ET-23-474 Sooy Vein	263.6 264.4 0.8	0.16 1,	,549.0	1.73	0.25	0.72 1,757.1
Deep Sulphide Zone	490.0 493.7 3.6	0.10 34	4.0	0.11	0.75	1.48 119.1
including	490.0 492.4 2.4	0.12 4	7.9	0.13	1.00	2.02 159.8
including	491.6 492.4 0.8	0.13 6	3.3	0.13	1.19	1.99 179.9

Notes: 1. Not true width.

Silver Tiger's CEO, Glenn Jessome, stated, "With further targeted drilling, the team has extended the high-grade Ag-Au-Cu-Zn-Pb Sulphide Zone 125 meters to the North and 375 meters to the South. These new drilling results have successfully tripled the known strike length of the Sulphide Zone, bringing the originally indicated 250 meters of strike extent to more than 750 meters." Mr. Jessome further stated "This steeply dipping body with true widths ranging from 2 to 25 meters and a down-dip extent ranging from 200 to 500 meters is open at depth and laterally, leaving significant potential for growth."

Drill Holes Previously Released from the Sulphide Zone.

Hole ID	Comment	From To m m	Length (1 m		Silver g/t	Coppe %	r Lead %	Zinc %	AgEq Total (2) g/t
ET-22-44	³ Sulphide Zone	362.8 367.	5 4.7	0.11	419.8	0.45	0.26	0.42	491.4
	including	365.2 366.	3 1.1	0.29	901.0	1.00	0.84	1.05	1,073.3
	Sulphide Zone	418.6 456.	4 37.8	0.19	171.7	0.39	1.85	3.67	388.8
	including	441.0 444.	3 3.3	0.19	633.8	1.04	4.80	11.38	1,239.0

12.11.2025 Seite 2/10

^{2.} Silver Equivalent ("EqAg") ratios are based on a silverto gold priceratio of 75:1 (Au:Ag). Copper,lead and zinc are converted using \$3.66/lb copper, \$0.90/lb lead, \$1.26/lb zinc at 100% metal recoveries based on a silver price of \$26.00/oz.

	including	443.2	444.3	1.1	0.18	977.0	1.65	4.79	12.32	1,671.5
ET-22-441	Sulphide Zone	415.3	435.3	20.0	0.35	369.0	0.85	4.11	8.15	845.1
	including	432.5	434.5	2.0	0.20	1,255.7	2.02	12.67	26.87	2,656.0
	including	432.5	433.8	1.3	0.21	1,484.1	2.71	14.67	29.82	3,097.9
ET-22-440) Sulphide Zone	377.1	434.3	57.2	0.20	231.5	0.41	0.71	1.02	336.2
	Sulphide Zone	397.9	434.3	36.4	0.25	314.6	0.58	0.90	1.40	457.2
	including	421.7	424.5	2.8	0.21	1,986.3	4.02	3.94	5.64	2,668.8
	including	421.7	423.2	1.5	0.25	2,714.0	5.41	80.0	1.04	3,289.9
	including	422.5	423.2	0.7	0.26	3,054.0	7.28	0.09	1.37	3,822.4
ET-22-438	HW Gold Zone	9.2	52.7	43.5	0.16	18.7	0.00	0.01	0.01	31.3
	including	29.0	29.6	0.6	2.26	566.0	0.02	0.02	0.02	739.5
	Sooy Vein Zone	321.3	324.5	3.2	0.52	300.5	0.18	0.73	0.33	384.8
	including	322.1	323.0	0.9	1.51	773.0	0.48	2.08	0.77	1,006.7
	Sulphide Zone	393.5	413.0	19.5	0.27	408.4	0.53	0.88	0.83	527.5
	including	394.8	398.5	3.7	0.24	879.4	0.76	0.86	1.36	1,035.8
	including	396.0	396.5	0.5	0.62	2,796.0	1.75	1.85	4.16	3,193.1
	including	403.8	411.8	8.0	0.51	564.3	0.90	1.68	1.31	771.9
	including	406.3	407.0	0.7	1.47	1,148.0	1.40	1.52	0.71	1,452.3
ET-22-434	HW Gold Zone	6.5	15.0	8.5	0.39	96.7	0.01	80.0	0.01	129.8
	including	10.1	11.6	1.5	2.04	336.0	0.02	0.17	0.04	496.6
	Sooy Vein Zone	184.6	197.6	13.0	0.16	172.5	0.36	2.08	2.56	354.0
	including	190.6	195.8	5.2	0.19	326.4	0.84	4.89	5.97	734.8
	including	192.3	194.4	2.1	0.24	496.1	1.76	7.17	8.62	1,139.2
	Sulphide Zone	306.7	313.3	6.6	0.11	376.8	0.32	0.14	0.09	421.9
	including	311.3	313.3	2.0	0.20	1,116.5	0.89	0.20	0.11	1,225.9
	including	312.3	313.3	1.0	0.25	1,859.0	1.44	0.33	0.19	2,030.4
	Sulphide Zone	361.7	381.6	19.9	0.22	605.6	1.13	4.04	7.43	1,072.9
	including	370.1	380.6	10.5	0.20	914.0	1.68	5.92	12.42	1,642.4
	including	359.0	360.2	1.2	0.19	1,345.0	1.57	2.10	0.83	1,587.4

12.11.2025 Seite 3/10

ET-22-433	³ HW Gold Zone	0.0	14.2	14.2	0.10	56.9	0.01	0.04	0.01	66.8
	Sooy Vein	190.9	201.9	11.0	0.29	165.4	0.16	1.43	4.42	382.5
	Zone									
	including	193.6	198.4	4.8	0.41	369.9	0.35	3.19	9.96	840.2
	including	194.7	195.8	1.1	0.12	634.5	0.57	4.68	18.48	1,422.5
	Sulphide Zone	330.5	374.9	44.4	0.16	508.2	0.55	1.76	3.17	720.5
	including	332.9	337.9	5.0	0.17	1,431.8	1.41	2.47	6.27	1,846.8
	including	335.5	336.1	0.6	0.18	3,225.0	4.19	5.34	15.59	4,285.5
	including	364.5	370.5	6.0	0.20	1,354.4	1.57	6.10	10.86	2,025.5
	including	366.8	367.8	1.0	0.19	2,371.5	3.07	10.00	17.81	3,508.8
ET-22-432	² HW Gold Zone	4.6	14.0	9.4	0.10	39.0	0.01	0.02	0.02	48.5
	Sooy Vein Zone	191.2	201.6	10.4	0.16	399.0	0.43	2.84	5.16	690.6
	including	195.6	197.7	2.1	0.24	1,153.6	1.29	9.76	16.82	2,084.8
	Sulphide Zone	348.4	383.2	34.8	0.13	257.4	0.47	1.18	2.02	407.4
	including	372.4	380.6	8.2	0.13	956.6	1.69	3.58	7.01	1,446.2
	including	378.5	380.6	2.1	0.17	1,663.5	4.32	6.28	11.50	2,622.5
ET-22-431	HW Gold	10.1	46.5	36.4	0.13	41.9	0.00	0.01	0.01	52.6
	Zone									
	including	10.1	11.6	1.5	0.11	731.0	0.00	0.05	0.00	740.9
	SooyVein	83.9	86.7	2.8	0.59	137.4	0.03	0.19	0.24	196.5
	Zone	339.5	342.6	3.1	0.06	211.5	0.08	0.02	0.03	225.2
	El Tigre	409.1	418.5	9.4	0.19	641.3	0.65	3.32	6.51	1,013.3
	Vein									
	including	413.5	415.6	2.1	0.19	1,536.1	1.62	7.71	13.66	2,341.9
ET-23-445	Sulphide Zone	397.7	400.8	3.1	0.24	129.6	0.16	0.81	1.97	246.8
	including	399.1	399.9	8.0	0.17	305.0	0.31	1.69	4.83	547.5
	Sulphide Zone	465.0	474.6	9.6	0.24	115.1	0.58	1.98	3.88	364.6

12.11.2025 Seite 4/10

including	467.0 468.6 1.6	0.59 441.7 2.14	7.58	12.00 1,269.6
including	468.1 468.6 0.5	0.52 857.0 1.74	6.44	14.60 1,700.0
ET-23-446 Sulphide Zone	e 382.8 400.7 17.9	0.19 200.7 0.42	2.23	3.55 425.9
including	390.5 392.5 2.0	0.17 666.2 0.93	4.26	8.67 1,156.4
including	394.6 397.0 2.4	0.31 427.6 0.66	4.03	5.05 777.4
including	394.6 395.1 0.5	0.48 804.0 1.22	3.99	0.57 1,071.5
ET-23-447 Sooy Vein Zo	ne 237.5 240.1 2.6	0.02 264.7 0.16	0.01	0.03 282.4
including	237.5 238.5 1.0	0.02 573.0 0.35	0.01	0.07 610.5
El Tigre Vein	Zone 311.0 312.0 1.0	0.08 1,689.2 0.80	0.08	0.18 1,780.2
including	311.5 312.0 0.5	0.16 3,351.0 1.59	0.13	0.33 3,530.4
ET-23-448 El Tigre Vein	Zone 253.0 257.9 4.9	0.03 484.8 0.33	0.01	0.08 521.7
including	254.9 255.9 1.0	0.04 1,194.5 0.84	0.03	0.19 1,285.5
including	254.9 255.4 0.5	0.05 1,560.0 1.14	0.04	0.27 1,683.6
ET-23-449 Sooy Vein Zo	ne 305.7 306.6 0.9	0.01 345.0 0.18	0.00	0.12 367.6
El Tigre Vein	451 F 452 1 0 G	0.05 18.6 0.03	0.80	1.53 95.3
ET-23-450 El Tigre Vein	Zone 267.4 268.5 1.1	0.20 135.0 0.49	0.19	1.37 246.5
ET-23-455 Sooy Vein	272.0 273.5 1.5	0.04 147.0 0.07	0.01	0.04 158.4
Sulphide Zone	e 468.8 481.2 12.4	0.14 97.8 0.13	0.93	1.78 201.9
including	468.8 474.7 5.9	0.12 201.1 0.24	1.92	3.69 401.5
including	470.3 474.1 3.8	0.10 292.5 0.34	2.70	5.26 570.8
including	472.3 473.5 1.2	0.12 436.4 0.50	3.32	6.66 792.7
ET-23-457 Sulphide Zone	e 441.0 479.7 38.7	0.11 297.5 0.28	1.42	2.19 438.9
including	441.0 456.8 15.8	0.17 692.6 0.60	2.99	4.61 986.8
including	445.0 451.3 6.3	0.15 1,100.1 0.87	5.10	8.01 1,581.4
including	445.0 448.4 3.4	0.13 1,245.7 1.00	6.38	13.43 1,948.8
including	447.8 448.4 0.6	0.15 1,943.0 1.58	7.29	10.95 2,642.2
ET-23-463 Open Pit Gold	d Zone 83.0 119.0 36.0	0.95 1.7 0.00	0.01	0.01 73.4
including	84.1 90.5 6.4	2.79 1.9 0.00	0.01	0.01 211.8
including				

12.11.2025 Seite 5/10

89.0 90.5 1.5 7.18 4.8 0.01 0.01 0.01 544.2

12.11.2025 Seite 6/10

	Sulphide Zone	461.0 470.9 9.9	0.13 609.7	0.61	0.41	0.70	711.2
	including	462.6 468.8 6.2	0.18 827.3	0.83	0.56	0.87	962.8
	including	462.6 463.3 0.7	0.19 1,431.0	2.08	0.48	1.69	1,712.7
	including	466.1 468.8 2.7	0.14 1,089.2	1.01	0.96	1.47	1,268.6
	including	466.1 468.1 2.0	0.14 1,165.6	5 1.04	0.85	0.51	1,313.3
	El Tigre Vein Zone	482.6 486.6 4.0	0.17 212.7	0.24	1.70	1.40	334.8
ET-23-464	including	482.6 485.8 3.2	0.18 243.3	0.27	2.02	1.63	385.2
	HW Gold Zone	487.0 490.0 3.0	0.04 63.1	0.08	0.24	0.03	80.5
	including	488.3 489.0 0.7	0.04 167.0	0.18	0.62	0.06	204.0
	HW Gold Zone	497.0 509.0 12.0	0.07 31.1	0.13	0.48	0.37	72.4
	including	497.0 500.0 3.0	0.08 69.2	0.09	0.73	1.16	139.9
	Sulphide Zone	538.0 551.9 13.9	0.23 27.4	0.02	1.16	6.22	280.5
	including	541.5 548.2 6.7	0.33 43.1	0.03	1.72	11.61	495.9
	including	547.0 547.7 0.7	0.21 38.9	0.04	2.55	24.64	936.4
	and	565.1 568.2 3.1	0.26 14.4	0.02	0.18	0.71	63.8

Notes: 1. Not true width.

2. Silver Equivalent ("AgEq") ratios are based on a silverto gold priceratio of 75:1 (Au:Ag). Copper,lead and zinc are converted using \$3.66/lb copper, \$0.90/lb lead, \$1.26/lb zinc at 100% metal recoveries based on a silver price of \$26.00/oz.

Attached as illustrations are the Sulphide Zone Long Section, Sulphide Zone-Cross Section 4490N, Sulphide Zone-Cross Section 5015N, El Tigre - Conceptual Cross Section, El Tigre-Conceptual Long Section, and El Tigre Long Section Showing Exploration Potential.

Sulphide Zone Long Section

Sulphide Zone-Cross Section 4490N

Sulphide Zone - Cross Section 5015N

El Tigre - Conceptual Cross Section Showing Mineralization Styles

El Tigre-Conceptual Long Section Showing Mineralization Styles

El Tigre-Long Section Showing Exploration Potential

Drill Hole Location Table

12.11.2025 Seite 7/10

Hole ID	Easting	Northing	Elevation (m)	Azimuth	Dip	Length (m)
ET-23-454	670812	3385017	1794.3	91	-72	452.0
ET-23-456	670810	3385018	1794.4	84	-71	455.0
ET-23-460	670703	3384473	1945.7	87	-65.5	644.0
ET-23-462	670888	3384500	2038.7	190	-87.5	545.0
ET-23-473	670704	3384658	1917.4	90	-66	581.0
ET-23-474	670737	3384757	1908.0	100	-71	572.0

El Tigre Resource Estimate

After acquiring El Tigre, Silver Tiger drilled 12,500 meters to define the wide halo of near surface gold mineralization around the mined high-grade veins of the historic El Tigre Mine. This allowed Silver Tiger to deliver a maiden resource estimate for the El Tigre Property to a depth of 150 meters containing indicated resources of 661,000 gold equivalent ounces at 0.77 g/t (21 g/t silver and 0.51 g/t gold) and inferred resources of 341,000 gold equivalent ounces at 1.59 g/t (88 g/t silver and 0.52 g/t gold). The National Instrument 43-101 Technical Report titled "NI 43-101 Technical Report and Updated Mineral Resource Estimate on the El Tigre Project, Sonora, México" effective as of September 7, 2017 and dated October 26, 2017 prepared by David Burga, P.Geo., Yungang Wu, P.Geo., Fred Brown, P.Geo., Jarita Barry, P.Geo., Eugene Puritch, P.Eng., FEC, CET, Alfred Hayden, P.Eng. and Richard H. Sutcliffe, Ph.D., P.Geo. of P&E Mining Consultants Inc. is available on the Corporation's website at www.silvertigermetals.com and on www.sedar.com under the Corporation's profile.

About Silver Tiger and the El Tigre Historic Mine District

<u>Silver Tiger Metals Inc.</u> is a Canadian company whose management has more than 25 years' experience discovering, financing and building large hydrothermal silver projects in Mexico. Silver Tiger's 100% owned 28,414 hectare Historic El Tigre Mining District is located in Sonora, Mexico. Principled environmental, social and governance practices are core priorities at Silver Tiger.

The El Tigre historic mine district is located in Sonora, Mexico and lies at the northern end of the Sierra Madre silver and gold belt which hosts many epithermal silver and gold deposits, including Dolores, Santa Elena and Las Chispas at the northern end. In 1896, gold was first discovered on the property in the Gold Hill area and mining started with the Brown Shaft in 1903. The focus soon changed to mining high-grade silver veins in the area with production coming from 3 parallel veins the El Tigre Vein, the Seitz Kelley Vein and the Sooy Vein. Underground mining on the middle El Tigre vein extended 1,450 meters along strike and was mined on 14 levels to a depth of approximately 450 meters. The Seitz Kelley Vein was mined along strike for 1 kilometer to a depth of approximately 200 meters. The Sooy Vein was only mined along strike for 250 meters to a depth of approximately 150 meters. Mining abruptly stopped on all 3 of these veins when the price of silver collapsed to less than 20¢ per ounce with the onset of the Great Depression. By the time the mine closed in 1930, it is reported to have produced a total of 353,000 ounces of gold and 67.4 million ounces of silver from 1.87 million tons (Craig, 2012). The average grade mined during this period was over 2 kilograms silver equivalent per ton.

The El Tigre silver and gold deposit is related to a series of high-grade epithermal veins controlled by a north-south trending structure cutting across the andesitic and rhyolitic tuffs of the Sierra Madre Volcanic Complex within a broad silver and gold mineralized prophylitic alteration zone developed in the El Tigre Formation that can be up to 150 meters wide. The veins dip steeply to the west and are typically 0.5 meter wide but locally can be up to 5 meters in width. The veins, structures and mineralized zones outcrop on surface and have been traced for 5.3 kilometers along strike in our brownfield exploration area. Historical mining and exploration activities focused on a 1.6 kilometer portion of the southern end of the deposits, principally on the El Tigre, Seitz Kelly and Sooy veins. The under explored Caleigh, Benjamin, Protectora and the Fundadora exposed veins continue north for more than 3 kilometers. Silver Tiger has delivered its maiden 43-101 compliant resource estimate and is currently drilling to update its resource estimate and

12.11.2025 Seite 8/10

publish a PEA.

VRIFY Slide Deck and 3D Presentation - Silver Tiger's El Tigre Project

VRIFY is a platform being used by companies to communicate with investors using 360° virtual tours of remote mining assets, 3D models and interactive presentations. VRIFY can be accessed by website and with the VRIFY iOS and Android apps.

Access the Silver Tiger Metals Inc. Company Profile on VRIFY at: https://vrify.com

The VRIFY Slide Deck and 3D Presentation for <u>Silver Tiger Metals Inc.</u> can be viewed at: https://vrify.com/explore/decks/492 and on the Corporation's website at: www.silvertigermetals.com.

Procedure, Quality Assurance / Quality Control and Data Verification

The diamond drill core (HQ size) is geologically logged, photographed and marked for sampling. When the sample lengths are determined, the full core is sawn with a diamond blade core saw with one half of the core being bagged and tagged for assay. The remaining half portion is returned to the core trays for storage and/or for metallurgical test work.

The sealed and tagged sample bags are transported to the Bureau Veritas facility in Hermosillo, Mexico. Bureau Veritas crushes the samples (Code PRP70-250) and prepares 200-300 gram pulp samples with ninety percent passing Tyler 200 mesh (Code PUL85). The pulps are assayed for gold using a 30-gram charge by fire assay (Code FA630) and over limits greater than 10 grams per tonne are re-assayed using a gravimetric finish (Code FA530). Silver and multi-element analysis is completed using total digestion (Code MA200 Total Digestion ICP). Over limits greater than 100 grams per tonne silver are re-assayed using a gravimetric finish (Code FA530).

Quality assurance and quality control ("QA/QC") procedures monitor the chain-of-custody of the samples and includes the systematic insertion and monitoring of appropriate reference materials (certified standards, blanks and duplicates) into the sample strings. The results of the assaying of the QA/QC material included in each batch are tracked to ensure the integrity of the assay data. All results stated in this announcement have passed Silver Tiger's QA/QC protocols.

Qualified Person

David R. Duncan, P. Geo., V.P. Exploration of the Corporation, is the Qualified Person for Silver Tiger as defined under National Instrument 43-101. Mr. Duncan has reviewed and approved the scientific and technical information in this press release.

For further information, please contact:

Glenn Jessome President and CEO 902 492 0298 jessome@silvertigermetals.com

CAUTIONARY STATEMENT:

Neither TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release.

This News Release includes certain "forward-looking statements". All statements other than statements of

12.11.2025 Seite 9/10

historical fact included in this release, including, without limitation, statements regarding potential mineralization, resources and reserves, the ability to convert inferred resources to indicated resources, the ability to complete future drilling programs and infill sampling, the ability to extend resource blocks, the similarity of mineralization at El Tigre to Delores, Santa Elena and Chispas, exploration results, and future plans and objectives of Silver Tiger, are forward-looking statements that involve various risks and uncertainties. Forward-looking statements are frequently characterized by words such as "may", "is expected to", "anticipates", "estimates", "intends", "plans", "projection", "could", "vision", "goals", "objective" and "outlook" and other similar words. Although Silver Tiger believes the expectations expressed in such forward-looking statements are based on reasonable assumptions, there can be no assurance that such statements will prove to be accurate and actual results and future events could differ materially from those anticipated in such statements. Important factors that could cause actual results to differ materially from Silver Tiger's expectations include risks and uncertainties related to exploration, development, operations, commodity prices and global financial volatility, risk and uncertainties of operating in a foreign jurisdiction as well as additional risks described from time to time in the filings made by Silver Tiger with securities regulators.

SOURCE: Silver Tiger Metals Inc.

View source version on accesswire.com:

https://www.accesswire.com/774213/Silver-Tiger-Intersects-33-meters-of-11536-gt-Silver-Equivalent-within-105-meters-

Dieser Artikel stammt von Rohstoff-Welt.de Die URL für diesen Artikel lautet:

https://www.rohstoff-welt.de/news/450838--Silver-Tiger-Intersects-3.3-meters-of-1153.6-g-t-Silver-Equivalent-within-10.5-meters-of-443.9-g-t-Silve

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere AGB/Disclaimer!

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt! Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2025. Es gelten unsere AGB und Datenschutzrichtlinen.

12.11.2025 Seite 10/10