

Trilogy Metals Announces Potential for By-product Germanium at the Bornite Copper-Cobalt Project, Alaska

07.09.2023 | [CNW](#)

VANCOUVER, Sept. 7, 2023 - [Trilogy Metals Inc.](#) (TSX: TMQ) (NYSE American: TMQ) ("Trilogy" or the "Company") is announce recent research conducted with the assistance of the Colorado School of Mines (the "School") and the United Geological Survey ("USGS") has highlighted the potential for germanium to be a by-product during future copper production at the South Reef area of the Bornite copper-cobalt project. Germanium is a critical element with increasing demand in many technologies and significant supply risks. China, the world's largest producer of germanium, has adopted export controls to restrict the export of germanium, among other metals.

Additionally, Ambler Metals LLC ("Ambler Metals"), the joint venture operating company owned equally by Trilogy and South32 Limited (ASX, LSE, JSE: S32; ADR: SOUHY) ("South32"), will be providing samples to the School and the USGS to benefit their collaboration on critical minerals in the US. The Bornite project is part of Ambler Metals' Upper Kobuk Mineral Project ("UKMP") in northwestern Alaska which also includes the flagship Arctic copper-zinc-lead-silver-gold project, and surrounding mining claims and NANA Regional Corporation, Inc. ("NANA") lands.

Bornite is located approximately 24 km southwest of the Arctic deposit that is envisioned to be served by the Ambler Arctic deposit (see Figure 1). The Bornite deposit has a total Inferred resource of 6.5 billion pounds of copper (see Table 1). It is a carbonate-hosted copper deposit with stacked stratabound mineralized bodies or 'reefs' (see Figure 2) that include the Lower and Upper Reefs, that together have an In-Pit Inferred resource of 170 million tonnes ("Mt") grading 1.14% copper (using a 0.5% copper cut-off) and the deeper and higher-grade Ruby Zone and South Reef area. South Reef has an Inferred resource of 1.1 Mt at 3.48% copper (using a 1.79% copper cut-off).

Germanium at South Reef

Germanium values ranging from <1 to 125 ppm were measured in 84 core samples taken from five drill holes from South Reef as part of a recently completed Master of Science thesis done at the School. The samples, averaging 15 cm in length, were analyzed to establish the presence of germanium sulphides at South Reef. Due to the known association between copper sulphides and germanium seen by the USGS in the 1980s, higher copper grades (>5% copper) in the South Reef core were a key criterion in the sampling strategy. Although the samples represent only a small part of the South Reef area, the results clearly demonstrate that germanium is present at levels that are significantly higher than values obtained using a standard analytical method where a volatile germanium compound is lost during reaction with hydrochloric acid.

Importantly, the thesis work confirms the close association between the germanium sulphide renierite ($\text{Cu}_{10}\text{ZnGe}_2\text{Fe}_4\text{S}_{16}$) and copper sulphides, most commonly bornite and chalcocite (see Figure 3). In the 1980s, the USGS identified renierite and germanite ($\text{Cu}_{13}\text{Ge}_2\text{Fe}_2\text{S}_{16}$) in samples from the Ruby Zone occurring as discrete grains up to 75 microns in size embedded within grains of bornite. The close association with copper sulphides suggests the germanium sulphides will be recovered in the copper concentrate during flotation without special or additional processing.

Tony Giardini, President and CEO of Trilogy, commented "We are excited about our ongoing collaboration with the USGS and the Colorado School of Mines. Germanium is an important metal with numerous applications, particularly in the manufacturing of semiconductor chips, fiber-optic systems, and high efficiency solar cells. Prices for the high-value metal have steadily increased to approximately \$2,750 per kilogram, a 35% increase from January 2020. We believe this trend will continue due to China's export curb. It is imperative that other sources of germanium are developed. The most significant Western source is the Ruby Zone Mine in Alaska, operated by [Teck Resources Ltd.](#) in partnership with the land owner, NANA, which is approximately 32 km from the Ambler Mining District."

Richard Gosse, VP Exploration of Trilogy, said "I would like to thank Alexander Jones for the research he did as part of his Master's thesis at the Colorado School of Mines on the distribution of germanium at the South Reef deposit, as well as his supervisor, Katharina Pfaff, Manager of the School's Mineral and Material Characterization Facility, and Dr. Garth Graham of the USGS."

their oversight and assistance in the collection and subsequent studies. The high standard of their analytical work has highlighted the importance of germanium at Bornite and we look forward to contributing to their new project to better understand the importance of critical mineral resources in the US."

Germanium at Bornite

The under-reporting of germanium using a standard analytical method was recognized by the Company in 2011. At that time, mostly continuous core samples ranging from 0.65 to 3.34 meters were selected from four drill holes. Germanium values ranged from <1 to 83 ppm compared to a maximum value of 1.15 ppm using a standard analytical method. The best composite sample obtained was 17.56 meters averaging 30 ppm germanium with 12.48% copper (see Table 2), part of a 176-meter drill interval grading 4.01% copper in hole RC11-0187. Prior to this work, only six samples from Bornite are known to have been analyzed for germanium using sample preparation methods specifically for germanium. Including the samples used in the Jones study, it appears only 140 samples have been correctly analyzed for germanium in the 70+ years since the first hole was drilled.

Work has now started to accurately determine the amount and distribution of germanium at Bornite. Samples collected from Kennecott's pile of mineralization that was excavated during shaft sinking in the 1960s were recently analyzed at a laboratory in Australia using an analytical method specialized to prevent the loss of the volatile germanium compound. This work confirms the loss of germanium using the standard four acid digest. In addition, Ambler Metals will soon begin re-analyzing composite samples and their resulting concentrates obtained from metallurgical test work conducted in 2019 and 2021.

Finally, Ambler Metals has recently accepted a proposal from the Center to Advance the Science of Exploration to Reclaim Mining ("CASERM") at the School with leveraged USGS funding to contribute samples from Bornite to further investigate the occurrence, distribution, and sequestration of critical elements, including germanium, using a suite of micro-analytical methods such as SEM- and XRF-based techniques, electron probe micro analysis, and LA-ICP-MS. Objectives of the study include compiling a comprehensive whole-rock 60+ geochemical dataset of select samples from the Bornite deposit that complements the existing dataset from South Reef related to the MSc study. Additional sampling of mineralized core for the study is in progress.

Germanium

Various modern technologies, including infra-red systems used in thermal imaging applications such as night-vision goggles, as well as fiber optics, semiconductors, and solar panels, use germanium. About 130 tonnes of germanium are produced worldwide each year, up from 50-70 tonnes twenty years ago, primarily from zinc residues and fly ash (waste from the burning of fossil fuels). China produces between 60-80%. Supply and price are largely determined by recovery processes, geopolitical and legal factors, and environmental regulations.

Estimates on the future demand for germanium vary widely and are largely based on different solar energy scenarios. Germanium is an essential component of solar photovoltaic cells that use amorphous silicon-germanium thin film technology. Future technologies that could also strongly affect demand are fiber optics and SiGe semiconductors used in 5G telecom and data center infrastructure. For more information on the demand and uses of germanium, see the paper by Madhav Patel and Athanasios Karamalidis¹.

Copper and Cobalt

Copper mineralization at Bornite comprises chalcopyrite, bornite, and chalcocite as stringers, veinlets, and breccia fillings within hydrothermally altered dolostone within a sequence of alternating carbonates (limestones and dolostones) and calcareous dolostones. As with the other world-class carbonate-hosted copper deposits, such as at Kipushi (DR Congo) and Tsumeb (Namibia), Bornite shows early pyrite-dolomite alteration followed by copper-dominant sulphide mineralization with associated cobalt, germanium, silver, and zinc.

Studies of cobalt mineralization at Bornite indicate that most of the cobalt occurs as cobaltiferous pyrite both within and around the deposit. Cobalt is also present as two cobalt-bearing sulphides, carrollite and cobaltite, that are associated with the copper mineralization. The Bornite Technical Report (as defined below) on the Mineral Resource Update of the Bornite project shows representative drill hole intersections with cobalt grades showing drill holes within South Reef containing higher grades than other holes in-pit.

Critical Minerals and Alaska

Critical minerals such as copper, cobalt and germanium play an essential role in powering modern technologies, from renewable energy systems and electric vehicles to advanced electronics and national defense. Trilogy's management is confident that high-grade Alaskan mineral deposits such as Bornite can play an important role in securing a reliable supply of these materials, which are essential for the United States' economic competitiveness and national security.

Copper, cobalt and germanium are included in the US Critical Materials list, which informs eligibility for tax credits for such materials under the Inflation Reduction Act.

Table 1. Mineral Resources for the Bornite Deposit.

Class	Type/Area	Cut-off (Cu %)	Tonnes (Mt)	Average Copper Grade (%)	Contained Copper (Mlb)
Inferred	In-Pit	0.5	170.4	1.15	4,303
	Outside-Pit South Reef	1.79	22.0	3.48	1,690
	Outside-Pit Ruby Zone	1.79	10.4	2.28	521
Total Inferred (100%)			202.7	1.46	6,514
Total Inferred (50% Attributable Interest)			101.3		3,257

Notes:

- (1) The effective date of the mineral resource is January 26, 2023. The QP for the mineral resource is an employee of Wood Canada Limited.
- (2) Mineral Resources are prepared in accordance with CIM Definition Standards (2014) and the CIM Estimation of Mineral Resources and Mineral Reserves Best Practice Guidelines (CIM, 2019).
- (3) Mineral resources are constrained by: an open pit shell at a cut-off grade of 0.5% Cu, with an average pit slope of 43 degrees; and underground mining shapes with a cut-off grade of 1.79% Cu. The cut-off grades include the considerations of a \$4.05/lb Cu price, process recovery of 87.2%, open pit mining costs of \$3.21/t mined, underground mining cost of \$73.62/t mined, process cost of \$19.14/t processed, G&A cost of \$4.14/t processed, treatment, refining, sales cost of \$0.73/lb Cu in concentrate, road use cost of \$8.04/t processed, 2% NSR royalty.
- (4) Figures may not sum due to rounding.
- (5) See technical report titled "NI 43-101 Technical Report on the Mineral Resource Update of the Bornite Project, Northwest Alaska, USA" with an effective date of January 26, 2023 and a release date of February 14, 2023 (the "Bornite Technical Report").

Table 2. Significant composite intercepts of germanium from a 50-sample subset of reanalyzed 2011 drill core using germanium-specific analytical methods. Composites were selected based on an approximate 10 ppm cut-off.

Hole	From (m)	To (m)	Width (m)	Copper Grade (%)	Germanium (ppm)	Associated Mineralogy
RC11-0183	323.74	330.49	6.75	24.47	16	bn-cp-py
RC11-0185	173.74	178.26	4.52	7.96	9	bn-cp-py
RC11-0187	458.79	476.35	17.56	12.48	30	bn-cc-cp-py
RC11-0194	756.53	762.13	5.60	9.80	8	bn-cc-cp-py

Table 3. 2011 drill hole locations, depths and orientations.

Hole	Easting	Northing	Elevation	Depth	Azimuth	Dip
RC11-0183	589401.6	7440451	198.307	359.36	112.9	-58.2
RC11-0185	589129.7	7439619	255.592	350.52	86.3	-52.4
RC11-0187	590273.5	7440008	306.097	714.75	122.4	-85.5
RC11-0194	590478.7	7440196	265.651	782.42	1.3	-70.4

¹ M. Patel & A. Karamalidis, Germanium: A review of its US demand, uses, resources, chemistry and separation technologies; in Separation and Purification Technology, Elsevier, 2021.

QA/QC Program

The drilling program, sampling and assaying protocol, and data verification for germanium completed during 2011 were managed by qualified persons (QPs) employed by NovaCopper Inc. The diamond drill holes were completed using HQ or NQ diameter core. Drill core was cut lengthwise into halves using a diamond saw; one-half was used for the assay sample and the other half retained in core boxes and archived at site. Samples were collected through mineralized zones using a 0.3 m minimum length and 3.1 m maximum length; median sample length is 2.6 m.

Each core sample was placed into a bag with a numbered tag, and quality control samples were inserted between core samples using the same numbering sequence. The samples were grouped into batches for shipping and laboratory submissions. Each batch of 20 samples contains one certified reference material (CRM), one blank (BLK), and one crushed duplicate (DUP). Blank samples are commercial landscape marble. Duplicate samples were prepared at the sample preparation facility by taking a second split from the entire crushed sample. Chain of custody records were maintained for sample shipments and the custody was transferred upon delivery from NovaCopper expeditor to the laboratory.

Samples were shipped to ALS Minerals laboratory in Fairbanks, Alaska, USA, for sample submission. ALS Minerals Fairbanks is a satellite sample preparation facility accredited under ALS Minerals. The ALS Minerals Fairbanks shipped the samples to ALS Minerals in Reno, Nevada, USA, for sample preparation and analysis. ALS Minerals is an independent laboratory certified under ISO 9001:2008 and accredited under ISO/IEC 17025:2005. ALS Minerals includes its own internal quality control samples comprising certified reference materials, blanks, and pulp duplicates.

Drill core samples were weighed, dried, coarsely crushed to 70% passing 6 mm, finely crushed to 70% passing 2 mm, riffle split to 250 g subsamples, and pulverized to 85% passing 75 µm. Gold analyses were completed using a 30 g lead fire assay and AAS finish (Au-AA23). Multi-element analyses for 48 elements were completed using a geochemical four acid digestion and ICP-ES/MS finish (ME-MS61m). Over-range assays for Ag, Cu, Zn, and S were completed using an ore grade four-acid digestion and ICP-ES finish (ME-OG62). Additional analyses were completed for Ba and Hg.

Au, Ag, Cu, Pb, and Zn assays for QC samples were reviewed to ensure that CRMs are within tolerance limits specified on supplier certificates; BLKs are below acceptable thresholds; and DUPs display statistical patterns normally expected for sample types, methods, and elements.

Samples submitted for germanium check analyses were analyzed at ALS Minerals by a three acid digestion (Ge-MS66), which comprises nitric-hydrofluoric-orthophosphoric acids specifically set up to avoid volatilization of germanium chloride that occurs with a conventional four acid digestion that comprises nitric-perchloric-hydrofluoric-hydrochloric acids. Although external germanium CRMs were not included with the check samples, higher germanium values are more in-line with expectations based on mineralogy.

Qualified Person

Richard Gosse, P.Geo., Vice President Exploration for [Trilogy Metals Inc.](#), is a Qualified Person as defined

