

Southern Cross Gold Ltd. Drills 473.0 g/t Gold Over 0.5 Metres at Sunday Creek

30.05.2024 | [ACCESS Newswire](#)

Multiple High-Grade Structures Extend Mineralization

Announces 60 km Drill Program Over Coming Year

VANCOUVER, May 30, 2024 - [Mawson Gold Ltd.](#) ("Mawson" or the "Company") (TSXV:MAW) (Frankfurt:MXR) (OTC PINK:MWSNF) announces [Southern Cross Gold Ltd.](#) ("Southern Cross Gold" or "SXG") has released results from two diamond drillholes from the Rising Sun prospect at its 100%-owned Sunday Creek Project in Victoria, Australia (Figures 1 to 6). Both holes intersected multiple high-grade structures and were successful in extending mineralization beyond the bounds of the modelled mineralized domains as well as defining continuity in other areas.

Highlights:

- SDDSC115A intercepted eleven high-grade mineralized structures at Rising Sun over a downhole width of 365.7 m
 - 1.5 m @ 12.4 g/t AuEq (10.6 g/t Au, 1.0% Sb) from 532.6 m
 - 3.3 m @ 6.4 g/t AuEq (2.6 g/t Au, 2.0% Sb) from 563.6 m
 - 0.2 m @ 25.9 g/t AuEq (15.4 g/t Au, 5.6% Sb) from 573.7 m
 - 10.4 m @ 3.0 g/t AuEq (1.2 g/t Au, 1.0% Sb) from 580.0 m
 - 3.2 m @ 48.2 g/t AuEq (45.3 g/t Au, 1.5% Sb) from 643.4m (ETW 2.5 m)
 - 0.3 m @ 87.2 g/t AuEq (86.4 g/t Au, 0.4% Sb) from 707.7 m
 - 0.1 m @ 95.3 g/t AuEq (87.1 g/t Au, 4.3% Sb) from 719.5 m
- SDDSC117 was drilled to test strike continuity of two high-grade targets in the footwall of the mineralized host area
 - 8.7 m @ 4.1 g/t AuEq (3.5 g/t Au, 0.3% Sb) from 741.9 m
 - 0.5 m @ 473.1 g/t AuEq (473.0 g/t Au, 0.0% Sb) from 913.6 m (ETW 0.3 m)
- The SXG Board has approved plans to drill 60 km over the next year, with a fifth drill rig to commence within weeks.
- SXG is commencing a specialized navigational ("NAVI") downhole application utilizing down hole motors to understand mineralization better.
- Seven drillholes at Sunday Creek are currently being processed and analyzed, with 4 holes in progress.
- Mawson owns 96,590,910 shares of SXG (51%), valuing its stake at A\$270.5 million (C\$245.3 million) based on:
 - 0.2 m @ 13.5 g/t AuEq (12.8 g/t Au, 0.4% Sb) from 455.9 m

Michael Hudson, Mawson Executive Chairman, states: "Sunday Creek continues to produce impressive news, release after release. Today's announcement discloses another set of extremely strong high-grade drill results from the Rising Sun project area. The holes were successful on multiple fronts as they extend mineralization beyond the bounds of the exploration target area as well as define continuity in other areas.

"Both holes reported here also each delivered a >100 g/t AuEq x m intersection. The project now contains a total of thirty-eight (38) of these significant hits. Importantly, the frequency of these significant hits continues to increase as we drill towards depth and understand the controls on high-grade mineralization better (Figure 7).

"With a 60 km drill program set to more than double the drill metres into the Sunday Creek project over the next year, SXG will expand this globally significant gold discovery via logical step outs along strike to increase volume along with the start of detailed controlled downhole NAVI-drilling program that aims to target continuity of super high-grade areas.

"Additionally, planning for a regional scale IP geophysical survey is underway that will test the 10 km long trend along strike from the core drilled area to further demonstrate the district scale potential of Sunday Creek."

Drill Hole Discussion

Two drillholes (SDDSC115A and 117) are reported from the Rising Sun prospect. Both holes intersected high-grade structures, extending mineralization beyond the bounds of the modelled mineralized domains as well as reinforcing continuity in other areas.

SDDSC115A was designed to test the footwall position of two high-grade vein sets and intercepted 11 mineralized structures, five of which are high-grade. This hole contains six assayed intervals of > 50 g/t Au (up to 202 g/t Au), and five assayed intervals > 5% Sb (up to 26.3% Sb). The hole traversed through the centre of the dyke/breccia host and provided continuity information in the plane of the 11 vein sets. High-grade continuity is well demonstrated in vein set RS55_L (Figure 3) where SDDSC115A drilled 3.2 m (ETW 2.5 m) @ 48.2 g/t AuEq (45.3 g/t Au, 1.5% Sb) from 643.4m (2 m @ 0.5 g/t Au lower cut) including 1.3 m @ 90.2 g/t AuEq from 643.4 m and 0.3 m @ 116.1 g/t AuEq from 646.3 m, which was located 68 m down-plunge of previously reported SDDSC107 (4.7 m @ 76.6 g/t AuEq), suggesting the possibility of a new high-grade mineralized domain.

Highlights from SDDSC115A include:

- 5.5 m @ 1.7 g/t AuEq (0.8 g/t Au, 0.5% Sb) from 512.4 m, including:
 - 0.3 m @ 6.1 g/t AuEq (2.4 g/t Au, 2.0% Sb) from 517.6 m
 - 1.5 m @ 12.4 g/t AuEq (10.6 g/t Au, 1.0% Sb) from 532.6 m including:
 - 1.2 m @ 15.3 g/t AuEq (13.2 g/t Au, 1.1% Sb) from 533.0 m
 - 3.3 m @ 6.4 g/t AuEq (2.6 g/t Au, 2.0% Sb) from 563.6 m including:
 - 0.8 m @ 6.7 g/t AuEq (5.1 g/t Au, 0.9% Sb) from 563.6 m
 - 1.2 m @ 11.3 g/t AuEq (3.1 g/t Au, 4.4% Sb) from 565.7 m
 - 0.2 m @ 25.9 g/t AuEq (15.4 g/t Au, 5.6% Sb) from 573.7 m
 - 10.4 m @ 3.0 g/t AuEq (1.2 g/t Au, 1.0% Sb) from 580.0 m, including:
 - 0.3 m @ 53.8 g/t AuEq (13.9 g/t Au, 21.2% Sb) from 580.2 m
 - 0.2 m @ 7.2 g/t AuEq (3.1 g/t Au, 2.2% Sb) from 587.7 m
 - 3.2 m @ 48.2 g/t AuEq (45.3 g/t Au, 1.5% Sb) from 643.4m (ETW 2.5 m), including:
 - 1.3 m @ 90.2 g/t AuEq (84.9 g/t Au, 2.8% Sb) from 643.4 m
 - 0.3 m @ 116.1 g/t AuEq (109.0 g/t Au, 3.8% Sb) from 646.3 m
 - 0.3 m @ 87.2 g/t AuEq (86.4 g/t Au, 0.4% Sb) from 707.7 m
 - 0.1 m @ 95.3 g/t AuEq (87.1 g/t Au, 4.3% Sb) from 719.5 m
 - 3.4 m @ 2.8 g/t AuEq (2.7 g/t Au, 0.1% Sb) from 746.0 m, including:
 - 0.3 m @ 15.4 g/t AuEq (15.3 g/t Au, 0.1% Sb) from 747.3 m
 - 3.8 m @ 4.0 g/t AuEq (3.2 g/t Au, 0.5% Sb) from 874.3 m, including:
 - 0.4 m @ 12.9 g/t AuEq (12.9 g/t Au, 0.0% Sb) from 875.6 m

SDDSC117 was designed to test the strike continuity of two high-grade targets in the footwall of the mineralized host and intercepted seven mineralized structures. This hole contains 3 assayed intervals of > 20 g/t Au (up to 473.0 g/t Au). SDDSC117 drilled along the footwall contact at a high intersection angle to mineralized vein sets. The high-grade intercept in the RS110 location (0.5 m @ 473.1 g/t AuEq) highlights the potential for high grade internal shoots and linking features within known planes of mineralization. Highlights from SDDSC117 include:

- 13.3 m @ 1.2 g/t AuEq (0.6 g/t Au, 0.3% Sb) from 606.6 m, including:
 - 0.2 m @ 7.9 g/t AuEq (0.9 g/t Au, 3.7% Sb) from 606.6 m
 - 3.5 m @ 1.4 g/t AuEq (0.6 g/t Au, 0.4% Sb) from 644.4 m
 - 0.5 m @ 6.0 g/t AuEq (3.6 g/t Au, 1.3% Sb) from 652.1 m
 - 2.0 m @ 5.6 g/t AuEq (5.6 g/t Au, 0.0% Sb) from 715.4 m
 - 8.7 m @ 4.1 g/t AuEq (3.5 g/t Au, 0.3% Sb) from 741.9 m, including:
 - 1.1 m @ 21.5 g/t AuEq (20.9 g/t Au, 0.3% Sb) from 745.8 m
 - 0.5 m @ 473.1 g/t AuEq (473.0 g/t Au, 0.0% Sb) from 913.6 m
 - 2.5 m @ 2.4 g/t AuEq (2.4 g/t Au, 0.0% Sb) from 934.7 m, including:
 - 0.2 m @ 11.3 g/t AuEq (11.3 g/t Au, 0.0% Sb) from 934.7 m
 - 0.4 m @ 9.1 g/t AuEq (9.1 g/t Au, 0.0% Sb) from 936.8 m

Pending Results and Update

Seven holes (SDDSC114W1, 118, 119, 119W1, 120, 121, 123) are currently being processed and analyzed, with four holes (SDDSC121W1, 122, 124, 125) in progress (Figures 1 and 2).

Increasing Drilling Program

The SXG Board has approved plans to drill 60 km over the next year, with the fifth drill rig to commence within weeks and a sixth rig to arrive during September 2024.

Over the next week SXG will commence a NAVI drilling program. NAVI drilling is a specialized drilling application utilizing down hole motors to make alterations to the direction of a diamond core drill hole. Detailed drilling (at approximately 20 m spacing) will be undertaken around super high-grade areas with the aim to build further confidence of grade continuity between high-grade intersections by drilling branch holes off an already drilled 'parent hole'.

Regional Programs

A large regional induced polarization survey over the 10km district-scale strike is now being planned to test the regional trend beyond the core drill area at Sunday Creek. The survey is planned to start in September 2024.

Further Information

Further discussion and analysis of the Sunday Creek project by Southern Cross Gold is available on the SXG website at www.southerncrossgold.com.au

No upper gold grade cut is applied in the averaging and intervals are reported as drill thickness. During future Mineral Resource studies, the requirement for assay top cutting will be assessed.

Figures 1 to 6 show project location, plan and longitudinal views of drill results reported here and Tables 1 to 3 provide collar and assay data. The true thickness of the mineralised intervals reported individually as estimated true widths ("ETW"), otherwise they are interpreted to be approximately 60-70% of the sampled thickness for other reported holes. Lower grades were cut at 1.0 g/t AuEq lower cutoff over a maximum width of 2 m with higher grades cut at 5.0 g/t Au lower cutoff over a maximum of 1 m width unless specified.

Technical Background and Qualified Person

The Qualified Person, Michael Hudson, Executive Chairman and a director of Mawson Gold, and a Fellow of the Australasian Institute of Mining and Metallurgy, has reviewed, verified and approved the technical contents of this release.

Analytical samples are transported to the Bendigo facility of On Site Laboratory Services ("On Site") which operates under both an ISO 9001 and NATA quality systems. Samples were prepared and analyzed for gold using the fire assay technique (PE01S method; 25 gram charge), followed by measuring the gold in solution with flame AAS equipment. Samples for multi-element analysis (BM011 and over-range methods as required) use aqua regia digestion and ICP-MS analysis. The QA/QC program of Southern Cross Gold consists of the systematic insertion of certified standards of known gold content, blanks within interpreted mineralized rock and quarter core duplicates. In addition, On Site inserts blanks and standards into the analytical process.

MAW considers that both gold and antimony that are included in the gold equivalent calculation ("AuEq") have reasonable potential to be recovered at Sunday Creek, given current geochemical understanding, historic production statistics and geologically analogous mining operations. Historically, ore from Sunday Creek was treated onsite or shipped to the Costerfield mine, located 54 km to the northwest of the project, for processing during WW1. The Costerfield mine corridor, now owned by Mandalay Resources Ltd contains two million ounces of equivalent gold (Mandalay Q3 2021 Results), and in 2020 was the sixth highest-grade global underground mine and a top 5 global producer of antimony.

MAW considers that it is appropriate to adopt the same gold equivalent variables as Mandalay Resources

Ltd in its Mandalay Technical Report, 2024 dated March 28, 2024. The gold equivalence formula used by Mandalay Resources was calculated using Costerfield's 2023 production costs, using a gold price of US\$1,900 per ounce, an antimony price of US\$12,000 per tonne and 2023 total year metal recoveries of 94% for gold and 89% for antimony, and is as follows:

$???? = ?? (?/?) + 1.88 \times ?? (\%)$.

Based on the latest Costerfield calculation and given the similar geological styles and historic toll treatment of Sunday Creek mineralization at Costerfield, SXG considers that a $???? = ?? (?/?) + 1.88 \times ?? (\%)$ is appropriate to use for the initial exploration targeting of gold-antimony mineralization at Sunday Creek

About Mawson Gold Limited (TSXV:MAW, FRANKFURT:MXR, OTCPINK:MWSNF)

Mawson Gold Limited has distinguished itself as a leading Nordic exploration company. Over the last decades, the team behind Mawson has forged a long and successful record of discovering, financing, and advancing mineral projects in the Nordics and Australia. Mawson holds the Skellefteå North gold discovery and a portfolio of historic uranium resources in Sweden. Mawson also holds 51% of [Southern Cross Gold Ltd.](#) (ASX: SXG) which owns or controls three high-grade, historic epizonal goldfields covering 470 km² in Victoria, Australia, including the exciting Sunday Creek Au-Sb discovery.

About Southern Cross Gold Ltd (ASX: SXG)

Southern Cross Gold holds the 100%-owned Sunday Creek project in Victoria and Mt Isa project in Queensland, the Redcastle joint venture in Victoria, Australia, and a strategic 10% holding in ASX-listed [Nagambie Resources Ltd.](#) (ASX: NAG) which grants SXG a Right of First Refusal over a 3,300 square kilometer tenement package held by NAG in Victoria.

On behalf of the Board,

"Michael Hudson"
Michael Hudson, Interim CEO and Executive Chairman

Further Information
www.mawsongold.com
1305 - 1090 West Georgia St., Vancouver, BC, V6E 3V7
Mariana Bermudez (Canada), Corporate Secretary
+1 (604) 685 9316 info@mawsongold.com

Forward-Looking Statement

This news release contains forward-looking statements or forward-looking information within the meaning of applicable securities laws (collectively, "forward-looking statements"). All statements herein, other than statements of historical fact, are forward-looking statements. Although Mawson believes that such statements are reasonable, it can give no assurance that such expectations will prove to be correct. Forward-looking statements are typically identified by words such as: believe, expect, anticipate, intend, estimate, postulate, and similar expressions, or are those, which, by their nature, refer to future events. Mawson cautions investors that any forward-looking statements are not guarantees of future results or performance, and that actual results may differ materially from those in forward-looking statements as a result of various factors, including, Mawson's expectations regarding its ownership in Southern Cross Gold, capital and other costs varying significantly from estimates, changes in world metal markets, changes in equity markets, the potential impact of epidemics, pandemics or other public health crises on the Company's business, risks related to negative publicity with respect to the Company or the mining industry in general; exploration potential being conceptual in nature, planned drill programs and results varying from expectations, delays in obtaining results, equipment failure, unexpected geological conditions, local community relations, dealings with non-governmental organizations, delays in operations due to permit grants, environmental and safety risks, and other risks and uncertainties disclosed under the heading "Risk Factors" in Mawson's most recent Annual Information Form filed on SEDAR+. Any forward-looking statement speaks only as of the date on which it is made and, except as may be required by applicable securities laws, Mawson disclaims any intent or obligation to update any forward-looking statement, whether as a result of new information, future events or results or otherwise.

Neither the TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this news release.

Figure 1: Sunday Creek plan view showing SDDSC115A and 117 reported here (blue highlight), selected prior reported drill holes and pending holes. For location see Figure 5.

Figure 2: Sunday Creek longitudinal section across A-B in the plane of the dyke breccia/altered sediment host (see Figure 1) looking towards the north (striking 236 degrees) showing mineralized veins sets. Showing SDDSC115A and 117 reported here and prior reported drill holes.

Figure 3: Sunday Creek longitudinal section across C-D in the plane of the modelled vein set RS55_L, looking towards the north-east (striking 139.9 degrees). Showing SDDSC115A and 117 (orange trace) reported here and prior reported drill holes.

Figure 4: Sunday Creek longitudinal section across E-F in the plane of the modelled vein set RS110, looking towards the north-east (striking 134.7 degrees). Showing SDDSC115A and 117 (orange trace) reported here and prior reported drill holes.

Figure 5: Sunday Creek regional plan view showing LiDAR, soil sampling, structural framework, regional historic epizonal gold mining areas and broad regional areas (Tonstal, Consols and Leviathan) tested by 12 holes for 2,383 m drill program. The regional drill areas are at Tonstal, Consols and Leviathan located 4,000-7,500 m along strike from the main drill area at Golden Dyke-Apollo.

Figure 6: Location of the Sunday Creek project, along with SXG's other Victoria projects and simplified geology.

Figure 7: Sunday Creek drilling analysis showing metres drilled and planned and the increasing strike rate. Cumulatively, 119 drill holes for 51,189 m have been reported by SXG (and [Mawson Gold Ltd.](#)) from Sunday Creek since late 2020. A total of 64 historic drill holes for 5,599 m were completed from the late 1960s to 2008. The project now contains a total of thirty-eight (38) >100 g/t AuEq x m and forty-seven (47) >50 to 100 g/t AuEq x m drill holes by applying a 2 m @ 1 g/t lower cut.

Table 1: Drill collar summary table for recent drill holes in progress.

Hole_ID	Depth (m)	Prospect	East GDA94_Z55	North GDA94_Z55	Elevation	Azimuth	Plunge
SDDSC111	496.7	Apollo	331291	5867823	316.8	270	-38
SDDSC112	490.9	Apollo	331464	5867865	333	267	-42
SDDSC112W1	766.4	Apollo	331329	5867859	200	267	-42
SDDSC113	905.5	Rising Sun	330511	5867853	296.6	67.5	-63.5
SDDSC114	878.6	Rising Sun	330464	5867914	286.6	82	-58
SDDSC115	17.6	Rising Sun	330464	5867912	286.6	83	-58.5
SDDSC115A	923.6	Rising Sun	330464	5867912	286.7	83	-59
SDDSC116	682.6	Rising Sun	331465	5867865	333.3	272.5	-41.5
SDDSC117	1101	Rising Sun	330510	5867852	296.5	70.5	-64.5
SDDSC118							

Rising Sun

330464

5867912

SDDSC119	854.1	Apollo	331498	5867858	336.7	272.5	-45.2
SDDSC120	1022.5	Rising Sun	331110	5867976	319.5	266.5	-55
SDDSC121	588.7	Rising Sun	330510	5867852	296.6	72	-63
SDDSC122	In progress plan 1200 m	Rising Sun	330338	5867860	267.7	74	-62
SDDSC114W1	625.1	Rising Sun	330464	5867914	286.6	82	-58
SDDSC119W1	643	Apollo	331498	5867858	336.7	272.5	-45.2
SDDSC123	124.3	Apollo	331499	5867859	337	276	-52
SDDSC124	In progress plan 940 m	Apollo	331499	5867859	337	274	-52.2
SDDSC121W1	In progress plan 1000 m	Rising Sun	330510	5867852	296.6	72	-63.8
SDDSC125	551.7 m	Golden Dyke	330462	5867920	285.6	212	-68

Table 2: Tables of mineralized drill hole intersections reported from SDDSC115A and 117 using two cut-off criteria. Lower grades cut at 1.0 g/t lower cutoff over a maximum of 2 m with higher grades cut at 5.0 g/t AuEq cutoff over a maximum of 1 m.

Hole-ID	From (m)	To (m)	Length	Au g/t	Sb %	AuEq g/t
SDDSC115A	452.9	453.1	0.2	0.2	1.1	2.2
SDDSC115A	455.3	456.1	0.7	3.7	0.4	4.4
Including	455.9	456.1	0.2	12.8	0.4	13.5
SDDSC115A	491.1	491.6	0.5	0.7	0.3	1.2
SDDSC115A	500.4	500.8	0.4	1.1	0.0	1.1
SDDSC115A	512.4	517.9	5.5	0.8	0.5	1.7
Including	517.6	517.9	0.3	2.4	2.0	6.1
SDDSC115A	528.9	529.5	0.6	0.5	0.3	1.1
SDDSC115A	532.6	534.2	1.5	10.6	1.0	12.4
Including	533.0	534.2	1.2	13.2	1.1	15.3
SDDSC115A	550.1	550.4	0.3	1.2	0.5	2.2
SDDSC115A	552.5	552.6	0.1	1.1	1.6	4.0
SDDSC115A	563.6	566.9	3.3	2.6	2.0	6.4
Including	563.6	564.4	0.8	5.1	0.9	6.7
Including	565.7	566.9	1.2	3.1	4.4	11.3
SDDSC115A	573.7	573.9	0.2	15.4	5.6	25.9

SDDSC115A	580.0	590.4	10.4	1.2	1.0	3.0
Including	580.2	580.5	0.3	13.9	21.2	53.8
Including	587.7	587.8	0.2	3.1	2.2	7.2
SDDSC115A	593.0	596.0	3.0	0.7	0.3	1.4
SDDSC115A	619.3	619.4	0.1	1.4	0.6	2.4
SDDSC115A	643.4	644.7	1.3	84.9	2.8	90.2
SDDSC115A	646.3	646.6	0.3	109.0	3.8	116.1
SDDSC115A	707.7	708.0	0.3	86.4	0.4	87.2
SDDSC115A	719.5	719.7	0.1	87.1	4.3	95.3
SDDSC115A	729.5	729.8	0.3	2.0	0.0	2.1
SDDSC115A	742.4	742.9	0.5	1.1	0.1	1.2
SDDSC115A	746.0	749.4	3.4	2.7	0.1	2.8
Including	747.3	747.6	0.3	15.3	0.1	15.4
SDDSC115A	753.5	754.5	1.0	3.1	0.0	3.1
SDDSC115A	768.9	769.8	0.9	1.2	0.0	1.2
SDDSC115A	785.6	786.2	0.6	1.4	0.0	1.4
SDDSC115A	791.5	794.1	2.6	1.6	0.0	1.6
SDDSC115A	846.9	847.6	0.7	1.3	0.0	1.3
SDDSC115A	853.9	854.4	0.5	1.6	0.0	1.7
SDDSC115A	865.6	865.9	0.3	1.0	0.0	1.0
SDDSC115A	869.2	869.5	0.3	2.2	0.0	2.2
SDDSC115A	874.3	878.1	3.8	3.2	0.5	4.0
Including	875.6	876.0	0.4	12.9	0.0	12.9
SDDSC115A	881.6	882.8	1.2	0.9	0.1	1.0
SDDSC115A	885.4	885.7	0.2	3.6	0.2	3.9
SDDSC117	313.7	314.0	0.2	1.4	0.0	1.4
SDDSC117	362.0	362.9	0.9	1.8	0.0	1.8
SDDSC117	381.2	383.4	2.2	0.4	0.0	0.4
SDDSC117	511.1	511.5	0.4	0.9	0.3	1.5
SDDSC117						

542.1

542.5

0.4

0.0

SDDSC117	557.7	558.3	0.6	0.9	1.5	3.7
SDDSC117	592.2	592.6	0.4	0.6	0.3	1.1
SDDSC117	606.6	619.9	13.3	0.6	0.3	1.2
Including	606.6	606.8	0.2	0.9	3.7	7.9
SDDSC117	636.0	636.4	0.4	0.6	0.7	2.0
SDDSC117	637.6	638.1	0.5	0.5	0.3	1.1
SDDSC117	644.4	647.9	3.5	0.6	0.4	1.4
SDDSC117	652.1	655.7	3.6	0.8	0.3	1.3
Including	652.1	652.5	0.5	3.6	1.3	6.0
SDDSC117	658.1	658.2	0.1	3.5	0.0	3.6
SDDSC117	684.3	688.3	4.0	0.4	0.3	1.0
SDDSC117	707.5	708.9	1.3	0.3	0.5	1.4
SDDSC117	715.4	717.4	2.0	5.6	0.0	5.6
SDDSC117	721.5	722.8	1.3	0.2	0.4	1.1
SDDSC117	739.1	739.5	0.3	0.9	0.6	2.0
SDDSC117	741.9	750.5	8.7	3.5	0.3	4.1
Including	745.8	746.9	1.1	20.9	0.3	21.5
SDDSC117	752.8	753.8	1.0	1.4	0.3	2.0
SDDSC117	759.7	760.4	0.6	1.0	0.0	1.0
SDDSC117	769.5	769.7	0.2	0.6	0.2	1.0
SDDSC117	789.9	793.0	3.1	0.5	0.5	1.4
SDDSC117	813.6	813.8	0.2	1.5	0.0	1.5
SDDSC117	845.0	849.8	4.8	0.7	0.0	0.7
SDDSC117	853.5	853.7	0.2	0.8	0.5	1.8
SDDSC117	856.1	860.1	3.9	0.7	0.1	0.8
SDDSC117	873.6	874.4	0.7	1.2	0.0	1.2
SDDSC117	888.3	888.8	0.6	3.1	0.0	3.1
SDDSC117	913.6	914.1	0.5	473.0	0.0	473.1
SDDSC117	934.7	937.3	2.5	2.4	0.0	2.4
Including						

934.7

934.9

0.0

Including	936.8	937.3	0.4	9.1	0.0	9.1
SDDSC117	950.4	950.6	0.1	1.4	0.0	1.4
SDDSC117	966.6	967.5	0.9	2.4	0.0	2.4
SDDSC117	1000.5	1000.9	0.4	1.4	0.0	1.4
SDDSC117	1008.0	1008.4	0.4	2.0	0.0	2.0

Table 3: All individual assays reported from SDDSC115A and 117 reported here >0.1g/t AuEq.

Hole-ID	From (m)	To (m)	Length (m)	Au g/t	Sb %	AuEq g/t
SDDSC115A	324.0	325.0	1.0	0.0	0.1	0.1
SDDSC115A	407.9	408.9	1.0	0.1	0.0	0.1
SDDSC115A	452.9	453.1	0.2	0.2	1.1	2.2
SDDSC115A	454.6	455.1	0.5	0.2	0.1	0.3
SDDSC115A	455.1	455.3	0.3	0.3	0.3	0.9
SDDSC115A	455.3	455.7	0.3	0.6	0.6	1.8
SDDSC115A	455.9	456.1	0.2	12.8	0.4	13.5
SDDSC115A	457.0	457.3	0.3	0.1	0.0	0.1
SDDSC115A	457.3	457.5	0.3	0.1	0.1	0.3
SDDSC115A	490.3	490.6	0.3	0.1	0.0	0.1
SDDSC115A	491.1	491.3	0.2	0.7	0.2	1.2
SDDSC115A	491.3	491.6	0.3	0.7	0.3	1.3
SDDSC115A	491.6	491.8	0.2	0.6	0.1	0.7
SDDSC115A	491.8	492.3	0.5	0.3	0.1	0.5
SDDSC115A	492.3	492.6	0.3	0.5	0.1	0.7
SDDSC115A	494.0	495.0	1.0	0.2	0.0	0.2
SDDSC115A	495.5	496.2	0.7	0.2	0.0	0.2
SDDSC115A	496.2	496.9	0.7	0.2	0.2	0.5
SDDSC115A	496.9	497.1	0.2	0.6	0.0	0.6
SDDSC115A	500.4	500.8	0.4	1.1	0.0	1.1
SDDSC115A	501.9	502.8	1.0	0.1	0.0	0.1
SDDSC115A	502.8	503.0	0.2	0.3	0.0	0.3

SDDSC115A 508.0	509.0	1.0	0.3	0.0	0.3
SDDSC115A 511.2	511.6	0.4	0.4	0.0	0.5
SDDSC115A 511.9	512.4	0.5	0.7	0.2	1.0
SDDSC115A 512.4	513.2	0.8	0.9	0.2	1.4
SDDSC115A 513.2	514.2	1.0	1.3	0.3	1.9
SDDSC115A 514.2	515.0	0.8	0.4	0.0	0.5
SDDSC115A 515.0	516.0	1.0	0.8	1.2	3.0
SDDSC115A 516.0	516.6	0.6	0.5	0.4	1.1
SDDSC115A 516.6	517.1	0.5	0.3	0.0	0.4
SDDSC115A 517.1	517.6	0.5	0.1	0.0	0.1
SDDSC115A 517.6	517.9	0.3	2.4	2.0	6.1
SDDSC115A 517.9	519.0	1.1	0.1	0.0	0.2
SDDSC115A 519.0	519.9	0.9	0.3	0.2	0.7
SDDSC115A 522.4	523.5	1.0	0.3	0.1	0.4
SDDSC115A 523.5	523.6	0.1	0.1	0.0	0.1
SDDSC115A 525.1	525.8	0.7	0.0	0.0	0.1
SDDSC115A 528.9	529.5	0.6	0.5	0.3	1.1
SDDSC115A 529.5	530.6	1.1	0.2	0.0	0.2
SDDSC115A 532.3	532.6	0.3	0.1	0.0	0.1
SDDSC115A 532.6	532.8	0.2	2.2	0.5	3.1
SDDSC115A 532.8	533.0	0.2	0.5	0.2	0.9
SDDSC115A 533.0	533.2	0.2	58.6	5.6	69.1
SDDSC115A 533.2	533.4	0.2	0.1	0.0	0.1
SDDSC115A 533.4	533.9	0.6	0.2	0.0	0.2
SDDSC115A 533.9	534.2	0.3	6.8	0.0	6.8
SDDSC115A 534.8	535.2	0.4	0.1	0.0	0.1
SDDSC115A 535.2	536.0	0.8	0.1	0.0	0.1
SDDSC115A 538.5	539.0	0.5	0.2	0.0	0.2
SDDSC115A 542.1	542.3	0.2	0.1	0.0	0.1
SDDSC115A					

545.7

546.8

0.0

SDDSC115A 550.1	550.4	0.4	1.2	0.5	2.2
SDDSC115A 550.4	551.0	0.6	0.1	0.0	0.1
SDDSC115A 552.5	552.6	0.1	1.1	1.6	4.0
SDDSC115A 555.4	556.4	1.0	0.1	0.0	0.1
SDDSC115A 558.4	559.4	1.0	0.4	0.3	0.9
SDDSC115A 559.4	559.6	0.2	0.3	0.2	0.7
SDDSC115A 560.7	561.8	1.2	0.1	0.1	0.3
SDDSC115A 562.8	563.6	0.9	0.1	0.1	0.2
SDDSC115A 563.6	564.4	0.8	5.1	0.9	6.7
SDDSC115A 564.4	564.8	0.4	0.3	0.4	1.1
SDDSC115A 564.8	565.2	0.5	1.3	0.6	2.4
SDDSC115A 565.2	565.7	0.4	0.4	0.3	0.9
SDDSC115A 565.7	565.8	0.2	0.3	26.3	49.7
SDDSC115A 565.8	566.0	0.2	0.1	0.0	0.1
SDDSC115A 566.0	566.5	0.5	1.4	1.1	3.5
SDDSC115A 566.5	566.7	0.3	0.4	0.7	1.7
SDDSC115A 566.7	566.9	0.2	17.6	2.9	23.1
SDDSC115A 566.9	567.1	0.3	0.3	0.1	0.5
SDDSC115A 567.1	568.0	0.9	0.2	0.1	0.4
SDDSC115A 568.0	568.6	0.6	0.1	0.0	0.2
SDDSC115A 573.7	573.9	0.2	15.4	5.6	25.9
SDDSC115A 576.7	576.9	0.2	0.2	0.0	0.3
SDDSC115A 579.8	580.0	0.2	0.1	0.3	0.7
SDDSC115A 580.0	580.2	0.2	1.1	1.4	3.7
SDDSC115A 580.2	580.5	0.3	13.9	21.2	53.8
SDDSC115A 580.5	580.7	0.2	0.3	0.4	0.9
SDDSC115A 580.7	581.6	0.9	0.2	0.3	0.7
SDDSC115A 581.6	582.2	0.6	0.6	0.8	2.1
SDDSC115A 582.2	582.7	0.5	0.1	0.1	0.3
SDDSC115A					

582.7

583.7

SDDSC115A 584.2	584.5	0.3	0.5	0.2	0.8
SDDSC115A 584.5	584.7	0.2	0.3	0.1	0.5
SDDSC115A 584.7	585.3	0.7	0.8	0.4	1.5
SDDSC115A 586.1	587.1	1.1	1.1	0.6	2.3
SDDSC115A 587.1	587.7	0.5	1.6	0.8	3.1
SDDSC115A 587.7	587.8	0.2	3.1	2.2	7.2
SDDSC115A 587.8	588.0	0.2	2.5	0.1	2.7
SDDSC115A 588.0	588.4	0.3	0.1	0.0	0.2
SDDSC115A 589.9	590.4	0.5	1.7	0.3	2.1
SDDSC115A 593.0	593.8	0.8	1.3	0.2	1.6
SDDSC115A 594.5	595.2	0.7	0.7	0.5	1.7
SDDSC115A 595.2	595.4	0.2	1.6	0.4	2.4
SDDSC115A 595.4	596.0	0.6	0.6	0.8	2.1
SDDSC115A 596.0	596.3	0.3	0.4	0.1	0.6
SDDSC115A 596.8	597.1	0.3	0.1	0.0	0.1
SDDSC115A 616.9	617.5	0.6	0.2	0.0	0.2
SDDSC115A 617.7	617.9	0.2	0.1	0.0	0.1
SDDSC115A 619.3	619.4	0.1	1.4	0.6	2.4
SDDSC115A 643.4	643.8	0.4	0.3	0.7	1.6
SDDSC115A 643.8	643.9	0.1	0.6	0.1	0.7
SDDSC115A 643.9	644.5	0.6	104.0	3.7	110.9
SDDSC115A 644.5	644.7	0.3	202.0	5.2	211.8
SDDSC115A 644.7	645.0	0.3	0.2	0.0	0.3
SDDSC115A 645.0	645.2	0.1	0.2	0.2	0.6
SDDSC115A 646.0	646.3	0.3	0.0	0.1	0.2
SDDSC115A 646.3	646.6	0.3	109.0	3.8	116.1
SDDSC115A 646.6	646.9	0.3	0.1	0.0	0.1
SDDSC115A 669.2	670.3	1.1	0.1	0.0	0.1
SDDSC115A 670.3	671.1	0.8	0.2	0.0	0.2
SDDSC115A					

678.3

679.0

0.7

0.0

SDDSC115A 679.0	679.5	0.5	0.2	0.0	0.2
SDDSC115A 697.8	698.0	0.2	0.1	0.2	0.4
SDDSC115A 707.7	708.0	0.3	86.4	0.4	87.2
SDDSC115A 708.0	709.0	1.0	0.2	0.0	0.2
SDDSC115A 719.5	719.7	0.2	87.1	4.3	95.3
SDDSC115A 729.5	729.8	0.4	2.0	0.0	2.1
SDDSC115A 742.1	742.4	0.3	0.1	0.0	0.2
SDDSC115A 742.4	742.9	0.5	1.1	0.1	1.2
SDDSC115A 742.9	743.4	0.6	0.2	0.0	0.2
SDDSC115A 743.4	743.8	0.4	0.2	0.0	0.2
SDDSC115A 743.8	744.3	0.5	0.2	0.0	0.3
SDDSC115A 744.9	745.0	0.1	0.4	0.0	0.5
SDDSC115A 745.0	746.0	1.0	0.1	0.0	0.1
SDDSC115A 746.0	746.3	0.4	2.0	0.1	2.1
SDDSC115A 746.3	746.7	0.4	1.1	0.2	1.4
SDDSC115A 746.7	747.0	0.3	4.0	0.4	4.7
SDDSC115A 747.0	747.3	0.3	3.5	0.2	3.9
SDDSC115A 747.3	747.6	0.3	15.3	0.1	15.4
SDDSC115A 747.6	748.6	1.0	0.8	0.0	0.8
SDDSC115A 748.6	749.0	0.5	0.2	0.0	0.2
SDDSC115A 749.0	749.4	0.4	1.0	0.1	1.2
SDDSC115A 749.4	749.9	0.6	0.6	0.0	0.6
SDDSC115A 753.5	754.5	1.0	3.1	0.0	3.1
SDDSC115A 755.4	755.8	0.5	0.3	0.0	0.4
SDDSC115A 768.9	769.8	0.9	1.2	0.0	1.2
SDDSC115A 781.3	782.0	0.7	1.0	0.0	1.0
SDDSC115A 785.6	786.2	0.6	1.4	0.0	1.4
SDDSC115A 789.0	789.7	0.7	0.3	0.0	0.3
SDDSC115A 791.5	791.9	0.4	1.3	0.1	1.4
SDDSC115A					

791.9

792.5

0.0

SDDSC115A 792.5	792.8	0.3	0.1	0.0	0.1
SDDSC115A 792.8	793.3	0.5	1.2	0.0	1.2
SDDSC115A 793.3	793.7	0.4	3.1	0.0	3.1
SDDSC115A 793.7	794.1	0.5	3.8	0.0	3.9
SDDSC115A 794.1	795.0	0.9	0.2	0.0	0.2
SDDSC115A 795.0	796.0	1.0	0.1	0.0	0.1
SDDSC115A 796.0	797.0	1.0	0.1	0.0	0.1
SDDSC115A 820.2	820.7	0.5	0.1	0.0	0.1
SDDSC115A 820.7	821.0	0.3	0.1	0.0	0.1
SDDSC115A 821.0	822.0	1.0	0.1	0.0	0.1
SDDSC115A 822.0	823.0	1.0	0.1	0.0	0.1
SDDSC115A 831.9	832.7	0.7	0.3	0.0	0.3
SDDSC115A 840.1	840.4	0.2	0.3	0.0	0.3
SDDSC115A 840.4	840.6	0.2	0.2	0.0	0.2
SDDSC115A 845.0	846.0	1.0	0.1	0.0	0.1
SDDSC115A 846.0	846.5	0.5	0.6	0.0	0.6
SDDSC115A 846.5	846.9	0.4	0.4	0.0	0.4
SDDSC115A 846.9	847.6	0.7	1.3	0.0	1.3
SDDSC115A 847.6	848.0	0.5	0.8	0.0	0.8
SDDSC115A 848.0	848.8	0.8	0.5	0.0	0.5
SDDSC115A 848.8	849.4	0.6	0.6	0.0	0.6
SDDSC115A 849.4	850.0	0.6	0.7	0.0	0.7
SDDSC115A 850.0	851.0	1.0	0.5	0.0	0.5
SDDSC115A 851.0	851.2	0.2	0.6	0.0	0.7
SDDSC115A 851.2	852.0	0.8	0.9	0.0	0.9
SDDSC115A 852.0	852.5	0.5	0.5	0.0	0.5
SDDSC115A 852.5	853.6	1.2	0.6	0.0	0.7
SDDSC115A 853.6	853.9	0.3	0.5	0.0	0.6
SDDSC115A 853.9	854.4	0.5	1.6	0.0	1.7
SDDSC115A					

854.4

854.6

0.0

SDDSC115A 855.6	856.6	1.0	0.1	0.1	0.2
SDDSC115A 858.7	859.1	0.4	0.2	0.0	0.2
SDDSC115A 859.1	859.4	0.2	0.3	0.0	0.3
SDDSC115A 859.4	859.8	0.4	0.1	0.0	0.1
SDDSC115A 859.8	860.8	1.1	0.1	0.0	0.2
SDDSC115A 861.4	862.4	1.1	0.5	0.2	0.8
SDDSC115A 862.4	863.5	1.1	0.1	0.0	0.2
SDDSC115A 863.5	864.3	0.8	0.1	0.0	0.2
SDDSC115A 864.3	864.9	0.6	0.2	0.0	0.2
SDDSC115A 864.9	865.6	0.7	0.1	0.0	0.1
SDDSC115A 865.6	865.9	0.3	1.0	0.0	1.0
SDDSC115A 867.9	868.5	0.6	0.1	0.0	0.1
SDDSC115A 868.5	869.2	0.7	0.2	0.0	0.2
SDDSC115A 869.2	869.5	0.3	2.2	0.0	2.2
SDDSC115A 870.3	871.0	0.7	0.7	0.0	0.8
SDDSC115A 871.0	872.0	1.0	0.4	0.0	0.4
SDDSC115A 874.0	874.3	0.3	0.7	0.1	0.9
SDDSC115A 874.3	874.9	0.6	1.1	0.1	1.2
SDDSC115A 874.9	875.6	0.7	1.8	0.0	1.8
SDDSC115A 875.6	876.0	0.4	12.9	0.0	12.9
SDDSC115A 876.0	876.6	0.7	1.7	0.7	2.9
SDDSC115A 876.6	877.1	0.5	2.4	1.2	4.6
SDDSC115A 877.1	878.1	1.0	2.6	0.7	3.9
SDDSC115A 878.1	879.1	1.1	0.4	0.1	0.5
SDDSC115A 879.1	880.2	1.1	0.2	0.0	0.2
SDDSC115A 880.5	881.1	0.7	0.2	0.0	0.2
SDDSC115A 881.1	881.6	0.5	0.2	0.0	0.3
SDDSC115A 881.6	882.8	1.2	0.9	0.1	1.0
SDDSC115A 882.8	883.7	0.9	0.7	0.0	0.7
SDDSC115A					

883.7

884.3

0.0

SDDSC115A 884.3	885.4	1.1	0.5	0.0	0.5
SDDSC115A 885.4	885.7	0.2	3.6	0.2	3.9
SDDSC115A 885.7	886.6	0.9	0.6	0.1	0.7
SDDSC115A 886.6	887.0	0.4	0.1	0.0	0.1
SDDSC115A 893.0	894.0	1.0	0.2	0.0	0.2
SDDSC115A 898.5	898.7	0.2	0.1	0.0	0.1
SDDSC117 273.2	273.7	0.4	0.2	0.0	0.2
SDDSC117 274.1	274.9	0.8	0.1	0.0	0.1
SDDSC117 283.4	284.2	0.8	0.3	0.0	0.3
SDDSC117 297.0	298.0	1.0	0.1	0.0	0.1
SDDSC117 307.7	308.5	0.8	0.1	0.0	0.1
SDDSC117 313.7	314.0	0.2	1.4	0.0	1.4
SDDSC117 319.2	319.9	0.8	0.2	0.0	0.2
SDDSC117 321.0	322.0	1.0	0.2	0.0	0.2
SDDSC117 325.3	326.3	1.0	0.2	0.0	0.2
SDDSC117 331.3	332.3	1.0	0.2	0.0	0.3
SDDSC117 332.3	333.0	0.7	0.6	0.0	0.6
SDDSC117 333.0	334.0	1.0	0.5	0.0	0.5
SDDSC117 362.0	362.6	0.6	2.0	0.0	2.0
SDDSC117 362.6	362.9	0.3	1.6	0.0	1.6
SDDSC117 362.9	364.0	1.1	0.2	0.0	0.2
SDDSC117 381.2	381.5	0.3	1.3	0.0	1.3
SDDSC117 381.5	382.2	0.7	0.1	0.0	0.1
SDDSC117 382.2	383.1	1.0	0.1	0.0	0.1
SDDSC117 383.1	383.4	0.3	1.3	0.0	1.3
SDDSC117 424.0	424.8	0.8	0.2	0.0	0.2
SDDSC117 426.2	427.0	0.9	0.3	0.0	0.3
SDDSC117 427.0	427.4	0.4	0.2	0.0	0.2
SDDSC117 493.3	493.5	0.2	0.5	0.1	0.6
SDDSC117					

498.4

498.9

0.5

0.0

SDDSC117	511.1	511.5	0.4	0.9	0.3	1.5
SDDSC117	511.5	511.7	0.2	0.2	0.0	0.2
SDDSC117	515.4	515.8	0.4	0.1	0.0	0.1
SDDSC117	523.2	524.2	1.0	0.1	0.0	0.1
SDDSC117	524.7	525.0	0.3	0.2	0.3	0.8
SDDSC117	526.1	526.4	0.3	0.2	0.0	0.3
SDDSC117	537.2	538.3	1.1	0.2	0.0	0.2
SDDSC117	542.1	542.5	0.5	1.3	0.0	1.3
SDDSC117	545.4	545.7	0.3	0.4	0.0	0.4
SDDSC117	557.7	557.8	0.1	1.7	0.8	3.2
SDDSC117	557.8	558.3	0.5	0.7	1.7	3.9
SDDSC117	568.0	569.0	1.0	0.1	0.0	0.1
SDDSC117	575.9	576.2	0.3	0.4	0.0	0.4
SDDSC117	580.4	580.9	0.4	0.2	0.0	0.2
SDDSC117	584.0	584.2	0.2	0.3	0.0	0.3
SDDSC117	585.0	586.0	1.0	0.2	0.0	0.2
SDDSC117	590.6	590.8	0.2	0.4	0.0	0.4
SDDSC117	592.0	592.2	0.2	0.2	0.0	0.2
SDDSC117	592.2	592.6	0.4	0.6	0.3	1.1
SDDSC117	606.3	606.6	0.3	0.2	0.0	0.3
SDDSC117	606.6	606.8	0.2	0.9	3.7	7.9
SDDSC117	606.8	607.0	0.2	1.7	0.3	2.2
SDDSC117	607.0	607.2	0.2	0.2	0.1	0.3
SDDSC117	607.2	607.8	0.6	0.2	0.4	0.9
SDDSC117	607.8	608.1	0.4	0.4	0.4	1.2
SDDSC117	608.1	608.5	0.4	0.4	0.9	2.1
SDDSC117	608.5	608.8	0.3	0.5	0.7	1.7
SDDSC117	608.8	609.5	0.7	0.3	0.0	0.4
SDDSC117	609.5	610.1	0.6	0.2	0.0	0.2
SDDSC117						

610.1

610.4

0.0

SDDSC117	610.4	610.7	0.3	1.7	0.1	1.8
SDDSC117	610.7	611.2	0.5	0.9	0.2	1.2
SDDSC117	611.2	611.5	0.3	0.6	0.5	1.5
SDDSC117	611.5	611.7	0.2	1.0	0.6	2.1
SDDSC117	611.7	612.0	0.3	0.3	0.3	0.9
SDDSC117	612.0	612.3	0.3	1.8	0.5	2.7
SDDSC117	612.3	612.8	0.5	0.1	0.0	0.2
SDDSC117	612.8	613.2	0.4	1.7	0.8	3.2
SDDSC117	613.2	613.5	0.3	0.7	0.8	2.3
SDDSC117	613.5	614.1	0.6	1.2	0.1	1.3
SDDSC117	614.1	614.5	0.4	0.5	0.0	0.5
SDDSC117	614.5	615.3	0.8	0.3	0.0	0.3
SDDSC117	615.3	615.6	0.4	0.5	0.0	0.6
SDDSC117	615.6	616.2	0.6	1.7	0.3	2.3
SDDSC117	616.2	616.5	0.3	0.2	0.0	0.2
SDDSC117	616.5	616.9	0.4	0.5	0.4	1.2
SDDSC117	616.9	617.2	0.3	0.2	0.5	1.1
SDDSC117	617.2	617.5	0.4	0.2	0.0	0.3
SDDSC117	617.5	617.8	0.3	0.7	1.0	2.6
SDDSC117	617.8	618.4	0.6	0.5	0.6	1.6
SDDSC117	618.4	619.3	0.9	0.3	0.2	0.6
SDDSC117	619.3	619.9	0.6	1.1	0.2	1.5
SDDSC117	629.6	629.9	0.3	0.5	0.2	0.8
SDDSC117	633.7	634.7	1.0	0.3	0.0	0.4
SDDSC117	634.7	635.5	0.9	0.2	0.0	0.2
SDDSC117	635.5	636.0	0.5	0.2	0.1	0.4
SDDSC117	636.0	636.4	0.4	0.6	0.7	2.0
SDDSC117	636.4	636.7	0.3	0.6	0.2	1.0
SDDSC117	636.7	637.0	0.3	0.1	0.0	0.2
SDDSC117						

637.0

637.3

0.0

SDDSC117	637.6	638.1	0.5	0.5	0.3	1.1
SDDSC117	638.1	638.5	0.4	0.2	0.0	0.2
SDDSC117	638.5	638.8	0.4	0.4	0.3	1.0
SDDSC117	640.1	640.9	0.8	0.1	0.0	0.1
SDDSC117	643.7	644.1	0.5	0.2	0.1	0.3
SDDSC117	644.4	644.7	0.3	0.9	0.3	1.5
SDDSC117	644.7	645.0	0.3	0.1	0.0	0.1
SDDSC117	645.3	645.7	0.3	1.1	0.0	1.2
SDDSC117	645.7	646.3	0.6	0.5	0.6	1.7
SDDSC117	646.3	646.5	0.2	1.4	1.4	4.1
SDDSC117	646.5	647.0	0.5	0.6	1.0	2.5
SDDSC117	647.0	647.4	0.4	0.2	0.0	0.3
SDDSC117	647.4	647.9	0.6	0.9	0.4	1.7
SDDSC117	647.9	648.2	0.3	0.4	0.0	0.5
SDDSC117	648.2	648.5	0.3	0.1	0.0	0.2
SDDSC117	648.5	649.1	0.6	0.1	0.0	0.1
SDDSC117	649.9	650.6	0.7	0.1	0.0	0.1
SDDSC117	652.1	652.5	0.5	3.6	1.3	6.0
SDDSC117	652.5	652.9	0.4	0.4	0.1	0.5
SDDSC117	652.9	653.2	0.3	0.8	0.2	1.3
SDDSC117	653.2	653.9	0.7	0.4	0.0	0.4
SDDSC117	653.9	654.3	0.4	0.4	0.1	0.5
SDDSC117	654.9	655.7	0.8	0.6	0.3	1.1
SDDSC117	657.0	658.1	1.1	0.4	0.1	0.5
SDDSC117	658.1	658.2	0.1	3.5	0.0	3.6
SDDSC117	668.6	669.1	0.5	0.3	0.0	0.4
SDDSC117	671.9	672.2	0.3	0.1	0.0	0.2
SDDSC117	672.2	672.7	0.5	0.2	0.4	1.0
SDDSC117	684.1	684.3	0.3	0.2	0.0	0.2
SDDSC117						

684.3

684.8

SDDSC117	684.8	685.4	0.6	0.1	0.2	0.4
SDDSC117	685.4	685.7	0.3	0.2	0.4	1.0
SDDSC117	685.7	686.1	0.4	0.7	0.2	1.1
SDDSC117	686.1	686.9	0.8	0.4	0.3	1.0
SDDSC117	686.9	687.8	0.9	0.3	0.2	0.6
SDDSC117	687.8	688.3	0.5	0.4	0.4	1.1
SDDSC117	688.3	689.0	0.7	0.2	0.2	0.5
SDDSC117	689.0	689.3	0.4	0.3	0.2	0.6
SDDSC117	690.1	690.7	0.6	0.3	0.0	0.3
SDDSC117	690.7	691.9	1.2	0.1	0.1	0.3
SDDSC117	691.9	692.2	0.3	0.2	0.0	0.2
SDDSC117	692.2	692.9	0.7	0.7	0.0	0.7
SDDSC117	695.0	696.0	1.0	0.2	0.0	0.2
SDDSC117	703.0	704.0	1.0	0.2	0.0	0.2
SDDSC117	704.0	705.0	1.0	0.2	0.0	0.2
SDDSC117	705.0	706.0	1.0	0.2	0.0	0.2
SDDSC117	706.0	707.0	1.0	0.8	0.1	0.9
SDDSC117	707.5	708.0	0.5	0.5	0.8	2.1
SDDSC117	708.0	708.4	0.4	0.1	0.2	0.4
SDDSC117	708.4	708.9	0.5	0.4	0.5	1.3
SDDSC117	708.9	709.9	1.1	0.1	0.1	0.2
SDDSC117	711.0	711.4	0.4	0.1	0.0	0.1
SDDSC117	711.4	711.7	0.4	0.2	0.1	0.4
SDDSC117	711.7	712.6	0.8	0.1	0.1	0.2
SDDSC117	714.2	714.5	0.3	0.2	0.1	0.4
SDDSC117	715.4	716.0	0.6	8.5	0.0	8.5
SDDSC117	717.0	717.4	0.4	15.9	0.2	16.2
SDDSC117	721.1	721.5	0.4	0.2	0.3	0.8
SDDSC117	721.5	721.7	0.3	0.9	1.5	3.7
SDDSC117						

722.5

722.6

0.0

SDDSC117	722.6	722.8	0.2	0.4	1.3	2.8
SDDSC117	722.8	723.0	0.2	0.2	0.4	1.0
SDDSC117	724.0	724.3	0.3	0.1	0.0	0.2
SDDSC117	728.4	728.6	0.2	0.1	0.1	0.2
SDDSC117	730.3	730.5	0.2	0.4	0.3	1.0
SDDSC117	734.0	735.0	1.0	0.4	0.0	0.5
SDDSC117	736.8	737.2	0.4	0.1	0.0	0.1
SDDSC117	738.4	738.5	0.1	0.1	0.1	0.3
SDDSC117	738.5	739.1	0.6	0.1	0.1	0.2
SDDSC117	739.1	739.5	0.3	0.9	0.6	2.0
SDDSC117	739.5	739.9	0.4	0.1	0.0	0.2
SDDSC117	741.7	741.9	0.2	0.2	0.3	0.6
SDDSC117	741.9	742.2	0.3	0.4	0.4	1.0
SDDSC117	742.2	742.7	0.5	0.2	0.0	0.2
SDDSC117	742.7	742.9	0.2	0.5	0.2	0.9
SDDSC117	742.9	743.3	0.5	0.6	0.5	1.6
SDDSC117	743.3	743.5	0.2	0.2	0.5	1.1
SDDSC117	743.5	743.9	0.4	0.3	0.0	0.3
SDDSC117	743.9	744.1	0.2	0.7	0.0	0.7
SDDSC117	744.1	744.5	0.4	0.6	0.2	1.0
SDDSC117	744.5	744.8	0.3	1.2	0.4	2.0
SDDSC117	744.8	745.2	0.4	1.6	0.2	1.9
SDDSC117	745.2	745.6	0.4	1.1	0.0	1.1
SDDSC117	745.6	745.8	0.2	2.3	0.0	2.3
SDDSC117	745.8	746.3	0.5	23.6	0.0	23.6
SDDSC117	746.3	746.6	0.4	29.9	0.1	30.0
SDDSC117	746.6	746.8	0.2	3.8	0.6	5.0
SDDSC117	746.8	746.9	0.1	5.7	1.8	9.0
SDDSC117	746.9	747.5	0.5	0.1	0.0	0.2
SDDSC117						

747.5

747.6

0.1

0.0

SDDSC117	747.6	748.1	0.5	0.5	0.3	1.0
SDDSC117	748.1	748.2	0.1	4.0	0.1	4.2
SDDSC117	748.2	748.6	0.5	0.2	0.0	0.2
SDDSC117	748.6	749.0	0.3	1.2	2.0	5.0
SDDSC117	749.0	749.7	0.7	1.5	0.7	2.8
SDDSC117	749.7	749.8	0.2	1.4	0.5	2.3
SDDSC117	749.8	750.3	0.5	0.5	0.3	1.1
SDDSC117	750.3	750.5	0.2	2.2	0.2	2.5
SDDSC117	750.5	751.4	0.9	0.3	0.1	0.4
SDDSC117	751.4	751.9	0.5	0.3	0.2	0.6
SDDSC117	751.9	752.2	0.3	0.3	0.1	0.4
SDDSC117	752.2	752.8	0.6	0.1	0.0	0.2
SDDSC117	752.8	753.0	0.2	1.7	0.3	2.2
SDDSC117	753.0	753.3	0.3	0.5	0.3	1.1
SDDSC117	753.3	753.8	0.5	1.8	0.3	2.4
SDDSC117	754.6	755.2	0.6	0.3	0.0	0.3
SDDSC117	755.9	756.7	0.8	0.1	0.0	0.2
SDDSC117	756.7	756.9	0.2	0.2	0.0	0.3
SDDSC117	756.9	757.5	0.6	0.1	0.1	0.2
SDDSC117	757.5	757.7	0.2	0.1	0.4	0.8
SDDSC117	757.7	758.1	0.4	0.1	0.0	0.1
SDDSC117	758.9	759.7	0.9	0.4	0.0	0.4
SDDSC117	759.7	760.4	0.6	1.0	0.0	1.0
SDDSC117	760.4	760.5	0.2	0.1	0.0	0.2
SDDSC117	761.8	762.3	0.5	0.4	0.1	0.5
SDDSC117	762.3	763.3	1.0	0.1	0.0	0.1
SDDSC117	763.5	763.6	0.1	0.1	0.0	0.1
SDDSC117	766.7	767.2	0.5	0.1	0.0	0.1
SDDSC117	767.2	767.4	0.2	0.2	0.0	0.2
SDDSC117						

767.9

768.9

0.0

SDDSC117	768.9	769.5	0.6	0.2	0.0	0.3
SDDSC117	769.5	769.7	0.2	0.6	0.2	1.0
SDDSC117	772.0	772.2	0.2	0.1	0.0	0.1
SDDSC117	773.5	773.7	0.2	0.1	0.0	0.1
SDDSC117	776.1	776.4	0.3	0.2	0.0	0.2
SDDSC117	776.8	777.0	0.2	0.1	0.0	0.1
SDDSC117	778.2	778.5	0.3	0.1	0.0	0.1
SDDSC117	780.0	780.1	0.1	0.2	0.0	0.2
SDDSC117	782.2	782.8	0.7	0.3	0.0	0.3
SDDSC117	782.8	783.5	0.7	0.1	0.1	0.1
SDDSC117	789.0	789.1	0.1	0.1	0.0	0.1
SDDSC117	789.1	789.6	0.5	0.4	0.0	0.4
SDDSC117	789.6	789.9	0.3	0.7	0.0	0.7
SDDSC117	789.9	790.0	0.2	1.1	0.1	1.3
SDDSC117	790.0	790.4	0.3	0.5	0.7	1.8
SDDSC117	790.4	790.7	0.3	0.7	0.3	1.3
SDDSC117	790.7	791.0	0.3	0.7	0.5	1.6
SDDSC117	791.0	791.6	0.6	0.2	0.1	0.2
SDDSC117	791.6	792.0	0.4	1.3	1.1	3.4
SDDSC117	792.6	793.0	0.4	0.2	1.4	2.7
SDDSC117	793.0	794.0	1.0	0.4	0.0	0.4
SDDSC117	794.0	794.6	0.6	0.2	0.1	0.3
SDDSC117	794.6	794.8	0.2	0.2	0.0	0.2
SDDSC117	795.2	795.6	0.4	0.5	0.2	0.8
SDDSC117	796.6	797.3	0.7	0.1	0.0	0.1
SDDSC117	798.0	798.5	0.5	0.1	0.0	0.1
SDDSC117	798.5	799.1	0.6	0.2	0.0	0.2
SDDSC117	799.1	800.1	1.0	0.4	0.0	0.4
SDDSC117	800.1	800.5	0.4	0.1	0.0	0.1
SDDSC117						

800.7

800.9

0.0

SDDSC117	800.9	801.5	0.6	0.3	0.0	0.3
SDDSC117	803.1	803.8	0.7	0.3	0.0	0.4
SDDSC117	803.8	804.3	0.5	0.2	0.0	0.2
SDDSC117	804.3	804.9	0.7	0.2	0.0	0.2
SDDSC117	808.2	808.6	0.4	0.1	0.0	0.1
SDDSC117	809.2	809.9	0.7	0.2	0.0	0.2
SDDSC117	809.9	810.4	0.5	0.5	0.0	0.6
SDDSC117	810.4	810.8	0.5	0.3	0.0	0.3
SDDSC117	811.4	811.9	0.5	0.1	0.0	0.1
SDDSC117	813.4	813.6	0.2	0.1	0.0	0.1
SDDSC117	813.6	813.8	0.2	1.5	0.0	1.5
SDDSC117	813.8	814.2	0.4	0.2	0.0	0.2
SDDSC117	814.2	815.2	1.0	0.2	0.0	0.2
SDDSC117	815.9	816.3	0.4	0.2	0.0	0.2
SDDSC117	819.2	819.4	0.2	0.5	0.0	0.5
SDDSC117	825.8	826.0	0.2	0.6	0.0	0.6
SDDSC117	826.0	826.3	0.3	0.5	0.0	0.5
SDDSC117	826.9	827.4	0.5	0.1	0.0	0.1
SDDSC117	827.9	828.6	0.7	0.2	0.0	0.2
SDDSC117	829.1	829.3	0.2	0.2	0.1	0.3
SDDSC117	829.3	829.6	0.3	0.1	0.0	0.1
SDDSC117	829.6	829.8	0.2	0.2	0.0	0.2
SDDSC117	829.8	830.0	0.2	0.2	0.0	0.2
SDDSC117	830.4	830.6	0.3	0.2	0.0	0.2
SDDSC117	832.7	833.3	0.6	0.2	0.0	0.2
SDDSC117	833.7	834.2	0.5	0.3	0.0	0.3
SDDSC117	834.2	834.4	0.2	0.2	0.0	0.2
SDDSC117	837.2	837.3	0.1	0.2	0.0	0.2
SDDSC117	838.8	839.1	0.3	0.7	0.0	0.7
SDDSC117						

839.1

839.4

0.0

SDDSC117	840.6	841.3	0.7	0.4	0.3	1.0
SDDSC117	841.3	842.3	1.1	0.2	0.0	0.2
SDDSC117	842.3	843.1	0.8	0.3	0.0	0.3
SDDSC117	843.1	843.5	0.4	0.2	0.0	0.2
SDDSC117	843.5	843.7	0.2	0.3	0.2	0.6
SDDSC117	844.3	845.0	0.7	0.1	0.0	0.1
SDDSC117	845.0	845.6	0.6	1.0	0.0	1.1
SDDSC117	845.6	846.5	0.9	0.1	0.0	0.1
SDDSC117	846.5	847.1	0.7	0.3	0.0	0.3
SDDSC117	847.1	848.0	0.9	1.5	0.0	1.5
SDDSC117	848.0	848.7	0.7	0.3	0.0	0.3
SDDSC117	848.7	849.1	0.4	0.2	0.0	0.2
SDDSC117	849.1	849.8	0.7	1.1	0.0	1.1
SDDSC117	850.0	850.9	0.8	0.1	0.0	0.1
SDDSC117	850.9	851.6	0.7	0.2	0.0	0.3
SDDSC117	851.6	851.8	0.2	0.2	0.0	0.2
SDDSC117	851.8	852.9	1.1	0.4	0.0	0.4
SDDSC117	852.9	853.5	0.6	0.2	0.0	0.2
SDDSC117	853.5	853.7	0.2	0.8	0.5	1.8
SDDSC117	854.3	855.3	1.0	0.5	0.0	0.6
SDDSC117	855.3	856.1	0.9	0.2	0.0	0.2
SDDSC117	856.1	856.6	0.5	1.4	0.0	1.4
SDDSC117	856.6	857.2	0.6	0.1	0.0	0.1
SDDSC117	857.2	857.8	0.6	1.3	0.0	1.3
SDDSC117	857.8	858.7	0.9	1.0	0.4	1.6
SDDSC117	859.8	860.1	0.2	0.9	0.1	1.0
SDDSC117	860.1	861.1	1.0	0.1	0.0	0.1
SDDSC117	861.1	861.8	0.7	0.4	0.0	0.4
SDDSC117	866.0	866.2	0.3	0.1	0.0	0.1
SDDSC117						

868.8

869.6

0.0

SDDSC117	869.6	869.8	0.2	0.9	0.0	0.9
SDDSC117	872.9	873.6	0.7	0.1	0.0	0.1
SDDSC117	873.6	874.4	0.7	1.2	0.0	1.2
SDDSC117	875.1	875.8	0.7	0.4	0.0	0.4
SDDSC117	876.5	877.3	0.8	0.2	0.0	0.2
SDDSC117	877.3	878.3	1.1	0.1	0.0	0.1
SDDSC117	880.9	881.5	0.6	0.2	0.0	0.2
SDDSC117	887.0	888.0	1.0	0.1	0.0	0.1
SDDSC117	888.0	888.3	0.3	0.6	0.0	0.6
SDDSC117	888.3	888.8	0.6	3.1	0.0	3.1
SDDSC117	889.5	890.0	0.5	0.2	0.0	0.2
SDDSC117	891.3	892.0	0.6	0.1	0.0	0.1
SDDSC117	892.0	892.8	0.9	0.2	0.0	0.2
SDDSC117	892.8	893.1	0.3	0.7	0.0	0.7
SDDSC117	910.2	911.3	1.0	0.1	0.0	0.1
SDDSC117	913.3	913.6	0.2	0.3	0.0	0.3
SDDSC117	913.6	914.1	0.5	473.0	0.0	473.1
SDDSC117	914.1	914.4	0.3	0.4	0.0	0.4
SDDSC117	915.0	916.0	1.0	0.2	0.0	0.2
SDDSC117	930.9	931.1	0.2	0.1	0.0	0.1
SDDSC117	934.7	934.9	0.2	11.3	0.0	11.3
SDDSC117	936.8	937.3	0.4	9.1	0.0	9.1
SDDSC117	937.3	938.0	0.8	0.2	0.0	0.2
SDDSC117	949.3	950.0	0.7	0.9	0.0	0.9
SDDSC117	950.0	950.4	0.4	0.6	0.0	0.6
SDDSC117	950.4	950.6	0.1	1.4	0.0	1.4
SDDSC117	950.6	951.5	1.0	0.3	0.0	0.3
SDDSC117	951.5	952.0	0.5	0.1	0.0	0.1
SDDSC117	958.9	959.4	0.5	0.1	0.0	0.1
SDDSC117						

964.0

964.6

0.0

SDDSC117	964.6	965.5	0.9	0.1	0.0	0.1
SDDSC117	965.5	966.0	0.6	0.4	0.0	0.4
SDDSC117	966.0	966.3	0.3	0.6	0.0	0.6
SDDSC117	966.3	966.6	0.3	0.9	0.0	0.9
SDDSC117	966.6	967.5	0.9	2.4	0.0	2.4
SDDSC117	967.5	967.8	0.3	0.3	0.0	0.3
SDDSC117	967.8	968.8	1.0	0.1	0.0	0.1
SDDSC117	968.8	969.4	0.7	0.2	0.0	0.2
SDDSC117	969.4	969.5	0.1	0.2	0.0	0.2
SDDSC117	971.6	972.0	0.5	0.3	0.0	0.3
SDDSC117	972.0	972.5	0.5	0.2	0.0	0.2
SDDSC117	972.5	972.9	0.4	0.2	0.0	0.2
SDDSC117	972.9	973.6	0.7	0.3	0.0	0.3
SDDSC117	973.6	974.5	0.9	0.4	0.0	0.4
SDDSC117	974.5	975.2	0.7	0.6	0.0	0.6
SDDSC117	984.0	984.5	0.5	0.1	0.0	0.1
SDDSC117	984.5	984.9	0.4	0.2	0.0	0.2
SDDSC117	984.9	985.1	0.3	0.2	0.0	0.2
SDDSC117	985.1	985.4	0.2	0.4	0.0	0.4
SDDSC117	985.4	986.1	0.7	0.2	0.0	0.2
SDDSC117	986.8	987.5	0.8	0.1	0.0	0.1
SDDSC117	989.6	990.3	0.7	0.3	0.0	0.3
SDDSC117	990.3	990.8	0.5	0.4	0.0	0.4
SDDSC117	993.0	993.9	0.9	0.1	0.0	0.1
SDDSC117	993.9	994.4	0.4	0.2	0.0	0.2
SDDSC117	994.4	995.1	0.7	0.1	0.0	0.1
SDDSC117	996.4	996.9	0.5	0.2	0.0	0.2
SDDSC117	1000.1	1000.5	0.5	0.8	0.0	0.8
SDDSC117	1000.5	1000.9	0.4	1.4	0.0	1.4
SDDSC117						

1000.9

1001.6

0.0

SDDSC117	1005.0	1005.6	0.6	0.5	0.0	0.5
SDDSC117	1008.0	1008.2	0.2	2.5	0.0	2.6
SDDSC117	1008.2	1008.4	0.2	1.6	0.0	1.6

SOURCE: [Mawson Gold Ltd.](#)

Dieser Artikel stammt von [Rohstoff-Welt.de](#)

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/472324--Southern-Cross-Gold-Ltd.-Drills-473.0-g-t-Gold-Over-0.5-Metres-at-Sunday-Creek.html>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).