

F3 Uranium Corp. Extends Mineralization with 67.0m of Radioactivity at Tetra Zone

05.08.2025 | [Newsfile](#)

Largest Radioactive Intervals to Date on Project

[F3 Uranium Corp.](#) (TSXV: FUU) (OTCQB: FUUFF) ("F3" or "the Company") is pleased to announce hand-held scintillometer results at Tetra Zone, where the widest intervals of radioactivity to date on the Patterson Lake North Project have been intersected with PLN25-217, which intersected a total of 67.0m composite radioactivity between 299.5m and 414.5m, including 49.0m of continuous radioactivity between 347.5m and 396.5m. Additionally, PLN25-212, approximately 23m up-dip of PLN25-217 and 31m along strike from the discovery hole PLN25-205, intersected the second widest interval to date with 39.5m composite radioactivity between 330.0m and 409.5m, including 27.5m of continuous radioactivity between 360.5m and 396.5m.

2025 Handheld Spectrometer Highlights:

Tetra Zone

PLN25-217 (line 11280S):

- 0.5m interval with radioactivity between 299.5m and 300.0m, and
- 0.5m interval with radioactivity between 315.5m and 316.0m, and
- 7.5m interval with radioactivity between 336.5m and 344.0m, and
- 49.0m interval with radioactivity between 347.5m and 396.5m, and
- 9.0m interval with radioactivity between 399.5m and 408.5m, and
- 0.5m interval with radioactivity between 414.0m and 414.5m.

PLN25-212 (line 11310S):

- 2.5m interval with radioactivity between 330.0m and 332.5m, and
- 0.5m interval with radioactivity between 346.5m and 347.0m, and
- 0.5m interval with radioactivity between 354.0m and 354.5m, and
- 27.5m interval with radioactivity between 360.5m and 388.0m, and
- 6.0m interval with radioactivity between 394.0m and 400.0m, and
- 2.5m interval with radioactivity between 407.0m and 409.5m.

Sam Hartmann, Vice President Exploration, commented:

"The substantial radioactive widths intersected in these drill holes were truly unexpected and highlight the significant potential we see at the Tetra Zone. Despite challenging drilling conditions and the non-traditional style of mineralization, each hole provides valuable insights into deposit model generation and drill plan adaptations. Notably, PLN25-217 confirms a theorized strike direction deviating from the current conductor model, and we will continue to explore this trend. To improve our conductor modeling around the Tetra Zone area, we are planning a ground geophysical program based on a tighter grid to support larger step-outs along the Tetra Zone, which stands to reduce the number of drill holes required for targeting. Additionally, we cored two drill holes at the JR Zone using casings set last winter with PLN25-215 and -216, which tested for crosscutting structures; those assays will be included in our maiden resource estimate, expected in Q4. We are very excited and look forward to further uncovering this unique system hosting the Tetra Zone."

Map 1. Broach Lake - Tetra Zone Scintillometer Results

To view an enhanced version of this graphic, please visit:
https://images.newsfilecorp.com/files/8110/261242_985f0bcef4782a44_002full.jpg

Map 2. Patterson Lake North - JR Zone Scintillometer Results

To view an enhanced version of this graphic, please visit:
https://images.newsfilecorp.com/files/8110/261242_985f0bcef4782a44_003full.jpg

Table 1: Drill Hole Summary and Handheld Spectrometer Results

Collar Information					* Hand-held Spectrometer Results On Mineralized Drillcore (>300 cps / >0.5m minimum)				Athabasca Unconformity (m)		
Hole ID	Section Line	Easting	Northing	Elevation	Az	Dip	From (m)	To (m)	Interval (m)	Max CPS	
PLN25-211	11340S	589409	6397962	584	46	-75	160.50	161.00	0.50	320	160.9
PLN25-212	11310S	589368	6397970	584	40	-72	330.00	330.50	0.50	360	164.2
							330.50	331.00	0.50	440	
							331.00	332.00	1.00	<300	
							332.00	332.50	0.50	310	
							346.50	347.00	0.50	330	
							354.00	354.50	0.50	380	
							360.50	361.00	0.50	410	
							361.00	362.00	1.00	<300	
							362.00	362.50	0.50	310	
							362.50	363.00	0.50	510	
							363.00	363.50	0.50	470	
							363.50	364.00	0.50	510	
							364.00	364.50	0.50	820	
							364.50	365.00	0.50	420	
							365.00	365.50	0.50	310	
							365.50	366.00	0.50	410	
							366.00	366.50	0.50	510	
							366.50	367.00	0.50	910	
							367.00	367.50	0.50	1100	
							367.50	368.00	0.50	1500	
							368.00	368.50	0.50	900	
							368.50	369.00	0.50	990	
							369.00	369.50	0.50	2500	
							369.50	370.00	0.50	3100	
							370.00	370.50	0.50	1400	
							370.50	371.00	0.50	560	
							371.00	371.50	0.50	1000	
							371.50	372.00	0.50	480	
							372.00	372.50	0.50	470	
							372.50	373.00	0.50	420	
							373.00	373.50	0.50	1100	
							373.50	374.00	0.50	680	
							374.00	374.50	0.50	3100	
							374.50	375.00	0.50	1700	
							375.00	375.50	0.50	930	
							375.50	376.00	0.50	370	
							376.00	376.50	0.50	330	
							376.50	377.00	0.50	320	
							377.00	377.50	0.50	390	
							377.50	378.00	0.50	460	

					378.00	378.50	0.50	2000	
					378.50	379.00	0.50	3000	
					379.00	379.50	0.50	3300	
					379.50	380.00	0.50	2500	
					380.00	380.50	0.50	700	
					380.50	381.00	0.50	960	
					381.00	381.50	0.50	3100	
					381.50	382.00	0.50	390	
					382.00	382.50	0.50	700	
					382.50	384.00	1.50	<300	
					384.00	384.50	0.50	310	
					384.50	385.00	0.50	670	
					385.00	385.50	0.50	320	
					385.50	386.00	0.50	670	
					386.00	387.50	1.50	<300	
					387.50	388.00	0.50	560	
					394.00	394.50	0.50	400	
					394.50	395.00	0.50	430	
					395.00	395.50	0.50	660	
					395.50	396.00	0.50	680	
					396.00	396.50	0.50	340	
					396.50	397.00	0.50	<300	
					397.00	397.50	0.50	380	
					397.50	398.00	0.50	340	
					398.00	398.50	0.50	2000	
					398.50	399.00	0.50	3000	
					399.00	399.50	0.50	1000	
					399.50	400.00	0.50	520	
					407.00	407.50	0.50	360	
					407.50	408.00	0.50	320	
					408.00	408.50	0.50	<300	
					408.50	409.00	0.50	360	
					409.00	409.50	0.50	350	
PLN25-213	11325S	589359 6397959 584	45	-73 Pilot hole for wedged hole below				154.3	
PLN25-213W1	11325S	589359 6397959 584	45	-73	278.00	278.50	0.50	750	154.3
					278.50	279.00	0.50	430	
					279.00	279.50	0.50	550	
					326.00	326.50	0.50	530	
					326.50	328.50	2.00	<300	
					328.50	329.00	0.50	300	
					346.00	346.50	0.50	380	
					389.50	390.00	0.50	530	
					392.50	393.00	0.50	300	
PLN25-214	11340S	589404 6397978 584	46	-75	342.00	342.50	0.50	860	155.7
					342.50	343.00	0.50	430	
					382.50	383.00	0.50	360	
PLN25-215	090S	587849 6410603 546	348	-59	249.00	249.50	0.50	370	194.4
					249.50	250.00	0.50	710	
					250.00	250.50	0.50	330	
					252.50	253.00	0.50	350	
					257.50	258.00	0.50	320	
PLN25-216	075S	587778 6410712 546	55	-64	169.50	170.00	0.50	310	194.3
					211.50	212.00	0.50	2900	
					213.00	213.50	0.50	370	
PLN25-217	11280S	589393 6398026 585	34	-85	299.50	300.00	0.50	300	160.1
					315.50	316.00	0.50	460	
					336.50	337.00	0.50	310	
					337.00	338.00	1.00	<300	

338.00	338.50	0.50	480
338.50	340.00	1.50	<300
340.00	340.50	0.50	450
340.50	341.00	0.50	650
341.00	341.50	0.50	320
341.50	343.00	1.50	<300
343.00	343.50	0.50	330
343.50	344.00	0.50	330
347.50	348.00	0.50	570
348.00	348.50	0.50	580
348.50	349.00	0.50	<300
349.00	349.50	0.50	340
349.50	350.00	0.50	<300
350.00	350.50	0.50	340
350.50	351.00	0.50	470
351.00	351.50	0.50	320
351.50	352.00	0.50	<300
352.00	352.50	0.50	700
352.50	354.50	2.00	<300
354.50	355.00	0.50	400
355.00	355.50	0.50	5100
355.50	356.00	0.50	730
356.00	356.50	0.50	910
356.50	357.00	0.50	<300
357.00	357.50	0.50	1000
357.50	358.00	0.50	910
358.00	358.50	0.50	1100
358.50	359.00	0.50	490
359.00	359.50	0.50	360
359.50	360.00	0.50	630
360.00	360.50	0.50	680
360.50	361.00	0.50	350
361.00	361.50	0.50	540
361.50	362.00	0.50	1200
362.00	362.50	0.50	430
362.50	363.00	0.50	680
363.00	363.50	0.50	540
363.50	364.00	0.50	330
364.00	364.50	0.50	810
364.50	365.00	0.50	610
365.00	365.50	0.50	1000
365.50	366.00	0.50	1100
366.00	367.00	1.00	<300
367.00	367.50	0.50	510
367.50	368.00	0.50	420
368.00	368.50	0.50	<300
368.50	369.00	0.50	340
369.00	369.50	0.50	820
369.50	370.00	0.50	1900
370.00	370.50	0.50	3300
370.50	371.00	0.50	2200
371.00	371.50	0.50	3500
371.50	372.00	0.50	8500
372.00	372.50	0.50	4500
372.50	373.00	0.50	1100
373.00	373.50	0.50	630
373.50	374.00	0.50	1200
374.00	374.50	0.50	1300

374.50	375.00	0.50	1300
375.00	375.50	0.50	800
375.50	376.00	0.50	310
376.00	376.50	0.50	300
376.50	377.00	0.50	620
377.00	377.50	0.50	760
377.50	378.00	0.50	1700
378.00	378.50	0.50	2100
378.50	379.00	0.50	2600
379.00	379.50	0.50	2700
379.50	380.00	0.50	1400
380.00	380.50	0.50	720
380.50	381.50	1.00	<300
381.50	382.00	0.50	2600
382.00	382.50	0.50	520
382.50	383.00	0.50	1500
383.00	383.50	0.50	360
383.50	384.00	0.50	680
384.00	384.50	0.50	450
384.50	385.00	0.50	<300
385.00	385.50	0.50	300
385.50	386.00	0.50	520
386.00	387.00	1.00	<300
387.00	387.50	0.50	350
387.50	388.00	0.50	370
388.00	388.50	0.50	440
388.50	389.00	0.50	480
389.00	389.50	0.50	2100
389.50	390.00	0.50	6400
390.00	390.50	0.50	4400
390.50	391.00	0.50	4500
391.00	391.50	0.50	2400
391.50	392.00	0.50	3200
392.00	392.50	0.50	750
392.50	393.00	0.50	<300
393.00	393.50	0.50	420
393.50	394.00	0.50	400
394.00	394.50	0.50	550
394.50	395.00	0.50	350
395.00	395.50	0.50	680
395.50	396.00	0.50	700
396.00	396.50	0.50	360
399.50	400.00	0.50	360
400.00	400.50	0.50	3600
400.50	401.00	0.50	5800
401.00	401.50	0.50	2000
401.50	402.00	0.50	500
402.00	402.50	0.50	<300
402.50	403.00	0.50	420
403.00	403.50	0.50	530
403.50	404.00	0.50	320
404.00	405.00	1.00	<300
405.00	405.50	0.50	300
405.50	406.00	0.50	<300
406.00	406.50	0.50	370
406.50	407.00	0.50	400
407.00	407.50	0.50	310
407.50	408.00	0.50	<300

408.00	408.50	0.50	300
414.00	414.50	0.50	420

Handheld spectrometer composite parameters:

- 1: Minimum Thickness of 0.5m
- 2: CPS Cut-Off of 300 counts per second
- 3: Maximum Internal Dilution of 2.0m

The natural gamma radiation detected in the drill core, as detailed in this news release, was measured in counts per second (cps) using a handheld Radiation Solutions RS-125 spectrometer which has been calibrated by Radiation Solutions Inc. The Company designates readings exceeding 300 cps on the handheld spectrometer (occasionally referred to as a scintillometer in industry parlance; this colloquial usage stems from historical naming conventions and the shared functionality of detecting gamma radiation between a spectrometer and a scintillometer)-as "anomalous", readings above 10,000 cps as "highly radioactive", and readings surpassing 65,535 cps as "off-scale". However, readers are cautioned that spectrometer or scintillometer measurements often do not directly or consistently correlate with the uranium grades of the rock samples and should be regarded solely as a preliminary indicator of the presence of radioactive materials.

Samples from the drill core are split into half sections on site. Where possible, samples are standardized at 0.5m down-hole intervals. One-half of the split sample is sent to SRC Geoanalytical Laboratories (an SCC ISO/IEC 17025: 2005 Accredited Facility) in Saskatoon, SK while the other half remains on site for reference. Analysis includes a 63 element suite including boron by ICP-OES, uranium by ICP-MS and gold analysis by ICP-OES and/or AAS.

All depth measurements reported are down-hole and true thicknesses are yet to be determined.

About the Patterson Lake North Project:

The Company's 42,961-hectare 100% owned Patterson Lake North Project (PLN) is located just within the south-western edge of the Athabasca Basin in proximity to Paladin's Triple R and NexGen Energy's Arrow high-grade uranium deposits, an area poised to become the next major area of development for new uranium operations in northern Saskatchewan. The PLN Project consists of the 4,074-hectare Patterson Lake North Property hosting the JR Zone Uranium discovery approximately 23km northwest of Paladin's Triple R deposit, the 19,864-hectare Minto Property, and the 19,022-hectare Broach Property hosting the Tetra Zone, F3's newest discovery 13km south of the JR Zone. All three properties comprising the PLN Project are accessed by Provincial Highway 955.

Qualified Person:

The technical information in this news release has been prepared in accordance with the Canadian regulatory requirements set out in National Instrument 43-101 and approved on behalf of the company by Raymond Ashley, P.Geo., President & COO of F3 Uranium Corp, a Qualified Person. Mr. Ashley has reviewed and approved the data disclosed.

About F3 Uranium Corp.:

F3 is a uranium exploration company, focusing on the high-grade JR Zone and new Tetra Zone discovery 13km to the south in the PW area on its Patterson Lake North (PLN) Project in the Western Athabasca Basin. F3 currently has 3 properties in the Athabasca Basin: Patterson Lake North, Minto, and Broach. The western side of the Athabasca Basin, Saskatchewan, is home to some of the world's largest high grade uranium deposits including Paladin's Triple R project and NexGen's Arrow project.

Forward Looking Statements

This news release contains certain forward-looking statements within the meaning of applicable securities laws. All statements that are not historical facts, including without limitation, statements regarding future

estimates, plans, programs, forecasts, projections, objectives, assumptions, expectations or beliefs of future performance, including statements regarding the suitability of the Properties for mining exploration, future payments, issuance of shares and work commitment funds, entry into of a definitive option agreement respecting the Properties, are "forward-looking statements." These forward-looking statements reflect the expectations or beliefs of management of the Company based on information currently available to it. Forward-looking statements are subject to a number of risks and uncertainties, including those detailed from time to time in filings made by the Company with securities regulatory authorities, which may cause actual outcomes to differ materially from those discussed in the forward-looking statements. These factors should be considered carefully and readers are cautioned not to place undue reliance on such forward-looking statements. The forward-looking statements and information contained in this news release are made as of the date hereof and the Company undertakes no obligation to update publicly or revise any forward-looking statements or information, whether as a result of new information, future events or otherwise, unless so required by applicable securities laws.

The TSX Venture Exchange and the Canadian Securities Exchange have not reviewed, approved or disapproved the contents of this press release, and do not accept responsibility for the adequacy or accuracy of this release.

ON BEHALF OF THE BOARD

"Dev Randhawa"
Dev Randhawa, CEO

Contact Information

Investor Relations
Telephone: 778-484-8030
Email: ir@f3uranium.com

F3 Uranium Corp.
750-1620 Dickson Avenue
Kelowna, BC V1Y9Y2

Dieser Artikel stammt von Rohstoff-Welt.de

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/700821--F3-Uranium-Corp.-Extends-Mineralization-with-67.0m-of-Radioactivity-at-Tetra-Zone.html>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).