

Spanish Mountain Gold Drilling Intersects 103.35 Metres Grading 0.88 g/t Gold With a Higher-Grade Subset of 56.40 Metres of 1.35 g/t Gold

03.02.2026 | [Business Wire](#)

[Spanish Mountain Gold Ltd.](#) (the "Company" or "Spanish Mountain Gold") (TSX-V: SPA) (FSE: S3Y) (OTCQB: SPAUF) is pleased to report additional assay results from four exploration drill holes within the Orca Fault target trend that were completed as part of its 2025 Fall Diamond Drill program ("2025 Fall Drill Program") for the Spanish Mountain Gold ("SMG") project, which is located in the Cariboo Gold Corridor, British Columbia, Canada.

This press release features multimedia. View the full release here:
<https://www.businesswire.com/news/home/20260203389419/en/>

Figure 1: Drill Long Section Through Orca Fault Area (looking northeast); section line A-A' (see Figure 4)

The company has completed approximately 10,870 metres ("m"), surpassing the original estimate of drilling of 9,000 to 10,000 m of exploration drilling planned under the 2025 Fall Drill Program, now continuing into 2026. Assays and geochemistry are pending receipt from the laboratory and/or reporting from four additional drill holes completed within the Orca Fault target area.

Highlights:

- 25-DH-1324 intersected broad gold mineralization from 69.00 m totaling 108.80 m grading 0.68 g/t gold that include two key intervals:
 - 27.75 m of 0.82 g/t gold from 69.00 m including 18.01 m of 1.10 g/t gold; and
 - 57.80 m of 0.82 g/t gold from 120.00 m including 3.08 m of 1.42 g/t gold and 2.42 m of 4.10 g/t gold.
- 25-DH-1325 intersected two intervals of gold mineralization including:
 - 103.35 m of 0.88 g/t gold from 15.65 m including 56.40 m of 1.35 g/t gold with a high-grade subset of 9.90 m of 3.54 g/t gold; and
 - 15.15 m of 0.65 g/t gold from 255.00 m including 1.85 m of 3.28 g/t gold.
- 25-DH-1326 intersected three intervals of gold mineralization including:
 - 116.50 m of 0.44 g/t gold from 20.00 m including 83.50 m of 0.51 g/t gold with a high-grade subset of 36.70 m of 0.79 g/t gold;
 - 10.00 m of 0.64 g/t gold from 191.00 m including 4.00 m of 1.28 g/t gold; and
 - 34.50 m of 0.82 g/t gold from 288.50 m including 18.00 m of 1.31 g/t gold with a high-grade subset of 3.50 m of 3.21 g/t gold.

Key Findings:

- Current exploration drilling assay results continues to intersect significant higher-grade mineralization over 530 m in strike length in the Orca Fault target area (Figure 4) and the continuity can now be traced across multiple parallel, adjacent drill sections over 80 to 190 m.

Main Deposit - Orca Fault area

Four additional drill holes were collared and successfully completed (see Figure 4) in the Orca Fault target area, 25-DH-1324 (Figure 1 and Table 1), 25-DH-1325 (Figure 3 and Table 2), 25-DH-1326 (Figure 2 and Table 3), and 25-DH-1327 (Figure 1, Figure 3, and Table 4). These drill holes continue to confirm and lend confidence to the extent of the Orca Fault target area over 530 m strike length, northwest to southeast, and

its geological and structural interpretation within the constraining open pit for the MRE (see July 3, 2025 news release).

The continued intersection of wide zones of higher-grade gold mineralization, such as in drill hole 25-DH-1325 (Figure 3 and Table 2) reinforces the opportunities for not only enhancing the Orca Fault target understanding but developing favorable structures outward into other areas of the Main deposit while exploring for higher-grade gold mineralization in the near surface, open pit environment, as defined in the recent MRE (see July 3, 2025 news release). Drill hole 25-DH-1325 intersected 0.88 g/t gold over 103.35 m to a downhole depth of 119.00 m that included three significant subintervals (see Table 2).

The analytical results from the lower portion of drill hole 25-DH-1324 (see Figure 1 and Table 1) were released and significantly lengthen the previously published main composite (see January 16, 2026 news release) to 108.80 m of 0.68 g/t gold. As well, both drillhole 25-DH-1326 (see Figure 2 and Table 3) and 25-DH-1327 (Figure 1, Figure 3 and Table 4) further reinforce the presence of significant, deeper, high-grade mineralization like 25-DH-1321 (see January 26, 2026 news release). These deeper analytical results for gold also correlate to the deeper gold mineralization in drill hole 25-DH-1316 and 25-DH-1318 (see January 6, 2026 news release), adding more information about the prospectivity of the mineral potential of the lithological units at depth.

All results to date continue to reinforce that tighter exploration drill spacing is unlocking additional mineral potential in the Main deposit. These exploration drill holes are presented on drill sections (Figure 1, Figure 2, and Figure 3) that shows the alignment of the higher-grade mineralization to the new Orca Fault target. The location of these drill holes is shown on a plan map at the end of the news release (Figure 4).

Table 1: Assay Results for 25-DH-1324

Drill hole	From (m)	To (m)	Width (m)	Gold (g/t)	Apparent True Thickness
25-DH-1324	16.00	17.15	1.15	13.47	Note 3) and 4)
	50.45	58.30	7.85	0.53	Note 3) and 4)
Including	50.45	51.80	1.35	1.17	Note 3)
	69.00	177.80	108.80	0.68	Note 3) and 5)
Including	71.18	89.19	18.01	1.10	Note 3) and 4)
Including	78.00	89.19	11.19	1.16	Note 3) and 4)
Including	69.91	97.66	27.75	0.82	Note 3)
Including	120.00	177.80	57.80	0.82	Note 3) and 5)
Including	122.00	125.08	3.08	1.42	Note 3) and 4)
	131.00	133.42	2.42	4.10	Note 3)
	240.00	240.50	0.50	1.57	Note 3)

Table 2: Assay Results for 25-DH-1325

Drill hole	From (m)	To (m)	Width (m)	Gold (g/t)	Apparent True Thickness
25-DH-1325	15.65	119.00	103.35	0.88	Note 3)
Including	44.00	100.40	56.40	1.35	Note 3)
Including	90.50	100.40	9.90	3.54	Note 3)

	147.48	148.70	1.22	1.12	Note 3)
	255.00	270.15	15.15	0.65	Note 3)
Including	268.30	270.15	1.85	3.28	Note 3)
	288.80	290.50	1.70	1.86	Note 3)

Table 3: Assay Results for 25-DH-1326

Drill hole	From (m)	To (m)	Width (m)	Gold (g/t)	Apparent True Thickness
25-DH-1326	20.00	136.50	116.50	0.44	Note 3)
Including	20.00	103.50	83.50	0.51	Note 3)
Including	64.00	100.70	36.70	0.79	Note 3)
Including	64.00	80.00	16.00	1.32	Note 3)
	155.55	165.00	9.45	0.48	Note 3)
	191.00	201.00	10.00	0.64	Note 3)
Including	192.50	196.50	4.00	1.28	Note 3)
	288.50	323.00	34.50	0.82	Note 3)
Including	303.50	321.50	18.00	1.31	Note 3)
Including	318.00	321.50	3.50	3.21	Note 3)

Table 4: Assay Results for 25-DH-1327

Drill hole	From (m)	To (m)	Width (m)	Gold (g/t)	Apparent True Thickness
25-DH-1327	17.85	22.85	5.00	0.75	Note 3)
	39.50	98.00	58.50	0.49	Note 3)
Including	39.50	79.00	39.50	0.59	Note 3)
Including	50.70	75.00	24.30	0.75	Note 3)
Including	56.54	66.53	9.99	1.21	Note 3)
	132.50	194.00	61.50	0.47	Note 3)
Including	140.20	172.50	31.30	0.77	Note 3)
Including	162.00	172.50	10.50	1.86	Note 3)
	212.00	248.00	36.00	0.55	Note 3)
Including	231.00	236.00	5.00	2.87	Note 3)
	263.00	264.00	1.00	1.43	Note 3)
	308.10	314.00	5.90	1.22	Note 3)

Notes for Table 1 to Table 4:

- 1) Reported intersections are calculated using a 0.15 g/t Au cut-off grade.
- 2) The complete assay table is available on the Company's website
- 3) True thickness of mineralization is unknown as the project is still at the exploration stage
- 4) Assay composites previously released January 26, 2026 from partial return of drill hole 25-DH-1324 from laboratory
- 5) Re-calculated composite for interval partially released January 26, 2026

The integration of assay results from these four exploration drill holes strengthens the overall continuity for the new Orca Fault target and the association of higher-grade mineralization over a strike length of 530 m, northwest to southeast (see Figure 4). Stronger continuity is also now being developed spanning multiple, parallel, adjacent drill sections ranging in strike length from 80 to 190 m, northeast to southwest, depending on the location along the 530 m strike length (see Figure 2).

Figure 4 illustrates the locations for four drill hole results outlined in this news release and the drill holes currently in the assay lab, or in process of being drilled. Drill collar location coordinates are summarized for the 2025 Fall Drill Program in Table 5 at the end of this news release.

Qualified Person

Julian Manco, M.Sc., P.Geo., Director of Exploration with Spanish Mountain Gold, is the Qualified Person as defined under National Instrument 43-101 who has reviewed the technical information in this news release and has approved the content for dissemination.

Abbreviations: metres = m, grams per tonne = g/t, gold = Au, mineral resource estimate = MRE, Spanish Mountain Gold = SMG

Drill Core Processing, Data Verification and Quality Assurance - Quality Control Program (QAQC)

Once received from the drill and processed, all drill core samples were sawn in half, labeled, and bagged. The remaining half of the drill core was securely stored on-site. Numbered security tags were applied to sample shipments to ensure chain of custody compliance. The Company inserts quality control (QC) samples at regular intervals, including blanks and reference materials, for all sample shipments to monitor laboratory performance.

Standards and blanks account for a minimum of 20% of the samples in addition to the laboratory's internal quality assurance programs. The QAQC program was overseen by the Company's Qualified Person, Julian Manco, P.Geo, Director of Exploration (as described below).

The data verification process involved a multi-step approach to ensure accuracy and integrity. This included a detailed quality control (QC) analysis of the data, which was performed using both internal and external platforms, such as the MxDeposit™ software. These QC checks involved the analysis of certified reference materials (CRMs), blanks, and duplicates to confirm the reliability of the assay results. In addition, a field inspection of the specific drill intervals mentioned in this release has been conducted to directly observe the geological features and verified the nature of the results presented.

Drill core samples were submitted to MSALABS's analytical facility in Prince George, British Columbia, for sample preparation and PhotonAssay™ analysis. The MSALABS facilities are accredited to the International Standards ISO/IEC 17025 and ISO 9001 standard for gold and multi-element assays, with all analytical methods incorporating quality control materials at defined frequencies and established data acceptance criteria. MSALABS Inc. is independent of the Company.

PhotonAssay™

The PhotonAssay™ method utilizes gamma ray analysis for gold detection using the Chrysos PhotonAssay™ instrument (PA1408X). This non-destructive, fully automated technique offers high accuracy for analyzing ores and pulps. Sample preparation begins with drying and crushing up to 1 kg of material to achieve at least 70% passing through a 2-millimetre (mm) sieve. The sample is then riffle split to obtain a suitable aliquot for 2 testing cycles (MSALABS Method CPA-Au1).

The PhotonAssay™ instrument bombards 400- to 600-gram samples contained in sealed containers with gamma rays. These containers remain sealed throughout the process, preserving the sample for potential further testing. The analysis is performed robotically, with results that integrate into existing laboratory management systems. Each sample is accompanied by a reference disc traceable to a Certified Reference Material (CRM). Both the sample and reference disc undergo gamma ray exposure, with signals detected and analyzed to ensure accurate and reliable results. The method offers a gold detection range from 0.015 parts per million (ppm - lower limit) to 10,000 ppm (upper limit). Quality control includes the use of reference materials and blanks, with all results reviewed by a competent person before reporting.

Spanish Mountain Gold implemented two QAQC methodologies to validate the accuracy of PhotonAssay™ results, both demonstrating good comparability: 1) comparative analysis of diverse mineralization styles using Total Au screen metallic methods with both FAS-415 (gravimetric finish) and FAS-211 (AAS finish), and 2) comprehensive testing of both sample aliquots and rejects using FAS-211 (AAS finish). QAQC Testing typically can include the following spot checks: 1) Pulverizing tests to evaluate variability in sample preparation, 2) Cross-analysis at external laboratories using screen metallic method, and 3) Four-cycle radiation testing to identify and calibrate potential variability in gold results with variable radiation intensity.

Multi-Elemental Analysis

For the 2025 drilling campaign Spanish Mountain Gold used IMS-230 method to provide multi-element determination using a four-acid digestion followed by ICP-OES and ICP-MS analysis.

Key Process Steps:

Sample Preparation: Samples are dried and ground to a specific criterion (85% passing 75 microns (?m) for rocks and drill core; 180?m for soils and sediments). A homogeneous 10-gram sample is required. **Digestion:** Samples undergo sequential digestion with nitric, perchloric, hydrofluoric, and hydrochloric acids, followed by dilution with deionized water.

Analysis: The solution is analyzed via ICP-OES and ICP-MS for multi-element quantification.

Quality Control: The process includes reference materials, blanks, and duplicates, with corrections for spectral interferences and thorough review before final reporting.

About Spanish Mountain Gold Ltd.

Spanish Mountain Gold Ltd. is focused on advancing its 100%-owned Spanish Mountain Gold Project (Project) towards its goal to build the next gold mine in the Cariboo Gold Corridor, British Columbia. On August 18, 2025, the Company filed an NI 43-101 Technical Report on SEDAR+ that sets out the Project's de-risked and optimized Preliminary Economic Assessment (PEA), with an updated Mineral Resource Estimate (MRE). We will continue to advance the Project to position the Company to make a construction decision in 2027. We are striving to be a leader in community and Indigenous relations by leveraging technology and innovation to build the 'greenest' gold mine in Canada. The Relentless Pursuit for Better Gold means seeking new ways to achieve optimal financial outcomes that are safer, minimize environmental impact and create meaningful sustainability for communities. Details on the Company are available on www.sedarplus.ca and on the Company's website: www.spanishmountaingold.com.

On Behalf of the Board,

"Peter Mah"

President, Chief Executive Officer and Director
Spanish Mountain Gold Ltd.

Neither the TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release.

FORWARD-LOOKING INFORMATION:

Certain of the statements and information in this press release constitute "forward-looking information". Any statements or information that express or involve discussions with respect to predictions, expectations, beliefs, plans, projections, objectives, assumptions or future events or performance (often, but not always, using words or phrases such as "expects", "anticipates", "believes", "plans", "estimates", "intends", "targets", "goals", "forecasts", "objectives", "potential" or variations thereof or stating that certain actions, events or results "may", "could", "would", "might" or "will" be taken, occur or be achieved, or the negative of any of these terms and similar expressions) are not statements of historical fact and may be considered forward-looking information. The Company's forward-looking information is based on the assumptions, beliefs, expectations and opinions of management as of the date of this press release and include but are not limited to statements with respect to, the potential for adding more higher-grade gold mineralization within the pit or outside the current pit design; and the receipt of further results from additional drilling under the 2025 Fall Drill Program, and the plan to make a construction decision in 2027. Other than as required by applicable securities laws, the Company does not assume any obligation to update forward-looking information if circumstances or management's assumptions, beliefs, expectations or opinions should change, or changes in any other events affecting such statements or information. For the reasons set forth above, investors should not place undue reliance on forward-looking information.

Table 5: Drill Collar Information for Drill Holes

Hole ID	EAST	NORTH	ELEV	AZIMUTH	DIP	DEPTH	COMMENT
25-DH-1334	604254	5827971	1116	120	-60	N/A	In Progress
25-DH-1333	604236	5828012	1104	120	-60	N/A	In Progress
25-DH-1332	604185	5828088	1091	120	-65	372	Successfully completed per design
25-DH-1331A	604595	5827901	1103	120	-60	240	Successfully completed per design
25-DH-1331	604594	5827899	1103	120	-60	55	Ended early due stuck drill rods
25-DH-1330	604332	5827990	1105	120	-60	351	Successfully completed per design
25-DH-1329	604467	5827962	1090	120	-60	255	Successfully completed per design
25-DH-1328	604278	5828018	1105	120	-58	402	Successfully completed per design
25-DH-1327	604411	5828026	1088	120	-60	327	Successfully completed per design
25-DH-1326	604327	5827963	1108	120	-60	351	Successfully completed per design
25-DH-1325	604385	5827966	1103	120	-60	309	Successfully completed per design
25-DH-1324	604343	5828053	1080	120	-60	276	Successfully completed per design
25-DH-1323	604286	5828046	1097	120	-60	338	Successfully completed per design
25-DH-1322	604279	5827995	1106	120	-60	231	Successfully completed per design
25-DH-1321	604350	5828016	1099	120	-60	348	Successfully completed per design
25-DH-1320	604561	5827809	1126	120	-60	57	Ended early due to major fault zone

25-DH-1319	604404 5827992 1095	120	-70 198	Successfully completed per design
25-DH-1318	604445 5828098 1055	120	-60 243	Successfully completed per design
25-DH-1317	604186 5828166 1076	120	-60 282	Successfully completed per design
25-DH-1316	604514 5828073 1050	120	-60 177	Successfully completed per design
25-DH-1315	604231 5828163 1075	120	-60 282	Successfully completed per design
25-DH-1314	604160 5828218 1056	120	-70 270	Successfully completed per design
25-DH-1313	604566 5827908 1100	120	-60 204	Successfully completed per design
25-DH-1312	604538 5827921 1095	120	-60 205	Successfully completed per design
25-DH-1311	604590 5827935 1084	120	-60 330	Successfully completed per design
25-DH-1310	604592 5827961 1091	120	-60 211	Successfully completed per design
25-DH-1309	604592 5827958 1071	120	-60 237	Successfully completed per design
25-DH-1308	603280 5829250 966	120	-60 150	Successfully completed per design
25-DH-1307	604565 5827974 1068	120	-60 200	Successfully completed per design
25-DH-1306	603451 5829400 927	120	-60 123	Successfully completed per design
25-DH-1305	603657 5829226 919	120	-60 126	Successfully completed per design
25-DH-1304	604536 5827986 1067	120	-60 225	Successfully completed per design
25-DH-1303	603960 5828754 943	100	-55 156	Successfully completed per design
25-DH-1302	604194 5828180 1066	120	-63 282	Successfully completed per design
25-DH-1301	603708 5829029 929	150	-55 188	Successfully completed per design
25-DH-1300	604388 5828063 1085	120	-60 274	Successfully completed per design
25-DH-1299	604369 5828043 1093	120	-60 336	Successfully completed per design
25-DH-1298	604402 5828088 1074	120	-59 334	Successfully completed per design
25-DH-1297	604354 5828069 1084	120	-59 342	Successfully completed per design
25-DH-1296	604484 5828054 1061	120	-50 180	Successfully completed per design
25-DH-1295	604484 5828054 1061	120	-60 33	Ended early due to drill trace spacing
25-DH-1294	604345 5828120 1075	120	-58 351	Successfully completed per design
25-DH-1293	604284 5828149 1076	120	-60 453	Successfully completed per design
25-DH-1292	604223 5828189 1068	120	-62 270	Successfully completed per design

View source version on businesswire.com: <https://www.businesswire.com/news/home/20260203389419/en/>

Contact

For more information, contact:

Peter Mah
(604) 601-3651
info@spanishmountaingold.com

Dieser Artikel stammt von [Rohstoff-Welt.de](#)

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/721001--Spanish-Mountain-Gold-Drilling-Intersects-103.35-Metres-Grading-0.88-g-t-Gold-With-a-Higher-Grade-Subset-of-5>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).