

Osisko Development Completes 13,000-Meter Infill Drilling Program at Cariboo Gold Project and Provides Update on Ongoing Lowhee Underground Drilling; Intercepts Include 44.68 g/t Gold Over 1.5 Meters From 27.9 Meters Downhole, Including 133.62 g/t Go

09.06.2026 | [GlobeNewswire](#)

HIGHLIGHTS

- 13,684 m of grid infill drilling completed (2,659 m new results) on 10-m drill spacing in 142 drill holes from August 2025 representing the entirety of the planned Appian infill program
- Highlight intercepts include: 44.68 g/t Au over 1.5 m from 27.9 m downhole (including 133.62 g/t Au over 0.5 m from 28.4 m downhole), and 25.78 g/t Au over 2.5 m from 41.3 m downhole (including 103.47 g/t Au over 0.5 m from 42.8 m downhole, and 12.51 g/t Au over 1.0 m from 41.8 m downhole)
- 2,995 m of additional infill and near mine exploration drilling completed as part of ongoing Lowhee zone underground diamond drilling
- Highlight intercepts include: 31.64 g/t Au over 2.0 m from 50.0 m downhole (including 125.24 g/t over 0.5 m from 50.5 m downhole), and 11.21 g/t Au over 4.9 m from 63.3 m downhole (including 58.19 g/t Au over 0.7 m from 65.0 m downhole, and 17.57 g/t Au over 0.7 m from 63.3 m downhole).
- Results to date continue to contribute to a more detailed understanding of spatial controls and local variability within Lowhee Zone and give positive indications for near mine potential

MONTREAL, June 09, 2026 -- [Osisko Development Corp.](#) (NYSE: ODV, TSXV: ODV) ("Osisko Development" or the "Company") is pleased to announce new infill drilling results from its completed 13,000-meter program on 10 meter drill spacing, as well as new results from additional infill and near mine exploration activities in the Lowhee Zone of the Company's permitted, 100%-owned Cariboo Gold Project (the "Project"), located in central British Columbia ("B.C."), Canada. Three of the six drill hole fans reported herein comprise the final 2,659 meters ("m") of the 13,000 m underground infill program, bringing the final tally of drilling with full results to 13,684 m. The remaining three fans comprise an additional 2,995 m of infill and near mine exploration drilling at the L1290-ORE-000 and L1260-ORE-002 levels. Reconciliation work is underway on an updated localized block model, with final results anticipated in the second quarter of 2026.

Chris Lodder, President, stated, *"The completion of the tighter infill drill spacing gives us a better understanding of vein corridor spatial geometries and local variability specific to this part of the Lowhee deposit, and gives us confidence going forward to help refine infill drill requirements, production designs and sequencing in the Lowhee deposit of the Cariboo Gold Project. The additional infill and near mine exploration intercepts reinforce the importance of continued drilling in underexplored zones."*

DRILL ASSAY HIGHLIGHTS

This news release includes assays from fifty-five (55) underground infill and near mine exploration HQ diamond drill ("DD") holes (63.5-millimeter diameter) totaling 5,654 m with depths ranging from 76.5 to 138 m (see *Table 1 and Figure 2*). Select photon and fire assay highlights include:

- 44.68 grams per tonne ("g/t") gold ("Au") over 1.5 m in BMU-25-176 from 27.9 downhole, including:
 - 133.62 g/t Au over 0.5 m from 28.4 m downhole
- 25.78 g/t Au over 2.5 m in BMU-26-055 from 41.3 m downhole, including:
 - 103.47 g/t Au over 0.5 m from 42.8 downhole, and
 - 12.51 g/t Au over 1.0 m from 41.8 downhole

- 31.64 g/t Au over 2 m in BMU-26-034 from 50.0 m downhole, including:
 - 125.24 g/t Au over 0.5 m from 50.5 m downhole, and
- 11.21 g/t Au over 4.9 m in BMU-26-031 from 63.3 m downhole, including:
 - 58.19 g/t Au over 0.7 m from 65.0 m downhole, and
 - 17.57 g/t Au over 0.7 m from 63.3 m downhole

- 21.84 g/t Au over 2.5 m in BMU-26-008 from 79.7 m downhole, including:
 - 91.3 g/t Au over 0.5 m from 79.7 m downhole, and
 - 6.79 g/t Au over 0.5 m from 81.2 m downhole, and
 - 5.97 g/t Au over 0.5 m from 80.7 m downhole, and
 - 2.66 g/t Au over 0.5 m from 80.2 m downhole, and
 - 2.47 g/t Au over 0.5 m from 81.7 m downhole
- 91.99 g/t Au over 0.5 m in BMU-26-013 from 73.75 m downhole
- 18.59 g/t Au over 2.65 m in BMU-26-006 from 43.35 m downhole, including:
 - 48.93 g/t Au over 1.0 m from 43.85 m downhole
- 4.76 g/t Au over 6.05 m in BMU-26-037 from 85.0 m downhole, including:
 - 44.79 g/t Au over 0.5 m from 88.5 m downhole, and
 - 6.13 g/t Au over 0.5 m from 88.0 m downhole, and
 - 4.02 g/t Au over 0.5 m from 87.0 m downhole
- 3.28 g/t Au over 7.3 m in BMU-25-179 from 81.7 m downhole, including:
 - 12.73 g/t Au over 0.95 m from 84.85 m downhole, and
 - 9.68 g/t Au over 0.9 m from 85.8 m downhole
- 46.37 g/t Au over 0.5 m in BMU-26-022 from 14.0 m downhole

Complete assay highlights, including true width estimates, are presented in Table 1 and drill hole locations and orientations are listed in Table 2. Intervals not recovered were assigned zero grade. Top cuts have not been applied to high grade assays.

DISCUSSION OF RESULTS

- Figures 4-6 (1260 level): Cut-off assay composites completing the planned 13,000 m systematic grid infill program. These last three fans were testing areas peripheral to reserve stopes, and outside the modeled vein corridors. Intercepts received to date suggest possible extensions of vein corridors, with potential for resource conversion and upside mineralization.
- Figures 7-8 (1290 Level): Cut-off assay composites from additional infill drilling at the 1290 levels show a degree of spatial correlation with the modelled reserve stopes with intercepts outside these areas suggesting potential for resource conversion and upside mineralization.
- Figure 9 (1260 Level): Cut-off assay composites from infill and near mine exploration drilling to the southeast at the 1260 level include several new intercepts outside the current vein corridors and resource footprint.
- All intercepts will be incorporated in the planned remodelling and mineral resource calculation process to determine their implications on an updated local block model and any potential adjustments to planned reserve stopes. In certain areas, this may support the addition of new planned reserve stopes, subject to the final estimation process outcome.

Figure 1: Cariboo Gold Project deposit map with Location of Lowhee Zone and Cow Portal underground access.

Figure 2: Location and overview of ongoing Lowhee Zone underground definition infill and near mine exploration diamond drilling

Figure 3: Lowhee Zone select underground drilling highlights (plan view).

Figure 4: L1260-ORE-003 Lowhee Zone grid infill select underground drill assay highlights (this release) with previously released surface and underground diamond drilling results in cross section by fan. Results from immediately adjacent fans within slice omitted for visual clarity (20 m slice looking 048°).

Figure 5: L1260-ORE-003 Lowhee Zone grid infill select underground drill assay highlights (this release) with previously released surface and underground diamond drilling results in cross section by fan. Results from immediately adjacent fans within slice omitted for visual clarity (20 m slice looking 060°).

Figure 6: L1260-ORE-003 Lowhee Zone grid infill select underground drill assay highlights (this release) with previously released surface and underground diamond drilling results in cross section by fan. Results from immediately adjacent fans within slice omitted for visual clarity (20 m slice looking 073°).

Figure 7: L1290-ORE-000 Lowhee Zone infill select underground drill assay highlights (this release) with previously released surface and underground diamond drilling results in cross section by fan. Results from immediately adjacent fans within slice omitted for visual clarity (20 m slice looking 017°).

Figure 8: L1290-ORE-000 Lowhee Zone infill select underground drill assay highlights (this release) with previously released surface and underground diamond drilling results in cross section by fan. Results from immediately adjacent fans within slice omitted for visual clarity (20 m slice looking 025°).

Figure 9: L1260-ORE-002 Lowhee Zone infill and near mine exploration select underground drill assay highlights (this release) with previously released surface and underground diamond drilling results in cross section by fan. Results from immediately adjacent fans within slice omitted for visual clarity (20 m slice looking 051°).

Table 1: Length weighted assay composites and individual samples ≥ 1.8 g/t for Lowhee Zone underground DD.

Drillhole ID	From (m)	Length (m)	Est. True Width (m)
BMU-25-167	14.8	2518	0.89
	Including 14.8	0523	
	49.4	3023	0.77
	Including 49.4	0930	
BMU-25-170	4	0057	0.43
	13.55	44065	0.82
	Including 14.05	0465	
	41.5	0235	0.43
	58.5	2985	0.91
	Including 58.5	6930	
	80.5	3238	1.36
	Including 80.5	3169	
BMU-25-173	17	0753	0.43
BMU-25-176	3	0456	0.28
	27.9	2068	1.36
	Including 28.4	085962	
BMU-25-179	81.7	3938	6.96
	Including 84.85	02073	
	and 85.8	0608	
	90.5	2204	1.87
	Including 90.5	0162	
BMU-26-001	44.7	4662	1.36
	Including 45.2	0538	

BMU-26-002	31.7	248	2.27
	Including 32.2	0231	
	and 33.2	030	
	48.2	20.09	1.90
	Including 48.9	0981	
	65.8	082	2.08
	Including 65.8	062	
	and 66.4	07.38	
	74	787	4.26
	Including 78.2	0684	
BMU-26-003	1.5	2.67	1.45
	Including 2	0.09	
	35.5	292	3.45
	Including 35.5	0260	
	73.35	2505	2.46
	Including 73.85	040	
	and 74.6	08.36	
BMU-26-004	58.5	091	0.41
	66.5	075	0.43
BMU-26-005	1	2.26	1.59
	Including 1	0210	
	and 2.75	0.95	
	14	2628	1.41
	Including 14	16.40	
	17.5	12.24	0.77
	Including 18	0547	
	30.9	3119	0.82
	Including 30.9	0442	
	37	284	0.71
	Including 37.5	082	
	40	4.153	0.86
	Including 40	0091	
	58	0410	4.12
	Including 62	0288	
	and 62.5	0099	
	76.25	288	1.18
	Including 76.75	0220	
	and 78.3	088	
	80.05	3.198	0.60
	Including 80.05	0005	
	and 80.55	0.158	
	90	2.118	0.64
	Including 90	002	
	104.5	007	0.32
	117.05	0.10605	1.15
	Including 117.55	0.13705	
	and 118.05	07235	
	128	126	0.71
	137.4	032	0.42
BMU-26-006	2.95	3253	0.71
	Including 3.45	0491	
	33.9	25.9	1.64

	Including 34.9	0582	
	and 35.4	059	
	43.35	2659	1.70
	Including 43.85	48.03	
	55.85	06835	0.32
BMU-26-007	No Significant Assays		
BMU-26-008	5.5	0.34	0.41
	11.9	0290	0.41
	23	032	0.38
	25	059	0.50
	29	054	0.50
	79.7	22584	1.92
	Including 79.7	00520	
	and 80.2	006	
	and 80.7	0192	
	and 81.2	0139	
	and 81.7	022	
	98.1	093	0.64
	Including 98.1	080	
	and 98.6	097	
BMU-26-009	No Significant Assays		
BMU-26-010	47.5	5205	4.39
	Including 47.5	080	
	and 48.5	092	
	and 51.45	01395	
	63.45	058	2.08
	Including 63.45	045	
	69	058	0.43
	111.95	210	2.87
	Including 111.95	01305	
BMU-26-011	31.9	0265	0.41
	35	261	0.91
	Including 35	055	
	37.5	083	0.50
	49	521	2.82
	Including 49	054	
	and 51	04500	
	55.2	057	0.45
	66.45	099	2.02
	Including 66.45	06500	
	and 66.95	0745	
	73	039	0.45
	79	098	0.41
BMU-26-012	15.5	066	0.38
BMU-26-013	46	065	0.38
	62	069	4.03
	Including 63.25	03535	
	and 63.75	04025	
	and 64.25	07578	
	68	215	3.29
	Including 70.5	02514	
	73.75	0429	0.45

BMU-26-014	2	0.69	0.41
	4.5	0.82	0.49
	35	3.22	3.22
	Including 35	0.52	
	and 37	0.74	
	51	5.20	1.00
	Including 51	0.12	
	and 51.4	0.12	
	and 51.8	0.20	
	59.8	0.02	0.41
	61.8	0.59	0.45
	65.1	6.23	1.09
	Including 65.8	0.57	
	76.7	7.82	1.30
	Including 76.7	0.72	
86.5	0.79	0.47	
92	9.54	2.66	
Including 93.6	0.42		
BMU-26-015	4	0.57	0.49
	13.75	1.47	0.82
	Including 13.75	0.42	
BMU-26-016	82	0.29	0.43
	39	0.53	0.47
	44.6	3.70	2.86
	Including 45.1	0.56	
	65.5	5.13	5.65
	Including 66.5	0.73	
	and 67	0.74	
	and 69.1	0.50	
	and 70.2	0.58	
	86	0.68	0.43
88.8	0.92	0.43	
92.9	0.32	0.47	
BMU-26-017	4.7	0.08	0.58
	40.1	0.06	0.32
	51	0.12	0.47
	67.5	0.81	0.50
	88	0.40	4.24
Including 89.15	0.60		
BMU-26-018	27.5	3.29	4.40
	Including 29.6	0.73	
	34.9	0.58	0.47
	49.1	5.06	1.36
	Including 49.6	0.02	
	74.25	7.57	1.30
Including 75.25	0.52		
BMU-26-019	14.2	0.53	0.48
	21.2	0.56	0.47
	42.5	3.72	4.17
	Including 43	0.51	
	and 44	0.44	
and 44.5	0.50		

	and	45	055	
	and	46.6	072	
		70.4	099	0.47
BMU-26-020		45.5	087	0.56
BMU-26-021		1.95	084	0.50
		27.7	082	0.50
		32.45	0505	0.43
		38	084	0.50
		70.2	033	0.48
BMU-26-022		14	0537	0.45
		62.1	0317	0.92
	Including	62.6	039	
BMU-26-023		47.7	082	0.47
		51.7	052	0.47
BMU-26-024		10.5	3416	3.86
	Including	11.55	0860	
		96	272	1.60
	Including	97.1	072	
		99.5	002	0.47
BMU-26-025		14.5	0527	0.49
		43	225	4.33
	Including	43	052	
	and	45.5	060	
	and	46	088	
		49.75	2195	1.93
	Including	49.75	0325	
	and	51.25	0195	
		63	070	3.99
	Including	63.5	049	
	and	66.5	073	
BMU-26-026		1.2	2.20	1.00
	Including	1.2	0.37	
		40	008	0.38
		54.05	453	1.55
	Including	54.55	0508	
		60	030	3.66
	Including	62.4	038	
	and	63.4	039	
BMU-26-027		2.45	0050	0.68
		97.5	087	0.56
		104.9	00574	0.45
		109.6	21248	1.91
	Including	109.6	0121	
	and	110.8	01373	
BMU-26-028		3.2	2.40	1.77
	Including	4.9	0077	
		15.2	0538	0.47
		22	2486	1.73
	Including	23	0550	
	and	23.5	0498	
		45.5	066	0.43
		59	090	0.43

	64	064	1.64
	Including 64	0455	
	and 65	056	
	69.5	063	0.41
BMU-26-029	1.6	3.83	1.23
	Including 2.1	0.60	
	33.4	039	0.35
	39.6	4.173	1.39
	Including 39.6	009	
	and 40.8	01502	
BMU-26-030	54.85	0565	0.35
BMU-26-031	4.2	0.65	0.80
	Including 5.5	04539	
	18.85	2005	1.15
	Including 19.35	0985	
	23.1	268	2.86
	Including 23.1	030	
	and 24.5	0561	
	55	059	0.43
	63.3	0821	4.09
	Including 63.3	0757	
	and 65	06779	
	70.2	237	2.05
	Including 71.2	0133	
	and 72.2	0233	
	79.1	829	2.40
	Including 79.1	090	
	and 80.6	04689	
BMU-26-032	36.5	373	0.94
	Including 36.5	0705	
BMU-26-033	40.5	0139	0.43
BMU-26-034	50	32.64	1.73
	Including 50.5	025.24	
BMU-26-035	10.5	0101	0.48
	48.5	253	0.94
	Including 48.5	054	
BMU-26-036	5.5	0.61	0.45
	45	268	1.30
	Including 45.5	063	
	60.5	024	1.50
	Including 61	0130	
	63.5	642	0.95
	Including 63.5	046	
	87.5	935	5.08
	Including 87.5	080	
	and 89.15	0909	
	and 92.35	0309	
	102.5	2037	1.41
	Including 102.5	0039	
	105	2055	1.41
	Including 105	0065	
	and 105.5	0066	

BMU-26-037	64.5	65 6	0.45
	66.5	65 57	0.47
	85	8 1065	5.69
	Including 87	87 2	
	and 88	88 5	
	and 88.5	88 79	
	92	92 9	2.12
	Including 93.5	93 55	
	98.55	98 8	0.77
	BMU-26-038	32.5	32 6
Including 32.5		32 3	
46.4		46 0	0.47
54.8		54 83	0.97
Including 54.8		54 57	
and 55.3		55 0	
85.9		85 8	3.87
BMU-26-039	Including 87.4	87 97	
	13	13 2	1.49
	Including 14	14 3	
	39.65	39 8	2.31
	Including 39.65	39 76	
	and 40.15	40 65	
	43	43 4	1.97
	Including 44.5	44 7	
	64	64 3	0.82
	Including 64.5	64 7	
BMU-26-040	72.55	72 85	0.74
	Including 73.05	73 65	
	78.9	78 3	0.38
	86.9	86 3	0.38
	0	0 20	0.47
	13.8	13 3	0.47
	40	40 5	6.14
	Including 40.5	40 30	
	and 41	41 33	
	and 41.5	41 82	
and 45.5	45 0		
BMU-26-041	65.4	65 0	0.45
	No Significant Assays		
BMU-26-042	3.8	3 88	1.00
	Including 4.5	4 89	
	16.75	16 25	0.38
	69.3	69 2	1.56
	Including 70.7	70 52	
	74	74 0	2.19
	Including 74.5	74 7	
and 75.6	75 3		
BMU-26-043	No Significant Assays		
BMU-26-044	56	56 7	1.53
	Including 56.5	56 36	
BMU-26-046	20	20 8	0.38
	44.75	44 25	0.47

	46.25	4765	1.27
	Including 46.25	0675	
	57.5	0880	0.38
BMU-26-049	43.95	806	1.63
	Including 44.45	0506	
	and 44.95	0505	
BMU-26-052	42.4	4036	1.59
	Including 42.9	0758	
	and 43.65	0495	
BMU-26-055	2.5	029	0.35
	36	379	1.15
	Including 36.5	676	
	41.3	2588	2.38
	Including 41.8	42.81	
	and 42.8	05347	
	55.25	675	2.11
	Including 55.25	0585	
	and 56.75	0751	
	59.6	0295	2.77
	Including 61.1	0508	
BMU-26-058	59.5	0080	1.18
	Including 59.5	007	
	and 60	0080	
BMU-26-061	No Significant Assays		

Table 2: Underground DD collar locations, drillhole orientations, and max depths. Negative dips point down.

Hole ID	Mine Location	Easting (UTM z12N)	Northing (UTM z 12N)	Elevation (m)	Dip	Azimuth	Depth (m)
BMU-25-167	L1260-ORE-003-DBY-013	596440.667	5882727.084	1264.922	35	137	117
BMU-25-170	L1260-ORE-003-DBY-013	596440.802	5882727.027	1264.291	25	137	105
BMU-25-173	L1260-ORE-003-DBY-013	596440.66	5882727.032	1263.529	15	137	99
BMU-25-176	L1260-ORE-003-DBY-013	596440.812	5882726.873	1262.956	5	137	99
BMU-25-179	L1260-ORE-003-DBY-013	596440.699	5882727.017	1262.574	-5	137	102
BMU-26-001	L1260-ORE-003-DBY-013	596440.714	5882727.075	1262.279	-15	137	84
BMU-26-002	L1260-ORE-003-DBY-013	596440.754	5882727.063	1261.746	-25	137	87
BMU-26-003	L1260-ORE-003-DBY-013	596440.777	5882727.016	1261.3	-35	137	96
BMU-26-004	L1290-ORE-000	596488.88	5882889.094	1291.795	33	288	125
BMU-26-005	L1260-ORE-002	596554.802	5882795.203	1261.637	45	137	138
BMU-26-006	L1260-ORE-003-DBY-013	596440.392	5882727.397	1260.969	-45	137	111
BMU-26-007	L1290-ORE-000	596488.713	5882889.197	1291.557	28	288	120
BMU-26-008	L1260-ORE-002	596554.834	5882795.201	1260.942	35	137	117
BMU-26-009	L1260-ORE-003-DBY-013	596440.323	5882726.661	1264.825	35	148	123
BMU-26-010	L1290-ORE-000	596488.786	5882889.128	1291.264	22	288	117
BMU-26-011	L1260-ORE-002	596554.76	5882795.183	1260.473	25	137	105
BMU-26-012	L1260-ORE-003-DBY-013	596440.504	5882726.526	1264.199	25	148	111
BMU-26-013	L1290-ORE-000	596488.721	5882889.189	1290.955	16	288	105
BMU-26-014	L1260-ORE-002	596554.95	5882795.104	1259.779	15	137	102
BMU-26-015	L1260-ORE-003-DBY-013	596440.553	5882726.416	1263.795	15	148	102
BMU-26-016	L1290-ORE-000	596488.578	5882889.235	1290.552	10	288	105.4
BMU-26-017	L1260-ORE-002	596555.101	5882795	1258.765	-5	137	96
BMU-26-018	L1260-ORE-003-DBY-013	596440.564	5882726.392	1263.097	5	148	87

BMU-26-019 L1290-ORE-000	596488.462	5882889.317	1290.282	3	288	90
BMU-26-020 L1260-ORE-003-DBY-013	596440.478	5882726.537	1262.567	-5	148	87.2
BMU-26-021 L1260-ORE-002	596555.086	5882795.087	1258.291	-15	137	99.3
BMU-26-022 L1290-ORE-000	596488.243	5882889.355	1289.961	-4	288	84
BMU-26-023 L1260-ORE-003-DBY-013	596440.504	5882726.495	1262.255	-15	148	90.2
BMU-26-024 L1260-ORE-002	596555.074	5882795.187	1257.876	-25	137	105.3
BMU-26-025 L1290-ORE-000	596488.511	5882889.253	1289.607	-16	288	76.5
BMU-26-026 L1260-ORE-003-DBY-013	596440.349	5882726.668	1261.96	-25	148	96
BMU-26-027 L1260-ORE-002	596555.006	5882795.284	1257.568	-35	137	117.3
BMU-26-028 L1290-ORE-000	596488.36	5882889.291	1289.247	-27	288	79.5
BMU-26-029 L1260-ORE-003-DBY-013	596440.35	5882726.533	1261.577	-35	148	104.9
BMU-26-030 L1260-ORE-002	596554.952	5882795.513	1257.503	-45	137	135.1
BMU-26-031 L1290-ORE-000	596488.513	5882889.25	1288.896	-38	288	82.5
BMU-26-032 L1260-ORE-003-DBY-013	596440.443	5882726.579	1261.192	-45	148	120.05
BMU-26-033 L1290-ORE-000	596489.052	5882889.305	1291.855	33	295	121.5
BMU-26-034 L1290-ORE-000	596489.035	5882889.3	1291.52	28	295	118.5
BMU-26-035 L1290-ORE-000	596488.946	5882889.367	1291.212	22	295	117
BMU-26-036 L1290-ORE-000	596488.915	5882889.401	1290.933	16	295	108
BMU-26-037 L1290-ORE-000	596488.765	5882889.295	1290.633	10	295	103.9
BMU-26-038 L1290-ORE-000	596488.897	5882889.482	1290.252	3	295	91.9
BMU-26-039 L1290-ORE-000	596488.63	5882889.607	1289.969	-4	295	87.4
BMU-26-040 L1290-ORE-000	596488.793	5882889.502	1289.5	-16	295	78.4
BMU-26-041 L1290-ORE-000	596488.716	5882889.586	1289.204	-27	295	81.2
BMU-26-042 L1290-ORE-000	596488.723	5882889.578	1288.881	-38	295	87.2
BMU-26-043 L1260-ORE-003-DBY-013	596439.884	5882725.792	1264.875	35	162	119.9
BMU-26-044 L1260-ORE-003-DBY-013	596439.995	5882725.451	1264.639	25	162	108
BMU-26-046 L1260-ORE-003-DBY-013	596440.054	5882725.434	1263.698	15	162	99.3
BMU-26-049 L1260-ORE-003-DBY-013	596439.882	5882725.752	1263.024	5	162	96
BMU-26-052 L1260-ORE-003-DBY-013	596439.997	5882725.694	1262.501	-5	162	96.3
BMU-26-055 L1260-ORE-003-DBY-013	596440.021	5882725.703	1262.192	-15	162	99.1
BMU-26-058 L1260-ORE-003-DBY-013	596439.965	5882725.858	1261.959	-25	162	105.3
BMU-26-061 L1260-ORE-003-DBY-013	596439.991	5882725.801	1261.52	-35	162	114.2

ABOUT LOWHEE ZONE

Geological mapping and geochemical sampling were carried out on Barkerville Mountain from 2017-2018, with the Lowhee Zone identified as a high-priority drill target. From 2019 to 2022, a total of 167 surface drill holes were completed, totaling 54,494.5 m.

Lowhee zone access is through Cow portal on the northwestern flank of Barkerville Mountain (Figure 1 and Figure 2) Cow portal construction was completed in Q4 2024 and development of the underground ramp into the Lowhee zone commenced in Q1 2025. The probable mineral reserves estimate for the Lowhee Zone includes 104,491 ounces of contained Au (923,162 tonnes grading 3.52 g/t Au) and represents approximately 5% of the total contained gold in the estimated probable mineral reserves for the Cariboo Gold Project.

ABOUT CARIBOO GOLD PROJECT

The Cariboo Gold Project is a permitted, 100%-owned feasibility-stage project located in the historic Wells-Barkerville mining camp of central British Columbia, Canada. Spanning approximately 186,740 hectares, the Company's land package includes 443 mineral titles and covers a ~83-kilometre strike of highly prospective exploration targets extending northwest to southeast. In late 2024, the Project was granted the *Mines Act* and *Environmental Management Act* (British Columbia) permits, marking the successful

completion of the permitting process for key approvals, solidifying the Project's shovel-ready status.

The Cariboo Gold Project hosts probable mineral reserves of 2.071 million ounces of contained Au (17,815 kt grading 3.62 g/t Au); measured mineral resources of 8,000 ounces of contained Au (47 kt grading 5.06 g/t Au); indicated mineral resources of 1.604 million ounces of contained Au (17,332 kt grading 2.88 g/t Au); and inferred mineral resources of 1.864 million ounces of contained Au (18,774 kt grading 3.09 g/t Au). Mineral resources are reported exclusive of mineral reserves.

Technical Reports

Scientific and technical information relating to the Cariboo Gold Project and the 2025 feasibility study on the Cariboo Gold Project is supported by the technical report, titled "*NI 43-101 Technical Report, Feasibility Study for the Cariboo Gold Project, District of Wells, British Columbia, Canada*" and dated June 11, 2025 (with an effective date of April 25, 2025) (the "Cariboo Technical Report").

For readers to fully understand the information in the Cariboo Technical Report, reference should be made to the full text of the Cariboo Technical Report in its entirety, including all assumptions, parameters, qualifications, limitations and methods therein. The Cariboo Technical Report is intended to be read as a whole, and sections should not be read or relied upon out of context. The Cariboo Technical Report was prepared in accordance with National Instrument 43-101 - *Standards of Disclosure for Mineral Projects* ("NI 43-101") and is available electronically on SEDAR+ (www.sedarplus.ca) and on EDGAR (www.sec.gov) under Osisko Development's issuer profile and on the Company's website at www.osiskodev.com.

Qualified Persons

The scientific and technical information contained in this news release has been reviewed, verified and approved by Scott Smith, P. Geo., Vice President, Exploration of Osisko Development, a "qualified person" within the meaning of NI 43-101. Verification includes core photo and three-dimensional review of logged drillhole data and assays consistent with the Company's standard operating procedures.

Quality Assurance (QA) - Quality Control (QC)

Whole core sampling was used for all definition infill HQ core completed in the logging facilities following daily QAQC checks for logging and sampling errors. Quality control (QC) samples are inserted at regular intervals in the sample stream, including blanks and reference materials with all sample shipments to monitor laboratory performance. Samples are bagged, labeled, sealed with numbered security tags.

Samples are taken by expeditor from the logging facilities direct to MSALABS's analytical facility in Prince George, B.C., Canada, for preparation and analysis. The MSALABS facility is accredited to the ISO/IEC 17025 standard for gold assays and all analytical methods include quality control materials at set frequencies with established data acceptance criteria. The entire sample is dried, crushed, and split into sealed containers. Analysis for gold is by gamma ray analysis using the Chryso PhotonAssay (PA1408X). Samples are bombarded with gamma rays and the resulting signal is sent to the detectors.

Near mine exploration infill HQ drill core samples are cut on site and submitted to ALS Geochemistry's analytical facility in North Vancouver, British Columbia for preparation and analysis. The ALS facility is accredited to the ISO/IEC 17025 standard for gold assays and all analytical methods include quality control materials at set frequencies with established data acceptance criteria. The entire sample is crushed, and 250 grams is pulverized. Analysis for gold is by 50 gram fire assay fusion with atomic absorption (AAS) finish with a lower limit of 0.01 ppm and upper limit of 100 ppm. Samples with gold assays greater than 100 ppm are re-analyzed using a 1,000-gram screen metallic fire assay. A selected number of samples are also analyzed using a 48 multi-elemental geochemical package by a 4-acid digestion, followed by Inductively Coupled Plasma Atomic Emission Spectroscopy (ICP-AES) and Inductively Coupled Plasma Mass Spectroscopy (ICP-MS).

ABOUT OSISKO DEVELOPMENT CORP.

Osisko Development Corp. is a continental North American gold development company focused on past producing mining camps with district scale potential. The Company's objective is to become an intermediate gold producer through the development of its flagship, fully permitted, 100%-owned Cariboo Gold Project, located in central British Columbia, Canada. Its project pipeline is complemented by the Tintic Project located in the historic East Tintic mining district in Utah, U.S.A., a brownfield property with significant exploration potential, extensive historical mining data, and access to established infrastructure. Osisko Development is focused on developing long-life mining assets in mining-friendly jurisdictions while maintaining a disciplined approach to capital allocation, development risk management, and mineral inventory growth.

For further information, visit our website at www.osiskodev.com or contact:

Sean Roosen	Philip Rabenok
Chairman and CEO	Vice President, Investor Relations
Email: sroosen@osiskodev.com	Email: prabenok@osiskodev.com
Tel: +1 (514) 940-0685	Tel: +1 (437) 423-3644

CAUTION REGARDING FORWARD LOOKING STATEMENTS

This news release contains "forward-looking information" (within the meaning of applicable Canadian securities laws) and "forward-looking statements" (within the meaning of the U.S. Private Securities Litigation Reform Act of 1995, as amended) (collectively, "forward-looking statements"). Such forward-looking statements are identified with words such as "may", "will", "would", "could", "anticipate", "believe", "expect", "plan", "intend", "potential", "estimate", "propose", "project", "outlook", "foresee", "objective", "strategy", variants of these words or the negative or comparable terminology, as well as terms usually used in the future and the conditional. Information contained in forward-looking statements is based upon certain material assumptions that were applied in drawing a conclusion or making a forecast or projection, including the assumptions, qualifications, limitations or statements pertaining to: the utility and significance of results to contribute to a more detailed understanding of spatial controls and local variability within the Lowhee Zone and its ability and significance in providing positive indication (if any) for near mine potential; the results, timing, utility and significance of the infill drill program and its impacts on the localized block model and/or future production stope designs and sequencing (if any); the tighter infill drilling spacing providing better understanding of vein corridor spatial geometries and local variability within Lowhee; the ability of results (if any) to help refine infill drill requirements, production designs and sequencing in the Lowhee deposit; the significance of continued drilling in underexplored zones; the interpretation and accuracy of intercepts to suggest possible extensions of vein corridors, with potential for resource conversion and upside mineralization; the interpretation and accuracy of assay composites showing a degree of spatial correlation with the modelled reserve stopes with intercepts outside these areas suggesting potential for resource conversion and upside mineralization; the prospectivity of exploration in the Lowhee Zone and targets outside of currently defined mineral reserves and/or mineral resources; the consistency of results with modelled reserve stopes (if at all); the interpretation and accuracy of spatial geometries, geological structure and local variability modeling and assumptions in regard to potential reserve or resource revisions (if at all); the ability and timing (if at all) to complete planned remodelling and mineral resource calculation process; the significance of implications (if any) on an updated local block model and any potential adjustments to planned reserve stopes; the ability of estimation results (if any) to support the addition of new planned reserve stopes; the results (if any) of further exploration work and ability of the Company to define and expand mineral resources beyond current mineral resource estimates; the ability and utility of exploration work (including drilling) to inform resource modeling, mine planning, production stope design procedures and parameters, refinement of infill drill requirements, and the appropriate drill spacing for future infill drilling (if at all); assumptions, qualifications and parameters underlying the Cariboo Technical Report (including, but not limited to, the mineral resources, mineral reserves, production profile, mine design and project economics); the results of the Cariboo Technical Report as an indicator of quality and robustness of the Cariboo Gold Project, as well as other considerations that are believed to be appropriate in the circumstances; the ability of the Company to achieve the estimates outlined in the Cariboo Technical Report in the timing contemplated (if at all); mineral resource category conversion; the future development and operations at the Cariboo Gold Project; management's perceptions of historical trends, current conditions and expected future developments; the utility and significance of historic data, including the significance of the district hosting past producing mines; the ability of exploration work (including drilling and sampling) to accurately predict mineralization; the ability of the Company to complete its exploration and development objectives for its projects in the timing contemplated and within expected costs (if at all); the ability to adapt to changes in gold prices, estimates of costs, estimates of planned exploration and development expenditures; the Company's strategy and objectives relating to the Cariboo Gold Project as well as its other projects; the assumptions, qualifications and limitations relating to the Cariboo Gold Project being permitted; the exploration potential and prospectivity (if any) of its properties; regulatory framework remaining defined and understood as well as

other considerations that are believed to be appropriate in the circumstances, and any other information herein that is not a historical fact may be "forward looking information". Actual results could differ materially due to a number of factors, including, without limitation: risks relating to third-party approvals, including the issuance of permits by governments, capital market conditions and the Company's ability to access capital on terms acceptable to the Company for the contemplated exploration and development at the Company's properties; risks related to the exploration, development and operation of the Cariboo Gold Project; risks related to geological modeling and resource estimation; health, safety and security incidents; regulatory delays or changes in regulatory framework and applicable laws; labour shortages or disputes; general economic and market conditions and business conditions in the mining industry; fluctuations in commodity and currency exchange rates; changes in regulatory framework and applicable laws, as well as those risks and factors disclosed in the Company's most recent annual information form, financial statements and management's discussion and analysis as well as other public filings on SEDAR+ (www.sedarplus.ca) and on EDGAR (www.sec.gov). Although the Company believes the expectations conveyed by the forward-looking statements are reasonable based on information available as of the date hereof, no assurances can be given as to future results, levels of activity and achievements. The Company disclaims any obligation to update any forward-looking statements, whether as a result of new information, future events or results or otherwise, except as required by law. Forward-looking statements are not guarantees of performance and there can be no assurance that these forward-looking statements will prove to be accurate, as actual results and future events could differ materially from those anticipated in such statements. Accordingly, readers should not place undue reliance on forward-looking statements.

Neither the TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this news release. No stock exchange, securities commission or other regulatory authority has approved or disapproved the information contained herein.

Photos accompanying this announcement are available at:

<https://www.globenewswire.com/NewsRoom/AttachmentNg/c95dd822-2dbf-4ceb-81d4-4cc026b1ce7a>

<https://www.globenewswire.com/NewsRoom/AttachmentNg/ff7153e1-c044-4a80-a130-da29b9095147>

<https://www.globenewswire.com/NewsRoom/AttachmentNg/f8ca8a7f-087e-449d-be05-40a1e2cfd4a3>

<https://www.globenewswire.com/NewsRoom/AttachmentNg/1524082c-2bc4-40b3-b223-e8b576d4c8e4>

<https://www.globenewswire.com/NewsRoom/AttachmentNg/1d1b5350-23ac-4a6f-86ab-5edf96284305>

<https://www.globenewswire.com/NewsRoom/AttachmentNg/475d36ae-85f3-4274-8588-8ccf4e0d07ac>

<https://www.globenewswire.com/NewsRoom/AttachmentNg/74e1fcae-2495-4feb-a1c3-28ec1e120682>

<https://www.globenewswire.com/NewsRoom/AttachmentNg/a823b3a5-ae02-4c1f-95cf-e3c59a1ada8f>

<https://www.globenewswire.com/NewsRoom/AttachmentNg/dfc31f11-5f8f-4bab-ad16-371a0f72b809>

Dieser Artikel stammt von Rohstoff-Welt.de

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/737072--Osisko-Development-Completes-13000-Meter-Infill-Drilling-Program-at-Cariboo-Gold-Project-and-Provides-Update>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).