

SAGA Metals Reports Assays from R-0044 to R-0046 with Intercepts Including 58.33% Fe₂O₃, 8.78% TiO₂, 0.415% V₂O₅ from 2026 Drilling at Trapper South, Radar Critical Minerals Project in Labrador

13:30 Uhr | [Newsfile](#)

Vancouver, June 11, 2026 - [Saga Metals Corp.](#) (TSXV: SAGA) (OTCQB: SAGMF) (FSE: 20H) ("SAGA" or the "Company"), a North American exploration company focused on critical mineral discoveries, is pleased to report additional assay results from drill holes R-0044, -0045 and -0046 completed in 2026 as part of its ongoing maiden Mineral Resource Estimate ("MRE") diamond drill program at the Trapper Zone within the 100%-owned Radar Titanium-Vanadium-Iron Project near Cartwright, Labrador, Canada.

The Trapper Zone forms part of an oxide corridor that includes the Falcon and Hawkeye Zones spanning 29 square kilometres near the center of the Property.

Figure 1: The Radar Property with the Dias QMAGT vertical gradient (Bzz) anomaly footprint shown in red (high-amplitude pixels only). The QMAGT-imaged central oxide-layering corridor validated over 29 km², encompassing the Trapper Zone, Hawkeye Zone, and the new Falcon Zone.

To view an enhanced version of this graphic, please visit:
https://images.newsfilecorp.com/files/12336/301016_df237b35d4733acc_001full.jpg

Trapper South Assay Highlights

- Analytical results received for three (3) additional diamond drill holes (R-0044 to R-0046) from the MRE drill program initiated in Q4 2025, delivering consistent broad intercepts of oxide mineralization.
- Key intercepts include:
 - Hole R-0044: 22.9 m @ 51.38% Fe₂O₃, 6.85% TiO₂, 0.416% V₂O₅;
 - Hole R-0045: 71.3 m @ 48.28% Fe₂O₃, 6.21% TiO₂, 0.373% V₂O₅;
 - Including 40.0 m @ 53.69% Fe₂O₃, 7.32% TiO₂, 0.441% V₂O₅;
 - Hole R-0046: 127.9 m @ 52.94% Fe₂O₃, 7.35% TiO₂, 0.388% V₂O₅;
 - Including 54.0 m @ 58.33% Fe₂O₃, 8.78% TiO₂, 0.415% V₂O₅;
 - Including 65.1 m @ 43.84% Fe₂O₃, 5.90% TiO₂, 0.316% V₂O₅;
 - Including 20.6 m @ 54.21% Fe₂O₃, 7.46% TiO₂, 0.426% V₂O₅;
- These results now bring the total MRE drill results to thirty-nine (39) diamond drill holes received to date. As reported previously, analytical results from the first thirty-six (36) diamond drill holes of the MRE drill program include:

DDH ID	FROM	TO	Length	True Thickness	Fe ₂ O ₃	TiO ₂	V ₂ O ₅
	m	m	m	m	%	%	%
R-0008	170.0	237.6	68.3	66.2	46.15	9.21	0.311
R-0009	94.0	181.2	87.2	84.4	50.67	10.15	0.339
R-0010	1.5	137.0	135.5	121.7	50.03	7.87	0.352
R-0011	58.1	153.3	95.2	50.8	39.49	6.49	0.222

R-00123.8	79.0	75.2	39.6	27.39	4.87	0.116
R-00139.5	121.0	111.5	97.9	37.08	5.14	0.242
R-00148.8	50.0	41.2	14.9	36.17	6.36	0.188
R-001573.3	174.0	100.7	88.9	38.56	6.80	0.229
R-001644.0	94.6	50.6	47.1	52.05	7.21	0.375
R-001750.6	140.6	90.0	73.0	51.86	6.76	0.417
R-001844.7	115.0	70.3	44.1	42.64	5.66	0.288
R-001966.6	112.3	45.7	41.6	49.51	6.56	0.374
R-002087.3	128.0	40.7	31.1	37.62	4.93	0.239
R-002196.0	127.4	31.4	16.5	53.18	7.08	0.414
R-002262.0	92.6	30.6	28.6	49.4	6.61	0.373
R-0023100.5	186.5	86.0	54.0	45.5	5.5	0.367
R-0024112.0	203.0	91.0	58.7	49.08	6.23	0.39
R-0024142.0	186.0	44.0	28.4	54.2	7.07	0.443
R-0025141.3	223.0	81.7	58.5	41.36	5.18	0.309
R-0025168.0	201.0	33.0	23.7	47.38	6.01	0.384
R-0026141.7	189.0	47.3	27.7	38.16	4.65	0.288
R-0026110.9	131.4	20.5	12.0	52.39	6.55	0.449
R-002781.2	162.0	80.8	63.4	42.74	5.18	0.320
R-0028105.7	211.0	105.3	54.5	42.39	5.40	0.306
R-0028144.0	182.0	38.0	19.7	49.43	6.50	0.382
R-002965.2	172.0	106.8	95.5	44.41	5.36	0.341
R-002965.2	104.0	38.8	34.7	53.02	6.46	0.441
R-003083.1	174.0	90.9	49.5	42.57	5.40	0.303
R-003083.1	101.7	18.6	10.2	50.81	6.56	0.398
R-003163.4	171.6	108.2	87.2	38.11	5.13	0.254
R-003197.0	140.1	43.1	34.7	42.71	5.88	0.309
R-003253.8	198.0	144.2	135.3	37.13	5.04	0.234
R-0032114.0	170.0	56.0	52.6	44.68	6.50	0.294
R-003367.4	168.0	100.6	77.5	44.07	6.38	0.286
R-003397.0	153.0	56.0	43.1	48.03	7.25	0.304
R-003468.8	195.0	126.2	124.0	43.19	6.05	0.293
R-0034106.1	170.0	63.9	62.8	48.61	7.01	0.344
R-00358.5	22.0	13.5	9.9	30.98	2.93	0.193
R-003655.0	128.0	73.0	36.5	45.34	6.31	0.345
R-003680.0	114.0	34.0	17.0	50.46	7.21	0.395
R-003752.2	103.0	50.8	41.9	45.93	6.46	0.348
R-003845.4	146.2	100.8	73.7	41.23	5.21	0.302
R-0038103.9	146.2	42.4	31.0	46.20	6.35	0.364
R-003984.0	194.0	110.1	106.5	47.42	5.95	0.354
R-003997.0	149.1	52.1	50.4	58.15	7.68	0.459
R-0039166.4	194.0	27.6	26.7	45.88	5.85	0.350
R-004084.9	130.0	45.1	31.9	51.20	7.94	0.340
R-00416.6	53.0	46.4	34.7	47.97	6.49	0.368
R-0042102.1	137.4	35.3	23.6	50.68	6.74	0.378
R-004328.4	68.2	39.8	30.4	47.93	7.24	0.307

Table 1: MRE drill program assay intercepts previously reported in Q4 2025 and 2026 to date from drill holes R-0008 to R-0043.

- Top 15 intercepts from the MRE Drill Program to date can be found in Table 4 below.
- Completed fifty (50) holes (R-0008 to R-0057) from Q4 2025 to date in 2026, with significant oxide intercepts including 202.3 m from R-0053 (true thickness of 132.1) of semi-massive oxide with extensive rhythmic oxide layering.
- MRE drilling to date has returned multiple holes of thick oxide core intercepts exceeding 70-144 metres and certain assay intervals frequently above 45-58% Fe₂O₃; 6-8% TiO₂; and 0.37-0.44% V₂O₅.
- Rhythmic banding and semi-massive to massive oxide mineralization are observed consistently in Trapper South, aligning with prior high-grade results from Trapper North.
- Drilling is progressing efficiently, with 11,600 m completed in the Trapper Zone to date.

- Confirmed 29 km² central oxide corridor
- Excellent core recovery and representative sampling support ongoing metallurgical test work and the advancement of the maiden Mineral Resource Estimate.

Michael Garagan, CGO & Director of SAGA Metals, commented:

"These latest results from holes R-0044 through R-0046 continue to demonstrate the impressive scale and continuity of the oxide system at Trapper South. Hole R-0046 in particular was a standout, stretching a full 490.1 m (over 1,600 feet) and reaching 280 m vertical depth while returning broad zones of strong oxide mineralization, including over 100 m of higher-grade material averaging 7.35% TiO₂; and 0.388% V₂O₅."

Holes R-0044 and R-0045 further reinforce the consistency we're seeing across the Trapper Zone, with thick intercepts of rhythmic oxide layering and semi-massive mineralization. The ability to repeatedly intersect wide zones of oxide mineralization with high grades across multiple sections speaks to the robustness of this system. These results continue to build our confidence as we advance toward a maiden Mineral Resource Estimate at Radar."

2026 Trapper South Drilling Summary

Drill Hole	Azimuth / Dip	Total Depth (m)	From (metres)	To (metres)	Semi-Massive Oxide (m)	Rhythmic Layering (m)	Total Oxide
R-0016	38° / -45°	206	44.0	102.0	45.8	12.2	58.0
R-0017	38° / -70°	161	50.6	140.6	87.1	3.0	90.1
R-0018	38° / -45°	188	44.7	156.4	65.0	46.6	111.7
R-0019	38° / -45°	182	66.6	133.0	38.0	28.5	66.5
R-0020	38° / -45°	206	50.8	138.0	28.5	58.7	87.2
R-0021	38° / -70°	152	81.3	127.4	33.5	12.6	46.1
R-0022	38° / -45°	149	22.5	118.7	31.6	59.7	91.3
R-0023	38° / -45°	272	100.5	239.3	30.6	76.4	107.1
R-0024	38° / -45°	254	108.9	219.8	46.8	62.1	108.9
R-0025	38° / -60°	275	123.0	253.6	6.9	118.1	125.0
R-0026	38° / -60°	302	108.8	273.7	16.2	138.6	154.8
R-0027	38° / -45°	217	81.3	175.3	34.2	59.9	94.1
R-0028	38° / -60°	227	105.1	215.9	22.5	87.1	109.6
R-0029	38° / -45°	214	65.2	184.0	13.4	105.4	118.8
R-0030	38° / -60°	211	83.1	189.2	25.4	79.6	105.0
R-0031	38° / -45°	215	63.4	171.6	2.4	105.9	108.3
R-0032	38° / -60°	263	53.8	214.7	18.5	136.0	154.4
R-0033	38° / -45°	251	67.7	203.5	23.7	112.4	136.1
R-0034	38° / -60°	233	48.7	214.1	66.1	93.5	159.7
R-0035	38° / -45°	97	8.5	66.3	0.0	35.0	35.0
R-0036	38° / -70°	212	47.4	128.0	68.0	8.6	76.6
R-0037	38° / -45°	206	42.6	146.0	50.8	52.6	103.4
R-0038	38° / -70°	182	45.4	146.2	55.9	45.0	100.9
R-0039	218° / -45°	251	84.0	196.3	82.2	23.3	105.5
R-0040	38° / -70°	170	38.3	130.0	44.7	28.7	73.4
R-0041	38° / -45°	100	6.6	84.2	38.5	30.9	69.4
R-0042	38° / -70°	161	88.6	137.4	26.6	10.0	36.6
R-0043	38° / -45°	119	28.4	101.6	37.5	35.7	73.3
R-0044	218° / -45°	176	82.9	105.8	19.3	3.7	22.9
R-0045	218° / -45°	245	39.3	223.6	67.4	71.7	139.1
R-0046 a	218° / -45°	491	7.4	147.9	121.7	19.3	141.0
R-0046 b			237.7	445.9	21.4	176.7	198.2
R-0047	218° / -45°	305	106.1	247.4	50.8	71.5	122.3
R-0048	38° / -45°	242	31.7	149.3	11.8	105.1	116.9
R-0049	38° / -60°	200	30.7	134.3	17.4	86.1	103.6
R-0050	218° / -45°	269	63.9	245.6	51.9	94.2	146.1

R-0051	38° / -60°	311	99.9	227.3	38.5	88.8	127.4
R-0052	38° / -45°	275	68.6	235.0	19.8	140.8	160.6
R-0053	38° / -60°	299	77.1	279.4	35.0	167.3	202.3
R-0054	38° / -45°	269	18.4	202.0	35.2	85.3	120.5
R-0055	38° / -60°	320	70.1	291.6	67.6	73.2	140.8
R-0056	38° / -45°	239	84.8	220.0	24.4	69.6	94.0
R-0057	38° / -60°	233	92.4	194.1	43.6	52.5	96.1
	Total (m)	9,550					

Table 2: Summary of drill holes R-0016 to R-0057, highlighting the oxide intercepts. See Figures 3-4 below, which depict the oxide mineralization in cross sections S6 and S8. True thickness represents the perpendicular width of the mineralized zone, while the total downhole oxide represents the length of the mineralization intercepted downhole.

	Total Meters Drilled	Total Samples
Trapper South 2025	2050	1313
Trapper South 2026	9550	5719
Trapper Total	11600	7032

Table 3: Summary of total meters drilled in Q4 2025 and 2026 to date, including total core samples cut and prepared.

Figure 2: Trapper South map outlining location of the initial 2026 focus for the remainder of the MRE drill program to be completed in 2026, including cross-sections S14, S13, S12, S11, S10, S9, S8, S7, S6, S5, and S4, showing the TMI of the 2025 Trapper Zone ground magnetic survey.

To view an enhanced version of this graphic, please visit:

https://images.newsfilecorp.com/files/12336/301016_df237b35d4733acc_005full.jpg

The latest results from these drill holes, R-0044, R-0045 and R-0046, once again demonstrate excellent continuity across broad zones of oxide mineralization, underscoring the growing potential for a sizable mineral resource that could create meaningful long-term value for SAGA shareholders.

Detailed Logging Highlights from Drill Hole R-0044 to R-0046

- Hole R-0044 (Cross-Section S06): Drill hole R-0044 is drilled on cross-section S6, with an azimuth of 218 and a dip of -45°, with a total depth of 167 m. The oxide zone is 22.9m thick, intersected at 82.85m, at a sheared felsic dyke marking the contact between gabbro norite and semi-massive oxide. Oxide zone includes rhythmic oxide layering (3.7 m) and semi-massive oxide (19.3 m) ending at 105.8 m.
- Hole R-0045 (Cross-Section S08): Drill hole R-0045 is drilled on cross-section S8, with an azimuth of 218 and a dip of -45° with a total depth of 245 m. The oxide zone is 139.2 m thick, intersected at 39.3 m at a sharp contact from gabbro norite to rhythmic banding. Semi-massive oxide starts at a faulted lower contact of a felsic dyke at 76.8 m. Oxide zone includes rhythmic oxide layering (71.7 m) and semi-massive oxide (67.4 m). The oxide zone ends at 223.6 m at a sharp contact from rhythmic banding to gabbro norite.
- Hole R-0046 (Cross-Section S08): Drill hole R-0046 is drilled on cross-section S8, with an azimuth of 218 and a dip of -45°, with a total depth of 491 m. This hole tests both of the magnetic anomalies in Trapper South. The first oxide zone is 140.5 m thick and is intersected at 7.4 m at a sharp contact of gabbro norite and rhythmic layering. This zone includes rhythmic oxide layering (18.7 m) and semi-massive oxide (121.8 m). The oxide zone ends at 147.9 m at a faulted contact of a felsic dyke. The second oxide zone is 198.2 m thick and is intersected at 237.7 m at a fault contact from gabbro norite to rhythmic banding. This zone includes rhythmic oxide layering (176.7 m) and semi-massive oxide (21.4 m). The oxide zone ends at 445.9 m at a sharp contact from rhythmic banding to gabbro norite. An intermediate zone (147.9 m to 237.7 m) with 39.0 m of rhythmic layering is observed from 176.6 m at a faulted contact of felsic dyke and ending at 215.5 m. This intermediate zone between the two magnetic anomalies is faulted and hosts many felsic dykes.

Figure 3: Cross section of S6 looking NW showing R-0019, -0027, -0028, -0042, -0043, -0044 and -0047,

highlighting intercepts of semi-massive oxides and layering sequence with the 3D Magnetic Inversion of the 2025 Trapper Zone ground magnetic survey. Assays shown for R-0019, R-0027, R-0028, R-0042, R-0043 and R-0044. Assays are pending for R-0047.

To view an enhanced version of this graphic, please visit:
https://images.newsfilecorp.com/files/12336/301016_df237b35d4733acc_006full.jpg

Figure 4: Cross section of S8 looking NW showing R-0016, -0017, -0023, -0026, -0035, -0045 and -0046, highlighting intercepts of semi-massive oxides and layering sequence with the 3D Magnetic Inversion of the 2025 Trapper Zone ground magnetic survey. Assays shown for R-0016, R-0017, R-0023, R-0026, R-0035, R-0045 and R-0046.

To view an enhanced version of this graphic, please visit:
https://images.newsfilecorp.com/files/12336/301016_df237b35d4733acc_007full.jpg

Sampling Summary

Saga's core cutting team finalized the cutting, sampling, and shipping of 450 samples from R-0047, -0048, and -0049. IGS Laboratories anticipates receiving the samples towards the beginning of next week. A total of 7,032 samples have been collected to date in the Trapper Zone.

Key Project Highlights

- Confirmed mineralization in 57 out of 57 drill holes completed and observed in two primary zones to date.
- Analytical results to date include numerous oxide-rich intercepts, including:

DDH ID	FROM TO	Length	True Thickness	Fe2O3	TiO2	V2O5	
	m	m	m	%	%	%	
R-0009	94.0	181.2	87.2	84.4	50.67	10.15	0.339
R-0008	170.0	237.6	68.3	66.2	46.15	9.21	0.311
R-0046	20.0	74.0	54.0	43.7	58.33	8.78	0.415
R-0040	84.9	130.0	45.1	31.9	51.20	7.94	0.340
R-0010	1.5	137.0	135.5	121.7	50.03	7.87	0.352
R-0039	97.0	149.1	52.1	50.4	58.15	7.68	0.459
R-0017	73.0	140.6	67.6	54.9	55.13	7.37	0.448
R-0045	104.0	144.0	40.0	31.1	53.69	7.32	0.441
R-0033	97.0	153.0	56.0	43.1	48.03	7.25	0.304
R-0043	28.4	68.2	39.8	30.4	47.93	7.24	0.307
R-0016	44.0	94.6	50.6	47.1	52.05	7.21	0.375
R-0036	80.0	114.0	34.0	17.0	50.46	7.21	0.395
R-0021	96.0	127.4	31.4	16.5	53.18	7.08	0.414
R-0024	142.0	186.0	44.0	28.4	54.20	7.07	0.443
R-0034	106.1	170.0	63.9	62.8	48.61	7.01	0.344

Table 4: Top 15 intercepts from the 2025 & 2026 drilling programs at the Trapper Zone

- Infrastructure including road access, deep-water port, nearby hydro-electric power and regional airport.
- Confirmed a 29.0 km² central oxide corridor that encompasses the Trapper, Falcon and Hawkeye Zones, demonstrating district-scale potential.
- Consistent grades and thicknesses with semi-massive to massive oxide reporting up to 72.33% Fe, 13.3% TiO₂, and 0.66% V₂O₅.
- Petrographic analysis confirms titanomagnetite mineralization is advantageous for simplified metallurgical processing.
- A total of 11,600 m has been completed and reported to date for the MRE drill program. See Figure 2 showcasing 2026 drill hole locations in Trapper South reported to date.

About the Radar Critical Mineral Property in Labrador

The Radar Property comprises 690 mineral claims across 9 mineral licenses, totalling approximately 24,175 hectares in southeastern Labrador, located approximately 10 km south of Cartwright. The Property entirely encloses the Dykes River Intrusive Complex (~160 km² at the surface) and is accessible year-round via paved Route 510, a Cartwright logging road, and a SAGA-constructed access trail. Infrastructure advantages include the deep-water port at Cartwright, the Cartwright Airport (YRF), and proximity to regional hydroelectric power from Muskrat Falls and Churchill Falls.

Diamond drilling, geophysics, trenching and geological mapping have confirmed a 29 km² oxide corridor encompassing the Trapper, Falcon and Hawkeye Zones. VTM mineralization at Radar is comparable to that of global Fe-Ti-V systems such as Panzihua (China) and Bushveld (South Africa). Subject to further exploration, resource definition, and metallurgical testing, the Project may represent a strategic source of titanium, vanadium, and iron for North American markets.

Figure 5: The Radar Property with the Dias QMAGT vertical gradient (Bzz) anomaly footprint shown in red (high-amplitude pixels only). The QMAGT-imaged central oxide-layering corridor validated over a 29 km² area, encompassing the Trapper Zone, Hawkeye Zone, and the new Falcon Zone, with additional targets highlighted to the west and north. The Property is well serviced by road access and is conveniently located near the town of Cartwright, Labrador.

To view an enhanced version of this graphic, please visit:

https://images.newsfilecorp.com/files/12336/301016_df237b35d4733acc_009full.jpg

Qualified Person

Paul J. McGuigan, P. Geo., is an Independent Qualified Person as defined under National Instrument 43-101 and has reviewed and approved the technical information disclosed in this news release.

Technical Information

Diamond drill core was logged and sampled by Company personnel at SAGA's core facility in Cartwright, Labrador. The drill core diameter was NQ. The core was cut lengthwise using a diamond saw, and one half was retained in the core box, while the other half was sampled at designated intervals for analysis.

Core samples were prepared and analyzed at the Impact Global Solutions (IGS) laboratory facility in Montréal, Québec. As part of the analytical quality assurance and quality control (QA/QC) program, certified reference standards, blanks, and duplicate samples were inserted into the sample stream at regular intervals to monitor analytical accuracy and precision.

Crush rejects and pulp samples are retained and stored in a secure facility for potential future verification and re-analysis. The Company maintains a rigorous QA/QC protocol consistent with industry standard practices.

About SAGA Metals Corp.

SAGA Metals Corp. is a North American mining company focused on the exploration and discovery of a diversified suite of critical minerals that support the North American transition to supply security. The Radar Ti-V-Fe Project comprises 24,175 hectares and entirely encloses the Dykes River intrusive complex, mapped at 160 km² on the surface near Cartwright, Labrador. Exploration to date, including 13,809 m of drilling, has confirmed a large, mineralized layered mafic intrusion hosting vanadiferous titanomagnetite (VTM) and ilmenite mineralization with strong grades of titanium and vanadium.

The Company has signed a definitive agreement to acquire 100% of the Wolverine Heavy Rare Earth Element Project in Labrador, a near-surface REE system hosted within a peralkaline caldera complex that shares strong geological similarities with the Tanbreez and Strange Lake deposits. The project features consistent mineralization, with zones spanning 26 km², including drill assays up to 2.03% TREO with approximately 28% HREO content, and sample assays up to 21.6% TREO.

The Double Mer Uranium Project covers 25,600 hectares and features uranium radiometrics that highlight an 18 km east-west trend, with a confirmed 14 km section producing samples as high as 0.428% U₃O₈. (2024 Double Mer Technical Report).

Additionally, SAGA owns the Legacy Lithium Project in Quebec's Eeyou Istchee James Bay region. This project spans 65,849 hectares and shares significant geological continuity with other major players in the area, including Rio Tinto, Li-FT Power, SOQUEM, and Loyal Metals.

With a portfolio spanning key commodities critical to the clean energy future, SAGA is strategically positioned to play an essential role in securing critical minerals.

On Behalf of the Board of Directors

Mike Stier, Chief Executive Officer

For more information, contact:

Rob Guzman, Investor Relations
SAGA Metals Corp.
Tel: +1 (844) 724-2638
Email: rob@sagametals.com
www.sagametals.com

Neither the TSX Venture Exchange nor its Regulation Service Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release.

Cautionary Disclaimer

This news release contains forward-looking statements within the meaning of applicable securities laws that are not historical facts. Forward-looking statements are often identified by terms such as "will", "may", "should", "anticipates", "expects", "believes", and similar expressions or the negative of these words or other comparable terminology. All statements other than statements of historical fact, included in this release are forward-looking statements that involve risks and uncertainties. In particular, this news release contains forward-looking information pertaining to the Company's Radar Project. There can be no assurance that such statements will prove to be accurate, and actual results and future events could differ materially from those anticipated in such statements. Important factors that could cause actual results to differ materially from the Company's expectations include, but are not limited to, changes in the state of equity and debt markets, fluctuations in commodity prices, delays in obtaining required regulatory or governmental approvals, environmental risks, limitations on insurance coverage, inherent risks and uncertainties involved in the mineral exploration and development industry, particularly given the early-stage nature of the Company's assets, and the risks detailed in the Company's continuous disclosure filings with securities regulations from time to time, available under its SEDAR+ profile at www.sedarplus.ca. The reader is cautioned that assumptions used in the preparation of any forward-looking information may prove to be incorrect. Events or circumstances may cause actual results to differ materially from those predicted, as a result of numerous known and unknown risks, uncertainties, and other factors, many of which are beyond the control of the Company. The reader is cautioned not to place undue reliance on any forward-looking information. Such information, although considered reasonable by management at the time of preparation, may prove to be incorrect and actual results may differ materially from those anticipated. This cautionary statement expressly qualifies forward-looking statements contained in this news release. The forward-looking statements contained in this news release are made as of the date of this news release, and the Company will update or revise publicly any of the included forward-looking statements only as expressly required by applicable law.

To view the source version of this press release, please visit <https://www.newsfilecorp.com/release/301016>

Dieser Artikel stammt von [Rohstoff-Welt.de](https://www.rohstoff-welt.de)

Die URL für diesen Artikel lautet:

<https://www.rohstoff-welt.de/news/737289--SAGA-Metals-Reports-Assays-from-R-0044-to-R-0046-with-Intercepts-Including-58.33Prozent-Fe2O3-8.78Prozent>

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere [AGB/Disclaimer!](#)

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt!
Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2026. Es gelten unsere [AGB](#) und [Datenschutzrichtlinien](#).